```
In [1]:
import pandas as pd
In [2]:
import numpy as np
In [3]:
import matplotlib.pyplot as plt
In [4]:
from sklearn.datasets import make classification
In [5]:
#without coefficient of underline model
X, y = make_classification(n_samples = 1000, n_features = 5 ,
                           n_clusters_per_class = 1, n_classes =2,
                           random_state = 2529)
In [6]:
X[0:5]
Out[6]:
array([[ 1.54701705, 0.84770596, -0.41725021, -0.62356778, -0.19388577],
       [0.80633556, 0.40985594, -0.45641095, -0.3052022, 0.50935923],
       [ 0.94390268, 0.70041038, 1.11385452, -0.49394417, 1.42305455],
       [1.92091517, 0.95815739, -1.2235022, -0.71578154, 0.66588981],
                      0.69035375, -1.18119669, -0.52009219, -0.22745417]])
       [ 1.45270369,
In [7]:
y[0:5]
Out[7]:
array([0, 0, 1, 0, 0])
In [8]:
X.shape, y.shape
Out[8]:
((1000, 5), (1000,))
In [9]:
from sklearn.model_selection import train_test_split
```

(300,)

```
In [10]:
X_train, X_test, y_train, y_test = train_test_split(X,y, test_size = 0.3,
                                                     random_state = 2529)
In [11]:
X_train.shape,X_test.shape,y_train.shape,y_test.shape
Out[11]:
((700, 5), (300, 5), (700,), (300,))
In [12]:
from sklearn.ensemble import RandomForestClassifier
In [13]:
model = RandomForestClassifier()
In [14]:
model.fit(X_train, y_train)
Out[14]:
RandomForestClassifier()
In [15]:
y_pred = model.predict(X_test)
In [16]:
y_pred.shape
Out[16]:
```

```
In [17]:
```

```
y_pred
```

```
Out[17]:
```

In [18]:

from sklearn.metrics import accuracy_score, confusion_matrix, classification_report

In [19]:

```
accuracy_score(y_test, y_pred)
```

Out[19]:

0.99

In [20]:

```
confusion_matrix(y_test, y_pred)
```

Out[20]:

```
array([[156, 1], [ 2, 141]], dtype=int64)
```

In [21]:

```
print(classification_report(y_test, y_pred))
```

	precision	recall	f1-score	support
0	0.99	0.99	0.99	157
1	0.99	0.99	0.99	143
accuracy			0.99	300
macro avg	0.99	0.99	0.99	300
weighted avg	0.99	0.99	0.99	300

```
In [22]:
```

```
from sklearn.model selection import GridSearchCV
parameters = {'n_estimators': [10,20,30,100,200,500], 'max_features': ['auto', 'sqrt'],
              'min_samples_split': [4,8], 'bootstrap': [True,False]}
gridsearch = GridSearchCV(RandomForestClassifier(),parameters)
gridsearch.fit(X_train, y_train)
Out[22]:
GridSearchCV(estimator=RandomForestClassifier(),
             param_grid={'bootstrap': [True, False],
                          'max_features': ['auto', 'sqrt'],
                          'min_samples_split': [4, 8],
                          'n_estimators': [10, 20, 30, 100, 200, 500]})
In [23]:
gridsearch.best_params_
Out[23]:
{'bootstrap': True,
 'max_features': 'auto',
 'min_samples_split': 8,
 'n_estimators': 10}
In [24]:
gridsearch.best_score_
Out[24]:
0.9885714285714287
In [25]:
gridsearch.best_estimator_
Out[25]:
RandomForestClassifier(min_samples_split=8, n_estimators=10)
In [26]:
gridsearch.best_index_
Out[26]:
6
In [27]:
y_pred_grid = gridsearch.predict(X_test)
```

In [28]:

```
confusion_matrix(y_test, y_pred_grid)
```

Out[28]:

In [29]:

print(classification_report(y_test, y_pred_grid))

	precision	recall	f1-score	support
0	0.98	0.99	0.99	157
1	0.99	0.98	0.99	143
accuracy			0.99	300
macro avg	0.99	0.99	0.99	300
weighted avg	0.99	0.99	0.99	300