

1 Interfacing of LED

```
int LEDpin =4;
int buttonpin =7;
bool buttonsate =false;

void setup ()
{
    pinMode (LEDpin, OUTPUT);
    pinMode (buttonpin, INPUT);
}
void loop ()
{
    buttonsate =digitalRead (buttonpin);
    if (buttonsate ==HIGH){
        digitalWrite (LEDpin, HIGH);
    }
    else{
        digitalWrite (LEDpin,LOW);
    }
}
```

2.Analog Sensor Interfacing (Temp Sensor LMT35)

```
const int lm35_pin = A1;    /* LM35 O/P pin */

void setup() {
    Serial.begin(9600);
}

void loop() {
    int temp_adc_val;
    float temp_val;
    temp_adc_val = analogRead(lm35_pin);    /* Read Temperature
    */
    temp_val = (temp_adc_val * 4.88);    /* Convert adc value to
    equivalent voltage */
    temp_val = (temp_val/10);    /* LM35 gives output of 10mv/°C
    */
    Serial.print("Temperature = ");
    Serial.print(temp_val);
    Serial.print(" Degree Celsius\n");
    delay(1000);
}
```

3. Interfacing Potentiometer for Position Control Simulation

```
#include <Servo.h>

Servo myServo;
int potpin = A0;
int potvalue = 0;
int angle = 0;
void setup() {
    myServo.attach(9);
    Serial.begin(9600);
}

void loop() {
    potvalue = analogRead(potpin);
    angle = map(potvalue, 0, 1023, 0, 180);
    myServo.write(angle);
    Serial.print("Potentiometer = ");
    Serial.print(potvalue);
    Serial.print(" | Servo angle = ");
    Serial.println(angle);

    delay(500);
}
```

4. Interfacing IR or Ultrasonic Sensor For Distance Measurement

```
int triggerpin = 3;
int echopin = 5;
long duration;
int distancecm;

void setup() {
    pinMode(triggerpin, OUTPUT);
    pinMode(echopin, INPUT);
    Serial.begin(9600);
}

void loop() {
    digitalWrite(triggerpin, LOW);
    delayMicroseconds(2);

    digitalWrite(triggerpin, HIGH);
    delayMicroseconds(10);
    digitalWrite(triggerpin, LOW);

    duration = pulseIn(echopin, HIGH);
    distancecm = duration * 0.034 / 2;
}
```

```

    Serial.print("Distance: ");
    Serial.print(distancecm);
    Serial.println(" cm");

    delay(500);
}

```

5. Controlling DC Motor Using Transistor Driver Circuit

```

int motorpin = 6;
void setup() {
    pinMode(motorpin, OUTPUT);
}

void loop() {
    // Gradually increase motor speed
    for (int speed = 0; speed <= 255; speed++) {
        analogWrite(motorpin, speed);
        delay(50);
    }

    delay(1000);

    for (int speed = 255; speed >= 0; speed--) {
        analogWrite(motorpin, speed);
        delay(50);
    }

    delay(1000);
}

```

6. Data Logging Using Arduino And Excel (Serial Communication)

```

void setup() {
    Serial.begin(9600);
    Serial.println("CLEARDATA");
    Serial.println("LABEL,Acolumn,Bcolumn,...");
    Serial.println("RESETTIMER");
}

void loop() {
    int sensorValue = analogRead(A0);
    Serial.print("DATA,TIME,TIMER,");
    Serial.println(sensorValue);
    delay(1000);
}

```