




Step 1: Start Hyperledger Composer Online version of Local. Click on Deploy a new business network




Step 2: Select empty business network




Step 3: Fill basic information, select empty business network and click —deploy button from right panel




Fill Basic Information:




Step 4: Connect to —hardware-assets business network that we have just deployed



click on —connect now button




Step 5: Click on —+Add a file...|| from left panel and select —model file (.cto)||



Write the following code in modal File:

```
/**
 * Hardware model
 */
namespace com.kpbirdasset
Hardware identified by hardwareId {
  o String hardwareId
  o String name
  o String type
  o String description
  o Double quantity
  → Employee owner
}
participant Employee identified by employeeId {
  o String employeeId
  o String firstName
  o String lastName
}
transaction Allocate {
  → Hardware hardware
  → Employee newOwner
}
```

Step 6: Click on —+Add a file...|| from left panel and select —script file (\*.js)||



Write following code in Script File.

functions @params and @transaction

```
/**
 * Track the trade of a commodity from one trader to another
 * @param {com.kpbird.Allocate} trade — the trade to be processed
 * @transaction
 */
function allocateHardware(allocate) {
  allocate.hardware.owner = allocate.newOwner;
  return getAssetRegistry('__com.kpbird.Hardware')
    .then(function (assetRegistry) {
      return assetRegistry.update(allocate.hardware);
    });
}
```

Step 7: permissions.acl file sample is already available, Add following code in permissions.acl file.


```
/**
 * New access control file
 */
rule AllAccess {
  description: —AllAccess — grant everything to everybody.||
  participant: —ANY||
  operation: ALL
  resource: —com.kpbird.**||
  action: ALLOW
}
rule SystemACL{
  description: —System ACL to permit all access||
  participant: —org.hyperledger.composer.system.Participant||
```

```

operation: ALL
resource: —org.hyperledger.composer.system.**||
action: ALLOW
}

```

Step 8: Now, It's time to test our hardware assets business network. Hyperledger composer gives —Test|| facility from composer panel it self. Click on —Test|| tab from top panel




Step 9: Create Assets. Click on —Hardware|| from left panel and click —+ Create New Assets|| from right top corner and add following code. We will create Employee#01 in next step. Click on —Create New|| button

```

{
  —$class||: —com.kpbird.Hardware||,
  —hardwareId||: —MAC01||,
  —name||: —MAC Book Pro 2015||,
  —type||: —Laptop||,
  —description||: —Mac Book Pro||,
  —quantity||: 1,
  —owner||: —resource:com.kpbird.Employee#01||
}

```




Steps 10: Let's create participants. Click —Employee|| and click —+ Create New Participants|| and add following code. We will add two employees


```
{
  —$class||: —com.kpbird.Employee||,
  —employeeId||: —01||,
  —firstName||: —Ketan||,
  —lastName||: —Parmar||
}
```

Click on —Create New|| on dialog

```
{
  —$class||: —com.kpbird.Employee||,
  —employeeId||: —02||,
  —firstName||: —Nirja||,
  —lastName||: —Parmar||
}
```



Step 11: It's time to do transaction, We will allocate Macbook Pro from Ketan (Employee#01) to Nirja (Employee#02). Click on —Submit Transaction|| button from left panel. In Transaction dialog, We can see all transaction functions on top —Transaction Type|| dropdown.




```


{
  —$class||: —com.kpbird.Allocate||,
  —hardware||: —resource:com.kpbird.Hardware#MAC01||,
  —newOwner||: —resource:com.kpbird.Employee#02||
}

```






Step 12: Click on —All Transactions|| from left panel to verify all transactions. In following screenshots you can see add assets, ass participants and allocation all operation are consider as transactions. —view records|| will give us more information about transaction.



Step 13: Now, It's time to deploy —hardware-assets|| business network to Hyperledger Fabric. Click on —Define|| tab from top panel and click —Export|| button from left panel. Export will create hardware-assets.bna file.



Download hardware-assets.bna file

bna is Business Network Archive file which contains model, script, network access and query file

Step 14: Start Docker and run following commands from ~/fabric-tools directory

Install business network to Hyperledger Fabric, If business network is already installed you can use

—update||

instead of —install||

\$composer runtime install -c PeerAdmin@hlfv1 -n hardware-assets

```
Ketan-Parmar:~/fabric-tools$ composer runtime install -c PeerAdmin@hlfv1 -n hardware-assets
✓ Installing runtime for business network hardware-assets. This may take a minute...
```

Command succeeded

Following command will deploy and start hardware-assets.bna file. Change hardware-assets.bna file before

you execute following command. networkadmin.card file will generate in ~/fabric-tools directory from previous command.

\$composer network start — card PeerAdmin@hlfv1 — networkAdmin admin — networkAdminEnrollSecret

adminpw — archiveFile /Users/ketan/Downloads/hardware-assets.bna — file networkadmin.card

```
Ketan-Parmar:fabric-tools ketan$ composer network start --card PeerAdmin@hlfv1 --networkAdmin admin --networkAdminEnrollSecret adminpw --archiveFile /Users/ketan/Downloads/hardware-assets.bna --file networkadmin.card
Starting business network from archive: /Users/ketan/Downloads/hardware-assets.bna
Business network definition:
  Identifier: hardware-assets@0.0.1
  Description: Hardware Assets will maintain Software company's hardware

Processing these Network Admins:
  userName: admin

✓ Starting business network definition. This may take a minute...
Successfully created business network card:
  Filename: networkadmin.card

Command succeeded
```

To connect business network you need connection card. so we can import networkadmin.card using following command

```
$composer card import -f networkadmin.card
```

To make sure networkadmin.card successfully install you can list cards using following command  
\$composer card list

```
Ketan-Parmar:fabric-tools ketan$ composer card list
The following Business Network Cards are available:
```

Connection Profile: hlfv1

Card Name	UserId	Business Network
admin@hardware-assets	admin	hardware-assets
PeerAdmin@trade-network	PeerAdmin	trade-network
admin@trade-network	admin	trade-network
PeerAdmin@hlfv1	PeerAdmin	

Issue `composer card list --name <Card Name>` to get details a specific card

Command succeeded

Following command will make sure that our hardware-assets business network is successfully running in Hyperledger Fabric.

```
$composer network ping --card admin@hardware-assets
```

```
Ketan-Parmar:fabric-tools ketan$ composer network ping --card admin@hardware-assets
The connection to the network was successfully tested: hardware-assets
  version: 0.16.0
  participant: org.hyperledger.composer.system.NetworkAdmin#admin
```

Command succeeded

Now It's time to interact with REST API. To develop Web or Mobile Application we require REST API. you can run following command to generate REST API for hardware-assets business network.


```
$composer-rest-server
```

```
Ketan-Parmar:fabric-tools ketan$ composer-rest-server
[?] Enter the name of the business network card to use: admin@hardware-assets
[?] Specify if you want namespaces in the generated REST API: always use namespaces
[?] Specify if you want to enable authentication for the REST API using Passport: No
[?] Specify if you want to enable event publication over WebSockets: Yes
[?] Specify if you want to enable TLS security for the REST API: No
```


To restart the REST server using the same options, issue the following command:  
`composer-rest-server -c admin@hardware-assets -n always -w true`

```
Discovering types from business network definition ...
Discovered types from business network definition
Generating schemas for all types in business network definition ...
Generated schemas for all types in business network definition
Adding schemas for all types to Loopback ...
Added schemas for all types to Loopback
Web server listening at: http://localhost:3000
Browse your REST API at http://localhost:3000/explorer
█
```

rest server will ask few basic information before generate rest api



## REST API for our hardware assets



## REST API methods for all operations