

# Higher-ranked Exception Types\*

Ruud Koot  
Utrecht University  
inbox@ruudkoot.nl

Jurriaan Hage  
Utrecht University  
j.hage@uu.nl

## Abstract

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

**Categories and Subject Descriptors** To DO.CR-number [subcategory]: third-level

**General Terms** To DO.term1, term2

**Keywords** To DO.keyword1, keyword2

## 1. Introduction

An often heard selling point of non-strict functional languages is that they provide strong and expressive type systems that make side-effects explicit. This supposedly makes software more reliable by lessening the mental burden of programmers. Many object-oriented programmers are quite surprised, then, that when they make the transition to a functional language, that they lose a fea-

ture their type system formerly did provide: tracking of uncaught exceptions.

There is a good excuse why this feature is missing from the type systems of contemporary non-strict functional languages: in a strict first-order language it is sufficient to annotate each function with a single set of uncaught exceptions the function may throw, in a non-strict higher-order language the situation becomes significantly more complicated. Let us first consider the two aspects “higher-order” and “non-strict” in isolation:

**Higher-order functions** The set of exceptions that may be raised by a higher-order function are not given by a fixed set of exceptions, but depends on the set of exceptions that may be raised by the function that is passed as its functional argument. Higher-order functions will thus end up being *exception polymorphic*.

**To DO.**concrete example?

**Non-strict evaluation** In non-strictly evaluated languages, exception are not a form of control flow, but a kind of value. Typically the set of values of each type are extended with an *exceptional value*  $\perp$  (more commonly denoted  $\perp$ , but we shall not do so for reasons of ambiguity), or family of exceptional values  $\perp^\ell$ . This means we do not only need to give all functions an exception-annotated function type, but every expression an exception-annotated type.

**To DO.**concrete example?

Take as an example the *map* function:

$$\begin{aligned} \text{map} &:: \forall \alpha \beta. (\alpha \rightarrow \beta) \rightarrow [\alpha] \rightarrow [\beta] \\ \text{map} &= \lambda f. \lambda xs. \text{case } xs \text{ of} \\ &\quad [] \quad \mapsto [] \\ &\quad (y : ys) \mapsto f y : \text{map } f ys \end{aligned}$$

For each type  $\tau$ , we denote its exception-annotated type by  $\tau \langle \xi \rangle$ .

For function types we will write  $\tau_1 \langle \xi_1 \rangle \xrightarrow{\xi} \tau_2 \langle \xi_2 \rangle$  instead of  $(\tau_1 \langle \xi_1 \rangle \rightarrow \tau_2 \langle \xi_2 \rangle) \langle \xi \rangle$ . If  $\xi$  is the empty exception set, then we will omit it completely.

The fully exception-polymorphic and exception-annotated type, or *exception type*, of *map* is

$$\begin{aligned} \forall \alpha \beta e_2 e_3. (\forall e_1. \alpha \langle e_1 \rangle \xrightarrow{e_3} \beta \langle e_2 e_1 \rangle) \\ \rightarrow (\forall e_4 e_5. [\alpha \langle e_4 \rangle] \langle e_5 \rangle \rightarrow [\beta \langle e_2 e_4 \cup e_3 \rangle] \langle e_5 \rangle) \end{aligned}$$

**To DO.**Why not  $\alpha \langle e_1 \rangle \xrightarrow{e_3} \beta \langle e_2 \rangle$ ?! Give some examples why higher-rankedness is needed. The example on the poster/*map* isn't sufficient. Postpone to a later section?

The exception type of the first argument  $\forall e_1. \alpha \langle e_1 \rangle \xrightarrow{e_3} \beta \langle e_2 e_1 \rangle$  states that it can be instantiated with a function that accepts any exceptional value as its argument (as the exception set  $e_1$  is universally quantified) and returns a possibly exceptional value. In case the return value is exceptional, then it will be one from the exception set  $e_2 e_1$ . Here  $e_2$  is an *exception operator*, a function that takes

\* This material is based upon work supported by the Netherlands Organisation for Scientific Research (NWO) under the project *Higher-ranked Polymorphism Explored* (612.001.120).

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

CONF 'yy, Month d-d, 20yy, City, ST, Country.  
Copyright is held by the owner/author(s). Publication rights licensed to ACM.  
ACM 978-1-nnnn-nnnn-n/yy/mm...\$15.00.  
http://dx.doi.org/10.1145/nnnnnnnn.nnnnnnn

an exception set, in this case and transforms it into another exception set, for example by adding a number of new elements to it, or discarding it and returning the empty set. Furthermore, the function itself may be an exceptional value from the exception set  $e_3$ .

The exception type of the second argument  $[\alpha(e_4)](e_5)$  states it should be a list. Any of the elements in the lists may be exception values from the exception set  $e_4$ . Any of the constructors that form the spine of the list may be exceptional values from the exception set  $e_5$ .

The result of *map* will be a list with the exception type  $[\beta(e_2 \ e_4 \cup e_3)](e_5)$ . Any constructors in the spine of this list may be exceptional values from the exception set  $e_5$ , the same exception set as where exceptional values in the spine of the input list could come from. By looking at the definition of *map* we can see why this is the case: *map* will only produce non-exceptional constructors, but the pattern-match on the input list will propagate any exceptional values encountered there. The elements of the list are produced by the function application  $f \ y$ . Recall that  $f$  has the exception type  $\forall e_1. \alpha(e_1) \xrightarrow{e_3} \beta(e_2 \ e_1)$ . Now one of two things can happen:

1. If  $f$  is an exceptional function value, then it must be one from the exception set  $e_3$ . Applying an argument to an exceptional value will cause the exceptional value to be propagated.
2. Otherwise  $f$  is a non-exceptional value. The argument  $y$  has exception type  $\alpha(e_4)$ —it is an element from the input list—and so can only be applied to  $f$  if we instantiate  $e_1$  to  $e_4$  first. If  $f \ y$  will produce an exceptional value it will thus be on from the exception set  $e_2 \ e_4$ .

To account for both cases we need to take the union of the two exception sets, giving us a value with the exception type  $\beta(e_2 \ e_4 \cup e_3)$ .

The get a better feeling of how these exception type and exception operators behave let us see what happens when we apply two different functions to *map*: the identity function *id* and the constant exceptional values *const*  $\perp^E$ . These two functions can be given the exception types:

$$\begin{aligned} id & : \forall e_1. \alpha(e_1) \xrightarrow{\emptyset} \alpha(e_1) \\ const \ \perp^E & : \forall e_1. \alpha(e_1) \xrightarrow{\emptyset} \beta(\{E\}) \end{aligned}$$

The term *id* simply propagates its input, so it will also propagate any exceptional values. The term *const*  $\perp^E$  discards its input and will always return the exceptional value  $\perp^E$ . This behavior is also reflected in their exception types.

If we apply *map* to *id* we need to unify the exception type of the formal parameter  $\forall e_1. \alpha(e_1) \xrightarrow{e_3} \beta(e_2 \ e_1)$  with the exception type of the actual parameter  $\forall e_1. \alpha(e_1) \xrightarrow{\emptyset} \alpha(e_1)$ . This can be accomplished by instantiating  $e_3$  to  $\emptyset$  and  $e_2$  to  $\lambda x. x$ , as  $(\lambda x. x) \ e_1 \rightsquigarrow e_1$ . This gives us the resulting exception type

$$map \ id : \forall \alpha \ e_4 \ e_5. [\alpha(e_4)](e_5) \rightarrow [\alpha(e_4)](e_5)$$

I.e., mapping the identity function over a list will propagate all existing exceptional values in the list and add no new ones.

If we apply *map* to *const*  $\perp^E$  we need to unify the exception type of the formal parameter with  $\forall e_1. \alpha(e_1) \xrightarrow{\emptyset} \beta(\{E\})$ , which can be accomplished by instantiating  $e_3$  to  $\emptyset$  and  $e_2$  to  $\lambda x. \{E\}$ , as  $(\lambda x. \{E\}) \ e_1 \rightsquigarrow \{E\}$ . This gives us the resulting exception type

$$map \ (const \ \perp^E) : \forall \alpha \beta \ e_4 \ e_5. [\alpha(e_4)](e_5) \rightarrow [\beta(\{E\})](e_5)$$

I.e., mapping the constant exceptional value over a list will discard all existing exceptional values from the list and only output non-

exceptional values or the exceptional value  $\perp^E$  as elements of the lists.

## 1.1 Overview

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

## 1.2 Contributions

- A *type system* that precisely tracks the uncaught exceptions using higher-ranked types.
- An *inference algorithm* that automatically infers such higher-ranked exception types.

## To do.

- **To do.** Untracked exceptions can break information flow security.

## 2. The $\lambda^U$ -calculus

The  $\lambda^U$ -calculus is simply typed  $\lambda$ -calculus extended with a set-union operator and singleton-set and empty-set constants at the term level.

### Types

$$\begin{aligned} \tau \in \mathbf{Ty} & ::= \mathcal{P} && \text{(base type)} \\ & | \tau_1 \rightarrow \tau_2 && \text{(function type)} \end{aligned}$$

### Terms

$$\begin{aligned} t \in \mathbf{Tm} & ::= x, y, \dots && \text{(variable)} \\ & | \lambda x : \tau. t && \text{(abstraction)} \\ & | t_1 \ t_2 && \text{(application)} \\ & | \emptyset && \text{(empty)} \\ & | \{c\} && \text{(singleton)} \\ & | t_1 \cup t_2 && \text{(union)} \end{aligned}$$

### Environments

$$\Gamma \in \mathbf{Env} ::= \cdot \quad | \quad \Gamma, x : \tau$$

## 2.1 Typing relation

The typing relation of the  $\lambda^U$ -calculus is an extension of the simply types  $\lambda$ -calculus' typing relation.

$$\begin{array}{c}
\frac{}{\Gamma, x : \tau \vdash x : \tau} [\text{T-VAR}] \quad \frac{\Gamma, x : \tau_1 \vdash t : \tau_2}{\Gamma \vdash \lambda x : \tau_1. t : \tau_1 \rightarrow \tau_2} [\text{T-ABS}] \\
\\
\frac{\Gamma \vdash t_1 : \tau_1 \rightarrow \tau_2 \quad \Gamma \vdash t_2 : \tau_1}{\Gamma \vdash t_1 t_2 : \tau_2} [\text{T-APP}] \\
\\
\frac{}{\Gamma \vdash \emptyset : \mathcal{P}} [\text{T-EMPTY}] \quad \frac{}{\Gamma \vdash \{c\} : \mathcal{P}} [\text{T-CON}] \\
\\
\frac{\Gamma \vdash t_1 : \tau \quad \Gamma \vdash t_2 : \tau}{\Gamma \vdash t_1 \cup t_2 : \tau} [\text{T-UNION}]
\end{array}$$

The empty-set and singleton-set constants are of base type and we can only take the set-union of two terms if they have the same type.

## 2.2 Semantics

TO DO.

## 2.3 Normalization

TO DO: Do we *need* to distribute unions over applications? Is a performance optimization? Do we lose any precision? If not, because terms can't inspect their arguments?

To reduce  $\lambda^U$ -terms to a normal form we combine the  $\beta$ -reduction rule of the simply typed  $\lambda$ -calculus with rewrite rules that deal with the associativity, commutativity, idempotence and identity (ACI1) properties of set-union operator.

If a term  $t$  is  $\eta$ -long it can be written in the form

$$t = \lambda x_1 \cdots x_n. \{f_1(t_{11}, \dots, t_{1q_1}), \dots, f_p(t_{p1}, \dots, t_{pq_p})\}$$

where  $f_i$  can be a free or bound variable, a singleton-set constant, or another  $\eta$ -long term; and  $q_i$  is equal to the arity of  $f_i$  (for all  $1 \leq i \leq p$ ). The notation  $\{f_1(t_{11}, \dots, t_{1q_1}), \dots, f_p(t_{p1}, \dots, t_{pq_p})\}$  is a shorthand for  $f_1(t_{11}, \dots, t_{1q_1}) \cup \dots \cup f_p(t_{p1}, \dots, t_{pq_p})$ , where we forget the associativity of the set-union operator and any empty-set constants. Note that despite the suggestive notation, this is not a true set, as there may still be duplicate elements  $f_i(t_{i1}, \dots, t_{iq_i})$ .

A normal form  $v$  of a term  $t$  can be written as

$$v = \lambda x_1 \cdots x_n. \{k_1(v_{11}, \dots, v_{1q_1}), \dots, k_p(v_{p1}, \dots, v_{pq_p})\}$$

where  $k_i$  can be a free or bound variable, or a singleton-set constant, but not a term as this would form a  $\beta$ -redex.<sup>1</sup> For each  $k_i, k_j$  with  $i < j$  we must also have that  $k_i < k_j$  for some total order on **Var**  $\cup$  **Con**. Not only does this imply that each term  $k_i(v_{i1}, \dots, v_{iq_i})$  occurs only once in  $k_1(v_{11}, \dots, v_{1q_1}), \dots, k_p(v_{p1}, \dots, v_{pq_p})$ , but also the stronger condition that  $k_i \neq k_j$  for all  $i \neq j$ .

## 3. Completion

$$\begin{array}{ll}
\kappa \in \mathbf{Kind} & ::= \text{EXN} \quad (\text{exception}) \\
& | \quad \kappa_1 \Rightarrow \kappa_2 \quad (\text{exception operator}) \\
\\
\varphi \in \mathbf{Exn} & ::= e \quad (\text{exception variables}) \\
& | \quad \lambda e : \kappa. \varphi \quad (\text{exception abstraction})
\end{array}$$

<sup>1</sup>Technically, terms that bind at least one variable would form a  $\beta$ -redex. Terms that do not bind any variables do not occur either as they merely form a subsequence of  $k_1(v_{11}, \dots, v_{1q_1}), \dots, k_p(v_{p1}, \dots, v_{pq_p})$  in this notation.

```

-- normalization of terms
||·|| : Tm → Nf
||λx1 ... xn.T|| =
  λx1 ... xn. { [fi(||ti1||, ..., ||tiqi||)] | fi(ti1, ..., tiqi) ∈ T }
-- β-reduction
[k(v1, ..., vq)]
= k(v1, ..., vq)
[(λy1 ... yq.T) (v1, ..., vq)]
= SUBST x y z
-- set-rewriting
{ { ... , ki(...) , ... , kj(...) , ... } }
| kj < ki = { { ... , ki(...) , ... , kj(...) , ... } }
{ { ... , ki(...) , kj(...) , ... } }
= { { ... , ki(...) , ... } }
{ T }
= T

```

Figure 1. Normalization algorithm for  $\lambda^U$ -terms.

$$\begin{array}{ll}
\widehat{\tau} \in \mathbf{ExnTy} & ::= \forall e :: \kappa. \widehat{\tau} \quad (\text{exception quantification}) \\
& | \quad \mathbf{bool} \quad (\text{boolean type}) \\
& | \quad [\widehat{\tau}(\varphi)] \quad (\text{list type}) \\
& | \quad \widehat{\tau}_1(\varphi_1) \rightarrow \widehat{\tau}_2(\varphi_2) \quad (\text{function type})
\end{array}$$

The completion procedure as a set of inference rules:

$$\begin{array}{c}
\frac{}{\overline{e_i} :: \kappa_i \vdash \mathbf{bool} : \mathbf{bool} \ \& \ e \ \overline{e_i} \triangleright e :: \kappa_i \Rightarrow \text{EXN}} [\text{C-BOOL}] \\
\\
\frac{\overline{e_i} :: \kappa_i \vdash \tau : \widehat{\tau} \ \& \ \varphi \triangleright \overline{e_j} :: \kappa_j}{\overline{e_i} :: \kappa_i \vdash [\tau] : [\widehat{\tau}(\varphi)] \ \& \ e \ \overline{e_i} \triangleright e :: \kappa_i \Rightarrow \text{EXN}, \overline{e_j} :: \kappa_j} [\text{C-LIST}] \\
\\
\frac{\vdash \tau_1 : \widehat{\tau}_1 \ \& \ \varphi_1 \triangleright \overline{e_j} :: \kappa_j \quad \overline{e_i} :: \kappa_i, \overline{e_j} :: \kappa_j \vdash \tau_2 : \widehat{\tau}_2 \ \& \ \varphi_2 \triangleright \overline{e_j} :: \kappa_j}{\overline{e_i} :: \kappa_i \vdash \tau_1 \rightarrow \tau_2 : \forall \overline{e_j} :: \kappa_j. (\widehat{\tau}_1(\varphi_1) \rightarrow \widehat{\tau}_2(\varphi_2)) \ \& \ e \ \overline{e_i} \triangleright e :: \kappa_j \Rightarrow \text{EXN}, \overline{e_k} :: \kappa_k}
\end{array}$$

Figure 2. Type completion ( $\Gamma \vdash \tau : \widehat{\tau} \ \& \ \varphi \triangleright \Gamma'$ )

The completion procedure as an algorithm:

```

C :: Env × Ty → ExnTy × Exn × Env
C  $\overline{e_i} :: \kappa_i$  bool =
  let  $e$  be fresh
  in ( $\mathbf{bool}$ ;  $e \ \overline{e_i}$ ;  $e :: \kappa_i \Rightarrow \text{EXN}$ )

```

## 4. Type system

### 4.1 Terms

$t \in \mathbf{Tm}$	$::=$	$x$	(term variable)
		$c_\tau$	(term constant)
		$\lambda x : \tau. t$	(term abstraction)
		$t_1 t_2$	(term application)
		$t_1 \oplus t_2$	(operator)
		<b>if</b> $t_1$ <b>then</b> $t_2$ <b>else</b> $t_3$	(conditional)
		$\downarrow_\tau^\ell$	(exception constant)
		$t_1 \mathbf{seq} t_2$	(forcing)
		<b>fix</b> $t$	(anonymous fixpoint)
		$\llbracket_\tau$	(nil constructor)
		$t_1 :: t_2$	(cons constructor)
		<b>case</b> $t_1$ <b>of</b> $\{\llbracket \cdot \rrbracket \mapsto t_2; x_1 :: x_2 \mapsto t_3\}$	(list eliminator)

### 4.2 Underlying type system

$\frac{}{\Gamma, x : \tau \vdash x : \tau}$ [T-VAR]	$\frac{}{\Gamma \vdash c_\tau : \tau}$ [T-CON]	$\frac{}{\Gamma \vdash \downarrow_\tau^\ell : \tau}$ [T-CRASH]
$\frac{\Gamma, x : \tau_1 \vdash t : \tau_2}{\Gamma \vdash \lambda x : \tau_1. t : \tau_1 \rightarrow \tau_2}$ [T-ABS]	$\frac{\Gamma \vdash t_1 : \tau_2 \rightarrow \tau \quad \Gamma \vdash t_2 : \tau_2}{\Gamma \vdash t_1 t_2 : \tau}$ [T-APP]	
$\frac{\Gamma \vdash t : \tau \rightarrow \tau}{\Gamma \vdash \mathbf{fix} t : \tau}$ [T-FIX]		
$\frac{\Gamma \vdash t_1 : \mathbf{int} \quad \Gamma \vdash t_2 : \mathbf{int}}{\Gamma \vdash t_1 \oplus t_2 : \mathbf{bool}}$ [T-OP]	$\frac{\Gamma \vdash t_1 : \tau_1 \quad \Gamma \vdash t_2 : \tau_2}{\Gamma \vdash t_1 \mathbf{seq} t_2 : \tau_2}$ [T-SEQ]	
$\frac{\Gamma \vdash t_1 : \mathbf{bool} \quad \Gamma \vdash t_2 : \tau \quad \Gamma \vdash t_3 : \tau}{\Gamma \vdash \mathbf{if} t_1 \mathbf{then} t_2 \mathbf{else} t_3 : \tau}$ [T-IF]		
$\frac{}{\Gamma \vdash \llbracket_\tau : [\tau]}$ [T-NIL]	$\frac{\Gamma \vdash t_1 : \tau \quad \Gamma \vdash t_2 : [\tau]}{\Gamma \vdash t_1 :: t_2 : [\tau]}$ [T-CONS]	
$\frac{\Gamma \vdash t_1 : [\tau_1] \quad \Gamma \vdash t_2 : \tau \quad \Gamma, x_1 : \tau_1, x_2 : [\tau_1] \vdash t_3 : \tau}{\Gamma \vdash \mathbf{case} t_1 \mathbf{of} \{\llbracket \cdot \rrbracket \mapsto t_2; x_1 :: x_2 \mapsto t_3\} : \tau}$ [T-CASE]		

### 4.3 Declarative exception type system

$\frac{}{\Gamma, x : \hat{\tau} \& \varphi; \Delta \vdash x : \hat{\tau} \& \varphi}$ [T-VAR]	
$\frac{}{\Gamma; \Delta \vdash c_\tau : \perp_\tau \& \emptyset}$ [T-CON]	$\frac{}{\Gamma; \Delta \vdash \downarrow_\tau^\ell : \perp_\tau \& \{\ell\}}$ [T-CRASH]
$\frac{\Gamma, x : \hat{\tau}_1 \& \varphi_1; \Delta \vdash t : \hat{\tau}_2 \& \varphi_2}{\Gamma; \Delta \vdash \lambda x : \hat{\tau}_1 \& \varphi_1. t : \hat{\tau}_1 \langle \varphi_1 \rangle \rightarrow \hat{\tau}_2 \langle \varphi_2 \rangle \& \emptyset}$ [T-ABS]	
$\frac{\Gamma; \Delta, e : \kappa \vdash t : \hat{\tau} \& \varphi \quad e \notin \text{fv}(\varphi)}{\Gamma; \Delta \vdash \Lambda e : \kappa. t : \forall e : \kappa. \hat{\tau} \& \varphi}$ [T-ANNABS]	
$\frac{\Gamma; \Delta \vdash t_1 : \hat{\tau}_2 \langle \varphi_2 \rangle \rightarrow \hat{\tau} \langle \varphi \rangle \& \varphi \quad \Gamma; \Delta \vdash t_2 : \hat{\tau}_2 \& \varphi_2}{\Gamma; \Delta \vdash t_1 t_2 : \hat{\tau} \& \varphi}$ [T-APP]	
$\frac{\Gamma; \Delta \vdash t_1 : \forall e : \kappa. \hat{\tau} \& \varphi \quad \Delta \vdash \varphi_2 : \kappa}{\Gamma; \Delta \vdash t_1 \langle \varphi_2 \rangle : \hat{\tau} \langle \varphi_2 / e \rangle \& \varphi}$ [T-ANNAAPP]	
$\frac{\Gamma; \Delta \vdash t : \hat{\tau} \langle \varphi' \rangle \rightarrow \hat{\tau} \langle \varphi' \rangle \& \varphi'' \quad \Delta \vdash \varphi' \leq \varphi \quad \Delta \vdash \varphi'' \leq \varphi}{\Gamma; \Delta \vdash \mathbf{fix} t : \hat{\tau} \& \varphi}$ [T-FIX]	
$\frac{\Gamma; \Delta \vdash t_1 : \mathbf{int} \& \varphi \quad \Gamma; \Delta \vdash t_2 : \mathbf{int} \& \varphi}{\Gamma; \Delta \vdash t_1 \oplus t_2 : \mathbf{bool} \& \varphi}$ [T-OP]	
$\frac{\Gamma; \Delta \vdash t_1 : \hat{\tau}_1 \& \varphi \quad \Gamma; \Delta \vdash t_2 : \hat{\tau}_2 \& \varphi}{\Gamma; \Delta \vdash t_1 \mathbf{seq} t_2 : \hat{\tau}_2 \& \varphi}$ [T-SEQ]	
$\frac{\Gamma; \Delta \vdash t_1 : \mathbf{bool} \& \varphi \quad \Gamma; \Delta \vdash t_2 : \hat{\tau} \& \varphi \quad \Gamma; \Delta \vdash t_3 : \hat{\tau} \& \varphi}{\Gamma; \Delta \vdash \mathbf{if} t_1 \mathbf{then} t_2 \mathbf{else} t_3 : \hat{\tau} \& \varphi}$ [T-IF]	
$\frac{}{\Gamma; \Delta \vdash \llbracket_\tau : [\perp_\tau \langle \emptyset \rangle] \& \emptyset}$ [T-NIL]	
$\frac{\Gamma; \Delta \vdash t_1 : \hat{\tau} \& \varphi_1 \quad \Gamma; \Delta \vdash t_2 : [\hat{\tau} \langle \varphi_1 \rangle] \& \varphi_2}{\Gamma; \Delta \vdash t_1 :: t_2 : [\hat{\tau} \langle \varphi_1 \rangle] \& \varphi_2}$ [T-CONS]	
$\frac{\Gamma; \Delta \vdash t_1 : [\hat{\tau}_1 \langle \varphi_1 \rangle] \& \varphi' \quad \Delta \vdash \varphi' \leq \varphi \quad \Gamma; \Delta \vdash t_2 : \hat{\tau} \& \varphi}{\Gamma; \Delta \vdash \mathbf{case} t_1 \mathbf{of} \{\llbracket \cdot \rrbracket \mapsto t_2; x_1 :: x_2 \mapsto t_3\} : \hat{\tau} \& \varphi}$ [T-CASE]	
$\frac{\Gamma; \Delta \vdash t : \hat{\tau}' \& \varphi' \quad \Delta \vdash \hat{\tau}' \leq \hat{\tau} \quad \Delta \vdash \varphi' \leq \varphi}{\Gamma; \Delta \vdash t : \hat{\tau} \& \varphi}$ [T-SUB]	

- In T-Abs and T-AnnAbs, should the term-level term-abstraction also have an explicit effect annotation?
- In T-AnnAbs, might need a side condition stating that  $e$  is not free in  $\Delta$ .
- In T-App, note the double occurrence of  $\varphi$  when typing  $t_1$ . Is subeffecting sufficient here? Also note that we do *not* expect an exception variable in the left-hand side annotation of the function space constructor.
- In T-AnnApp, note the substitution. We will need a substitution lemma for annotations.
- In T-Fix, there might be some universal quantifiers in our way. Do annotation applications in  $t$  take care of this, already? Perhaps we do need to change **fix**  $t$  into a binding construct to resolve this? Also, there is some implicit subeffecting going on between the annotations and effect.
- In T-Case, note the use of explicit subeffecting. Can this be done using implicit subeffecting?

- For T-Sub, should we introduce a term-level coercion, as in Dussart–Henglein–Mossin? We now do shape-conformant subtyping, is subeffecting sufficient?
- Do we need additional kinding judgements in some of the rules? Can we merge the kinding judgement with the subtyping and/or -effecting judgement? Kind-preserving substitutions.

#### 4.4 Type elaboration system

- In T-APP and T-Fix, note that there are substitutions in the premises of the rules. Are these inductive? (Probably, as these premises are not “recursive” ones.)

$$\begin{array}{c}
\frac{}{\Gamma, x : \widehat{\tau} \& \varphi; \Delta \vdash x \hookrightarrow x : \widehat{\tau} \& \varphi} \text{[T-VAR]} \\
\frac{}{\Gamma; \Delta \vdash c_\tau \hookrightarrow c_\tau : \tau \& \emptyset} \text{[T-CON]} \quad \frac{}{\Gamma; \Delta \vdash \frac{\ell}{\tau} \hookrightarrow \frac{\ell}{\tau} : \perp_\tau \& \{\ell\}} \text{[T-CRASH]} \\
\frac{\Delta, \overline{e_i} : \kappa_i \vdash \widehat{\tau}_1 \triangleright \tau_1 \quad \Delta, \overline{e_i} : \kappa_i \vdash \varphi_1 : \text{EXN} \quad \Gamma, x : \widehat{\tau}_1 \& \varphi_1; \Delta, \overline{e_i} : \kappa_i \vdash t \hookrightarrow t' : \widehat{\tau}_2 \& \varphi_2}{\Gamma; \Delta \vdash \lambda x : \tau_1. t \hookrightarrow \lambda \overline{e_i} : \kappa_i. \lambda x : \widehat{\tau}_1 \& \varphi_1. t' : \forall \overline{e_i} : \kappa_i. \widehat{\tau}_1(\varphi_1) \rightarrow \widehat{\tau}_2(\varphi_2) \& \emptyset} \text{[T-ABS]} \\
\frac{\Delta \vdash \widehat{\tau}_2 \leq \widehat{\tau}[\overline{e_i}/\overline{e_i}] \quad \Delta \vdash \varphi_2 \leq \varphi[\overline{e_i}/\overline{e_i}] \quad \overline{\Delta \vdash \varphi_i : \kappa_i}}{\Gamma; \Delta \vdash t_1 \hookrightarrow t'_1 : \forall \overline{e_i} : \kappa_i. \widehat{\tau}_1(\varphi_1) \rightarrow \widehat{\tau}(\varphi) \& \varphi' \quad \Gamma; \Delta \vdash t_2 \hookrightarrow t'_2 : \widehat{\tau}_2 \& \varphi_2} \text{[T-APP]} \\
\frac{\Gamma; \Delta \vdash t_1 \hookrightarrow t'_1 : \widehat{\tau}_1(\varphi_1) \rightarrow \widehat{\tau}(\varphi) \& \varphi' \quad \Gamma; \Delta \vdash t_2 \hookrightarrow t'_2 : \widehat{\tau}_2 \& \varphi_2}{\Gamma; \Delta \vdash t_1 t_2 \hookrightarrow t'_1(\varphi_1) t'_2 : \widehat{\tau}[\overline{e_i}/\overline{e_i}] \& \varphi[\overline{e_i}/\overline{e_i}] \cup \varphi'} \text{[T-APP]} \\
\frac{\Gamma; \Delta \vdash t \hookrightarrow t' : \forall \overline{e_i} : \kappa_i. \widehat{\tau}(\varphi) \rightarrow \widehat{\tau}'(\varphi') \& \varphi'' \quad \Delta \vdash \widehat{\tau}'[\overline{e_i}/\overline{e_i}] \leq \widehat{\tau}[\overline{e_i}/\overline{e_i}] \quad \Delta \vdash \varphi'[\overline{e_i}/\overline{e_i}] \leq \varphi[\overline{e_i}/\overline{e_i}] \quad \overline{\Delta \vdash \varphi_i : \kappa_i}}{\Gamma; \Delta \vdash \mathbf{fix} \ t \hookrightarrow \mathbf{fix} \ t' : \widehat{\tau}[\overline{e_i}/\overline{e_i}] \& \varphi[\overline{e_i}/\overline{e_i}] \cup \varphi''} \text{[T-FIX]} \\
\frac{\Gamma; \Delta \vdash t_1 \hookrightarrow t'_1 : \widehat{\mathbf{int}} \& \varphi_1 \quad \Gamma; \Delta \vdash t_2 \hookrightarrow t'_2 : \widehat{\mathbf{int}} \& \varphi_2}{\Gamma; \Delta \vdash t_1 \oplus t_2 \hookrightarrow t'_1 \oplus t'_2 : \widehat{\mathbf{bool}} \& \varphi_1 \cup \varphi_2} \text{[T-OP]} \\
\frac{\Gamma; \Delta \vdash t_1 \hookrightarrow t'_1 : \widehat{\tau}_1 \& \varphi_1 \quad \Gamma; \Delta \vdash t_2 \hookrightarrow t'_2 : \widehat{\tau}_2 \& \varphi_2}{\Gamma; \Delta \vdash t_1 \mathbf{seq} \ t_2 \hookrightarrow t'_1 \mathbf{seq} \ t'_2 : \widehat{\tau}_1 \cup \widehat{\tau}_2 \& \varphi_1 \cup \varphi_2} \text{[T-SEQ]} \\
\frac{\Gamma; \Delta \vdash t_1 \hookrightarrow t'_1 : \widehat{\mathbf{bool}} \& \varphi_1 \quad \Gamma; \Delta \vdash t_2 \hookrightarrow t'_2 : \widehat{\tau}_2 \& \varphi_2 \quad \Gamma; \Delta \vdash t_3 \hookrightarrow t'_3 : \widehat{\tau}_3 \& \varphi_3}{\Gamma; \Delta \vdash \mathbf{if} \ t_1 \mathbf{then} \ t_2 \mathbf{else} \ t_3 \hookrightarrow \mathbf{if} \ t'_1 \mathbf{then} \ t'_2 \mathbf{else} \ t'_3 : \widehat{\tau}_1 \cup \widehat{\tau}_2 \& \varphi_1 \cup \varphi_2 \cup \varphi_3} \text{[T-IF]}
\end{array}$$

$$\frac{}{\Gamma; \Delta \vdash \perp_\tau \hookrightarrow \perp_\tau : \perp_\tau \& \emptyset} \text{[T-NIL]}$$

$$\frac{\Gamma; \Delta \vdash t_1 \hookrightarrow t'_1 : \widehat{\tau}_1 \& \varphi_1 \quad \Gamma; \Delta \vdash t_2 \hookrightarrow t'_2 : [\widehat{\tau}'_1(\varphi'_1)] \& \varphi_2}{\Gamma; \Delta \vdash t_1 :: t_2 \hookrightarrow t'_1 :: t'_2 : [\widehat{\tau}_1 \sqcup \widehat{\tau}'_1(\varphi_1 \cup \varphi'_1)] \& \varphi_2} \text{[T-CONS]}$$

$$\begin{array}{c}
\Gamma; \Delta \vdash t_1 \hookrightarrow t'_1 : [\tau_1(\varphi_1)] \& \varphi'_1 \quad \Gamma; \Delta \vdash t_2 \hookrightarrow t'_2 : \widehat{\tau}_2 \& \varphi_2 \\
\Gamma, x_1 : \widehat{\tau}_1 \& \varphi_1, x_2 : [\tau_1(\varphi_1)] \& \varphi'_1; \Delta \vdash t_3 \hookrightarrow t'_3 : \widehat{\tau}_3 \& \varphi_3 \\
\hline
\Gamma; \Delta \vdash \mathbf{case} \ t_1 \mathbf{of} \ \{\square \mapsto t_2; x_1 :: x_2 \mapsto t_3\} \hookrightarrow \\
\mathbf{case} \ t'_1 \mathbf{of} \ \{\square \mapsto t'_2; x_1 :: x_2 \mapsto t'_3\} : \widehat{\tau}_2 \sqcup \widehat{\tau}_3 \& \varphi'_1 \cup \varphi_2 \cup \varphi_3
\end{array}$$

- For T-Fix: how would a binding fixpoint construct work?

#### 4.5 Type inference algorithm

$$\mathcal{R} : \mathbf{TyEnv} \times \mathbf{KiEnv} \times \mathbf{Tm} \rightarrow \mathbf{ExnTy} \times \mathbf{Exn}$$

$$\mathcal{R} \ \Gamma \ \Delta \ x = \Gamma_x$$

$$\mathcal{R} \ \Gamma \ \Delta \ c_\tau = \langle \perp_\tau; \emptyset \rangle$$

$$\mathcal{R} \ \Gamma \ \Delta \ \frac{\ell}{\tau} = \langle \perp_\tau; \{\ell\} \rangle$$

$$\mathcal{R} \ \Gamma \ \Delta \ (\lambda x : \tau. t) = \mathbf{let} \ (\widehat{\tau}_1; e_1; \overline{e_i} : \kappa_i) = \mathcal{C} \ \emptyset \ \tau \ (\widehat{\tau}_2; \varphi_2) = \mathcal{R} \ (\Gamma, x : \widehat{\tau}_1 \& e_1) \ (\Delta, \overline{e_i} : \kappa_i)$$

$$\begin{array}{c}
\mathcal{R} \ \Gamma \ \Delta \ (t_1 \ t_2) = \mathbf{let} \ (\widehat{\tau}_1; \varphi_1) = \mathcal{R} \ \Gamma \ \Delta \ t_1 \ (\widehat{\tau}_2; \varphi_2) = \mathcal{R} \ \Gamma \ \Delta \ t_2 \ (\widehat{\tau}'_2(e'_2) \rightarrow \widehat{\tau}'(\varphi'); \overline{e_i} : \kappa_i) = \mathcal{I} \ \widehat{\tau}_1 \ \theta = [e'_2 \mapsto \varphi_2] \circ \mathcal{M} \ \emptyset \ \widehat{\tau}_2 \ \widehat{\tau}'_2 \\
\mathbf{in} \ (\llbracket \theta \widehat{\tau}' \rrbracket_\Delta; \llbracket \theta \varphi' \cup \varphi_1 \rrbracket_\Delta) \\
\mathcal{R} \ \Gamma \ \Delta \ (\mathbf{fix} \ t) = \mathbf{let} \ (\widehat{\tau}; \varphi) = \mathcal{R} \ \Gamma \ \Delta \ t \ (\widehat{\tau}'(e') \rightarrow \widehat{\tau}''(\varphi''); \overline{e_i} : \kappa_i) = \mathcal{I} \ \widehat{\tau} \\
\mathbf{in} \ (\widehat{\tau}_0; \varphi_0; i) \leftarrow \langle \perp_{[\widehat{\tau}]}; \emptyset; 0 \rangle \\
\mathbf{do} \ \theta \leftarrow [e' \mapsto \varphi_i] \circ \mathcal{M} \ \emptyset \ \widehat{\tau}_i \ \widehat{\tau}' \\
(\widehat{\tau}_{i+1}; \varphi_{i+1}; i) \leftarrow \langle \llbracket \theta \widehat{\tau}'' \rrbracket_\Delta; \llbracket \theta \varphi'' \rrbracket_\Delta; i+1 \rangle \\
\mathbf{until} \ (\widehat{\tau}_i; \varphi_i) \equiv (\widehat{\tau}_{i-1}; \varphi_{i-1}) \\
\mathbf{return} \ (\widehat{\tau}_i; \llbracket \varphi \cup \varphi_i \rrbracket_\Delta) \\
\mathcal{R} \ \Gamma \ \Delta \ (t_1 \oplus t_2) = \mathbf{let} \ (\widehat{\mathbf{int}}; \varphi_1) = \mathcal{R} \ \Gamma \ \Delta \ t_1 \ (\widehat{\mathbf{int}}; \varphi_2) = \mathcal{R} \ \Gamma \ \Delta \ t_2 \\
\mathbf{in} \ (\widehat{\mathbf{bool}}; \llbracket \varphi_1 \cup \varphi_2 \rrbracket_\Delta) \\
\mathcal{R} \ \Gamma \ \Delta \ (t_1 \mathbf{seq} \ t_2) = \mathbf{let} \ (\widehat{\tau}_1; \varphi_1) = \mathcal{R} \ \Gamma \ \Delta \ t_1 \ (\widehat{\tau}_2; \varphi_2) = \mathcal{R} \ \Gamma \ \Delta \ t_2 \\
\mathbf{in} \ (\widehat{\tau}_2; \llbracket \varphi_1 \cup \varphi_2 \rrbracket_\Delta) \\
\mathcal{R} \ \Gamma \ \Delta \ (\mathbf{if} \ t_1 \mathbf{then} \ t_2 \mathbf{else} \ t_3) = \mathbf{let} \ (\widehat{\mathbf{bool}}; \varphi_1) = \mathcal{R} \ \Gamma \ \Delta \ t_1 \ (\widehat{\tau}_2; \varphi_2) = \mathcal{R} \ \Gamma \ \Delta \ t_2 \ (\widehat{\tau}_3; \varphi_3) = \mathcal{R} \ \Gamma \ \Delta \ t_3 \\
\mathbf{in} \ (\llbracket \widehat{\tau}_2 \sqcup \widehat{\tau}_3 \rrbracket_\Delta; \llbracket \varphi_1 \cup \varphi_2 \cup \varphi_3 \rrbracket_\Delta) \\
\mathcal{R} \ \Gamma \ \Delta \ \perp_\tau = \langle \llbracket \perp_\tau \rrbracket_\Delta; \emptyset \rangle \\
\mathcal{R} \ \Gamma \ \Delta \ (t_1 :: t_2) = \mathbf{let} \ (\widehat{\tau}_1; \varphi_1) = \mathcal{R} \ \Gamma \ \Delta \ t_1 \ (\llbracket \widehat{\tau}_2(\varphi'_2) \rrbracket_\Delta; \varphi_2) = \mathcal{R} \ \Gamma \ \Delta \ t_2 \\
\mathbf{in} \ (\llbracket (\widehat{\tau}_1 \sqcup \widehat{\tau}_2)(\varphi_1 \cup \varphi'_2) \rrbracket_\Delta; \varphi_2) \\
\mathcal{R} \ \Gamma \ \Delta \ (\mathbf{case} \ t_1 \mathbf{of} \ \{\square \mapsto t_2; x_1 :: x_2 \mapsto t_3\}) = \mathbf{let} \ (\widehat{\tau}_1(\varphi'_1); \varphi_1) = \mathcal{R} \ \Gamma \ \Delta \ t_1 \ (\widehat{\tau}_2; \varphi_2) = \mathcal{R} \ (\Gamma, x_1 : \widehat{\tau}_1 \& \varphi'_1, x_2 : [\widehat{\tau}_1(\varphi'_1)] \& \varphi_1) \ (\widehat{\tau}_3; \varphi_3) = \mathcal{R} \ \Gamma \ \Delta \ t_3 \\
\mathbf{in} \ (\llbracket \widehat{\tau}_2 \sqcup \widehat{\tau}_3 \rrbracket_\Delta; \llbracket \varphi_1 \cup \varphi_2 \cup \varphi_3 \rrbracket_\Delta)
\end{array}$$

- In R-App and R-Fix: check that the fresh variables generated by  $\mathcal{I}$  are substituted away by the substitution  $\theta$  created by  $\mathcal{M}$ . Also, we don't need those variables in the algorithm if we don't generate the elaborated term.

- In R-Fix we could get rid of the auxillary underlying type function if the fixpoint construct was replaced with a binding variant with an explicit type annotation.

- **[ToCRSE]**, make sure the way we handle fixpoints of exceptional value in a manner that is sound w.r.t. to the operational semantics we are going to give to this.

- Note that we do not construct the elaborated term, as it is not useful other than for metatheoretic purposes.

- Lemma: The algorithm maintains the invariant that exception types and exceptions are in normal form.

#### 4.6 Subtyping

- Is S-REFL an admissible/derivable rule, or should we drop

$$\frac{}{\Delta \vdash \widehat{\tau} \leq \widehat{\tau}} [\text{S-REFL}] \quad \frac{\Delta \vdash \widehat{\tau}_1 \leq \widehat{\tau}_2 \quad \Delta \vdash \widehat{\tau}_2 \leq \widehat{\tau}_3}{\Delta \vdash \widehat{\tau}_1 \leq \widehat{\tau}_3} [\text{S-TRANS}]$$

$$\frac{}{\Delta \vdash \widehat{\mathbf{bool}} \leq \widehat{\mathbf{bool}}} [\text{S-BOOL}] \quad \frac{}{\Delta \vdash \widehat{\mathbf{int}} \leq \widehat{\mathbf{int}}} [\text{S-INT}]$$

$$\frac{\Delta \vdash \widehat{\tau}_1 \leq \widehat{\tau}_1 \quad \Delta \vdash \varphi'_1 \leq \varphi_1 \quad \Delta \vdash \widehat{\tau}_2 \leq \widehat{\tau}'_2 \quad \Delta \vdash \varphi_2 \leq \varphi'_2}{\Delta \vdash \widehat{\tau}_1 \langle \varphi_1 \rangle \rightarrow \widehat{\tau}_2 \langle \varphi_2 \rangle \leq \widehat{\tau}'_1 \langle \varphi'_1 \rangle \rightarrow \widehat{\tau}'_2 \langle \varphi'_2 \rangle} [\text{S-ARR}]$$

$$\frac{\Delta \vdash \widehat{\tau} \leq \widehat{\tau}' \quad \Delta \vdash \varphi \leq \varphi'}{\Delta \vdash [\widehat{\tau} \langle \varphi \rangle] \leq [\widehat{\tau}' \langle \varphi' \rangle]} [\text{S-LIST}] \quad \frac{\Delta, e : \kappa \vdash \widehat{\tau}_1 \leq \widehat{\tau}_2}{\Delta \vdash \forall e : \kappa. \widehat{\tau}_1 \leq \forall e : \kappa. \widehat{\tau}_2} [\text{S-FORALL}]$$

- Possibly useful lemma:  $\widehat{\tau}_1 = \widehat{\tau}_2 \iff \widehat{\tau}_1 \leq \widehat{\tau}_2 \wedge \widehat{\tau}_2 \leq \widehat{\tau}_1$ .

## 5. Operational semantics

### 5.1 Evaluation

- The reduction relation is non-deterministic.
- We do not have a Haskell-style imprecise exception semantics (e.g. E-IF).
- We either need to omit the type annotations on  $\frac{\ell}{\tau}$ , or add them to **if then else** and **case of**  $\{\llbracket \cdot \rrbracket \mapsto \cdot\}$ .
- We do not have a rule E-ANNAPPEXN. Check that the canonical forms lemma gives us that terms of universally quantified type cannot be exceptional values.

## 6. Interesting observations

- Exception types are not invariant under  $\eta$ -reduction.

## 7. Metatheory

### 7.1 Declarative type system

**Lemma 1** (Canonical forms).

1. If  $\widehat{v}$  is a possibly exceptional value of type  $\widehat{\mathbf{bool}}$ , then  $\widehat{v}$  is either **true**, **false**, or  $\frac{\ell}{\tau}$ .
2. If  $\widehat{v}$  is a possibly exceptional value of type  $\widehat{\mathbf{int}}$ , then  $\widehat{v}$  is either some integer  $n$ , or an exceptional value  $\frac{\ell}{\tau}$ .
3. If  $\widehat{v}$  is a possibly exceptional value of type  $[\widehat{\tau} \langle \varphi \rangle]$ , then  $\widehat{v}$  is either  $\llbracket \cdot \rrbracket$ ,  $t :: t'$ , or  $\frac{\ell}{\tau}$ .
4. If  $\widehat{v}$  is a possibly exceptional value of type  $\widehat{\tau}_1 \langle \varphi_1 \rangle \rightarrow \widehat{\tau}_2 \langle \varphi_2 \rangle$ , then  $\widehat{v}$  is either  $\lambda x : \widehat{\tau}_1 \cdot \varphi_1.t'$  or  $\frac{\ell}{\tau}$ .
5. If  $\widehat{v}$  is a possibly exceptional value of type  $\forall e : \kappa. \widehat{\tau}$ , then  $\widehat{v}$  is  $\Delta e : \kappa.t$ .

*Proof.* For each part, inspect all forms of  $\widehat{v}$  and discard the unwanted cases by inversion of the typing relation. Note that  $\perp_\tau$  cannot give us a type of the form  $\forall e : \kappa. \widehat{\tau}$ .  $\square$

**TO DO.:** Say something about T-SUB?

**Theorem 1** (Progress). *If  $\Gamma; \Delta \vdash t : \widehat{\tau} \& \varphi$  with  $t$  a closed term, then  $t$  is either a possibly exceptional value  $\widehat{v}$  or there is a closed term  $t'$  such that  $t \longrightarrow t'$ .*

*Proof.* By induction on the typing derivation  $\Gamma; \Delta \vdash t : \widehat{\tau} \& \varphi$ .

The case T-VAR can be discarded, as a variable is not a closed term. The cases T-CON, T-CRASH, T-ABS, T-ANNABS, T-NIL and T-CONS are immediate as they are values.

Case T-APP: We can immediately apply the induction hypothesis to  $\Gamma; \Delta \vdash t_1 : \widehat{\tau}_2 \langle \varphi_2 \rangle \rightarrow \widehat{\tau} \langle \varphi \rangle \& \varphi$ , giving us either a  $t'_1$  such that  $t_1 \longrightarrow t'_1$  or that  $t_1 = \widehat{v}$ . In the former case we can make

$$\frac{t_1 \longrightarrow t'_1}{t_1 t_2 \longrightarrow t'_1 t_2} [\text{E-APP}] \quad \frac{}{(\lambda x : \widehat{\tau} \& \varphi.t) t_2 \longrightarrow t_1[t_2/x]} [\text{E-APPABS}]$$

$$\frac{t \longrightarrow t'}{t \langle \varphi \rangle \longrightarrow t' \langle \varphi \rangle} [\text{E-ANNAPP}] \quad \frac{}{(\Delta e : \kappa.t) \langle \varphi \rangle \longrightarrow t[\varphi/e]} [\text{E-ANNABSABS}]$$

$$\frac{t \longrightarrow t'}{\mathbf{fix} \, t \longrightarrow \mathbf{fix} \, t'} [\text{E-FIX}] \quad \frac{}{\mathbf{fix} \, (\lambda x : \widehat{\tau} \& \varphi.t) \longrightarrow t[\mathbf{fix} \, (\lambda x : \widehat{\tau} \& \varphi.t)/x]} [\text{E-FIXABS}]$$

$$\frac{}{\mathbf{fix} \, \frac{\ell}{\tau} \longrightarrow \frac{\ell}{\tau}} [\text{E-FIXEXN}]$$

$$\frac{t_1 \longrightarrow t'_1}{t_1 \oplus t_2 \longrightarrow t'_1 \oplus t_2} [\text{E-OP1}] \quad \frac{t_2 \longrightarrow t'_2}{t_1 \oplus t_2 \longrightarrow t_1 \oplus t'_2} [\text{E-OP2}]$$

$$\frac{}{v_1 \oplus v_2 \longrightarrow \llbracket v_1 \oplus v_2 \rrbracket} [\text{E-OP}]$$

$$\frac{}{\frac{\ell}{\tau} \oplus t_2 \longrightarrow \frac{\ell}{\tau}} [\text{E-OPEXN1}] \quad \frac{}{t_1 \oplus \frac{\ell}{\tau} \longrightarrow \frac{\ell}{\tau}} [\text{E-OPEXN2}]$$

$$\frac{t_1 \longrightarrow t'_1}{t_1 \mathbf{seq} \, t_2 \longrightarrow t'_1 \mathbf{seq} \, t_2} [\text{E-SEQ1}] \quad \frac{}{v_1 \mathbf{seq} \, t_2 \longrightarrow t_2} [\text{E-SEQ2}]$$

$$\frac{}{\frac{\ell}{\tau} \mathbf{seq} \, t_2 \longrightarrow \frac{\ell}{\tau}} [\text{E-SEQEXN}]$$

$$\frac{t_1 \longrightarrow t'_1}{\mathbf{if} \, t_1 \, \mathbf{then} \, t_2 \, \mathbf{else} \, t_3 \longrightarrow \mathbf{if} \, t'_1 \, \mathbf{then} \, t_2 \, \mathbf{else} \, t_3} [\text{E-IF}]$$

$$\frac{}{\mathbf{if} \, \mathbf{true} \, \mathbf{then} \, t_2 \, \mathbf{else} \, t_3 \longrightarrow t_2} [\text{E-IFTRUE}]$$

$$\frac{}{\mathbf{if} \, \mathbf{false} \, \mathbf{then} \, t_2 \, \mathbf{else} \, t_3 \longrightarrow t_3} [\text{E-IFFALSE}]$$

$$\frac{}{\mathbf{if} \, \frac{\ell}{\tau} \, \mathbf{then} \, t_2 \, \mathbf{else} \, t_3 \longrightarrow \frac{\ell}{\tau}} [\text{E-IFEXN}]$$

$$\frac{t_1 \longrightarrow t'_1}{\mathbf{case} \, t_1 \, \mathbf{of} \, \{\llbracket \cdot \rrbracket \mapsto t_2; x_1 :: x_2 \mapsto t_3\} \longrightarrow \mathbf{case} \, t'_1 \, \mathbf{of} \, \{\llbracket \cdot \rrbracket \mapsto t_2; x_1 :: x_2 \mapsto t_3\}} [\text{E-CASE}]$$

$$\frac{}{\mathbf{case} \, \llbracket \cdot \rrbracket \, \mathbf{of} \, \{\llbracket \cdot \rrbracket \mapsto t_2; x_1 :: x_2 \mapsto t_3\} \longrightarrow t_2} [\text{E-CASENIL}]$$

$$\frac{}{\mathbf{case} \, t_1 :: t'_1 \, \mathbf{of} \, \{\llbracket \cdot \rrbracket \mapsto t_2; x_1 :: x_2 \mapsto t_3\} \longrightarrow t_3[t_1/t'_1; x_1/x_2]} [\text{E-CASENIL}]$$

$$\frac{}{\mathbf{case} \, \frac{\ell}{\tau} \, \mathbf{of} \, \{\llbracket \cdot \rrbracket \mapsto t_2; x_1 :: x_2 \mapsto t_3\} \longrightarrow \frac{\ell}{\tau}} [\text{E-CASEEXN}]$$

**Figure 3.** Operational semantics ( $t_1 \longrightarrow t_2$ )

progress using E-APP. In the latter case the canonical forms lemma tells us that either  $t_1 = \lambda x : \widehat{\tau}_2 \& \varphi_2.t'_1$  or  $t_1 = \frac{\ell}{\tau}$ , in which case we can make progress using E-APPABS or E-APPEXN, respectively.

The remaining cases follow by analogous reasoning.  $\square$

**Lemma 2** (Annotation substitution).

1. If  $\Delta, e : \kappa' \vdash \varphi : \kappa$  and  $\Delta \vdash \varphi' : \kappa'$  then  $\Delta \vdash \varphi[\varphi'/e] : \kappa$ .
2. If  $\Delta, e : \kappa' \vdash \varphi_1 \leq \varphi_2$  and  $\Delta \vdash \varphi' : \kappa'$  then  $\Delta \vdash \varphi_1[\varphi'/e] \leq \varphi_2[\varphi'/e]$ .
3. If  $\Delta, e : \kappa' \vdash \widehat{\tau}_1 \leq \widehat{\tau}_2$  and  $\Delta \vdash \varphi' : \kappa'$  then  $\Delta \vdash \widehat{\tau}_1[\varphi'/e] \leq \widehat{\tau}_2[\varphi'/e]$ .
4. If  $\Gamma; \Delta, e : \kappa' \vdash t : \widehat{\tau} \& \varphi$  and  $\Delta \vdash \varphi' : \kappa'$  then  $\Gamma; \Delta \vdash t[\varphi'/e] : \widehat{\tau}[\varphi'/e] \& \varphi$ .

$$\begin{aligned}
e[\varphi/e] &\equiv \varphi \\
e'[\varphi/e] &\equiv e' && \text{if } e \neq e' \\
\{\ell\}[\varphi/e] &\equiv \{\ell\} \\
\emptyset[\varphi/e] &\equiv \emptyset \\
(\lambda e' : \kappa.\varphi')[\varphi/e] &\equiv \lambda e' : \kappa.\varphi'[\varphi/e] && \text{if } e \neq e' \text{ and } e' \notin \text{fv}(\varphi) \\
(e_1 e_2)[\varphi/e] &\equiv (e_1[\varphi/e]) (e_2[\varphi/e]) \\
(e_1 \cup e_2)[\varphi/e] &\equiv e_1[\varphi/e] \cup e_2[\varphi/e]
\end{aligned}$$

**Figure 4.** Annotation substitution

$$\begin{aligned}
x[t/x] &\equiv t \\
x'[t/x] &\equiv x' && \text{if } x \neq x' \\
c_\tau[t/x] &\equiv c_\tau \\
(\lambda x' : \widehat{\tau}.t')[t/x] &\equiv \lambda x' : \widehat{\tau}.t'[t/x] && \text{if } x \neq x' \text{ and } x' \notin \text{fv}(t) \\
&\dots
\end{aligned}$$

**Figure 5.** Term substitution

**TO DO.** In part 4, either we need the assumption  $e \notin \text{fv}(\varphi)$  (which seems to be satisfied everywhere we want to apply this lemma), or we also need to apply the substitution to  $\varphi$  (is this expected or not in a type-and-effect system)? T-FIX seems to be to only rule where an exception variable can flow from  $\widehat{\tau}$  to  $\varphi$ ...

*Proof.* 1. By induction on the derivation of  $\Delta, e : \kappa' \vdash \varphi : \kappa$ . The cases A-VAR, A-ABS and A-APP are analogous to the respective cases in the proof of term substitution below. In the case A-CON one can strengthen the assumption  $\Delta, e : \kappa' \vdash \{\ell\} : \text{EXN}$  to  $\Delta \vdash \{\ell\} : \text{EXN}$  as  $e \notin \text{fv}(\{\ell\})$ , the result is then immediate; similarly for A-EMPTY. The case A-UNION goes analogous to A-APP.

2. **TO DO.**

3. **TO DO.**

4. By induction on the derivation of  $\Gamma; \Delta, e : \kappa' \vdash t : \widehat{\tau} \& \varphi$ . Most cases can be discarded by a straightforward application of the induction hypothesis; we show only the interesting case.

Case T-ANNAPP: **TO DO.**

**TO DO.**

□

**Lemma 3** (Term substitution). *If  $\Gamma, x : \widehat{\tau}' \& \varphi'; \Delta \vdash t : \widehat{\tau} \& \varphi$  and  $\Gamma; \Delta \vdash t' : \widehat{\tau}' \& \varphi'$  then  $\Gamma; \Delta \vdash t[t'/x] : \widehat{\tau} \& \varphi$ .*

*Proof.* By induction on the derivation of  $\Gamma, x : \widehat{\tau}' \& \varphi'; \Delta \vdash t : \widehat{\tau} \& \varphi$ .

Case T-VAR: We either have  $t = x$  or  $t = x'$  with  $x \neq x'$ . In the first case we need to show that  $\Gamma; \Delta \vdash x[t'/x] : \widehat{\tau} \& \varphi$ , which by definition of substitution is equal to  $\Gamma; \Delta \vdash x : \widehat{\tau} \& \varphi$ , but this is one of our assumptions. In the second case we need to show that  $\Gamma, x' : \widehat{\tau} \& \varphi; \Delta \vdash x'[t'/x] : \widehat{\tau} \& \varphi$ , which by definition of substitution is equal to  $\Gamma, x' : \widehat{\tau} \& \varphi; \Delta \vdash x' : \widehat{\tau} \& \varphi$ . This follows immediately from T-VAR.

Case T-ABS: Our assumptions are

$$\Gamma, x : \widehat{\tau}' \& \varphi', y : \widehat{\tau}_1 \& \varphi_1; \Delta \vdash t : \widehat{\tau}_2 \& \varphi_2 \quad (1)$$

$$\Gamma; \Delta \vdash t' : \widehat{\tau}' \& \varphi'. \quad (2)$$

By the Barendregt convention we may assume that  $y \neq x$  and  $y \notin \text{fv}(t')$ . We need to show that  $\Gamma; \Delta \vdash (\lambda y : \widehat{\tau}_1 \& \varphi_1.t)[t'/x] : \widehat{\tau}_2 \& \varphi_2 \& \emptyset$ ,

which by definition of substitution is equal to

$$\Gamma; \Delta \vdash \lambda y : \widehat{\tau}_1 \& \varphi_1.t[t'/x] : \widehat{\tau}_1 \langle \varphi_1 \rangle \rightarrow \widehat{\tau}_2 \langle \varphi_2 \rangle \& \emptyset. \quad (3)$$

We weaken (2) to  $\Gamma, y : \widehat{\tau}_1 \& \varphi_1; \Delta \vdash t' : \widehat{\tau}' \& \varphi'$  and apply the induction hypothesis on this and (1) to obtain

$$\Gamma, y : \widehat{\tau}_1 \& \varphi_1; \Delta \vdash t[t'/x] : \widehat{\tau}_2 \& \varphi_2. \quad (4)$$

The desired result (3) can be constructed from (4) using T-ABS.

Case T-ANNABS: Our assumptions are  $\Gamma, x : \widehat{\tau}' \& \varphi'; \Delta, e : \kappa \vdash t : \widehat{\tau} \& \varphi$  and  $\Gamma; \Delta \vdash t' : \widehat{\tau}' \& \varphi'$ . By the Barendregt convention we may assume that  $e \notin \text{fv}(t')$ . We need to show that  $\Gamma; \Delta \vdash (\lambda e : \kappa.t)[t'/x] : \widehat{\tau} \& \varphi$ , which is equal to  $\Gamma; \Delta \vdash \lambda e : \kappa.t[t'/x] : \widehat{\tau} \& \varphi$  by definition of substitution. By applying the induction hypothesis we obtain  $\Gamma; \Delta, e : \kappa \vdash t[t'/x] : \widehat{\tau} \& \varphi$ . The desired result can be constructed using T-ANNABS.

Case T-APP: Our assumptions are

$$\Gamma, x : \widehat{\tau}' \& \varphi'; \Delta \vdash t_1 : \widehat{\tau}_2 \langle \varphi_2 \rangle \rightarrow \widehat{\tau} \langle \varphi \rangle \& \varphi \quad (5)$$

$$\Gamma, x : \widehat{\tau}' \& \varphi'; \Delta \vdash t_2 : \widehat{\tau}_2 \& \varphi_2. \quad (6)$$

We need to show that  $\Gamma; \Delta \vdash (t_1 t_2)[t'/x] : \widehat{\tau} \& \varphi$ , which by definition of substitution is equal to

$$\Gamma; \Delta \vdash (t_1[t'/x]) (t_2[t'/x]) : \widehat{\tau} \& \varphi. \quad (7)$$

By applying the induction hypothesis to (5) respectively (6) we obtain

$$\Gamma; \Delta \vdash t_1[t'/x] : \widehat{\tau}_2 \langle \varphi_2 \rangle \rightarrow \widehat{\tau} \langle \varphi \rangle \& \varphi \quad (8)$$

$$\Gamma; \Delta \vdash t_2[t'/x] : \widehat{\tau}_2 \& \varphi_2. \quad (9)$$

The desired result (7) can be constructed by applying T-APP to (8) and (9).

All other cases are either immediate or analogous to the case of T-APP. □

**Lemma 4** (Inversion).

1. *If  $\Gamma; \Delta \vdash \lambda x : \widehat{\tau} \& \varphi.t : \widehat{\tau}_1 \langle \varphi_1 \rangle \rightarrow \widehat{\tau}_2 \langle \varphi_2 \rangle \& \varphi_3$ , then*

- $\Gamma, x : \widehat{\tau} \& \varphi; \Delta \vdash t : \widehat{\tau}' \& \varphi'$ ,
- $\Delta \vdash \widehat{\tau}_1 \leq \widehat{\tau}$  and  $\Delta \vdash \varphi_1 \leq \varphi$ ,
- $\Delta \vdash \widehat{\tau}' \leq \widehat{\tau}_2$  and  $\Delta \vdash \varphi' \leq \varphi_2$ .

2. *If  $\Gamma; \Delta \vdash \lambda e : \kappa.t : \forall e : \kappa.\widehat{\tau} \& \varphi$ , then*

- $\Gamma; \Delta, e : \kappa \vdash t : \widehat{\tau}' \& \varphi'$ ,
- $\Delta, e : \kappa \vdash \widehat{\tau}' \leq \widehat{\tau}$ ,
- $\Delta \vdash \varphi' \leq \varphi$ .
- **TO DO.**  $e \notin \text{fv}(\varphi)$  and/or  $e \notin \text{fv}(\varphi')$ .

*Proof.* 1. By induction on the typing derivation.

Case T-ABS: We have  $\widehat{\tau} = \widehat{\tau}_1$ ,  $\varphi = \varphi_1$  and take  $\widehat{\tau}' = \widehat{\tau}_2$ ,  $\varphi' = \varphi_2$ , the result then follows immediately from the assumption  $\Gamma, x : \widehat{\tau} \& \varphi; \Delta \vdash t : \widehat{\tau}_2 \& \varphi_2$  and reflexivity of the subtyping and subeffecting relations.

Case T-SUB: We are given the additional assumptions

$$\Gamma; \Delta \vdash \lambda x : \widehat{\tau} \& \varphi.t : \widehat{\tau}'_1 \langle \varphi'_1 \rangle \rightarrow \widehat{\tau}'_2 \langle \varphi'_2 \rangle \& \varphi'_3, \quad (10)$$

$$\Delta \vdash \widehat{\tau}'_1 \langle \varphi'_1 \rangle \rightarrow \widehat{\tau}'_2 \langle \varphi'_2 \rangle \leq \widehat{\tau}_1 \langle \varphi_1 \rangle \rightarrow \widehat{\tau}_2 \langle \varphi_2 \rangle, \quad (11)$$

$$\Delta \vdash \varphi'_3 \leq \varphi_3. \quad (12)$$

Applying the induction hypothesis to (10) gives us

$$\Gamma, x : \widehat{\tau} \& \varphi; \Delta \vdash t : \widehat{\tau}''_2 \& \varphi''_2, \quad (13)$$

$$\Delta \vdash \widehat{\tau}'_1 \leq \widehat{\tau}, \quad \Delta \vdash \varphi'_1 \leq \varphi, \quad (14)$$

$$\Delta \vdash \widehat{\tau}''_2 \leq \widehat{\tau}'_2, \quad \Delta \vdash \varphi''_2 \leq \varphi'_2. \quad (15)$$

Inversion of the subtyping relation on (11) gives us

$$\Delta \vdash \widehat{\tau}'_1 \leq \widehat{\tau}, \quad \Delta \vdash \varphi'_1 \leq \varphi, \quad (16)$$

$$\Delta \vdash \widehat{\tau}''_2 \leq \widehat{\tau}'_2, \quad \Delta \vdash \varphi''_2 \leq \varphi'_2. \quad (17)$$



The result follows from (13) and combining (16) with (14) and (15) with (17) using the transitivity of the subtyping and subeffecting relations.

2. By induction on the typing derivation.

Case T-ANNABS: We need to show that  $\Gamma; \Delta, e : \kappa \vdash t : \widehat{\tau} \& \varphi$ , which is one of our assumptions, and that  $\Delta, e : \kappa \vdash \widehat{\tau} \leq \widehat{\tau}$  and  $\Delta \vdash \varphi \leq \varphi$ ; this follows from the reflexivity of the subtyping, respectively subeffecting, relation (noting that  $e \notin \text{fv}(\varphi)$ ).

Case T-SUB: Similar to the case T-SUB in part 1.  $\square$

**Theorem 2** (Preservation). *If  $\Gamma; \Delta \vdash t : \widehat{\tau} \& \varphi$  and  $t \longrightarrow t'$ , then  $\Gamma; \Delta \vdash t' : \widehat{\tau} \& \varphi$ .*

*Proof.* By induction on the typing derivation  $\Gamma; \Delta \vdash t : \widehat{\tau} \& \varphi$ .

The cases for T-VAR, T-CON, T-CRASH, T-ABS, T-ANNABS, T-NIL, and T-CONS can be discarded immediately, as they have no applicable evaluation rules.  $\square$

**To DO.**

## 7.2 Syntax-directed type elaboration

### 7.3 Type inference algorithm

**Theorem 3** (Syntactic soundness). *If  $\mathcal{R} \Gamma \Delta t = \langle \widehat{\tau}; \varphi \rangle$ , then  $\Gamma; \Delta \vdash t : \widehat{\tau} \& \varphi$ .*

*Proof.* By induction on the term  $t$ .  $\square$

**To DO.**

**Theorem 4** (Termination).  *$\mathcal{R} \Gamma \Delta t$  terminates.*

*Proof.* By induction on the term  $t$ .  $\square$

**To DO.**

## 8. Related work

**To DO.**

## References

P. Q. Smith, and X. Y. Jones. ...reference text...