

Academic Evidence Investigator

An LLM-powered multi-agent planning agent for academic evidence

Unit 11 individual implementation of the Unit 6 group design

Ruwan Perera

One goal in, a referenced briefing out



Goal

Research question from a postgraduate researcher

Plan

Sub-questions and search queries

Retrieve

Semantic Scholar and Crossref

Appraise


Finding, design, stance, limitations

Report

Grounded briefing with Harvard references

Autonomous re-planning: if the Critic judges the evidence thin or one-sided, the agent decides by itself to search again with a revised plan, up to a fixed cycle limit.

LangGraph realises the proposed architecture



Shared ResearchState
Beliefs: papers, appraisals, verdict. Intention: the Planner's current queries (BDI; Archibald et al., 2024). Append-only audit trail.

Why LangGraph
Explicit conditional edge and bounded loop: the evaluator-optimiser pattern (LangChain, no date). ReAct-style alternation of reasoning and acting (Yao et al., 2023).

The LLM proposes, Python verifies

Agent	LLM does (Qwen2.5-7B-Instruct)	Python guarantees
Planner	Decomposes the question, writes queries	Schema check, no repeated queries, keyword fallback
Retrieval	Nothing	Rate limits, retries only transient errors, logs outages
Processing	Nothing, by design	DOI then title + author dedupe, relevance ranking
Critic	Appraises abstracts in one batched call	Drops invented paper ids; stop rule is explicit thresholds
Reporter	Drafts the briefing	Every finding must cite a retrieved paper

Language understanding goes to the model; anything with one correct answer stays in code (Unit 6 proposal, s.3).

Four decisions that make it trustworthy



Rule-based stopping

The Critic's sufficient / relevant / balanced verdict uses explicit thresholds. Self-reflection reduces but does not remove hallucination (Ji et al., 2023).



Grounded reporting

Citations to papers that were never retrieved are stripped; findings left uncited are dropped (Lewis et al., 2020; Huang et al., 2025).



Graceful degradation


Every LLM step has a deterministic fallback, so a rate limit lowers quality, not availability. The audit trail records which path ran.



Explicit offline mode

Reproducible demos and tests. Never a silent fallback: mixing demo data into a live briefing would misrepresent the evidence.

Demonstration: from question to briefing



Research briefing

Does generative AI improve university students' academic performance?

> Judged sufficient and balanced after 1 search cycle(s).

Run 5 · semantic_scholar+crossref; llm=localhost:qwen2.5:7b · report: deterministic · JSON

Summary

12 papers were appraised. Stances: supports 9, opposes 2, mixed 1. Study designs: observational 5, theoretical 3, experimental 2, other 1, review 1. Findings below are the most question-relevant sentence of each abstract, so read the sources before relying on them.

Key findings

- The study suggests that generative AI tools can positively impact student and faculty performance in higher education. (Isak and Isak, 2025)
- Generative AI literacy, particularly in technical proficiency and creative application, positively influences academic performance. (Khanal, 2025)
- AI literacy and self-regulated learning are positively associated with academic performance and well-being in higher education. (Shi et al., 2025)
- XAI methods can provide more interpretable and valuable predictions for student grades, enhancing confidence in AI

Evidence status
Written by Python from the Critic's verdict, never by the LLM

Key findings
Each cites retrieved papers in Harvard in-text style

Evidence table
Design, stance and relevance per paper

Audit trail + SQLite
Every search, re-plan and decision is stored and viewable

Demonstration: the Critic drives re-planning

```
cycle 1  planner    plan: 3 keyword queries
cycle 1  processing 6 received, 4 duplicates removed, 2 retained
cycle 1  critic     insufficient: 2 relevant papers (need 5); designs not varied
cycle 2  planner    re-plan: '... randomised controlled trial', '... meta-analysis'
cycle 2  critic     insufficient: still 2 relevant papers
cycle 3  planner    re-plan: broadened to 'retrieval reduce'
cycle 3  critic     insufficient: 3 relevant papers
cycle 3  reporter   cycle limit reached: briefing marked provisional
```

Offline run of "Does retrieval reduce hallucination?" (evidence/run-offline-max-cycles.log)

Contrast: "How do LLM-based agents plan, act and reflect?" was judged sufficient and balanced after one cycle (10 papers, 4 designs).

Testing: 83 tests, no network needed

83


tests passed

0

failures

96%

line coverage



4 live tests skip unless RUN_LIVE_TESTS=1

Sources and the LLM are injected, so tests use scripted fakes and synthetic API fixtures.

Functional tests prove

- Critic triggers a re-plan
- Loop stops at the cycle limit
- One source down, run continues
- Cross-source duplicates merged
- Invented citation removed
- Total LLM outage still reports
- Hostile HTML is escaped

What testing found, and what changed

R1	"LLM-based" never matched "large language models"	**Synonym folding + stemming: 2 papers in 3 cycles became 10 in 1**
R2	All-neutral evidence flagged as one-sided	**Only uniform supports/opposes counts as bias**
R3	Unclosed SQLite connections	**Shared Storage; suite now fails on any leak**
R4	HTTP 404 retried like a rate limit	**Retry only timeouts, 429 and 5xx**
R5	References ordered by title	**Alphabetical by first author, per Harvard**
R6	Live: hosted Qwen withdrawn, credit used up (400/402)	**Configurable endpoint; Qwen runs locally under Ollama**
R7	Live: Semantic Scholar throttled (429)	**Longer back-off, Retry-After, optional API key**
R8	Live: one bad appraisal discarded all 12	**Validate each item; 11 of 12 now kept from the LLM**
R9	Live: briefing JSON missing a comma	**Opt-in JSON mode constrains output to valid JSON**

R1 to R5 came from offline testing; R6 to R9 came from the live run on Windows 11 with Qwen2.5-7B under Ollama. Each fix has a regression test (docs/TESTING.md), and the Git history shows every step.

Responsible use, limits and next steps

Legal, ethical, professional

- Provider rate limits and polite-pool etiquette respected
- Tokens only from the environment, never stored
- Gaps framed within retrieved papers only
- States it supports, not replaces, the researcher

Limits and next steps

- Heuristic appraisal is approximate without the LLM
- Abstracts only; term-overlap relevance
- Synchronous web requests, single user
- Next: embeddings, PostgreSQL, labelled evaluation

Key references: Archibald, B. et al. (2024) Software and Systems Modeling, 23. Huang, L. et al. (2025) ACM TOIS, 43(2). Ji, Z. et al. (2023) Findings of EMNLP. LangChain (no date) Workflows and agents. Lewis, P. et al. (2020) NeurIPS, 33. Yao, S. et al. (2023) ICLR. Full Harvard list in README.md.