

C201 Review Questions #8

Feel free to talk to other people around you.

True or False

- 1) ____ The same array can hold both floats and integers.
- 2) ____ An array that is declared to be 5 characters long actually holds 6 elements.
- 3) ____ If A has been declared as "char A[4];", then A can be assigned via 'A = "abcd";'
- 4) ____ C++ Array sizes must be decided in advance by the programmer.
- 5) ____ If there are fewer initializers in an initializer list than the number of elements in the array, then the remaining elements are initialized to the last value in the list.
- 6) ____ It is an error if an initializer list contains more initializers than there are elements in list.
- 7) ____ When an array is passed to a function, the address of the first element of the array is passed by value to the function.
- 8) ____ Arrays and strings are constant pointers.
- 9) ____ C++ has two dimensional arrays, but not three dimensional.
- 10) ____ The library string.h contains the islower function.

11) Determine the output from the following program.

```
int F(int *, int *);

main()
{
    int A[] = {1,2};
    int B = 4, C;
    int *P = &B;

    C = F(A,P);

    cout << "A[0]= " << A[0] << " A[1]= " << A[1] << endl;
    cout << " B= " << B << " C= " << C << endl;
}

int F (int *M, int *N)
{
    *N = 123;
    M[0] = 6;
    return 789;
}
```