Name:	Dan Cassidy
Class:	CSCI-C 490, Mobile Application Development
Assignment:	Homework 1 Part 1
Date:	2015-07-09

```
1   /*-------------------------------------------------------------------------------------------------------
2    * Author:      Dan Cassidy
3    * Date:        2015-07-09
4    * Assignment:  HW1-1
5    * Source File: Program.java
6    * Language:    Java
7    * Course:      CSCI-C 490, Android Programming, MoWe 08:00
8   -------------------------------------------------------------------------------------------------------*/
9
10
11  import java.util.Scanner;
12
13  /**
14   * A small Java program to print out the first <i>n</i> (0 < <i>n</i> < 94) Fibonacci numbers.
15   * @author Dan Cassidy
16   */
17  public class Program
18  {
19      /**
20       * Entry point into the Java program.
21       * @param args Command line arguments. <i>Not used.</i>
22       * @return Nothing.
23       */
24      public static void main(String[] args)
25      {
26          // Define min and max.
27          final byte NUM_MIN = 1;
28          final byte NUM_MAX = 93;
29
30          // Give the user a small description.
31          System.out.println("Please enter the number of Fibonacci numbers to display. This should");
32          System.out.println("be a positive number up to and including 93.");
33
34          // Declare and prep variables for later use.
35          byte numFib = 0;
36          boolean validInput = false;
37          Scanner consoleInput = new Scanner(System.in);
38
39          // Loop while the user does not provide valid input.
40          while (!validInput)
41          {
42              System.out.print("Choice: ");
43              try
44              {
45                  // Get console input.
46                  numFib = Byte.parseByte(consoleInput.nextLine());
47
48                  // Check for valid input and throw an exception if invalid.
49                  if (numFib < NUM_MIN || numFib > NUM_MAX)
50                      throw new Exception();
51                  else
52                      validInput = true;
53              }
54              catch (Exception ex)
55              {
56                  System.out.println("Please enter a valid number.");
57              }
58          }
59
60          // Print the Fibonacci numbers.
```

```
61          System.out.println("First " + (numFib > 1 ? numFib + " " : "") + "Fibonacci Number" +
62                  (numFib != 1 ? "s": "") + ":");
63          Fibonacci.calculateAndDisplay(numFib);
64      }
65  }
66
```

```
1  /*-------------------------------------------------------------------------------------------------
2   * Author:      Dan Cassidy
3   * Date:        2015-07-09
4   * Assignment:  HW1-1
5   * Source File: Fibonacci.java
6   * Language:    Java
7   * Course:      CSCI-C 490, Android Programming, MoWe 08:00
8  -------------------------------------------------------------------------------------------------*/
9
10 /**
11  * Simple class dealing with Fibonacci numbers. Only handles up to the 93rd (F92) Fibonacci number
12  * due to the fact the class only uses the long primitive type.
13  * @author Dan Cassidy
14  */
15 public class Fibonacci
16 {
17     private final static byte F0 = 0;
18     private final static byte F1 = 1;
19
20     /**
21      * Calculates and displays a given number of Fibonacci numbers.
22      * @param sequenceLength The number of Fibonacci numbers to calculate and display.
23      */
24     public static void calculateAndDisplay(byte sequenceLength)
25     {
26         // Declare the requisite numbers.
27         long fibA = F1, fibB = F0, fibSum = 0;
28
29         // Display the first couple numbers in the sequence, if needed.
30         if (sequenceLength > 0)
31             System.out.print(F0 + " ");
32         if (sequenceLength > 1)
33             System.out.print(F1 + " ");
34
35         // Iteratively calculate and display the rest of the Fibonacci sequence.
36         for (int i = 2; i < sequenceLength; i++)
37         {
38             fibSum = fibA + fibB;
39             fibB = fibA;
40             fibA = fibSum;
41             System.out.print(fibSum + " ");
42         }
43     }
44 }
45
```

Shows the program response to bad input, as well as the first Fibonacci number (edge case of 1).



Shows “normal choice of 2.

Shows “normal” choice of 10.



Shows the edge case of 93.



Name:	Dan Cassidy
Class:	CSCI-C 490, Mobile Application Development
Assignment:	Homework 1 Part 2
Date:	2015-07-09

```
1   /*---------------------------------------------------------------------------------------------------
2    * Author:      Dan Cassidy and Dr. Zhang
3    * Date:        2015-07-09
4    * Assignment:  HW1-2
5    * Source File: StudentRecord.java
6    * Language:    Java
7    * Course:      CSCI-C 490, Android Programming, MoWe 08:00
8   ---------------------------------------------------------------------------------------------------*/
9
10  /**
11   * A small record of grades for a student.
12   * @author Dan Cassidy
13   * @author Dr. Zhang
14   */
15  public class StudentRecord
16  {
17      private int quiz1 = 0;
18      private int quiz2 = 0;
19      private int quiz3 = 0;
20      private int midterm = 0;
21      private int finalExam = 0;
22
23      private double numericScore = 0.0D;
24      private char letterGrade = '?';
25
26      private final int A_GRADE = 90;
27      private final int B_GRADE = 80;
28      private final int C_GRADE = 70;
29      private final int D_GRADE = 60;
30
31      private final int NUMBER_OF_QUIZZES = 3;
32
33      private final int QUIZ_MIN_SCORE = 0;
34      private final int QUIZ_MAX_SCORE = 10;
35      private final int MIDTERM_MIN_SCORE = 0;
36      private final int MIDTERM_MAX_SCORE = 100;
37      private final int FINAL_EXAM_MIN_SCORE = 0;
38      private final int FINAL_EXAM_MAX_SCORE = 100;
39
40      private final int QUIZ_WEIGHT = 25;
41      private final int MIDTERM_WEIGHT = 35;
42      private final int FINAL_EXAM_WEIGHT = 40;
43
44      /**
45       * Constructor.
46       * @param quiz1 Student score for quiz 1.
47       * @param quiz2 Student score for quiz 2.
48       * @param quiz3 Student score for quiz 3.
49       * @param midterm Student score for the midterm.
50       * @param finalExam Student score for the final exam.
51       */
52      public StudentRecord(int quiz1, int quiz2, int quiz3, int midterm, int finalExam)
53      {
54          // Use this object's own mutators to set its instance variables, allowing verification
55          // to happen in a single location.
56          this.setQuiz1(quiz1);
57          this.setQuiz2(quiz2);
58          this.setQuiz3(quiz3);
59          this.setMidterm(midterm);
60          this.setFinalExam(finalExam);
```

```
61      }
62
63      // BEGIN GETTERS AND SETTERS -->
64      public int getQuiz1()
65      {
66          return this.quiz1;
67      }
68
69      public void setQuiz1(int score)
70      {
71          if (score >= QUIZ_MIN_SCORE && score <= QUIZ_MAX_SCORE)
72              this.quiz1 = score;
73      }
74
75      public int getQuiz2()
76      {
77          return this.quiz1;
78      }
79
80      public void setQuiz2(int score)
81      {
82          if (score >= QUIZ_MIN_SCORE && score <= QUIZ_MAX_SCORE)
83              this.quiz2 = score;
84      }
85
86      public int getQuiz3()
87      {
88          return this.quiz1;
89      }
90
91      public void setQuiz3(int score)
92      {
93          if (score >= QUIZ_MIN_SCORE && score <= QUIZ_MAX_SCORE)
94              this.quiz3 = score;
95      }
96
97      public int getMidterm()
98      {
99          return this.midterm;
100     }
101
102     public void setMidterm(int score)
103     {
104         if (score >= MIDTERM_MIN_SCORE && score <= MIDTERM_MAX_SCORE)
105             this.midterm = score;
106     }
107
108     public int getFinalExam()
109     {
110         return this.finalExam;
111     }
112
113     public void setFinalExam(int score)
114     {
115         if (score >= FINAL_EXAM_MIN_SCORE && score <= FINAL_EXAM_MAX_SCORE)
116             this.finalExam = score;
117     }
118     // <-- END GETTERS AND SETTERS
119
120     /**
```

```
121         * This method calculates the numericScore based on the scores of the quizzes and exams.
122         * @return Nothing.
123         */
124        public void computeNumericScore()
125        {
126            this.numericScore =
127                (double)(quiz1 + quiz2 + quiz3) / (NUMBER_OF_QUIZZES * QUIZ_MAX_SCORE) * QUIZ_WEIGHT +
128                (double)midterm / MIDTERM_MAX_SCORE * MIDTERM_WEIGHT +
129                (double)finalExam / FINAL_EXAM_MAX_SCORE * FINAL_EXAM_WEIGHT;
130        }
131
132        /**
133         * This method calculates the letterGrade based on the numberScore.
134         * @return Nothing.
135         */
136        public void computeLetterGrade()
137        {
138            computeNumericScore();
139            if (numericScore >= A_GRADE)
140                letterGrade = 'A';
141            else if (numericScore >= B_GRADE)
142                letterGrade = 'B';
143            else if (numericScore >= C_GRADE)
144                letterGrade = 'C';
145            else if (numericScore >= D_GRADE)
146                letterGrade = 'D';
147            else
148                letterGrade = 'F';
149        }
150
151        /**
152         * This method compares two StudentRecord objects. It will return true only if two objects
153         * have same score for each of the quizzes and exams.
154         * @param other Another StudentRecord object that will be compared against for equality.
155         * @return boolean, showing whether the two student records are equal (true) or not (false).
156         */
157        public boolean equals(StudentRecord other)
158        {
159            if (other == null)
160                return false;
161            else
162                return  (this.quiz1 == other.quiz1) &&
163                        (this.quiz2 == other.quiz2) &&
164                        (this.quiz3 == other.quiz3) &&
165                        (this.midterm == other.midterm) &&
166                        (this.finalExam == other.finalExam);
167        }
168
169        /**
170         * This method returns a string representation of the data in the calling object.
171         * @return A string representation of the StudentRecord object.
172         */
173        public String toString()
174        {
175            this.computeLetterGrade();
176            return  "Quiz 1: " + this.quiz1 + ", " +
177                    "Quiz 2: " + this.quiz2 + ", " +
178                    "Quiz 3: " + this.quiz3 + ", " +
179                    "Midterm: " + this.midterm + ", " +
180                    "Final Exam: " + this.finalExam + ", " +
```

```
181                     "Grade: " + this.letterGrade + " (" +
182                     this.numericScore + "%)";
183         }
184     }// StudentRecord
185
```

Demonstration that the equals() method finds two students equal if they have the same grades.



Demonstration that the equals() method finds two students not equal if they have differing grades.



Demonstration that the quiz weight is calculated properly.



Demonstration that the midterm weight is calculated properly.



Demonstration that the final exam weight is calculated properly.