



Uncertainty Quantification of Thermal Damage in Hyperthermia as a Cancer Therapy

25th International Conference on Computational Science - 2025
Singapore

Gustavo Coelho Martins, Gustavo Resende Fatigate, Marcelo Lobosco,
Ruy Freitas Reis


July 7–9th, 2025

Pós-Graduação em Modelagem Computacional
Departamento de Ciência da Computação
Universidade Federal de Juiz de Fora

1. Introduction
2. Mathematical Model
3. Numerical Scheme
4. Thermal Damage
5. Uncertainty Quantification
6. Results
7. Conclusion and Future Works

Introduction

Cancer is a major global health issue, and breast cancer is the leading cause of death for the female population in several countries.



- Promising non-invasive cancer treatment;
- Overheat the tumour area, inducing necrosis;
- Complement of chemotherapy and radiotherapy treatment;
- One strategy involves using a magnetic nanoparticles ferrofluid.

Mathematical Model


Was considered the Pennes equation to simulate bioheat ¹:

$$\begin{cases} \rho c \frac{\partial T}{\partial t} = \nabla \cdot k \nabla T + \omega_b \rho_b c_b (T_a - T) + Q_m + Q_r & \text{em } \Omega \times I \\ k \nabla T \cdot \vec{n} = 0 & \text{em } \partial\Omega \times I \\ T(\cdot, 0) = 37, 0 & \text{em } \Omega \end{cases} \quad (1)$$

¹Fatigate, G. R., Lobosco, M., and Reis, R. F. (2023). A 3D Approach Using a Control Algorithm to Minimize the Effects on the Healthy Tissue in the Hyperthermia for Cancer Treatment. *Entropy*, 25(4), 684.

- Possible to use high energy potential;
- Water-based ferrofluid solution;
- Ferromagnetic fluid with properties 0.1, 0.2 or 0.3 cc;
- SAR² is responsible for modeling the overhear generated by the injections.

$$Q_r = \sum_{i=1}^{N_p} A e^{-r_i^2/r_{0,i}^2},$$



²Salloum, M., Ma, R., and Zhu, L. (2009). Enhancement in treatment planning for magnetic nanoparticle hyperthermia: optimization of the heat absorption pattern. *International Journal of Hyperthermia*, 25(4), 309-321.

Simplifications adopted to the Pennes Model

- The heat transfer occurs by the capillaries;
- Isotropic blood flow;
- The vascular geometry was not considered;
- The temperature of capillaries is equal to the body temperature;

Numerical Scheme

The solution was approximated using the FDM in a heterogeneous medium using a FTCS

$$T_{i,j,k}^{n+1} = \frac{h_t}{\rho c} \left[\frac{k_{i+1/2,j,k}(T_{i+1,j,k}^n - T_{i,j,k}^n) - k_{i-1/2,j,k}(T_{i,j,k}^n - T_{i-1,j,k}^n)}{h^2} + \frac{k_{i,j+1/2,k}(T_{i,j+1,k}^n - T_{i,j,k}^n) - k_{i,j-1/2,k}(T_{i,j,k}^n - T_{i,j-1,k}^n)}{h^2} + \frac{k_{i,j,k+1/2}(T_{i,j,k+1}^n - T_{i,j,k}^n) - k_{i,j,k-1/2}(T_{i,j,k}^n - T_{i,j,k-1}^n)}{h^2} + \rho_b c_b \omega_b (T_a - T_{i,j,k}^n) + Q_m + Q_r \right] + T_{i,j,k}^n \quad (2)$$

Thermal Damage

The thermal damage due to applying the Arrhenius model in the tumor and healthy regions.

$$\Omega(x, y, z, t) = \ln \left(\frac{C(0)}{C(t)} \right) = \int_0^t A e^{\frac{-E_a}{R_u T(x, y, z, \tau)}} d\tau. \quad (3)$$

- If the computed damage parameter $\Omega(x, y, z, t)$ reaches 1.0, it is considered that approximately 63.2% of cellular death.
- An Arrhenius damage parameter of 4 suggests that nearly 98.2% cellular death.
- Omega values in the range of $4 \leq \Omega \leq 10$ are considered a complete tumor ablation.

Uncertainty Quantification

We applied Monte Carlo with a 1,000 sample to quantify the uncertainties associated with the two correlated parameters in the Arrhenius model. To analyze the influence of the frequency factor A and the activation energy E_a .

$$E_a \approx 2.63 \times 10^3 \ln(A) + 2.46 \times 10^4 \begin{cases} E_{a_u} & = W \sim U(E_{a_{min}}, E_{a_{max}}), \\ A & = e^{3.832 \times 10^{-4} E_a - 10.042}, \end{cases}$$

$$\ln(A) = 3.832 \times 10^{-4} E_a - 10.042 \begin{cases} A_u & = W \sim U(A_{min}, A_{max}), \\ E_a & = 2.63 \times 10^3 \ln(A_u) + 2.46 \times 10^4. \end{cases}$$

Results

- C program implementation
- AMD® EPYC™ 7713
- NVIDIA A100 GPU (for CUDA paralization)
- Single core execution
- Results shown by Paraview
- Execution parameters and domain taken from bibliography




Figure 1: Simulated breast tumor




Figure 2: Temperature distribution computed from the bioheat equation at $t = 50\text{min}$




Figure 3: Simulation results for the scenario with uncertainty in the frequency factor A at 5 minutes of treatment.




Figure 4: Simulation results for the scenario with uncertainty in the frequency factor A at 10 minutes of treatment.




Figure 5: Simulation results for the scenario with uncertainty in the frequency factor A at 50 minutes of treatment.




Figure 6: Simulation results for the scenario with uncertainty in the frequency factor E_a at 5 minutes of treatment.




Figure 7: Simulation results for the scenario with uncertainty in the frequency factor E_a at 10 minutes of treatment.




Figure 8: Simulation results for the scenario with uncertainty in the frequency factor E_a at 50 minutes of treatment.




Figure 9: Results of the uncertainty quantification caused by variations in A and E_a for assessing tumor damage during hyperthermia.

Conclusion and Future Works

- Variations in the activation energy A have a minor influence on tissue damage predictions.
- However, the variations in the activation energy E_a significantly affect the outcomes.
- The confidence intervals observed in the thermal damage indicate that uncertainty in E_a exists between 15 and 35 minutes to reach the critical damage threshold ($\Omega \geq 4$).



- In future works we consider the study of different tissue layers in the human body with realistic tumor and tissue shapes
- Incorporate Multigrid Monte Carlo (MGMC) methods to accelerate simulations and improve computational efficiency
- Finally we intend to validate the model results with clinical or experimental data

Obrigado!
Thanks!



³



⁴



³423278/2021-5

⁴APQ-01226-21