



A Computational Immune Approach for Modeling Different Levels of Severity in COVID-19 Infections

25th International Conference on Computational Science - 2025
Singapore

Laura Polverari e Silva Marcelo Lobosco and Ruy Freitas Reis

July 7–9th, 2025

Pós-Graduação em Modelagem Computacional
Departamento de Ciência da Computação
Universidade Federal de Juiz de Fora



1. Introduction
2. Methods
3. Numerical Results
4. Conclusion and Future Works
5. References

Introduction

- COVID-19 is the disease caused by the SARS-CoV-2 virus, first identified in Wuhan, China in 2019.
- The virus spread rapidly across the world, leading the World Health Organization to declare a pandemic in March 2020.
- Over 777 million cases and 7 million deaths have been registered worldwide, as of February 2025.

- In this study, we adapt a model to simulate disease severity¹. The model is calibrated using differential evolution and validated against data from the literature, including:
 - $CD4^+$ and $CD8^+$ T cells,
 - Viral load,
 - Antibodies.
- We consider three severity scenarios: **(1)** mild, **(2)** severe, and **(3)** critical.

¹Reis, Ruy Freitas, et al. "A validated mathematical model of the cytokine release syndrome in severe COVID-19." *Frontiers in Molecular Biosciences* 8 (2021): 639423.

Methods

The mathematical model consists of twelve ordinary differential equations (ODEs). It represents key components of the immune response to SARS-CoV-2 infection, including:

- Antigen-presenting cells (APCs),
- T cells,
- B cells.

- Virus (V):

$$\frac{d}{dt}V = \pi_v V - \frac{c_{v1}V}{c_{v2} + V} - k_{v1}VA - k_{v2}VT_{ke}$$

- Immature antigen-presenting cells (A_p):

$$\frac{d}{dt}A_p = \alpha_{ap}(A_{p0} - A_p) - \beta_{ap}A_p \frac{c_{ap1}V}{c_{ap2} + V}$$

- Activated antigen-presenting cells (A_{pm}):

$$\frac{d}{dt}A_{pm} = \beta_{ap}A_p \frac{c_{ap1}V}{c_{ap2} + V} - \delta_{apm}A_{pm}$$

- Naïve CD4+ T cells (T_{hn}):

$$\frac{d}{dt} T_{hn} = \alpha_{th}(T_{hn0} - T_{hn}) - \beta_{th} A_{pm} T_{hn}$$

- Effector CD4+ T cells (T_{he}):

$$\frac{d}{dt} T_{he} = \beta_{th} A_{pm} T_{hn} + \pi_{th} A_{pm} T_{he} - \delta_{th} T_{he}$$

- Naïve CD8+ T cells (T_{kn}):

$$\frac{d}{dt} T_{kn} = \alpha_{tk} (T_{kn0} - T_{kn}) - \beta_{tk} A_{pm} T_{kn}$$

- Effector CD8+ T cells (T_{ke}):

$$\frac{d}{dt} T_{ke} = \beta_{tk} A_{pm} T_{kn} + \pi_{tk} A_{pm} T_{ke} - \delta_{tk} T_{ke}$$

- B cells (B):

$$\frac{d}{dt}B = \alpha_b(B_0 - B) + \pi_{b1}VB + \pi_{b2}T_{he}B - \beta_{ps}A_{pm}B - \beta_{pl}T_{he}B - \beta_{bm}T_{he}B$$

- Short-lived plasma cells (P_s):

$$\frac{d}{dt}P_s = \beta_{ps}A_{pm}B - \delta_{ps}P_s$$

- Long-lived plasma cells (P_l):

$$\frac{d}{dt}P_l = \beta_{pl}T_{he}B - \delta_{pl}P_l + \gamma_{bm}B_m$$

- Memory B cells (B_m):

$$\frac{d}{dt}B_m = \beta_{bm}T_{he}B + \pi_{bm1}B_m \left(1 - \frac{B_m}{\pi_{bm2}}\right) - \gamma_{bm}B_m$$

- Antibodies (A):

$$\frac{d}{dt}A = \pi_{ps}P_s + \pi_{pl}P_l - \delta_a A$$

- The Differential Evolution (DE) technique is applied to optimize a set of parameters p , aiming to find numerical results that best fit experimental data. The target variables include:
 - Populations of mature $CD4^+$ and $CD8^+$ T cells,
 - Viral load,
 - Antibody concentration.
- Objective function:

$$\min O(p) = \omega_{T_{he}} \frac{\|T_{he} - \overline{T_{he}}\|_2}{\|T_{he}\|_2} + \omega_{T_{ke}} \frac{\|T_{ke} - \overline{T_{ke}}\|_2}{\|T_{ke}\|_2} + \omega_V \frac{\|V - \overline{V}\|_2}{\|V\|_2} + \omega_A \frac{\|A - \overline{A}\|_2}{\|A\|_2}$$

Numerical Results


- The mathematical model was implemented in C++ using the CVODE package to solve systems of ordinary differential equations;
 - Backward Differentiation Formula (BDF) was used to integrate the ODE system;
- Moreover, a library implementing the DE algorithm was utilized.²

²https://github.com/ruyfreis/differential_evolution.git


- Three scenarios—**mild, severe, and critical**—are considered for simulations, based on $CD4^+$ and $CD8^+$ T cell population data from the literature.
- Each scenario uses distinct lymphocyte data, while virus concentration and antibody levels are taken from a shared dataset.
- Model results for $CD4^+$ and $CD8^+$ T cells, viral load, and antibodies are plotted alongside data from the literature.
- Virus and antibody levels are shown on \log_{10} and \log_2 scales, respectively.


- Parameter adjustments are made for all scenarios:
 - **Mild and severe cases:** 15 parameters (14 model parameters and one initial condition) are optimized.
 - **Critical case:** 12 parameters (11 model parameters and one initial condition) are adjusted.

Numerical Results: Mild scenario



Numerical Results: Severe scenario





- The simulation results align well with the literature and provide insights into immune dynamics in mild, severe, and critical scenarios.
- Overall, the results indicate a severity-linked immune dysfunction:
 - Milder cases exhibit higher T cell levels and faster viral clearance.
 - Critical cases display a reduced immune response and prolonged viral presence.

Conclusion and Future Works

- This study presented a computational model for simulating the immune response to SARS-CoV-2, validated using experimental data.
- The model successfully captured the dynamics of mature $CD4^+$ and $CD8^+$ T cells, viral load, and antibody levels.
- The simulated curves generally remained within the experimental confidence intervals, demonstrating the model's qualitative validity.



- Some ideas for future work to improve the model's accuracy and computational efficiency include:
 - Uncertainty quantification;
 - Sensitivity analysis;
 - High-performance computing.

Obrigado!
Thanks!



References



- Gardner, D. J., Reynolds, D. R., Woodward, C. S., and Balos, C. J. (2022). Enabling new flexibility in the SUNDIALS suite of nonlinear and differential/algebraic equation solvers. *ACM Transactions on Mathematical Software (TOMS)*, 48(3):1–24.
- Reis, R., Pigozzo, A., Bonin, C., Quintela, B. d. M., Pompei, L., Vieira, A., Silva, L. L., Xavier, M. P., Weber dos Santos, R., and Lobosco, M. (2021). A validated mathematical model of the cytokine release syndrome in severe COVID-19. *Front. Molecular Biosci.*, 8.
- Storn, R. and Price, K. (1997). Differential evolution – a simple and efficient heuristic for global optimization over continuous spaces. *Journal of Global Optimization*, 11(4):341–359.



WHO (2023). Coronavirus disease (covid-19) pandemic. Available at: <https://www.who.int/europe/emergencies/situations/covid-19>. Accessed on February 05, 2025.

Zhang, X., Tan, Y., Ling, Y., Lu, G., Liu, F., Yi, Z., Jia, X., Wu, M., Shi, B., Xu, S., Chen, J., Wang, W., Chen, B., Jiang, L., Yu, S., Lu, J., Wang, J., Xu, M., Yuan, Z., Zhang, Q., Zhang, X., Zhao, G., Wang, S., Chen, S., and Lu, H. (2020). Viral and host factors related to the clinical outcome of covid-19. *Nature*, 583(7816):437–440.