

Developer Manual

1. Overview

This documentation will enable the developer to customize and improve the system with ease.

This covers customization of the Ant build script, theme, internationalization, images, database schema and the file listing.

2. Ant Build Script

The developer can modify the openmpis/build.xml file. Some targets are listed which can be overwritten.

```
<?xml version="1.0" encoding="UTF-8"?>
<!-- You may freely edit this file. See commented blocks below for -->
<!-- some examples of how to customize the build. -->
<!-- (If you delete it and reopen the project it will be recreated.) -->
<project name="openmpis" default="default" basedir=".">
  <description>Builds, tests, and runs the project OpenMPIS.</description>
  <import file="nbproject/build-impl.xml"/>
<!--
```

There exist several targets which are by default empty and which can be used for execution of your tasks. These targets are usually executed before and after some main targets. They are:

-pre-init:	called before initialization of project properties
-post-init:	called after initialization of project properties
-pre-compile:	called before javac compilation
-post-compile:	called after javac compilation
-pre-compile-single:	called before javac compilation of single file
-post-compile-single:	called after javac compilation of single file
-pre-compile-test:	called before javac compilation of JUnit tests
-post-compile-test:	called after javac compilation of JUnit tests
-pre-compile-test-single:	called before javac compilation of single JUnit test
-post-compile-test-single:	called after javac compilation of single JUnit test
-pre-dist:	called before archive building
-post-dist:	called after archive building
-post-clean:	called after cleaning build products
-pre-run-deploy:	called before deploying
-post-run-deploy:	called after deploying

Example of plugging an obfuscator after the compilation could look like

```
<target name="-post-compile">
  <obfuscate>
    <fileset dir="${build.classes.dir}"/>
  </obfuscate>
</target>
```

For list of available properties check the imported nbproject/build-impl.xml file.

Other way how to customize the build is by overriding existing main targets. The target of interest are:

init-macrodef-javac:	defines macro for javac compilation
init-macrodef-junit:	defines macro for junit execution

init-macrodef-debug: defines macro for class debugging
do-dist: archive building
run: execution of project
javadoc-build: javadoc generation

Example of overriding the target for project execution could look like

```
<target name="run" depends="<PROJNAME>-impl.jar">  
  <exec dir="bin" executable="launcher.exe">  
    <arg file="${dist.jar}"/>  
  </exec>  
</target>
```

Notice that overridden target depends on jar target and not only on compile target as regular run target does. Again, for list of available properties which you can use check the target you are overriding in nbproject/build-impl.xml file.

```
-->  
<target name="help" description="Displays this help menu.">  
  <echo message="To build everything and install the database schema, type: ant"/>  
  <echo message="You can now deploy dist/openmpis.war to the application server."/>  
  <echo message=""/>  
  <echo message="To create the WAR file only, type: ant dist"/>  
  <echo message="This will create dist/openmpis.war."/>  
  <echo message=""/>  
  <echo message="To compile only, type: ant compile"/>  
  <echo message="This will generate the compiled classes in the build/ directory."/>  
  <echo message=""/>  
  <echo message="To generate documentation only, type: ant javadoc"/>  
  <echo message="This will generate the API's in the dist/javadocs directory."/>  
  <echo message=""/>  
  <echo message="To install the database schema only, type: ant create-database"/>  
  <echo message=""/>  
  <echo message="To remove the database schema, type: ant drop-database"/>  
  <echo message=""/>  
  <echo message="To start from scratch, type: ant clean"/>  
  <echo message="This will erase build/ and dist/ directories."/>  
</target>  
<target depends="create-database" name="-post-dist">  
  <target depends="library-inclusion-in-archive,javadoc-build" name="create-database"  
description="Installs the OpenMPIS schema on the MySQL database server.">  
    <property file="src/sqlmapconfig.properties"/>  
    <property name="sql.url" value="jdbc:mysql://localhost:3306"/>  
    <sql driver="${driver}" url="${sql.url}" userid="${username}" password="${password}" src="database/  
MySQL/openmpis-mysql-schema-1.0.sql" rdbms="mysql">  
      <classpath>  
        <pathelement location="build/web/WEB-INF/lib/mysql-connector-java-5.1.6-bin.jar"/>  
      </classpath>  
    </sql>  
</target>
```

```
<target depends="library-inclusion-in-archive" name="drop-database" description="Removes the
database schema from the database server.">
  <input message="This will remove the database. Proceed?" validargs="y,n" addproperty="do.delete"
/>
  <condition property="do.abort">
    <equals arg1="n" arg2="${do.delete}"/>
  </condition>
  <fail if="do.abort">Database dropping aborted by user.</fail>
  <property file="src/sqlmapconfig.properties"/>
  <sql driver="${driver}" url="${url}" userid="${username}" password="${password}">
    <classpath>
      <pathelement location="build/web/WEB-INF/lib/mysql-connector-java-5.1.6-bin.jar"/>
    </classpath>
    DROP DATABASE openmpis;
  </sql>
</target>
</project>
```

3. Theme

The developer can customize the cascading stylesheet to change the theme. The default theme (openmpis/web/styles/openmpis.css) can be renamed and the elements modified to suit the designs of the organization.

```
/* Basic HTML elements */
body {
    background-color: #bbbbbb;
    width: 100%;
    color: #000000;
    font: normal normal normal 9pt sans-serif;
    text-align: center;
    margin: 0px 0px 0px 0px;
    height: 100%;
}

a {
    color: #7f7f7f;
    font: normal normal normal 9pt sans-serif;
    text-decoration: none;
}

a:hover {
    color: #000000;
    text-decoration: underline;
}

h1 {
    color: #355d0d;
}

/* Specific classes */
.textareaclass, .inputclass, [selected], .selectclass, .fileclass {
    border: 1px solid #6c6c6c;
    background-color: #cccccc;
    width: 300px;
}

.hiddeninputclass {
    border: 1px solid #6c6c6c;
    background-color: #cccccc;
    width: 300px;
    display: none;
}

.weightinputclass, .heightinputclass, .ageinputclass {
    border: 1px solid #6c6c6c;
    background-color: #cccccc;
    width: 40px;
}
```

```
}

.optionclass {
    border: 0px solid #6c6c6c;
    background-color: #cccccc;
    width: 250px;
}

.monthselectclass {
    border: 1px solid #6c6c6c;
    background-color: #cccccc;
    width: 100px;
}

.monthoptionclass {
    border: 0px solid #6c6c6c;
    background-color: #cccccc;
    width: 70px;
}

.dayselectclass, .feetselectclass, .inchesselectclass {
    border: 1px solid #6c6c6c;
    background-color: #cccccc;
    width: 40px;
}

.dayoptionclass, .feetoptionclass, .inchesoptionclass {
    border: 0px solid #6c6c6c;
    background-color: #cccccc;
    width: 15px;
}

.yearselectclass {
    border: 1px solid #6c6c6c;
    background-color: #cccccc;
    width: 70px;
}

.yearoptionclass {
    border: 0px solid #6c6c6c;
    background-color: #cccccc;
    width: 40px;
}

.buttonclass, .searchbuttonclass {
    border: 1px solid #6c6c6c;
    background-color: #cccccc;
}

.feedbackbuttonclass, .loginbuttonclass, .userbuttonclass, .casebuttonclass {
    border: 1px solid #6c6c6c;
```

```
background-color: #cccccc;
margin-left: 9.4em;
}

.feedbackclass, .loginclass, .searchclass, .adduserclass {
    text-align: left;
}

.logincontentclass {
    white-space: normal;
    text-align: justify;
    margin-left: 10.4em;
}

.errorclass {
    color: #ff0000;
}

.standalonelabelclass {
    width: 10em;
    text-align: left;
    margin-right: 0.5em;
    display: block;
    color: #2a5104;
}

.labelclass {
    width: 10em;
    float: left;
    text-align: left;
    margin-right: 0.5em;
    display: block;
    color: #2a5104;
}

.contentclass {
    white-space: normal;
    text-align: justify;
}

.table {
    display: table;
    width: 100%;
    border-spacing: 1px;
}

.hiddentable {
    display: table;
}

.row {
```



```
    display: table-row;
}

.cell {
    display: table-cell;
    font: normal normal normal 9pt sans-serif;
    color: #111111;
    text-align: left;
    padding: 2px;
    border: 1px solid #ffffff;
}

.hiddencell {
    display: table-cell;
    font: normal normal normal 9pt sans-serif;
    color: #111111;
    text-align: left;
    padding: 2px;
}

.columnheader {
    display: table-cell;
    font: bold normal normal 12pt sans-serif;
    color: #000000;
    text-align: center;
    padding: 2px;
    border: 1px solid #ffffff;
}

/* Specific ids */

/* Specific divs */
div#container {
    position: relative;
    min-height: 100%;
    height: 100%;
    text-align: center;
}

div#header {
    height: 100px;
    background-color: #bbbbbb;
    background: url(..images/openmpis.png) no-repeat center center;
}

div#header img {
    margin-top: 0px;
}

div#menu {
    white-space: nowrap;
```

```
margin: 0px 0px 0px 0px;
padding: 0px;
text-align: center;
}

div#menu li {
    display: inline;
    list-style-type: none;
}

div#menu a {
    color: #ffffff;
    text-decoration: none;
    display: inline-block;
    font: normal normal normal 14pt sans-serif;
    background: url(../images/oval-dark.png) no-repeat center center;
    height: 40px;
    width: 150px;
    padding-top: 10px;
    margin-left: 2px;
    margin-right: 2px;
}

div#menu a:hover, div#menu a.chosen {
    color: #000000;
    text-decoration: none;
    display: inline-block;
    font: normal normal normal 14pt sans-serif;
    background: url(../images/oval-light.png) no-repeat center center;
    height: 40px;
    width: 150px;
    padding-top: 10px;
    margin-left: 2px;
    margin-right: 2px;
}

div#content {
    width: 100%;
    text-align: center;
    padding-top: 10px;
    padding-bottom: 60px;
}

div#content img {
    border: 0px;
}

div#content .photoclass {
    border: 1px solid olive;
    height: 300px;
    width: 200px;
```

```
}

div#contentitem {
  white-space: nowrap;
  margin: 0px auto 0px auto;
  padding: 10px;
  text-align: justify;
}

div#contenthome {
  white-space: nowrap;
  margin: 0px auto 0px auto;
  padding: 0px;
  text-align: center;
}

div#contenthome li {
  display: inline;
  list-style-type: none;
}

div#contenthome a {
  display: inline-block;
}

div#footer {
  clear: both;
  width: 100%;
  height: 30px;
  margin: 30px auto 0px auto;
  background-color: #424242;
  border: 1px;
  padding-top: 10px;
  padding-bottom: 10px;
  font: normal normal normal 7pt sans-serif;
  position: fixed;
  bottom: 0;
  left: 0;
  z-index: 100;
}

div#link a, div#copyright a {
  font: normal normal normal 7pt sans-serif;
}

div#link li {
  display: inline;
  list-style-type: none;
  padding-left: 1em;
  margin-left: 1em;
  border-left: 1px solid #000000;
```

```
}

div#link li:first-child {
    border-left:none
}

div#copyright {
    float: left;
    padding-left: 10px;
    width: 20%;
}

div#link {
    float: right;
    padding-right: 10px;
    width: 49%;
}

div#pagination {
    text-align: center;
}

div#pagination a {
    border: 1px solid #6c6c6c;
    background: #cccccc;
    padding: 2px 5px 2px 5px;
    color: #000000;
    font: normal normal normal 9pt sans-serif;
    text-decoration: none;
}

div#casemenu {
    text-align: center;
}

div#casemenu li {
    display: inline;
    list-style-type: none;
    padding-left: 1em;
    margin-left: 1em;
    border-left: 1px solid #000000;
}

div#casemenu li:first-child {
    border-left:none
}
```

4. Internationalization

The developer can add localized messages by creating an application resources property file for the given language based on the openmpis/src/com/googlecode/openmpis/resource/ApplicationResources.properties file. Menu items, global variables and styles can also be modified here.

```
### Error messages ###
error.title=Error
error.404=The requested resource is not available.
error.unauthorized=You are not authorized to access this page.
error.session.required=Your session has expired. Please log in again.
error.feedback=Feedback cannot be forwarded to administrator. Probable e-mail problem.
error.keyword.required=<p class="errorclass">Please enter keyword/s without special characters.</p>
error.firstname.required=<span class="errorclass">Please enter a valid first name.</span>
error.firstname.invalid=<span class="errorclass">First name is invalid.</span>
error.nickname.required=<span class="errorclass">Please enter a valid nickname.</span>
error.nickname.invalid=<span class="errorclass">Nickname is invalid.</span>
error.middlename.required=<span class="errorclass">Please enter a valid middle name.</span>
error.middlename.invalid=<span class="errorclass">Middle name is invalid.</span>
error.lastname.required=<span class="errorclass">Please enter a valid last name.</span>
error.lastname.invalid=<span class="errorclass">Last name is invalid.</span>
error.email.required=<span class="errorclass">Please enter a valid e-mail address.</span>
error.email.invalid=<span class="errorclass">Email address is invalid.</span>
error.email.duplicate=<span class="errorclass">Email address already exists.</p>
error.subject.invalid=<span class="errorclass">Subject must be at least 2 characters long.</span>
error.message.invalid=<span class="errorclass">Message must be at least 10 characters long.</span>
error.login.invalid=<p class="errorclass">Username or password is invalid or this account is suspended.</p>
error.javascript.disabled=<p class="errorclass">JavaScript must be enabled.</p>
error.username.required=<span class="errorclass">Please enter a valid username.</span>
error.username.invalid=<span class="errorclass">Username is invalid.</span>
error.username.duplicate=<span class="errorclass">Username {0} already exists.</p>
error.password.required=<span class="errorclass">Please enter a valid password.</span>
error.password.invalid=<span class="errorclass">Password is invalid. It should contain 8-10 alphanumeric characters only.</span>
error.answer.required=<span class="errorclass">Please enter a valid answer.</span>
error.answer.invalid=<span class="errorclass">Answer is invalid.</span>
error.question.invalid=<p class="errorclass">Question or answer is invalid.</p>
error.designation.required=<span class="errorclass">Please enter a valid designation or position.</span>
error.designation.invalid=<span class="errorclass">Designation or position is invalid.</span>
error.agency.required=<span class="errorclass">Please enter a valid agency or institution.</span>
error.agency.invalid=<span class="errorclass">Agency or institution is invalid.</span>
error.number.required=<span class="errorclass">Please enter a valid telephone number.</span>
error.number.invalid=<span class="errorclass">Telephone number is invalid.</span>
error.number.duplicate=<span class="errorclass">Telephone number already exists.</p>
error.password.mismatch=<span class="errorclass">Passwords did not match.</span>
error.code.mismatch=<span class="errorclass">Codes did not match.</span>
error.birthdate.invalid=<span class="errorclass">Birth day is greater than the actual number of days for the month.</span>
```

error.birthmonth.invalid=Birth month is greater than the current month.
error.birthday.invalid=Birth day is greater than the current month's day.
error.street.required=Please enter a valid street name.
error.street.invalid=Street name is invalid.
error.city.required=Please enter a valid city.
error.city.invalid=City is invalid.
error.province.required=Please enter a valid province.
error.province.invalid=Province is invalid.
error.relative.duplicate=Relative already exists.</p>
error.weight.required=Please enter a valid weight.
error.weight.invalid=Weight is invalid.
error.marks.required=Please enter distinguishing marks.
error.marks.invalid=Distinguishing marks are invalid.
error.personaleffects.required=Please enter valid personal effects.
error.personaleffects.invalid=Personal effects are invalid.
error.circumstance.required=Please enter a valid circumstance of disappearance.
error.circumstance.invalid=Circumstance of disappearance is invalid.
error.reward.invalid=Reward is invalid.
error.institution.required=Please enter a valid institution.
error.institution.invalid=Institution is invalid.
error.photo.required=Please enter a photo.
error.photo.invalid=Photo is invalid. It must be in PNG, JPG or GIF format.
error.monthmissingorfound.invalid=Month is greater than the current month.
error.daymissingorfound.invalid=Day is greater than the current month's day.
error.codisid.invalid=CODIS ID is invalid.
error.afisid.invalid=AFIS ID is invalid.
error.dentalid.invalid=Dental ID is invalid.
error.remarks.required=Please enter a remark.
error.remarks.invalid=Remark is invalid.
error.report.required=Please enter a progress report.
error.report.invalid=Progress report is invalid.

Labels

label.id=ID
label.group=Group
label.username=Username
label.password=Password
label.password.verify=Verify Password
label.name=Name
label.firstname=First Name
label.nickname=Nickname
label.middlename=Middle Name
label.lastname=Last Name
label.date.birth=Birth Date
label.age=Age
label.agency=Agency
label.designation=Designation

label.number=Contact Number
label.email=E-mail Address
label.ipaddress=IP Address
label.date.lastlogin=Last Login
label.date.encoded=Date Encoded
label.date.missing=Date Missing
label.date.found=Date Found
label.question=Question
label.answer=Answer
label.creatorid=Creator ID
label.status=Status
label.count=#
label.code=Confirmation Code
label.code.verify=Verify Code
label.subject=Subject
label.message=Message
label.address=Address
label.address.street=Street
label.address.city=City
label.address.province=Province/State
label.address.country=Country
label.address.missingfrom=Missing from
label.address.possiblelocation=Possible Location
label.address.currentlocation=Current Location
label.case.id=Case ID
label.case.type=Case Type
label.sex=Sex
label.height=Height
label.height.ft=feet
label.height.in=inches
label.height.cm=centimeters
label.weight=Weight
label.weight.lbs=pounds
label.weight.kg=kilograms
label.religion=Religion
label.race=Race
label.color.eye=Eye Color
label.color.hair=Hair Color
label.condition=Medical Condition
label.marks=Distinguishing Marks
label.circumstance=Circumstance
label.personaleffects=Personal Effects
label.remarks=Remarks
label.reward=Reward (PhP)
label.codis.id=CODIS ID
label.afis.id=AFIS ID
label.dental.id=Dental ID
label.relative.id=Relative ID
label.abductor.id=Abductor ID
label.investigator.id=Investigator ID
label.relation=Relation

label.institution=Institution
label.missing.day=day(s) missing
label.photo=Photo
label.agedphoto=Aged Photo
label.assign=Assign to
label.relative.existing=Existing Relative
label.relative.new=New Relative
label.abductor.existing=Existing Abductor
label.abductor.new=New Abductor
label.investigator.existing=Existing Investigator
label.cases.handed=Handled Cases
label.cases.encoded=Encoded Cases
label.users.encoded=Encoded Users
label.unknown=Unknown
label.progress=Progress Reports
label.from=From
label.for=For
label.date.sent=Date Sent
label.report=Report
label.date.reported=Date Written/Updated
label.abductor.name=Abductor
label.relative.name=Relative
label.investigator.username=Investigator

Sexes ###
sex.0=Unknown
sex.1=Male
sex.2=Female

Eye colors ###
color.eye.0=Unknown
color.eye.1=Amber
color.eye.2=Blue
color.eye.3=Brown
color.eye.4=Gray
color.eye.5=Green
color.eye.6=Hazel
color.eye.7=Others

Hair colors ###
color.hair.0=Unknown
color.hair.1=Auburn
color.hair.2=Black
color.hair.3=Blond
color.hair.4=Brown
color.hair.5=Gray/White
color.hair.6=Red
color.hair.7=Others

Religions ###
Sub-religions and sects excluded

religion.0=Unknown
religion.1=Atheist
religion.2=Buddhist
religion.3=Christian
religion.4=Hindu
religion.5=Islamic
religion.6=Jew
religion.7=Others

Races

race.0=Unknown
race.1=African
race.2=African American
race.3=Asia/Pacific
race.4=Caucasian
race.5=European
race.6=Hispanic
race.7=Indian
race.8=Mixed Race
race.9=Middle Eastern
race.10=Mongolian
race.11=Native American
race.12=Southeast Asian
race.13=Others

Months

month.1=January
month.2=February
month.3=March
month.4=April
month.5=May
month.6=June
month.7=July
month.8=August
month.9=September
month.10=October
month.11=November
month.12=December

Groups

group.0=Administrator
group.1=Encoder
group.2=Investigator

Status

User status

status.user.0=Active
status.user.1=Suspended

Case status

status.case.0=On-going
status.case.1=Solved

status.case.2=Unsolved

Messages

status.message.0=Unread

status.message.1=Read

Case types

type.0=Endangered Missing

type.1=Family Abduction

type.2=Non-Family Abduction

type.3=Endangered Runaway

type.4=Unknown

type.5=Found

type.6=Abandoned

type.7=Throwaway

type.8=Unidentified

Relations

relation.0=Husband

relation.1=Wife

relation.2=Father

relation.3=Mother

relation.4=Son

relation.5=Daughter

relation.6=Brother

relation.7=Sister

relation.8=Stepfather

relation.9=Stepmother

relation.10=Stepson

relation.11=Stepdaughter

relation.12=Stepbrother

relation.13=Stepsister

relation.14=Uncle

relation.15=Aunt

relation.16=Nephew

relation.17=Niece

relation.18=Grandfather

relation.19=Grandmother

relation.20=Grandson

relation.21=Granddaughter

relation.22=Cousin

relation.23=In-law

relation.24=Fiancé

relation.25=Fiancée

relation.26=Boyfriend

relation.27=Girlfriend

relation.28=Friend

relation.29=Nanny

relation.30=Others

Security questions

question.0=What is your favorite color?

question.1=What is the name of your favorite pet?
question.2=What is the name of your high school?

Global tags

```
global.style=styles/missingfilipinos.css
global.footer.copyright=<p class="copyrightclass">© 2008-2009 <a
href="http://openmpis.googlecode.com">OpenMPIS</a>. All rights reserved.</p>
global.footer.link=<ul><li><a href="viewPrivacy.do" accesskey="a">Privacy Policy</a></li><li><a
href="viewTerms.do" accesskey="b">Terms</a></li><li><a href="viewDisclaimer.do"
accesskey="c">Disclaimer</a></li><li><a href="viewAccessibility.do"
accesskey="d">Accessibility</a></li><li><a href="viewSitemap.do"
accesskey="e">Sitemap</a></li><li><a href="http://validator.w3.org/check/referer">Valid
XHTML</a></li><li><a href="http://jigsaw.w3.org/css-validator/check/referer">Valid CSS</a></li></ul>
global.menu=<ul><li><a href="viewHome.do" accesskey="1">Home</a></li><li><a href="viewCase.do?
action=list" accesskey="2">Cases</a></li><li><a href="viewAbout.do"
accesskey="3">About</a></li><li><a href="viewSearch.do" accesskey="4">Search</a></li><li><a
href="viewFeedback.do" accesskey="5">Feedback</a></li><li><a href="viewStatistics.do"
accesskey="6">Statistics</a></li><li><a href="viewForm.do" accesskey="7">Forms</a></li><li><a
href="viewTips.do" accesskey="8">Safety Tips</a></li><li><a href="viewLogin.do">Log In</a></li></ul>
global.contact=IF YOU HAVE ANY INFORMATION CONCERNING THIS CASE, PLEASE CONTACT US
AT +63 2 426-9760 OR THE NEAREST LAW ENFORCEMENT AGENCY.
```

Pagination-related tags and messages

```
pagination.firstpage.enabled=<input type="button" name="firstpage" value="First Page"
onclick="javascript: window.location = '{0}';" class="buttonclass"/>
pagination.firstpage.disabled=<input type="button" name="firstpage" value="First Page"
disabled="disabled" class="buttonclass"/>
pagination.lastpage.enabled=<input type="button" name="lastpage" value="Last Page"
onclick="javascript: window.location = '{0}';" class="buttonclass"/>
pagination.lastpage.disabled=<input type="button" name="lastpage" value="Last Page"
disabled="disabled" class="buttonclass"/>
pagination.nextpage.enabled=<input type="button" name="nextpage" value="Next Page"
onclick="javascript: window.location = '{0}';" class="buttonclass"/>
pagination.nextpage.disabled=<input type="button" name="nextpage" value="Next Page"
disabled="disabled" class="buttonclass"/>
pagination.previouspage.enabled=<input type="button" name="previouspage" value="Previous Page"
onclick="javascript: window.location = '{0}';" class="buttonclass"/>
pagination.previouspage.disabled=<input type="button" name="previouspage" value="Previous Page"
disabled="disabled" class="buttonclass"/>
```

Case-related tags and messages

```
case.title=Case
case.heading=<h1>Success</h1>
case.menu=<ul><li><a href="viewHome.do" accesskey="1">Home</a></li><li><a class="chosen"
href="viewCase.do?action=list" accesskey="2">Cases</a></li><li><a href="viewAbout.do"
accesskey="3">About</a></li><li><a href="viewSearch.do" accesskey="4">Search</a></li><li><a
href="viewFeedback.do" accesskey="5">Feedback</a></li><li><a href="viewStatistics.do"
accesskey="6">Statistics</a></li><li><a href="viewForm.do" accesskey="7">Forms</a></li><li><a
href="viewTips.do" accesskey="8">Safety Tips</a></li><li><a href="viewLogin.do">Log In</a></li></ul>
case.submenu=<ul><li><a href="viewCase.do?action=listMissing">Missing</a></li><li><a
href="viewCase.do?action=listFamilyAbduction">Family Abductions</a></li><li><a href="viewCase.do?
```

```
action=listNonFamilyAbduction">Non-Family Abductions</a></li><li><a href="viewCase.do?
action=listRunaway">Runaway</a></li><li><a href="viewCase.do?
action=listUnknown">Unknown</a></li><li><a href="viewCase.do?
action=listFound">Found</a></li><li><a href="viewCase.do?
action=listAbandoned">Abandoned</a></li><li><a href="viewCase.do?
action=listThrowaway">Throwaway</a></li><li><a href="viewCase.do?
action=listUnidentified">Unidentified</a></li><li><a href="viewCase.do?
action=listSolved">Solved</a></li><li><a href="viewCase.do?
action=listUnsolved">Unsolved</a></li></ul>
case.list=<h1>Case List (Page {0} of {1})</h1>
case.list.allmissing=<h1>All Missing Persons List (Page {0} of {1})</h1>
case.list.missing=<h1>Missing Persons List (Page {0} of {1})</h1>
case.list.familyabduction=<h1>Family Abductions List (Page {0} of {1})</h1>
case.list.nonfamilyabduction=<h1>Non-Family Abductions List (Page {0} of {1})</h1>
case.list.runaway=<h1>Runaway Persons List (Page {0} of {1})</h1>
case.list.unknown=<h1>Missing Persons with Unknown Circumstance List (Page {0} of {1})</h1>
case.list.found=<h1>Found Persons List (Page {0} of {1})</h1>
case.list.abandoned=<h1>Abandoned Persons List (Page {0} of {1})</h1>
case.list.throwaway=<h1>Throwaway Persons List (Page {0} of {1})</h1>
case.list.unidentified=<h1>Unidentified Persons List (Page {0} of {1})</h1>
case.list.solved=<h1>Solved Cases List (Page {0} of {1})</h1>
case.list.unsolved=<h1>Unsolved Cases List (Page {0} of {1})</h1>
case.add=<h1>Add Case</h1>
case.edit=<h1>Edit Case</h1>
case.delete=<h1>Delete Case</h1>
case.view=<h1>View Case</h1>
case.content.empty=There are no cases in the database.
case.content.deleted=Successfully deleted person {0} "{1}" {2} with case ID {3}.
case.content.person=The case ID is {0} and was created on {1}.
case.content.relative=The relative ID is {0}.
case.content.abductor=The abductor ID is {0}.
case.content.investigator=The investigator ID is {0} and investigator username is {1}. Please do not forget
to sign the case reporting form.
case.content.confirm=Are you sure you want to delete person {0} "{1}" {2}?
case.content.confirm.relative=This will also delete relative {0} {1}.
case.content.confirm.abductor=Likewise, abductor {0} "{1}" {2} will also be deleted.
case.add.buttons=<input type="submit" class="casebuttonclass" value="Save"/>&nbsp;&nbsp;&nbsp;<input
type="reset" class="buttonclass" value="Clear"/>&nbsp;&nbsp;&nbsp;<input type="button" class="buttonclass"
value="Cancel" onclick="javascript: window.location = 'viewCase.do?action=list';"/>
case.delete.buttons=<input type="submit" class="casebuttonclass" value="Save"/>&nbsp;&nbsp;&nbsp;<input
type="button" class="buttonclass" value="Cancel" onclick="javascript: window.location = 'viewCase.do?
action=list';"/>&nbsp;&nbsp;&nbsp;<input type="button" class="buttonclass" value="Delete" onclick="javascript:
window.location = '{0}';"/>
case.new.button=<input type="button" name="addcase" value="Add Case" onclick="javascript:
window.location = 'viewPerson.do?action=newPerson';" class="buttonclass"/>
case.delete.confirm.buttons=<input type="submit" class="casebuttonclass"
value="Delete"/>&nbsp;&nbsp;&nbsp;<input type="button" class="buttonclass" value="Cancel"
onclick="javascript: window.location = 'viewCase.do?action=list';"/>
case.assign.buttons=<input type="submit" class="casebuttonclass" value="Save"/>&nbsp;&nbsp;&nbsp;<input
type="button" class="buttonclass" value="Cancel" onclick="javascript: window.location = 'viewCase.do?
action=list';"/>
```

```
case.print.poster=<input type="button" name="poster" value="Print Poster" onclick="javascript:
window.location = '{0}';" class="buttonclass"/>
case.reports=There are {0} <a href="viewReport.do?action=viewReport&id={1}">progress reports</a> for
this person.
case.add.sighting.button=<input type="button" name="poster" value="Add Sighting" onclick="javascript:
window.location = '{0}';" class="buttonclass"/>
case.add.progress.button=<input type="button" name="addreport" value="Add Progress Report"
onclick="javascript: window.location = '{0}';" class="buttonclass"/>
case.print.progress.buttons=<input type="button" name="listreport" value="View Progress Report"
onclick="javascript: window.location = '{0}';" class="buttonclass"/>&nbsp;&nbsp;<input type="button"
name="printreport" value="Print Progress Report" onclick="javascript: window.location = '{1}';"
class="buttonclass"/>
```

Relative-related tags and messages

```
relative.title=Relative
relative.add=<h1>Add Relative</h1>
relative.edit=<h1>Edit Relative</h1>
relative.delete=<h1>Delete Relative</h1>
relative.view=<h1>View Relative</h1>
relative.content.deleted=Successfully deleted relative {0} {1} with ID {2}.
relative.content.confirm=Are you sure you want to delete {0} {1}?
relative.content.locked=Relative cannot be deleted. {0} person(s) are attributed to him/her.
relative.add.buttons=<input type="submit" class="relativebuttonclass" value="Save"/>&nbsp;&nbsp;<input
type="reset" class="buttonclass" value="Clear"/>&nbsp;&nbsp;<input type="button" class="buttonclass"
value="Cancel" onclick="javascript: window.location = 'viewCase.do?action=list';"/>
relative.delete.buttons=<input type="submit" class="relativebuttonclass"
value="Save"/>&nbsp;&nbsp;<input type="button" class="buttonclass" value="Cancel" onclick="javascript:
window.location = 'viewCase.do?action=list';"/>&nbsp;&nbsp;<input type="button" class="buttonclass"
value="Delete" onclick="javascript: window.location = '{0}';"/>
relative.delete.confirm.buttons=<input type="submit" class="relativebuttonclass"
value="Delete"/>&nbsp;&nbsp;<input type="button" class="buttonclass" value="Cancel"
onclick="javascript: window.location = 'viewCase.do?action=list';"/>
```

Abductor-related tags and messages

```
abductor.title=Abductor
abductor.add=<h1>Add Abductor</h1>
abductor.edit=<h1>Edit Abductor</h1>
abductor.delete=<h1>Delete Abductor</h1>
abductor.view=<h1>View Abductor</h1>
abductor.content.deleted=Successfully deleted abductor {0} "{1}" {2} with ID {3}.
abductor.content.confirm=Are you sure you want to delete {0} "{1}" {2}?
abductor.content.locked=Abductor cannot be deleted. {0} person(s) are attributed to him/her.
abductor.add.buttons=<input type="submit" class="abductorbuttonclass"
value="Save"/>&nbsp;&nbsp;<input type="reset" class="buttonclass" value="Clear"/>&nbsp;&nbsp;<input
type="button" class="buttonclass" value="Cancel" onclick="javascript: window.location = 'viewCase.do?
action=list';"/>
abductor.delete.buttons=<input type="submit" class="abductorbuttonclass"
value="Save"/>&nbsp;&nbsp;<input type="button" class="buttonclass" value="Cancel" onclick="javascript:
window.location = 'viewCase.do?action=list';"/>&nbsp;&nbsp;<input type="button" class="buttonclass"
value="Delete" onclick="javascript: window.location = '{0}';"/>
abductor.delete.confirm.buttons=<input type="submit" class="abductorbuttonclass"
```

```
value="Delete"/>&nbsp;&nbsp;<input type="button" class="buttonclass" value="Cancel"
onclick="javascript: window.location = 'viewCase.do?action=list';"/>
abductor.print.poster=<input type="button" name="poster" value="Print Poster" onclick="javascript:
window.location = '{0}';" class="buttonclass"/>
```

Progress report-related tags and messages

```
report.title=Progress Report
report.list=<h1>Progress Report List (Page {0} of {1})</h1>
report.add=<h1>Add Progress Report</h1>
report.edit=<h1>Edit Progress Report</h1>
report.delete=<h1>Delete Progress Report</h1>
report.content.empty=There are no progress reports.
report.content.deleted=Successfully deleted progress report {0}.
report.content.created=Successfully created progress report for {0} {1} {2} on {3}.
report.content.updated=Successfully updated progress report {0}.
report.content.confirm=Are you sure you want to delete {0}?
report.add.buttons=<input type="submit" class="reportbuttonclass" value="Save"/>&nbsp;&nbsp;<input
type="reset" class="buttonclass" value="Clear"/>&nbsp;&nbsp;<input type="button" class="buttonclass"
value="Cancel" onclick="javascript: window.location = 'viewReport.do?action=list';"/>
report.edit.buttons=<input type="submit" class="reportbuttonclass" value="Save"/>&nbsp;&nbsp;<input
type="button" class="buttonclass" value="Cancel" onclick="javascript: window.location = 'viewReport.do?
action=list';"/>
#report.delete.buttons=<input type="submit" class="reportbuttonclass"
value="Save"/>&nbsp;&nbsp;<input type="button" class="buttonclass" value="Cancel" onclick="javascript:
window.location = 'viewReport.do?action=list';"/>&nbsp;&nbsp;<input type="button" class="buttonclass"
value="Delete" onclick="javascript: window.location = '{0}';"/>
report.new.button=<input type="button" name="adduser" value="Add Progress Report"
onclick="javascript: window.location = 'viewUser.do?action=newUser';" class="buttonclass"/>
report.delete.confirm.buttons=<input type="submit" class="reportbuttonclass"
value="Delete"/>&nbsp;&nbsp;<input type="button" class="buttonclass" value="Cancel"
onclick="javascript: window.location = 'viewReport.do?action=list';"/>
```

User-related tags and messages

```
user.title=User
user.list=<h1>User List (Page {0} of {1})</h1>
user.add=<h1>Add User</h1>
user.edit=<h1>Edit User</h1>
user.delete=<h1>Delete User</h1>
user.content.empty=There are no users in the database.
user.content.deleted=Successfully deleted user {0}.
user.content.created=Successfully created user {0} with user ID {1} on {2}. Please do not forget to sign
the user application form.
user.content.updated=Successfully updated profile of {0}.
user.content.confirm=Are you sure you want to delete {0}?
user.add.buttons=<input type="submit" class="userbuttonclass" value="Save"/>&nbsp;&nbsp;<input
type="reset" class="buttonclass" value="Clear"/>&nbsp;&nbsp;<input type="button" class="buttonclass"
value="Cancel" onclick="javascript: window.location = 'viewUser.do?action=list';"/>
user.edit.buttons=<input type="submit" class="userbuttonclass" value="Save"/>&nbsp;&nbsp;<input
type="button" class="buttonclass" value="Cancel" onclick="javascript: window.location = 'viewUser.do?
action=list';"/>
#user.delete.buttons=<input type="submit" class="userbuttonclass" value="Save"/>&nbsp;&nbsp;<input
```



```
type="button" class="buttonclass" value="Cancel" onclick="javascript: window.location = 'viewUser.do?
action=list';"/>&nbsp;&nbsp;&nbsp;<input type="button" class="buttonclass" value="Delete" onclick="javascript:
window.location = 'viewUser.do?action=eraseUser&id={0}';"/>
user.new.button=<input type="button" name="adduser" value="Add User" onclick="javascript:
window.location = 'viewUser.do?action=newUser';" class="buttonclass"/>
user.delete.confirm.buttons=<input type="submit" class="userbuttonclass"
value="Delete"/>&nbsp;&nbsp;&nbsp;<input type="button" class="buttonclass" value="Cancel"
onclick="javascript: window.location = 'viewUser.do?action=list';"/>
```

Administrator-related tags and messages

```
admin.home.title=Administrator Home
admin.home.heading=<h1>Administrator Home</h1>
admin.home.menu=<ul><li><a class="chosen" href="viewUserHome.do">Home</a></li><li><a
href="viewUser.do?action=list">Users</a></li><li><a href="viewStatistics.do">Statistics</a></li><li><a
href="viewMessage.do?action=listFeedback">Feedbacks</a></li><li><a href="viewLogout.do">Log Out</
a></li></ul>
admin.home.content=Welcome, {0}!
admin.home.content.feedbacks=You have <a href="viewMessage.do?action=listFeedback">{0} new
feedback(s)</a>.
admin.user.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a class="chosen"
href="viewUser.do?action=list">Users</a></li><li><a href="viewStatistics.do">Statistics</a></li><li><a
href="viewMessage.do?action=listFeedback">Feedbacks</a></li><li><a href="viewLogout.do">Log Out</
a></li></ul>
admin.statistics.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a href="viewUser.do?
action=list">Users</a></li><li><a class="chosen" href="viewStatistics.do">Statistics</a></li><li><a
href="viewMessage.do?action=listFeedback">Feedbacks</a></li><li><a href="viewLogout.do">Log Out</
a></li></ul>
admin.feedback.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a href="viewUser.do?
action=list">Users</a></li><li><a href="viewStatistics.do">Statistics</a></li><li><a class="chosen"
href="viewMessage.do?action=listFeedback">Feedbacks</a></li><li><a href="viewLogout.do">Log Out</
a></li></ul>
admin.global.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a href="viewUser.do?
action=list">Users</a></li><li><a href="viewStatistics.do">Statistics</a></li><li><a
href="viewMessage.do?action=listFeedback">Feedbacks</a></li><li><a href="viewLogout.do">Log Out</
a></li></ul>
```

Encoder-related tags and messages

```
encoder.home.title=Encoder Home
encoder.home.heading=<h1>Encoder Home</h1>
encoder.home.menu=<ul><li><a class="chosen" href="viewUserHome.do">Home</a></li><li><a
href="viewUser.do?action=list">Users</a></li><li><a href="viewCase.do?
action=list">Cases</a></li><li><a href="viewReport.do?action=list">Progress</a></li><li><a
href="viewStatistics.do">Statistics</a></li><li><a href="viewLogout.do">Log Out</a></li></ul>
encoder.home.content=Welcome, {0}!
encoder.user.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a class="chosen"
href="viewUser.do?action=list">Users</a></li><li><a href="viewCase.do?
action=list">Cases</a></li><li><a href="viewReport.do?action=list">Progress</a></li><li><a
href="viewStatistics.do">Statistics</a></li><li><a href="viewLogout.do">Log Out</a></li></ul>
encoder.case.list=<h1>My Encoded Cases (Page {0} of {1})</h1>
encoder.case.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a href="viewUser.do?
action=list">Users</a></li><li><a class="chosen" href="viewCase.do?action=list">Cases</a></li><li><a
```

```
href="viewReport.do?action=list">Progress</a></li><li><a
href="viewStatistics.do">Statistics</a></li><li><a href="viewLogout.do">Log Out</a></li></ul>
encoder.statistics.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a href="viewUser.do?
action=list">Users</a></li><li><a href="viewCase.do?action=list">Cases</a></li><li><a
href="viewReport.do?action=list">Progress</a></li><li><a class="chosen"
href="viewStatistics.do">Statistics</a></li><li><a href="viewLogout.do">Log Out</a></li></ul>
encoder.report.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a href="viewUser.do?
action=list">Users</a></li><li><a href="viewCase.do?action=list">Cases</a></li><li><a class="chosen"
href="viewReport.do?action=list">Progress</a></li><li><a
href="viewStatistics.do">Statistics</a></li><li><a href="viewLogout.do">Log Out</a></li></ul>
encoder.global.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a href="viewUser.do?
action=list">Users</a></li><li><a href="viewCase.do?action=list">Cases</a></li><li><a
href="viewReport.do?action=list">Progress</a></li><li><a
href="viewStatistics.do">Statistics</a></li><li><a href="viewLogout.do">Log Out</a></li></ul>
```

Investigator-related tags and messages

```
investigator.home.title=Investigator Home
investigator.home.heading=<h1>Investigator Home</h1>
investigator.home.menu=<ul><li><a class="chosen" href="viewUserHome.do">Home</a></li><li><a
href="viewUser.do?action=viewUser">Profile</a></li><li><a href="viewCase.do?
action=list">Cases</a></li><li><a href="viewMessage.do?action=listSighting">Sightings</a></li><li><a
href="viewReport.do?action=list">Progress</a></li><li><a
href="viewStatistics.do">Statistics</a></li><li><a href="viewLogout.do">Log Out</a></li></ul>
investigator.home.content=Welcome, {0}!
investigator.home.content.sightings=You have <a href="viewMessage.do?action=listSighting">{0} new
sighting(s)</a>.
investigator.case.list=<h1>My Case List (Page {0} of {1})</h1>
investigator.case.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a href="viewUser.do?
action=viewUser">Profile</a></li><li><a class="chosen" href="viewCase.do?
action=list">Cases</a></li><li><a href="viewMessage.do?action=listSighting">Sightings</a></li><li><a
href="viewReport.do?action=list">Progress</a></li><li><a
href="viewStatistics.do">Statistics</a></li><li><a href="viewLogout.do">Log Out</a></li></ul>
investigator.user.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a class="chosen"
href="viewUser.do?action=viewUser">Profile</a></li><li><a href="viewCase.do?
action=list">Cases</a></li><li><a href="viewMessage.do?action=listSighting">Sightings</a></li><li><a
href="viewReport.do?action=list">Progress</a></li><li><a
href="viewStatistics.do">Statistics</a></li><li><a href="viewLogout.do">Log Out</a></li></ul>
investigator.sighting.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a
href="viewUser.do?action=viewUser">Profile</a></li><li><a href="viewCase.do?
action=list">Cases</a></li><li><a class="chosen" href="viewMessage.do?
action=listSighting">Sightings</a></li><li><a href="viewReport.do?action=list">Progress</a></li><li><a
href="viewStatistics.do">Statistics</a></li><li><a href="viewLogout.do">Log Out</a></li></ul>
investigator.global.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a href="viewUser.do?
action=viewUser">Profile</a></li><li><a href="viewCase.do?action=list">Cases</a></li><li><a
href="viewMessage.do?action=listSighting">Sightings</a></li><li><a href="viewReport.do?
action=list">Progress</a></li><li><a href="viewStatistics.do">Statistics</a></li><li><a
href="viewLogout.do">Log Out</a></li></ul>
investigator.statistics.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a
href="viewUser.do?action=viewUser">Profile</a></li><li><a href="viewCase.do?
action=list">Cases</a></li><li><a href="viewMessage.do?action=listSighting">Sightings</a></li><li><a
href="viewReport.do?action=list">Progress</a></li><li><a class="chosen"
```



```
href="viewStatistics.do">Statistics</a></li><li><a href="viewLogout.do">Log Out</a></li></ul>
investigator.report.menu=<ul><li><a href="viewUserHome.do">Home</a></li><li><a href="viewUser.do?
action=viewUser">Profile</a></li><li><a href="viewCase.do?action=list">Cases</a></li><li><a
href="viewMessage.do?action=listSighting">Sightings</a></li><li><a class="chosen"
href="viewReport.do?action=list">Progress</a></li><li><a
href="viewStatistics.do">Statistics</a></li><li><a href="viewLogout.do">Log Out</a></li></ul>
investigator.assign=<h1>Assign Investigator</h1>
investigator.title=Investigator
```

Log out-related tags and messages

```
logout.title=Log Out
logout.heading=<h1>Log Out</h1>
logout.menu=<ul><li><a href="viewHome.do" accesskey="1">Home</a></li><li><a href="viewCase.do?
action=list" accesskey="2">Cases</a></li><li><a href="viewAbout.do"
accesskey="3">About</a></li><li><a href="viewSearch.do" accesskey="4">Search</a></li><li><a
href="viewFeedback.do" accesskey="5">Feedback</a></li><li><a href="viewStatistics.do"
accesskey="6">Statistics</a></li><li><a href="viewForm.do" accesskey="7">Forms</a></li><li><a
href="viewTips.do" accesskey="8">Safety Tips</a></li><li><a href="viewLogin.do">Log In</a></li></ul>
logout.content=You have successfully logged out.
```

Home-related messages and tags

```
home.title=Home
home.menu=<ul><li><a class="chosen" href="viewHome.do" accesskey="1">Home</a></li><li><a
href="viewCase.do?action=list" accesskey="2">Cases</a></li><li><a href="viewAbout.do"
accesskey="3">About</a></li><li><a href="viewSearch.do" accesskey="4">Search</a></li><li><a
href="viewFeedback.do" accesskey="5">Feedback</a></li><li><a href="viewStatistics.do"
accesskey="6">Statistics</a></li><li><a href="viewForm.do" accesskey="7">Forms</a></li><li><a
href="viewTips.do" accesskey="8">Safety Tips</a></li><li><a href="viewLogin.do">Log In</a></li></ul>
home.content=<ul><li><a href="viewCase.do?action=listAllMissing" accesskey="8"></a></li><li><a
href="viewCase.do?action=listAllFound" accesskey="9"></a></li><li><a href="viewCase.do?action=listUnidentified"
accesskey="0"></a></li></ul>
home.alert=<h3>ALERT! Have you seen these persons?</h3>
```

About-related messages and tags

```
about.title=About
about.heading=<h1>About OpenMPIS</h1>
about.menu=<ul><li><a href="viewHome.do" accesskey="1">Home</a></li><li><a href="viewCase.do?
action=list" accesskey="2">Cases</a></li><li><a class="chosen" href="viewAbout.do"
accesskey="3">About</a></li><li><a href="viewSearch.do" accesskey="4">Search</a></li><li><a
href="viewFeedback.do" accesskey="5">Feedback</a></li><li><a href="viewStatistics.do"
accesskey="6">Statistics</a></li><li><a href="viewForm.do" accesskey="7">Forms</a></li><li><a
href="viewTips.do" accesskey="8">Safety Tips</a></li><li><a href="viewLogin.do">Log In</a></li></ul>
accessibility.title=Accessibility
disclaimer.title=Disclaimer
privacy.title=Privacy Policy
sitemap.title=Sitemap
terms.title=Terms and Conditions
```

Search-related messages and tags

```
search.title=Search
search.heading=<h1>Search</h1>
search.menu=<ul><li><a href="viewHome.do" accesskey="1">Home</a></li><li><a href="viewCase.do?
action=list" accesskey="2">Cases</a></li><li><a href="viewAbout.do"
accesskey="3">About</a></li><li><a class="chosen" href="viewSearch.do" accesskey="4">Search</a></
li><li><a href="viewFeedback.do" accesskey="5">Feedback</a></li><li><a href="viewStatistics.do"
accesskey="6">Statistics</a></li><li><a href="viewForm.do" accesskey="7">Forms</a></li><li><a
href="viewTips.do" accesskey="8">Safety Tips</a></li><li><a href="viewLogin.do">Log In</a></li></ul>
search.empty=No results.
search.searchbutton=<input type="submit" class="searchbuttonclass" value="Search"/>
```

Feedback-related messages and tags

```
feedback.title=Feedback
feedback.heading=<h1>Feedback</h1>
feedback.address=Advanced Science and Technology Institute, ASTI Bldg., CP Garcia Ave., UP
Technology Park, Diliman, Quezon City
feedback.number=+63 2 426 9760 ext. 1302
feedback.menu=<ul><li><a href="viewHome.do" accesskey="1">Home</a></li><li><a
href="viewCase.do?action=list" accesskey="2">Cases</a></li><li><a href="viewAbout.do"
accesskey="3">About</a></li><li><a href="viewSearch.do" accesskey="4">Search</a></li><li><a
class="chosen" href="viewFeedback.do" accesskey="5">Feedback</a></li><li><a
href="viewStatistics.do" accesskey="6">Statistics</a></li><li><a href="viewForm.do"
accesskey="7">Forms</a></li><li><a href="viewTips.do" accesskey="8">Safety Tips</a></li><li><a
href="viewLogin.do">Log In</a></li></ul>
feedback.content=Thank you. Your feedback has been forwarded to the administrator.
feedback.buttons=<input type="submit" class="feedbackbuttonclass"
value="Submit"/>&nbsp;&nbsp;&nbsp;<input type="reset" class="buttonclass" value="Clear"/>
feedback.list.button=<input type="button" class="buttonclass" value="Back" onclick="javascript:
window.location = 'viewMessage.do?action=listFeedback';"/>
feedback.list=<h1>Feedbacks (Page {0} of {1})</h1>
feedback.content.empty=There are no feedbacks.
```

Sighting-related messages and tags

```
sighting.title=Sighting
sighting.heading=<h1>Sighting</h1>
sighting.menu=<ul><li><a href="viewHome.do" accesskey="1">Home</a></li><li><a class="chosen"
href="viewCase.do?action=list" accesskey="2">Cases</a></li><li><a href="viewAbout.do"
accesskey="3">About</a></li><li><a href="viewSearch.do" accesskey="4">Search</a></li><li><a
href="viewFeedback.do" accesskey="5">Feedback</a></li><li><a href="viewStatistics.do"
accesskey="6">Statistics</a></li><li><a href="viewForm.do" accesskey="7">Forms</a></li><li><a
href="viewTips.do" accesskey="8">Safety Tips</a></li><li><a href="viewLogin.do">Log In</a></li></ul>
sighting.content=Thank you. Your sighting has been forwarded to the investigator.
sighting.add.buttons=<input type="submit" class="casebuttonclass" value="Save"/>&nbsp;&nbsp;&nbsp;<input
type="reset" class="buttonclass" value="Clear"/>&nbsp;&nbsp;&nbsp;<input type="button" class="buttonclass"
value="Cancel" onclick="javascript: window.location = 'viewCase.do?action=list';"/>
sighting.list.button=<input type="button" class="buttonclass" value="Back" onclick="javascript:
window.location = 'viewMessage.do?action=listSighting';"/>
sighting.list=<h1>Sightings (Page {0} of {1})</h1>
sighting.content.empty=There are no sightings.
```

Statistics-related messages and tags

```
statistics.title=Statistics
statistics.heading=<h1>Statistics</h1>
statistics.menu=<ul><li><a href="viewHome.do" accesskey="1">Home</a></li><li><a href="viewCase.do?action=list" accesskey="2">Cases</a></li><li><a href="viewAbout.do" accesskey="3">About</a></li><li><a href="viewSearch.do" accesskey="4">Search</a></li><li><a href="viewFeedback.do" accesskey="5">Feedback</a></li><li><a class="chosen" href="viewStatistics.do" accesskey="6">Statistics</a></li><li><a href="viewForm.do" accesskey="7">Forms</a></li><li><a href="viewTips.do" accesskey="8">Safety Tips</a></li><li><a href="viewLogin.do">Log In</a></li></ul>
statistics.content=<ol><li>Geographic Information System (To be implemented in version 1.1)</li><li>Figures<ol><li><a href="viewUser.do?action=countUsers">Users</a></li><li><a href="viewCase.do?action=countCases">Cases</a></li></ol></li></ol>
statistics.content.users=There are {0} user(s): {1} administrator(s), {2} encoder(s) and {3} investigator(s).
statistics.content.status=There are {0} active and {1} suspended user(s).
statistics.content.cases=There are {0} case(s): {1} on-going, {2} solved and {3} unsolved.
statistics.content.missing=There are {0} missing case(s), {1} family abduction case(s), {2} non-family abduction case(s), {3} runaway case(s) and {4} unknown case(s).
statistics.content.found=There are {0} found case(s), {1} abandoned case(s), {2} throwaway case(s) and {3} unidentified case(s).
statistics.content.relative=There are {0} relative(s).
statistics.content.abductors=There are {0} abductor(s).
statistics.print.users=<input type="button" name="users" value="Print Users" onclick="javascript: window.location = 'viewUser.do?action=printUsers';" class="buttonclass"/>
statistics.print.cases=<input type="button" name="cases" value="Print Cases" onclick="javascript: window.location = 'viewCase.do?action=printCases';" class="buttonclass"/>
```

Form-related messages and tags

```
form.title=Forms
form.heading=<h1>Forms</h1>
form.menu=<ul><li><a href="viewHome.do" accesskey="1">Home</a></li><li><a href="viewCase.do?action=list" accesskey="2">Cases</a></li><li><a href="viewAbout.do" accesskey="3">About</a></li><li><a href="viewSearch.do" accesskey="4">Search</a></li><li><a href="viewFeedback.do" accesskey="5">Feedback</a></li><li><a href="viewStatistics.do" accesskey="6">Statistics</a></li><li><a class="chosen" href="viewForm.do" accesskey="7">Forms</a></li><li><a href="viewTips.do" accesskey="8">Safety Tips</a></li><li><a href="viewLogin.do">Log In</a></li></ul>
form.content=<ol><li><a href="viewCaseForm.do">Case Reporting Form</a></li><li><a href="viewUserForm.do">User Application Form</a></li></ol>
```

Tips-related messages and tags

```
tips.title=Safety Tips
tips.heading=<h1>Safety Tips</h1>
tips.menu=<ul><li><a href="viewHome.do" accesskey="1">Home</a></li><li><a href="viewCase.do?action=list" accesskey="2">Cases</a></li><li><a href="viewAbout.do" accesskey="3">About</a></li><li><a href="viewSearch.do" accesskey="4">Search</a></li><li><a href="viewFeedback.do" accesskey="5">Feedback</a></li><li><a href="viewStatistics.do" accesskey="6">Statistics</a></li><li><a href="viewForm.do" accesskey="7">Forms</a></li><li><a class="chosen" href="viewTips.do" accesskey="8">Safety Tips</a></li><li><a href="viewLogin.do">Log In</a></li></ul>
tips.content=<ol><li>Do not talk to strangers.</li><li>Avoid walking alone at night.</li><li>Inform your
```

relatives of your whereabouts.If you got separated from your group or family, do not look for them.Be cautious of your surroundings.

Log in-related messages and tags

login.title=Log In

login.heading=<h1>Log In</h1>

login.menu=HomeCasesAboutSearchFeedbackStatisticsFormsSafety TipsLog In

login.content=Forgot password? Click here.

login.buttons=<input type="submit" class="loginbuttonclass" value="Log In"/> <input type="reset" class="buttonclass" value="Clear"/>

Password retrieval-related messages and tags

password.title=Password Reset

password.heading=<h1>Password Reset</h1>

password.menu=HomeCasesAboutSearchFeedbackStatisticsFormsSafety TipsLog In

password.content=Your password has been sent to {0}.

password.buttons=<input type="submit" class="loginbuttonclass" value="Send Password"/> <input type="reset" class="buttonclass" value="Clear"/>

The localized filename must be reflected on the Struts configuration file (openmpis/web/WEB-INF/struts-config.xml). This configuration file also controls all the action forms, beans and mappings for the entire application.

```
<?xml version="1.0" encoding="UTF-8" ?>
```

```
<!DOCTYPE struts-config PUBLIC
```

```
    "-//Apache Software Foundation//DTD Struts Configuration 1.2//EN"
```

```
    "http://jakarta.apache.org/struts/dtds/struts-config_1_2.dtd">
```

```
<struts-config>
```

```
  <form-beans>
```

```
    <form-bean
```

```
      name="feedbackForm"
```

```
      type="com.googlecode.openmpis.form.FeedbackForm"/>
```

```
    <form-bean
```

```
      name="searchForm"
```

```
      type="com.googlecode.openmpis.form.SearchForm"/>
```

```
    <form-bean
```

```
      name="loginForm"
```

```
      type="com.googlecode.openmpis.form.LoginForm"/>
```

```
<form-bean
  name="passwordForm"
  type="com.googlecode.openmpis.form.PasswordForm"/>
<form-bean
  name="userForm"
  type="com.googlecode.openmpis.form.UserForm"/>
<form-bean
  name="personForm"
  type="com.googlecode.openmpis.form.PersonForm"/>
<form-bean
  name="relativeForm"
  type="com.googlecode.openmpis.form.RelativeForm"/>
<form-bean
  name="abductorForm"
  type="com.googlecode.openmpis.form.AbductorForm"/>
<form-bean
  name="reportForm"
  type="com.googlecode.openmpis.form.ReportForm"/>
<form-bean
  name="investigatorForm"
  type="com.googlecode.openmpis.form.InvestigatorForm"/>
<form-bean
  name="messageForm"
  type="com.googlecode.openmpis.form.MessageForm"/>
</form-beans>
<global-exceptions>
</global-exceptions>
<global-forwards>
  <forward
    name="failure"
    path="/WEB-INF/errors/error.jsp"/>
  <forward
    name="expired"
    path="/WEB-INF/errors/sessionError.jsp"/>
  <forward
    name="unauthorized"
    path="/WEB-INF/errors/authorizationError.jsp"/>
</global-forwards>
<action-mappings>
  <action
    path="/viewHome"
    type="com.googlecode.openmpis.action.HomeAction"
    scope="request">
    <forward name="home" path="/WEB-INF/pages/home.jsp"/>
  </action>
  <action
    path="/viewAbout"
    type="org.apache.struts.actions.ForwardAction"
    parameter="/WEB-INF/pages/about/about.jsp"/>
  <action
    path="/viewPrivacy"
```

```
        type="org.apache.struts.actions.ForwardAction"
        parameter="/WEB-INF/pages/about/privacy.jsp"/>
<action
    path="/viewTerms"
    type="org.apache.struts.actions.ForwardAction"
    parameter="/WEB-INF/pages/about/terms.jsp"/>
<action
    path="/viewDisclaimer"
    type="org.apache.struts.actions.ForwardAction"
    parameter="/WEB-INF/pages/about/disclaimer.jsp"/>
<action
    path="/viewAccessibility"
    type="org.apache.struts.actions.ForwardAction"
    parameter="/WEB-INF/pages/about/accessibility.jsp"/>
<action
    path="/viewSitemap"
    type="org.apache.struts.actions.ForwardAction"
    parameter="/WEB-INF/pages/about/sitemap.jsp"/>
<action
    path="/viewStatistics"
    type="org.apache.struts.actions.ForwardAction"
    parameter="/WEB-INF/pages/statistics/statistics.jsp" />
<action
    path="/viewSearch"
    type="org.apache.struts.actions.ForwardAction"
    parameter="/WEB-INF/pages/search/searchForm.jsp"/>
<action
    path="/viewTips"
    type="org.apache.struts.actions.ForwardAction"
    parameter="/WEB-INF/pages/tips/tips.jsp"/>
<action
    path="/viewLogin"
    type="org.apache.struts.actions.ForwardAction"
    parameter="/WEB-INF/pages/session/loginForm.jsp"/>
<action
    path="/viewFeedback"
    type="org.apache.struts.actions.ForwardAction"
    parameter="/WEB-INF/pages/feedback/feedbackForm.jsp"/>
<action
    path="/viewPassword"
    type="org.apache.struts.actions.ForwardAction"
    parameter="/WEB-INF/pages/password/passwordForm.jsp"/>
<action
    path="/viewForm"
    type="org.apache.struts.actions.ForwardAction"
    parameter="/WEB-INF/pages/form/form.jsp"/>
<action
    path="/viewCaseForm"
    type="org.apache.struts.actions.ForwardAction"
    parameter="/WEB-INF/pages/form/OpenMPIS Case Form 1.0.pdf"/>
<action
```



```
        path="/viewUserForm"
        type="org.apache.struts.actions.ForwardAction"
        parameter="/WEB-INF/pages/form/OpenMPIS User Form 1.0.pdf"/>
<!-- List, add, view, edit, delete and count users -->
<action
    path="/viewUser"
    type="com.googlecode.openmpis.action.UserAction"
    scope="request"
    name="userForm"
    input="/WEB-INF/pages/session/userForm.jsp"
    validate="false"
    parameter="action">
    <forward name="list-user" path="/WEB-INF/pages/session/listUsers.jsp"/>
    <forward name="list-user-redo" redirect="true" path="/viewUser.do?action=list"/>
    <forward name="add-user" path="/WEB-INF/pages/session/addUserForm.jsp"/>
    <forward name="add-user-redo" path="/WEB-INF/pages/session/addUserForm.jsp"/>
    <forward name="add-user-success" path="/WEB-INF/pages/session/userSuccess.jsp"/>
    <forward name="edit-user" path="/WEB-INF/pages/session/editUserForm.jsp"/>
    <forward name="edit-user-redo" path="/WEB-INF/pages/session/editUserForm.jsp"/>
    <forward name="edit-user-success" path="/WEB-INF/pages/session/userSuccess.jsp"/>
    <forward name="delete-user" path="/WEB-INF/pages/session/deleteUserForm.jsp"/>
    <forward name="delete-user-redo" path="/WEB-INF/pages/session/deleteUserForm.jsp"/>
    <forward name="delete-user-success" path="/WEB-INF/pages/session/userSuccess.jsp"/>
    <forward name="user-statistics" path="/WEB-INF/pages/statistics/userStatistics.jsp"/>
</action>
<!-- List and count persons, relatives and abductors and assign investigator -->
<action
    path="/viewCase"
    type="com.googlecode.openmpis.action.CaseAction"
    scope="request"
    name="investigatorForm"
    input="/WEB-INF/pages/session/investigatorForm.jsp"
    validate="false"
    parameter="action">
    <forward name="list-person" path="/WEB-INF/pages/person/listPersons.jsp"/>
    <forward name="list-person-all-missing" path="/WEB-INF/pages/person/listPersons.jsp"/>
    <forward name="list-person-missing" path="/WEB-INF/pages/person/listPersons.jsp"/>
    <forward name="list-person-familyabduction" path="/WEB-INF/pages/person/listPersons.jsp"/>
    <forward name="list-person-nonfamilyabduction" path="/WEB-INF/pages/person/listPersons.jsp"/>
    <forward name="list-person-all-found" path="/WEB-INF/pages/person/listPersons.jsp"/>
    <forward name="list-person-abandoned" path="/WEB-INF/pages/person/listPersons.jsp"/>
    <forward name="list-person-throwaway" path="/WEB-INF/pages/person/listPersons.jsp"/>
    <forward name="list-person-unidentified" path="/WEB-INF/pages/person/listPersons.jsp"/>
    <forward name="list-person-solved" path="/WEB-INF/pages/person/listPersons.jsp"/>
    <forward name="list-person-unsolved" path="/WEB-INF/pages/person/listPersons.jsp"/>
    <forward name="list-abductor" path="/WEB-INF/pages/person/listPersons.jsp"/>
    <forward name="case-statistics" path="/WEB-INF/pages/statistics/caseStatistics.jsp"/>
    <forward name="assign-investigator" path="/WEB-INF/pages/session/investigatorForm.jsp"/>
    <forward name="edit-person-success" path="/WEB-INF/pages/session/personSuccess.jsp"/>
</action>
```

```
<!-- Add, view, edit and delete persons -->
<action
  path="/viewPerson"
  type="com.googlecode.openmpis.action.PersonAction"
  scope="request"
  name="personForm"
  input="/WEB-INF/pages/session/personForm.jsp"
  validate="false"
  parameter="action">
  <forward name="list-person" redirect="true" path="/viewCase.do?action=list"/>
  <forward name="view-person" path="/WEB-INF/pages/person/viewPersonForm.jsp"/>
  <forward name="add-person" path="/WEB-INF/pages/session/personForm.jsp"/>
  <forward name="add-person-redo" path="/WEB-INF/pages/session/personForm.jsp"/>
  <forward name="edit-person" path="/WEB-INF/pages/session/personForm.jsp"/>
  <forward name="edit-person-redo" path="/WEB-INF/pages/session/personForm.jsp"/>
  <forward name="delete-person" path="/WEB-INF/pages/session/deletePersonForm.jsp"/>
  <forward name="delete-person-redo" path="/WEB-INF/pages/session/deletePersonForm.jsp"/>
  <forward name="delete-person-success" path="/WEB-INF/pages/session/personSuccess.jsp"/>
  <forward name="select-investigator" path="/viewCase.do?action=selectInvestigator"/>
  <forward name="add-relative" path="/viewRelative.do?action=newRelative"/>
</action>
<!-- Add, view, edit and delete relatives -->
<action
  path="/viewRelative"
  type="com.googlecode.openmpis.action.RelativeAction"
  scope="request"
  name="relativeForm"
  input="/WEB-INF/pages/session/relativeForm.jsp"
  validate="false"
  parameter="action">
  <forward name="list-person" redirect="true" path="/viewCase.do?action=list"/>
  <forward name="view-relative" path="/WEB-INF/pages/session/relativeForm.jsp"/>
  <forward name="add-relative" path="/WEB-INF/pages/session/relativeForm.jsp"/>
  <forward name="add-relative-redo" path="/WEB-INF/pages/session/relativeForm.jsp"/>
  <forward name="add-relative-success" path="/WEB-INF/pages/session/relativeSuccess.jsp"/>
  <forward name="edit-relative" path="/WEB-INF/pages/session/relativeForm.jsp"/>
  <forward name="edit-relative-redo" path="/WEB-INF/pages/session/relativeForm.jsp"/>
  <forward name="edit-relative-success" path="/WEB-INF/pages/session/relativeSuccess.jsp"/>
  <forward name="delete-relative" path="/WEB-INF/pages/session/deleteRelativeForm.jsp"/>
  <forward name="delete-relative-redo" path="/WEB-INF/pages/session/deleteRelativeForm.jsp"/>
  <forward name="delete-relative-success" path="/WEB-INF/pages/session/relativeSuccess.jsp"/>
  <forward name="select-investigator" path="/viewCase.do?action=selectInvestigator"/>
  <forward name="add-abductor" path="/viewAbductor.do?action=newAbductor"/>
</action>
<!-- Add, view, edit and delete abductors -->
<action
  path="/viewAbductor"
  type="com.googlecode.openmpis.action.AbductorAction"
  scope="request"
  name="abductorForm"
  input="/WEB-INF/pages/session/abductorForm.jsp"
```



```
        validate="false"
        parameter="action">
<forward name="list-person" redirect="true" path="/viewCase.do?action=list"/>
<forward name="view-abductor" path="/WEB-INF/pages/session/abductorForm.jsp"/>
<forward name="add-abductor" path="/WEB-INF/pages/session/abductorForm.jsp"/>
<forward name="add-abductor-redo" path="/WEB-INF/pages/session/abductorForm.jsp"/>
<forward name="add-abductor-success" path="/WEB-INF/pages/session/abductorSuccess.jsp"/>
<forward name="edit-abductor" path="/WEB-INF/pages/session/abductorForm.jsp"/>
<forward name="edit-abductor-redo" path="/WEB-INF/pages/session/abductorForm.jsp"/>
<forward name="edit-abductor-success" path="/WEB-INF/pages/session/abductorSuccess.jsp"/>
<forward name="delete-abductor" path="/WEB-INF/pages/session/deleteAbductorForm.jsp"/>
<forward name="delete-abductor-redo" path="/WEB-INF/pages/session/deleteAbductorForm.jsp"/
>
    <forward name="delete-abductor-success" path="/WEB-INF/pages/session/abductorSuccess.jsp"/
>
    <forward name="select-investigator" path="/viewCase.do?action=selectInvestigator"/>
</action>
<!-- Add, view, edit and delete progress reports -->
<action
    path="/viewReport"
    type="com.googlecode.openmpis.action.ReportAction"
    scope="request"
    name="reportForm"
    input="/WEB-INF/pages/session/reportForm.jsp"
    validate="false"
    parameter="action">
<forward name="list-person" redirect="true" path="/viewCase.do?action=list"/>
<forward name="list-report" path="/WEB-INF/pages/session/listReports.jsp"/>
<forward name="view-report" path="/WEB-INF/pages/session/reportForm.jsp"/>
<forward name="add-report" path="/WEB-INF/pages/session/reportForm.jsp"/>
<forward name="add-report-redo" path="/WEB-INF/pages/session/reportForm.jsp"/>
<forward name="add-report-success" path="/WEB-INF/pages/session/reportSuccess.jsp"/>
<forward name="edit-report" path="/WEB-INF/pages/session/reportForm.jsp"/>
<forward name="edit-report-redo" path="/WEB-INF/pages/session/reportForm.jsp"/>
<forward name="edit-report-success" path="/WEB-INF/pages/session/reportSuccess.jsp"/>
<forward name="delete-report" path="/WEB-INF/pages/session/deleteReportForm.jsp"/>
<forward name="delete-report-redo" path="/WEB-INF/pages/session/deleteReportForm.jsp"/>
<forward name="delete-report-success" path="/WEB-INF/pages/session/reportSuccess.jsp"/>
</action>
<!-- List, add, edit, view and delete sightings and feedbacks -->
<action
    path="/viewMessage"
    type="com.googlecode.openmpis.action.MessageAction"
    scope="request"
    name="messageForm"
    input="/WEB-INF/pages/sighting/sightingForm.jsp"
    validate="false"
    parameter="action">
<forward name="list-feedback" path="/WEB-INF/pages/session/listMessages.jsp"/>
<forward name="list-sighting" path="/WEB-INF/pages/session/listMessages.jsp"/>
<forward name="list-feedback-redo" path="/viewMessage.do?action=listFeedback"/>
```

```
<forward name="list-sighting-redo" path="/viewMessage.do?action=listSighting"/>
<forward name="view-message" path="/WEB-INF/pages/session/viewMessageForm.jsp"/>
<forward name="add-sighting" path="/WEB-INF/pages/sighting/sightingForm.jsp"/>
<forward name="add-sighting-redo" path="/WEB-INF/pages/sighting/sightingForm.jsp"/>
<forward name="add-sighting-success" path="/WEB-INF/pages/sighting/sightingSuccess.jsp"/>
<forward name="list-person" redirect="true" path="/viewCase.do?action=listAllMissing"/>
</action>
<!-- User home page -->
<action
    path="/viewUserHome"
    type="com.googlecode.openmpis.action.AuthenticateAction"
    scope="request">
    <forward name="authenticated" path="/WEB-INF/pages/session/index.jsp"/>
</action>
<!-- Log in -->
<action
    path="/login"
    type="com.googlecode.openmpis.action.LoginAction"
    scope="request"
    name="loginForm"
    input="/WEB-INF/pages/session/loginForm.jsp"
    validate="false">
    <forward name="login-success" redirect="true" path="/viewUserHome.do"/>
    <forward name="login-redo" path="/viewLogin.do"/>
</action>
<!-- Log out -->
<action
    path="/viewLogout"
    type="com.googlecode.openmpis.action.LogoutAction"
    scope="request">
    <forward name="logout-success" path="/WEB-INF/pages/session/logoutSuccess.jsp"/>
</action>
<!-- Send feedback -->
<action
    path="/feedback"
    type="com.googlecode.openmpis.action.FeedbackAction"
    scope="request"
    name="feedbackForm"
    input="/WEB-INF/pages/feedback/feedbackForm.jsp"
    validate="false">
    <forward name="feedback-success" path="/WEB-INF/pages/feedback/feedbackSuccess.jsp"/>
    <forward name="feedback-redo" path="/WEB-INF/pages/feedback/feedbackForm.jsp"/>
</action>
<!-- Reset password -->
<action
    path="/resetPassword"
    type="com.googlecode.openmpis.action.PasswordAction"
    scope="request"
    name="passwordForm"
    input="/WEB-INF/pages/password/passwordForm.jsp"
    validate="true">
```

```
<forward name="password-success" path="/WEB-INF/pages/password/passwordSuccess.jsp"/>
<forward name="password-redo" path="/WEB-INF/pages/password/passwordForm.jsp"/>
</action>
<!-- Search -->
<action
    path="/search"
    type="com.googlecode.openmpis.action.SearchAction"
    name="searchForm"
    input="/WEB-INF/pages/search/searchForm.jsp"
    validate="true">
    <forward name="search-success" path="/WEB-INF/pages/search/searchSuccess.jsp"/>
</action>
</action-mappings>
<controller processorClass="org.apache.struts.tiles.TilesRequestProcessor" nocache="true"/>
<message-resources parameter="com.googlecode.openmpis.resource.ApplicationResource"/>
                                <message-resources                key="_PH"
parameter="com.googlecode.openmpis.resource.ApplicationResource__PH"/>

<!-- ===== Tiles plugin =====>
<!--
This plugin initialize Tiles definition factory. This later can takes some
parameters explained here after. The plugin first read parameters from
web.xml, then overload them with parameters defined here. All parameters
are optional.
The plugin should be declared in each struts-config file.
- definitions-config: (optional)
Specify configuration file names. There can be several comma
separated file names (default: ?? )
- moduleAware: (optional - struts1.1)
Specify if the Tiles definition factory is module aware. If true
(default), there will be one factory for each Struts module.
If false, there will be one common factory for all module. In this
later case, it is still needed to declare one plugin per module.
The factory will be initialized with parameters found in the first
initialized plugin (generally the one associated with the default
module).
true : One factory per module. (default)
false : one single shared factory for all modules
- definitions-parser-validate: (optional)
Specify if xml parser should validate the Tiles configuration file.
true : validate. DTD should be specified in file header (default)
false : no validation

Paths found in Tiles definitions are relative to the main context.
-->
<plug-in className="org.apache.struts.tiles.TilesPlugin" >
    <set-property property="definitions-config" value="/WEB-INF/tiles-defs.xml" />
    <set-property property="moduleAware" value="true" />
</plug-in>

<!-- ===== Validator plugin ===== -->
```

```
<!--  
<plug-in className="org.apache.struts.validator.ValidatorPlugIn">  
  <set-property  
    property="pathnames"  
    value="/WEB-INF/validator-rules.xml,/WEB-INF/validation.xml"/>  
</plug-in>  
-->  
</struts-config>
```

5. Images

The developer can add new pictures under the `openmpis/web/images` directory. The file `favicon.ico` contains the *salakot* logo of OpenMPIS.

6. Database Schema

The developer can modify the database by editing the openmpis/database/openmpis-schema.druid file. He will also have to modify the SQL maps, data transfer objects, services and data access objects in the openmpis/src/com/googlecode/openmpis directory if needed. The generated SQL file is in openmpis/database/MySQL directory.

```
-- =====
-- ===  Sql Script for Database : OpenMPIS
-- ===
-- === Build : 135
-- =====

BEGIN WORK;

CREATE DATABASE IF NOT EXISTS openmpis;

USE openmpis;
-- =====

CREATE TABLE abductor
(
  id          serial,
  firstName   varchar(30),
  nickname    varchar(30),
  middleName  varchar(30),
  lastName    varchar(30),
  birthMonth  int2,
  birthDay    int2,
  birthYear   int2,
  street      varchar(60),
  city        varchar(30),
  province    varchar(30),
  country     varchar(30),
  sex         int2      not null default 0,
  feet        int2,
  inches      int2,
  weight      int2,
  religion     int2      not null default 0,
  race        int2      not null default 0,
  eyeColor    int2      not null default 0,
  hairColor   int2      not null default 0,
  marks       text,
  personalEffects text,
  remarks     text      not null,
  photo       text,
  agedPhoto   text,
  codisID     varchar(30) unique,
  afisID      varchar(30) unique,
  dentalID    varchar(30) unique,
```

```
    primary key(id)
)
TYPE = InnoDB;

CREATE INDEX openmpis.abductorIDX1 ON abductor(id);
```

-- =====

```
CREATE TABLE log
(
    id serial,
    log text not null,
    date date not null,

    primary key(id)
)
TYPE = InnoDB;

CREATE INDEX openmpis.logIDX1 ON log(id);
```

-- =====

```
CREATE TABLE message
(
    id serial,
    date date not null,
    email varchar(60) not null,
    firstName varchar(30) not null,
    lastName varchar(30) not null,
    subject varchar(60) not null,
    message text not null,
    status int2 not null default 0,
    ipAddress varchar(30) not null,
    personID int4,
    userID int4 not null,

    primary key(id)
)
TYPE = InnoDB;

CREATE INDEX openmpis.messageIDX1 ON message(id);
```

-- =====

```
CREATE TABLE person
(
    id serial,
    status int2 not null default 0,
    type int2 not null,
    firstName varchar(30),
```

nickname varchar(30),
middleName varchar(30),
lastName varchar(30),
birthMonth int2,
birthDay int2,
birthYear int2,
street varchar(60),
city varchar(30),
province varchar(30),
country varchar(30),
sex int2 not null,
feet int2 not null,
inches int2 not null,
weight int2 not null,
religion int2 not null default 0,
race int2 not null default 0,
eyeColor int2 not null default 0,
hairColor int2 not null default 0,
medicalCondition text,
marks text not null,
personalEffects text not null,
remarks text,
monthMissingOrFound int2 not null,
dayMissingOrFound int2 not null,
yearMissingOrFound int2 not null,
missingFromCity varchar(30),
missingFromProvince varchar(30),
missingFromCountry varchar(30),
possibleCity varchar(30),
possibleProvince varchar(30),
possibleCountry varchar(30),
circumstance text,
reward int4 default 0,
institution varchar(60),
institutionStreet varchar(60),
institutionCity varchar(30),
institutionProvince varchar(30),
institutionCountry varchar(30),
institutionEmail varchar(60),
institutionNumber varchar(30),
photo text,
agedPhoto text,
codisID varchar(30) unique,
afisID varchar(30) unique,
dentalID varchar(30) unique,
date date not null,
encoderID int4 not null,
investigatorID int4,
relativeID int4,
abductorID int4,
relationToRelative int2,


```
relationToAbductor int2,

primary key(id)
)
TYPE = InnoDB;

CREATE INDEX openmpis.personIDX1 ON person(id);

-- =====

CREATE TABLE relative
(
  id      serial,
  firstName varchar(30) not null,
  middleName varchar(30) not null,
  lastName  varchar(30) not null,
  street    varchar(60) not null,
  city      varchar(30) not null,
  province  varchar(30) not null,
  country   varchar(30) not null,
  email     varchar(60),
  number    varchar(30) unique not null,

  primary key(id)
)
TYPE = InnoDB;

CREATE INDEX openmpis.relativeIDX1 ON relative(id);

-- =====

CREATE TABLE report
(
  id      serial,
  personID int4 not null,
  investigatorID int4 not null,
  report    text not null,
  date      date not null,

  primary key(id)
)
TYPE = InnoDB;

CREATE INDEX openmpis.reportIDX1 ON report(id);

-- =====

CREATE TABLE user
(
  id      serial,
  groupID int2 not null,
```

Documentation for developer

```
username  varchar(6)  unique not null,
password  varchar(32) not null,
firstName varchar(30) not null,
middleName varchar(30) not null,
lastName  varchar(30) not null,
birthMonth int2,
birthDay  int2,
birthYear int2,
email     varchar(60) unique not null,
designation varchar(30) not null,
agency    varchar(60) not null,
number    varchar(30) not null,
ipAddress varchar(30),
lastLogin date,
date      date      not null,
creatorID int4       not null,
status    int2       not null default 0,
question  int2       not null,
answer    varchar(30),

    primary key(id)
)
TYPE = InnoDB;

CREATE INDEX openmpis.userIDX1 ON user(id);

-- =====

INSERT INTO user
(GROUPID, USERNAME, PASSWORD, FIRSTNAME, MIDDLENAME, LASTNAME, BIRTHMONTH,
BIRTHDAY, BIRTHYEAR,
EMAIL, DESIGNATION, AGENCY, NUMBER,
IPADDRESS, LASTLOGIN, DATE,
STATUS, QUESTION, ANSWER, CREATORID)
VALUES
(0, 'RB0106', MD5('admin[123]'), 'Rey Vincent', 'Potencio', 'Babilonia', '01', '06', '1982',
'rvbabilonia@gmail.com', 'SRSI', 'Advanced Science and Technology Institute', '+63 2 426 9760 ext.
1302',
'127.0.0.1', '2009-02-15', '2009-02-15',
0, 0, 'green', 0);

COMMIT;
-- =====
```

6. File Listing

These are the Web pages and Web-related files:

```
openmpis/web/  
  index.jsp  
  robots.txt  
  sitemap.xml  
  
openmpis/web/scripts/  
  md5.js  
  openmpis.js  
  
openmpis/web/styles/  
  missingfilipinos.css  
  openmpis.css  
  
openmpis/web/WEB-INF/  
  errors/  
    authorizationError.jsp  
    error.jsp  
    resourceError.jsp  
    sessionError.jsp  
  pages/  
    home.jsp  
    about/  
      about.jsp  
      accessibility.jsp  
      disclaimer.jsp  
      privacy.jsp  
      sitemap.jsp  
      terms.jsp  
    feedback/  
      feedbackForm.jsp  
      feedbackSuccess.jsp  
    form/  
      form.jsp  
      OpenMPIS Case Form 1.0.odt  
      OpenMPIS Case Form 1.0.pdf  
      OpenMPIS User Form 1.0.odt  
      OpenMPIS User Form 1.0.pdf  
    password/  
      passwordForm.jsp  
      passwordSuccess.jsp  
    person/  
      listPersons.jsp  
      viewPersonForm.jsp  
    search/  
      searchForm.jsp  
      searchSuccess.jsp
```

- session/
 - [abductorForm.jsp](#)
 - [abductorSuccess.jsp](#)
 - [addUserForm.jsp](#)
 - [deleteAbductorForm.jsp](#)
 - [deletePersonForm.jsp](#)
 - [deleteRelativeForm.jsp](#)
 - [deleteUserForm.jsp](#)
 - [editUserForm.jsp](#)
 - [index.jsp](#)
 - [investigatorForm.jsp](#)
 - [listMessages.jsp](#)
 - [listReports.jsp](#)
 - [listUsers.jsp](#)
 - [loginForm.jsp](#)
 - [logoutSuccess.jsp](#)
 - [personForm.jsp](#)
 - [personSuccess.jsp](#)
 - [relativeForm.jsp](#)
 - [relativeSuccess.jsp](#)
 - [reportForm.jsp](#)
 - [reportSuccess.jsp](#)
 - [userSuccess.jsp](#)
 - [viewMessageForm.jsp](#)
- sighting/
 - [sightingForm.jsp](#)
 - [sightingSuccess.jsp](#)
- statistics/
 - [caseStatistics.jsp](#)
 - [statistics.jsp](#)
 - [userStatistics.jsp](#)
- tips/
 - [tips.jsp](#)
- [struts-bean.tld](#)
- [struts-config.xml](#)
- [struts-html.tld](#)
- [struts-logic.tld](#)
- [struts-nested.tld](#)
- [struts-tiles.tld](#)
- tags/
 - [footer.tag](#)
 - [header.tag](#)
- [tiles-defs.xml](#)
- [validation.xml](#)
- [validator-rules.xml](#)
- [web.xml](#)

These are the Java source codes and XML-based SQL maps:

- [openmpis/src/](#)
 - [log4j.properties](#)

mail.properties
sqlmapconfig.properties

openmpis/src/com/googlecode/openmpis/
action/

AbductorAction.java
AuthenticateAction.java
CaseAction.java
FeedbackAction.java
HomeAction.java
LoginAction.java
LogoutAction.java
MessageAction.java
package.html
PasswordAction.java
PersonAction.java
RelativeAction.java
ReportAction.java
SearchAction.java
UserAction.java

dto/

Abductor.java
Log.java
Message.java
package.html
Person.java
Relative.java
Report.java
User.java

form/

AbductorForm.java
FeedbackForm.java
InvestigatorForm.java
LoginForm.java
MessageForm.java
package.html
PasswordForm.java
PersonForm.java
RelativeForm.java
ReportForm.java
SearchForm.java
UserForm.java

persistence/ibatis/

abductor.xml

dao/

AbductorDAO.java

impl/

AbductorDAOImpl.java
LogDAOImpl.java
MessageDAOImpl.java
package.html

```

        PersonDAOImpl.java
        RelativeDAOImpl.java
        ReportDAOImpl.java
        UserDAOImpl.java
    LogDAO.java
    MessageDAO.java
    package.html
    PersonDAO.java
    RelativeDAO.java
    ReportDAO.java
    UserDAO.java
log.xml
message.xml
person.xml
relative.xml
report.xml
service/
    AbductorService.java
    impl/
        AbductorServiceImpl.java
        LogServiceImpl.java
        MessageServiceImpl.java
        package.html
        PersonServiceImpl.java
        RelativeServiceImpl.java
        ReportServiceImpl.java
        UserServiceImpl.java
    LogService.java
    MessageService.java
    package.html
    PersonService.java
    RelativeService.java
    ReportService.java
    UserService.java
sqlmapconfig.xml
user.xml
resource/
    ApplicationResource.properties
    ApplicationResource__PH.properties
util/
    Configuration.java
    Constants.java
    Mail.java
    package.html
    Pagination.java
    SqlMapConfig.java
    Validator.java
```