

Armenia CCDR Microsimulation

Renato Vargas Julie Rozenberg Colin Lenoble
Natsuko Kiso Nozaki

Table of contents

0.1	Introduction	1
0.2	Preamble	2
0.3	Datasets	3
0.4	Data preparation income outliers and missings	7
0.4.1	Household consumption aggregates and characteristics	7
0.4.2	Demographic characteristics, education, Labor Force	7
0.4.3	The regression	13
0.4.4	Total income and shares	14
0.5	UN Population Projections	16
0.6	Macro Scenarios	19
0.7	Reweighting of the dataset	23
0.7.1	Aggregation of population data	23
0.7.2	Reweighting	26
0.7.3	Rescaling labor income according to changes to the wage bill	38
0.8	Microsimulation	42
0.8.1	Macro scenarios without additional impacts	42
0.8.2	Climate change	44
0.8.3	Food prices	55
0.8.4	Disaggregation of poverty measures	68

0.1 Introduction

In this calculation file, we “age” the household survey according to demographic projections and different macroeconomic scenarios to explore the impact of climate-related risks and policy measures on the consumption expenditure distribution.

As a convention, code is presented in the following format in this guide:

```
# Some comment that is not evaluated by R
some_variable <- some_function(some_object, some_parameter = TRUE)
```

We assume that the reader has created an Rstudio project and is familiar with basic R functions. Within that project we recommend the following file structure:

```
root/
  scripts
    my_script.R
  data/
  |   my_data.sav
  |   my_data.dta
  |   my_data.csv
  output
    my_output1.csv
    my_output2.xlsx
```

Using RStudio project makes it possible to not use `setwd()` to establish the root directory and refer to subdirectories in a relative manner, making interoperability easier within teams and not hard coding a particular computer's file structure into the code. If you are not using RStudio, just add `setwd(r'(C:\My\path\to\project\root)')` at the beginning of your coding session.

0.2 Preamble

We start with a clean environment, making sure that any objects from a previous session are not present. We take this opportunity to keep our country ISO code in a variable `iso` in case we need it later.

```
# Clean workspace
rm(list = ls())

# Armenia country ISO code
iso <- "ARM"

# Survey year
surveyyear <- 2022

# Exchange rate USD per dram
er <- 0.002310
```

We call the appropriate libraries.

Rather than calling our libraries as we go, we will make sure we have everything we need from the beginning.

```
# Load packages
library(tidyverse) # includes dplyr, ggplot2 and others
library(haven)     # to read SPSS and Stata datasets
library(readxl)    # to read from MS-Excel
library(openxlsx)  # to write to MS-Excel.
library(gt)        # pretty tables
library(car)       # Companion to applied regression
library(modelr)    # regression models
#library(ebal)     # Entropy reweighting
library(anesrake)  # Raking reweighting
#library(weights)  # Weigthed survey statistics
library(janitor)   # pretty subtotals
library(broom)     # More regressions
library(purrr)     # map vectors (aggregation)
library(zoo)       # Calculate moving window average and max value

# Geopackages
library(sf)        # to read and write shapefile maps
library(terra)     # to perform geocalculations
library(tmap)      # for static and interactive maps
```

Stata integration

```
library(RStata)    # stata integration for wentropy function
options("RStata.StataPath" = "\"C:\\Program Files (x86)\\Stata11\\StataMP\"")
options("RStata.StataVersion" = 11)
```

0.3 Datasets

We then load the datasets that we need for this study. The World Bank has processed some of these already for poverty analysis and so we have the original SPSS datasets with all variables for Households **hh** and for Individuals **pp**, as well as a consumption aggregate **ca** and a household income **ic** dataset, which are Stata datasets. This is for the year 2022. These are imported using the **haven** package. These are based on Armenia Integrated Living Conditions Survey 2022 (ARMSTAT, 2023).

```

# Original SPSS datasets
# Households (hh)
hh <- read_sav(
  "data/ARM-HH-survey/original-spss-files/ILCS-ARM-2022-Households.sav")
# Persons (pp)
pp <- read_sav(
  "data/ARM-HH-survey/original-spss-files/ILCS-ARM-2022-Persons.sav")

# Processed WB datasets
# Consumption aggregate at household level (ca)
ca <- read_dta("data/ARM-HH-survey/CONSAGG2022.dta")
# Processed income at household level (ic)
ic <- read_dta("data/ARM-HH-survey/totinc.dta")

# Food diary
food_with_prices <- read_dta("data/ARM-HH-survey/FOOD_with_prices_short.dta")

```

We will work non-destructively, meaning we will not rewrite these data sets and we will only create intermediate data frame objects from them to perform transformations, selections and other data management tasks. For example, we will keep household assignment to poverty status and consumption deciles handy by creating a subset of our `ca` data with only our household identifiers, deciles, and poverty.

```

# From the WB processed dataset, we extract deciles and poverty
deciles <- ca %>%
  select( hhid, decile, poor_Avpovln2022,
          poor_Foodpovln2022, poor_Lpovln2022, poor_Upovln2022)

```

Our population data comes from UN's projections.

```

# Population projections UN 2022
population_projections <- read_dta("data/UN2022_population.dta") %>%
  filter(country == iso)

```

Macro scenario dataset

```

scenario_file <- "data/ARM-Microsimulation/ARM_MacroScenarioInformation.xlsx"
scenario_varlist <- read_xlsx(
  "data/ARM-Microsimulation/ARM_Macro_varlist.xlsx")
prices_2030 <-
  read_csv("data/ARM-Microsimulation/prices2030.csv")

```

Economic sectors.

```
sectors <- read_xlsx("data/ARM-HH-survey/economic_activity_codes.xlsx")
```

We also have geographical information for level 1 in Shapefile format, which we import with the `sf` package. We rename the column with the name of the administrative region to match our household survey data set conventions to ease mergers. The `dplyr` package from the `tidyverse` meta package allows us to “pipe” or link processing steps using the `%>%` pipe, which can be inserted using **Ctrl + m**. Although there is no geoprocessing in this analysis, this will come in handy for graphical presentations. Let’s have a look at it.

```
# Geodata
# Armenia marzes or administrative level 1 shapefile
adm1 <- read_sf("data/ARM-Geodata/ARM-ADM1.shp") %>%
  select(NAM_1, COD_HH_SVY, geometry) %>%
  # Make sure that names match the rest of datasets
  mutate(NAM_1 = if_else(NAM_1 == "Gergharkunik", "Gegharkunik", NAM_1))
names(adm1)[2] <- "hh_02"

tm_shape(adm1)+
  tm_polygons("NAM_1", legend.show = FALSE) +
  tm_text("NAM_1", size = 3/4)
```



Marzes names are more accurate in the shapefile than in the survey. We will use them from here on instead of the survey factor labels.

```
hh <- hh %>%
  left_join(adm1, join_by(hh_02 == hh_02)) %>%
  select(-geometry)

ic <- ic %>%
  left_join(adm1, join_by(hh_02 == hh_02)) %>%
  select(-geometry)
```

Labor productivity

```
file <- r"(data/ARM-Microsimulation/LaborProductivityChanges.xlsx)"
sheets <- excel_sheets(file)

# Use lapply to read and process each sheet
heat_l_pdcty <- lapply(sheets, function(sheet) {
  info <- read_excel(
    file,
    sheet = sheet,
    col_names = TRUE,
    col_types = c("text", "text", "numeric", "text", "numeric")
  )
  info$sector <- sheet
  return(info)
})

# Bind all data frames in the list into a single data frame
heat_l_pdcty <- bind_rows(heat_l_pdcty)
```

Finally, but not least important, we have our vulnerability information.

```
buildings_aal <-
  read_xlsx("data/ARM-Vulnerability-Analysis/Data_AAL_AAE.xlsx",
    sheet = "Building_AAL") %>%
  # Make sure that names match the rest of datasets
  mutate(NAM_1 = if_else(NAM_1 == "Gergharkunik", "Gegharkunik", NAM_1))
buildings_1in100 <-
  read_xlsx("data/ARM-Vulnerability-Analysis/Data_AAL_AAE.xlsx",
    sheet = "Building_1in100")
crops_productivity <-
```

```

read.csv("data/ARM-Vulnerability-Analysis/ARM_crops_combined_REF_shock_admin1.csv") %>%
rename(NAM_1 = Province)
livestock_productivity <-
read.csv(
  "data/ARM-Vulnerability-Analysis/ARM_livestock_REF_shock_admin1.csv"
) %>%
rename(NAM_1 = Province)
crops_aal <-
read_xlsx("data/ARM-Vulnerability-Analysis/Data_AAL_AAE.xlsx",
  sheet = "Agriculture_AAL")
crops_1in100 <-
read_xlsx("data/ARM-Vulnerability-Analysis/Data_AAL_AAE.xlsx",
  sheet = "Agriculture_1in100")

```

0.4 Data preparation income outliers and missings

0.4.1 Household consumption aggregates and characteristics

Initial necessary variables.

```

consumption_aggregates <- ca %>%
  mutate(rural = ifelse(urb_rur == 2, 1, 0), # Create rural indicator
    yhh = totc, # Total household expenditure
    wgt_adj = pweight) %>% # Make a copy of the weight variable
  select(hhid, rural, hhsize, hhsize_R, marz, aepc, yhh, wgt_adj, weight,
    Foodpovln2022, Lpovln2022, Upovln2022, Avpovln2022,
    poor_Foodpovln2022, poor_Lpovln2022, poor_Upovln2022,
    poor_Avpovln2022, decile ) # Keep only necessary columns

```

0.4.2 Demographic characteristics, education, Labor Force

Here the original code calls for Zone data, which is not present in our dataset, due to the different administrative structure of Armenia. However, we use `hh_01_code` (settlement) for this purpose.

```

# Zone data
zone_data <- hh %>%
  select(interview__key, hh_01_code, hh_02, hh_03, NAM_1) %>%
  mutate(
    hhid = interview__key, # Household id

```

```

zone = hh_01_code,      # Settlement
marz = hh_02,          # Marz
NAM_1 = NAM_1,          # Marz name
urb_rur = hh_03         # Urban / rural
)

```

Demographic data, merge with zone data Note that ed_03 (educy) below is not years of education, but education level (primary, general, secondary, etc.) However, it is ordered in a way that higher levels imply more years of education. We perform several steps within the first pipe call.

```

pp_microsim <- pp %>%
  rename(hhid = interview__key) %>%
  left_join(zone_data, join_by( hhid == hhid)) %>%
  mutate(# Demographic characteristics
    pid = paste0(interview__key, "-",
                  str_pad(mem_001__id, 2, pad = "0")), # Unique person id
    gender = mem_02,
    age = mem_05,
    head = ifelse(mem_03 == 1, 1, 0),
    # Education level
    educy = ifelse(is.na(ed_03) | ed_03 == 8, 0, ed_03),
    # Labor Force Status
    lstatus = case_when(
      # 1. Employed
      est_03 == 1 | est_04 == 1 | est_05 == 1 | est_06 == 1 | est_08 == 1 ~ 1L,
      # 2. Unemployed (available, and searching)
      est_10 == 1 ~ 2L,
      # 3. Inactive (available, not searching)
      est_10 == 2 ~ 3L,
      # Out of the labor force
      .default = 4L # Default to OLF
    ),
    employed = (lstatus == 1),
    # Salaried status (1. paid employee; 2 self-employed)
    salaried = ifelse(!is.na(emp_11a), 1L,
                      ifelse(is.na(emp_11a) & employed == TRUE, 0L, NA_integer_))
  ) %>%
  rename(rel = mem_03) # %>%
  # select(hhid, pid, gender, age, head, rel, zone, marz, urb_rur, educy,
  #        lstatus, employed, salaried, )

```


Later, when we conduct the reweighting of the dataset, we need to summarise into three levels of education.

```
pp_microsim <- pp_microsim %>%
  mutate(calif = case_when(
    educy >= 0 & educy <= 2 ~ "None - General",
    educy > 3 & educy <= 7 ~ "Secondary - Vocational",
    educy > 7 & educy <= 11 ~ "Higher +",
    TRUE ~ NA_character_ # This handles any values outside the specified ranges
  ))

# View the first few rows to confirm the recoding
head(pp_microsim[,c("calif")])
```

```
# A tibble: 6 x 1
  calif
  <chr>
1 Secondary - Vocational
2 None - General
3 Secondary - Vocational
4 Secondary - Vocational
5 Secondary - Vocational
6 Secondary - Vocational
```

Count the number of employed persons by household.

```
pp_microsim <- pp_microsim %>%
  mutate(employed = (lstatus == 1)) %>%
  group_by(hhid) %>%
  mutate(employed_hh = sum(employed, na.rm = TRUE)) %>% # Count within each household
  ungroup()
```

Here the original Stata code calculates income variables and aggregates them by household. We skip that because the dataset “ic” already has these elements calculated by the WB poverty team. We’ll add them later.

Primary and Secondary Job income

- **emp__11** 11.How much was %rostartitle%'s payment for wages/salary/income for last month?
- **emp__12** 12.What period of time was the wage/income for?

- **emp_25** 25.How much was %roster%’s payment for wages/salary/income for last month?
- **emp_26** 26.What period of time was the wage/income for?

Bonus, In-Kind, and food from job was not asked in Armenia, If it were, you should add a `mutate()` statement like the ones below for each subcategory.

```
pp_microsim <- pp_microsim %>%
  # Labor income primary job
  mutate(annual_labor_income_primary = case_when(
    emp_12 == 1 ~ emp_11 * 365,
    emp_12 == 2 ~ (emp_11/7) * 365, # Assuming weekly rate
    emp_12 == 3 ~ (emp_11/14) * 365,
    emp_12 == 4 ~ emp_11 * 12,
    emp_12 == 5 ~ emp_11 * 2,
    emp_12 == 6 ~ emp_11,
    emp_12 == 7 ~ NA
  )) %>%
  # Labor income secondary job
  mutate(annual_labor_income_secondary = case_when(
    emp_26 == 1 ~ emp_25 * 365,
    emp_26 == 2 ~ (emp_25/7) * 365, # Assuming weekly rate
    emp_26 == 3 ~ (emp_25/14) * 365,
    emp_26 == 4 ~ emp_25 * 12,
    emp_26 == 5 ~ emp_25 * 2,
    emp_26 == 6 ~ emp_25,
    emp_26 == 7 ~ NA
  )) %>%
  # Annual labor total in thousands of dram
  mutate(annual_labor_total = (coalesce(annual_labor_income_primary, 0) +
    coalesce(annual_labor_income_secondary, 0))/1000)

# Restore annual_labor_total to NA if both NA
pp_microsim <- pp_microsim %>%
  mutate(annual_labor_total =
    if_else(
      is.na(annual_labor_income_primary)
      & is.na(annual_labor_income_secondary),
      NA,
      annual_labor_total))
```

26.23% employed with no labor income reported!!! We calculate this way:

```
total_employed_no_income <- pp_microsim %>%
  filter(employed == TRUE & is.na(annual_labor_total)) %>%
  nrow()

total_employed <- pp_microsim %>%
  filter(employed == TRUE) %>%
  nrow()

percent_employed_no_income <- (total_employed_no_income / total_employed) * 100

print(percent_employed_no_income)
```

```
[1] 28.57496
```

Let's flag outliers now

```
pp_microsim <- pp_microsim %>%
  # Filter for employed and positive income
  #filter(employed == TRUE & annual_labor_total > 0) %>%
  mutate(
    sd = sd(annual_labor_total, na.rm = TRUE), # Calculate standard deviation
    d = annual_labor_total / sd,
    # Combined outlier condition
    outlier = (d > 5) | (employed == TRUE & annual_labor_total == 0),
    # Mark potential missings
    missings = if_else(employed == TRUE, is.na(annual_labor_total), NA)
  )
```

Economic sector

```
pp_microsim <- pp_microsim %>%
  mutate(emp_04 = as.integer(emp_04)) %>%
  left_join(sectors, join_by("emp_04" == "economic_activity_code") ) %>%
  rename(sector = ea_shortcode)
```

Impute sector for those with missing employed by hh head sector.

Step 1: Impute sector for missing employed by the sector of any other hh member.

```

pp_microsim <- pp_microsim %>%
  group_by(hhid) %>%
  mutate(
    # Create a temporary variable 'other_sector' which captures the sector of any employed in
    other_sector = if_else(employed == TRUE & !is.na(sector), sector, NA_real_)
  ) %>%
  # Use 'fill' to propagate 'other_sector' values within the household
  fill(other_sector, .direction = "downup") %>%
  mutate(
    # Impute missing 'sector' values based on the 'other_sector'
    sector = if_else(is.na(sector) & employed == TRUE, other_sector, sector)
  ) %>%
  # Drop the temporary 'other_sector' variable
  select(-other_sector) %>%
  ungroup()

```

Step 2: Assign a specific value for missing sectors for those employed with no one else in the hh to assign value. We select services as it's the heaviest sector in the dataset (we do it like this, instead of say, matching, because it's only 2 observations).

```

pp_microsim <- pp_microsim %>%
  mutate(sector = if_else(is.na(sector) & employed == TRUE, 3, sector))

```

Step 4: Label the sector variable.

```

pp_microsim <- pp_microsim %>%
  mutate(sector_name = factor(sector, levels = c(1, 2, 3),
                              labels = c("Agriculture",
                                           "Manufacturing", "Services"))
  )

```

Step 5: No sector for OLF and clonevar industry=sector (this from original Stata code).

```

pp_microsim <- pp_microsim %>%
  mutate(lstatus = as.numeric(lstatus),
         sector = if_else(lstatus == 4, as.character(NA), as.character(sector)),
         industry = as.factor(sector)) %>%
  mutate(sector_w = sector) # We need this for reweighting and not messing up
                           # and not mess up the regression below.

```

0.4.3 The regression

Prepare the data.

```
pp_microsim <- pp_microsim %>%  
  mutate(  
    educy2 = educy^2,  
    age2 = age^2,  
    male = case_when(  
      gender == 1 ~ 1,  
      gender == 2 ~ 0  
    ),  
    lnlab = log(annual_labor_total),  
    simuli = NA_real_ # Initialize simuli  
  )
```

Filter the data for regression conditions.

```
regression_data <- pp_microsim %>%  
  filter(employed == TRUE & outlier == FALSE & missings == FALSE)
```

Regression model.

```
model <- lm(lnlab ~ age + gender + educy + age2 + marz + sector,  
            data = regression_data)
```

Predict for specific conditions

```
pp_microsim <- pp_microsim %>%  
  mutate(  
    condition = (lstatus == 1 & (outlier == TRUE | missings == TRUE))  
  )
```

Applying predictions.

Note: The ‘predict’ function in R does not directly support conditions within the function call, so we handle this by filtering or subsetting the data as needed.

temp2 equivalent - Note: ‘type = “response”’ might be needed depending on model type.

```
pp_microsim$simuli[pp_microsim$condition==TRUE] <- exp(
  predict(model, pp_microsim[pp_microsim$condition==TRUE, ], type = "response"))
```

Handling negative values in 'simuli'.

```
pp_microsim <- pp_microsim %>%
  mutate(
    simuli = if_else(simuli < 0, 0, simuli)
  )
```

There were 8 observations that met the criteria:

We will replace `annual_labor_total` with this value for those observations.

```
pp_microsim <- pp_microsim %>%
  mutate(annual_labor_total = if_else(
    employed == TRUE & (outlier == TRUE | missings == TRUE),
    simuli, annual_labor_total))

# And get monthly incomes for everyone
pp_microsim <- pp_microsim %>%
  mutate(monthly_labor_income = annual_labor_total / 12)
```

Merging datasets.

```
pp_microsim <- pp_microsim %>%
  left_join(consumption_aggregates, by = "hhid")
```

0.4.4 Total income and shares

Total labor income at HH level.

```
pp_microsim <- pp_microsim %>%
  group_by(hhid) %>%
  mutate(lab_hh = sum(annual_labor_total, na.rm = TRUE)) %>%
  ungroup()
```

Monthly incomes come from the `ic` data set.

```
incomes <- ic %>%
  select(interview__key, inc1, inc2, inc3, inc4, inc5, inc6, inc7, inc8)
```

Total income at HH level (the commented out portion was a less efficient way of accomplishing the same result of coalescing NAs to 0 so that the sum can be performed). Note that here we need to use the magrittr pipe %>% instead of the newer Native Pipe %>, because we need to reference the correct scope with the dot ..

```
pp_microsim <- pp_microsim %>%
  left_join(incomes, by = c("hhid" = "interview__key")) %>%
  mutate(across(inc5:inc8, ~replace_na(., 0))) %>%
  mutate(nli_hh = 12 * rowSums(select(., inc5:inc8), na.rm = TRUE)) %>%
  mutate(income_hh = lab_hh + nli_hh)

# pp_microsim <- pp_microsim %>%
#   left_join(incomes, join_by(hhid == interview__key)) %>%
#   mutate(nli_hh = ( coalesce(inc5) +
#                     coalesce(inc6) +
#                     coalesce(inc7) +
#                     coalesce(inc8)) * 12) %>%
#   mutate(income_hh = lab_hh + nli_hh)
```

Calculating shares:

```
pp_microsim <- pp_microsim %>%
  mutate(
    s_lab = lab_hh / income_hh,
    s_nli = nli_hh / income_hh,
    lny = log(income_hh),
    lnc = log(yhh), # comes from consumption aggregates
    mpc = yhh / income_hh
  )
```

Shares of labor and non-labor income, and additional calculations.

```
pp_microsim <- pp_microsim %>%
  mutate(
    share = if_else(employed == TRUE, annual_labor_total / lab_hh, NA_real_),
    ylb = yhh * s_lab,
    ynl = yhh * (1 - s_lab),
    ylbi = if_else(employed == TRUE, ylb * share, NA_real_)
  )
```

Final subset of data.

```
pp_microsim <- pp_microsim %>%
  select(hhid, pid, industry, yhh, ylb, ynl, ylbi, salaried,
         rural, hhsize, hhsize_R, marz.x, aepc, yhh, wgt_adj, weight,
         Foodpovln2022, Lpovln2022, Upovln2022, Avpovln2022,
         poor_Foodpovln2022, poor_Lpovln2022, poor_Upovln2022,
         poor_Avpovln2022, decile, zone, urb_rur,
         gender, age, head, rel, zone, educy, calif, sector, sector_name,
         annual_labor_total, annual_labor_income_primary,
         annual_labor_income_secondary, monthly_labor_income,
         lstatus, sector_w, NAM_1 ) %>%
  rename(marz = marz.x)

# Exporting to Stata (might be necessary for reweighting with wentropy)
# write_dta(pp_microsim, path = "outputs/pp_microsim.dta", version = 10)
```

0.5 UN Population Projections

Now we are ready to move to our demographic projections and macroeconomic model information.

First, filtering based on country (our `iso` variable).

```
population_projections <- population_projections %>%
  filter(country == iso)
```

Collapsing data by summing up variables starting with “yf” and “ym” and reshaping data to long format.

```
population_projections <- population_projections %>%
  group_by(Variant, country, cohort) %>%
  summarise(across(starts_with(c("yf", "ym")), sum)) %>%
  ungroup()
```

``summarise()`` has grouped output by 'Variant', 'country'. You can override using the ``groups`` argument.

```
population_projections <- pivot_longer(population_projections,
                                       cols = starts_with(c("yf", "ym")),
                                       names_to = c(".value", "year"),
                                       names_pattern = "(yf|ym)(.*)")
```


Creating new variable `total_population` as the sum of `yf` and `ym`. Dropping `country` variables.

```
population_projections <- population_projections %>%  
  mutate(total_population = yf + ym) %>%  
  select( -country) %>%  
  mutate(year = as.numeric(year))
```

Summarizing the year to find the range.

```
minyear <- surveyyear # Make sure `surveyyear` is correctly defined  
maxyear <- max(as.numeric(population_projections$year))  
  
# Print the year range as a check  
print(paste("Min Year:", minyear, "- Max Year:", maxyear))
```

```
[1] "Min Year: 2022 - Max Year: 2100"
```

```
# With minyear and maxyear defined above  
# Initialize a list to store growth data  
pop_growth <- list()  
  
# Loop over variants  
variants <- unique(population_projections$Variant)  
for (variant in variants) {  
  for (t in minyear:maxyear) {  
  
    # Calculate population for year t  
    pop_t <- population_projections %>%  
      filter(year == t, Variant == variant) %>%  
      summarise(sum_pop = sum(total_population)) %>%  
      pull(sum_pop)  
  
    # Calculate population for base year  
    pop_base <- population_projections %>%  
      filter(year == minyear, Variant == variant) %>%  
      summarise(sum_pop = sum(total_population)) %>%  
      pull(sum_pop)  
  
    # Calculate growth rate and store in list with dynamic naming  
    growth_rate <- pop_t / pop_base
```

```

    pop_growth[[paste0(t, "_", variant)]] <- list(
      growth_rate = growth_rate, pop_t = pop_t
    )
  }
}

# Convert list to dataframe
pop_growth <- do.call(rbind, lapply(names(pop_growth), function(x) {
  # Extract year and variant from the name
  parts <- unlist(strsplit(x, "_"))
  year <- as.integer(parts[1])
  variant <- parts[2]

  # Create a tibble for each entry
  tibble(year = year,
          variant = variant,
          total_population = pop_growth[[x]]$pop_t,
          pop_growth_rate = pop_growth[[x]]$growth_rate)
}))

# Arrange the dataframe for better readability
pop_growth <- arrange(pop_growth, variant, year)

# Display the first few rows of the dataframe
pop_growth[c(1:09),]

```

```

# A tibble: 9 x 4
  year variant          total_population pop_growth_rate
<int> <chr>              <dbl>          <dbl>
1  2022 Constant-fertility    2780.          1
2  2023 Constant-fertility    2778.         0.999
3  2024 Constant-fertility    2778.         0.999
4  2025 Constant-fertility    2776.         0.998
5  2026 Constant-fertility    2774.         0.998
6  2027 Constant-fertility    2770.         0.996
7  2028 Constant-fertility    2766.         0.995
8  2029 Constant-fertility    2761.         0.993
9  2030 Constant-fertility    2755.         0.991

```

We load elasticities.

```
elasticities <- c(0.82, 0.9, 0.79) # Agr, Manuf, Services
yearsto <- c(2030)
```

0.6 Macro Scenarios

The following code accomplishes the following:

- Import data from Excel sheets corresponding to each scenario and combine them into one data frame.
- Rename columns, create a 'scenid' to identify scenarios, and merge with population projections.
- Calculate real wages and consumption per capita.

```
# Macro Scenario File imported in "Datasets" section (scenario_file)
sheets <- excel_sheets(scenario_file)
scenario_sheets <- sheets[c(1,2)]

# Define the names of the scenarios and the variants
# modify list with the tab numbers in the Excel file
scenarios <- scenario_sheets %>%
  # Convert all text to lowercase
  str_to_lower() %>%
  # Replace all spaces and hyphens with underscores
  str_replace_all("[ -]", "_") %>%
  # Remove the word 'scenario' or 'scenarios'
  str_remove_all("scenario?s?") %>%
  # Remove leading and trailing underscores
  str_replace_all("^_|_+$", "")

# Create an empty list to store data frames for each scenario
scen_data_list <- list()

# Import data for each scenario and store it in the list
for (i in seq_along(scenarios)) {
  sheet_data <- read_excel(scenario_file,
                           sheet = scenario_sheets[i],
                           range = "B3:AT31",
                           col_names = FALSE)
  sheet_data$scenario_id <- scenarios[i]
  colnames(sheet_data) <- scenario_varlist$var_short_name
```

```
scen_data_list[[i]] <- sheet_data  
}
```

New names:

New names:

```
* `` -> `...1`  
* `` -> `...2`  
* `` -> `...3`  
* `` -> `...4`  
* `` -> `...5`  
* `` -> `...6`  
* `` -> `...7`  
* `` -> `...8`  
* `` -> `...9`  
* `` -> `...10`  
* `` -> `...11`  
* `` -> `...12`  
* `` -> `...13`  
* `` -> `...14`  
* `` -> `...15`  
* `` -> `...16`  
* `` -> `...17`  
* `` -> `...18`  
* `` -> `...19`  
* `` -> `...20`  
* `` -> `...21`  
* `` -> `...22`  
* `` -> `...23`  
* `` -> `...24`  
* `` -> `...25`  
* `` -> `...26`  
* `` -> `...27`  
* `` -> `...28`  
* `` -> `...29`  
* `` -> `...30`  
* `` -> `...31`  
* `` -> `...32`  
* `` -> `...33`  
* `` -> `...34`  
* `` -> `...35`  
* `` -> `...36`  
* `` -> `...37`
```

```

* `` -> `...38`
* `` -> `...39`
* `` -> `...40`
* `` -> `...41`
* `` -> `...42`
* `` -> `...43`
* `` -> `...44`
* `` -> `...45`

```

```

# Combine all data frames into one
combined_data <- bind_rows(scen_data_list)

# Rename population_m from the data set because we will use
# UN pop projections from the other data set.
combined_data <- combined_data %>%
  rename(population_m_macrodata = population_m)

# Calculate real wages
combined_data <- combined_data %>%
  mutate(rwage_agr_m_amd = wage_agr_m_amd / cpi,
         rwage_man_m_amd = wage_man_m_amd / cpi,
         rwage_ser_m_amd = wage_ser_m_amd / cpi)

pop_data <- population_projections %>%
  group_by(Variant, year) %>%
  summarise(female = sum(yf),
           male = sum(ym),
           total_population = sum(total_population) ) %>%
  ungroup()

```

`summarise()` has grouped output by 'Variant'. You can override using the `.groups` argument.

```

# Filter population data to macro model years
pop_data <- pop_data %>%
  filter(year <= max(combined_data$year),
         Variant == variants[7])

# Merge the combined data with population projections
macro_data <- combined_data %>%
  left_join(pop_data, by = c("year"))

# Calculate consumption per capita and other totals

```

```

macro_data <- macro_data %>%
  mutate(
    consumption_pc = consumption_b_amd / (total_population),
    total_employment = lab_agr_1000p + lab_man_1000p + lab_ser_1000p,
    employment_rate = working_age_pop_m / total_population
  )

# Function to add growth rate columns directly in the dataframe
calculate_growth <- function(data, value_column) {
  growth_col_name <- paste0(value_column, "_growth") # dynamic name for growth column
  data %>%
    arrange(year) %>%
    group_by(Variant, scenario_id) %>%
    mutate(
      base_value = first(!sym(value_column)),
      !!sym(growth_col_name) := !!sym(value_column) / base_value
    ) %>%
    select(-base_value) %>% # optionally remove base_value column if not needed
    ungroup()
}

# Columns to calculate growth for
value_columns <- c(
  "gdp_b_amd",          # GDP
  "consumption_b_amd",  # Consumption
  "consumption_pc",     # Consumption PC
  "remittances_b_amd",  # Remittances
  "total_employment",   # Employment
  "employment_rate",    # Employment rate
  "working_age_pop_m",  # Working age population
  "va_agr_b_amd",       # Value added agriculture
  "va_man_b_amd",       # Value added manufacturing
  "va_ser_b_amd",       # Value added services
  "wage_agr_m_amd",     # Nominal wage agriculture
  "wage_man_m_amd",     # Nominal wage manufacturing
  "wage_ser_m_amd",     # Nominal wage services
  "rwage_agr_m_amd",    # Real wage agriculture
  "rwage_man_m_amd",    # Real wage manufacturing
  "rwage_ser_m_amd"     # Real wage services
)

# Applying the growth calculation to the macro_data for each column

```

```

for (col in value_columns) {
  macro_data <- calculate_growth(macro_data, col)
}

# Now `macro_data` will have growth rate columns for each of the variables listed
# We rearrange the dataset for clarity
macro_data <- macro_data %>%
  relocate(scenario_id, Variant, .before = year) %>%
  arrange(scenario_id, Variant, year)

```

0.7 Reweighting of the dataset

0.7.1 Aggregation of population data

This is based on a custom command to reweight the survey according to macroeconomic data for every possible combination of variant, year, and country. In the macro data we know they only used the “medium” variant and we only need to reweight for a specific year (2030) for Armenia (ARM), so we will conduct the reweighting directly with these parameters.

```

# We join several cohorts from 0 to 29 years old and from
# 60 onwards, because the reweighting procedure works
# best if each category is at least 5% of the population
# The solution here works best for Armenia.

population_projections <- population_projections %>%
  # filter(Variant == "Medium") %>%
  # Recoding cohorts into ordered factors
  mutate(cohort_short = factor(case_when(
    cohort %in% c("P0004", "P0509", "P1014",
                  "P1519", "P2024", "P2529") ~ "P0029",
    cohort %in% c("P3034", "P3539") ~ "P3039",
    cohort %in% c("P4044", "P4549") ~ "P4049",
    cohort %in% c("P5054", "P5559") ~ "P5059",
    cohort %in% c("P6064", "P6569", "P7074", "P7579",
                  "P8084", "P8589", "P9094", "P9599",
                  "P100up") ~ "P60up"
  ), levels = c("P0029", "P3039",
                "P4049", "P5059", "P60up"))) %>%

  # Convert factor 'cohort' to numeric codes
  mutate(cohort_code = as.integer(cohort_short))

```

```
# Checking the resulting dataset
print(pop_data)
```

```
# A tibble: 60 x 5
  Variant year female male total_population
  <chr>   <dbl> <dbl> <dbl>         <dbl>
1 Medium  1991  1867. 1750.         3618.
2 Medium  1992  1850. 1724.         3575.
3 Medium  1993  1799. 1658.         3457.
4 Medium  1994  1763. 1610.         3374.
5 Medium  1995  1741. 1581.         3323.
6 Medium  1996  1731. 1568.         3299.
7 Medium  1997  1719. 1552.         3271.
8 Medium  1998  1705. 1535.         3241.
9 Medium  1999  1689. 1517.         3206.
10 Medium 2000  1672. 1496.         3169.
# i 50 more rows
```

Let's now create cohorts in our `pp_microsim` data to match our population projection data.

```
# Convert 'age' into 'cohort' factor with levels ordered as specified
pp_microsim <- pp_microsim %>%
  mutate(cohort = factor(case_when(
    age >= 0 & age <= 29 ~ "P0029",
    age >= 30 & age <= 39 ~ "P3039",
    age >= 40 & age <= 49 ~ "P4049",
    age >= 50 & age <= 59 ~ "P5059",
    age >= 60 ~ "P60up"
  ), levels = c("P0029", "P3039", "P4049", "P5059", "P60up")))

# Convert the 'cohort' and 'gender' factor to numeric codes
pp_microsim <- pp_microsim %>%
  mutate(cohort_code = as.integer(cohort)) %>%
  mutate(gender_code = as.integer(gender))
```

We also need demographic targets for 2030

```
# Ensure pop_targets_2030 is correctly prepared
# We use the "Medium" variant = variants[7]
pop_targets_2030 <- population_projections %>%
```



```

filter(year == 2030, Variant == variants[7]) %>%
group_by(cohort_code, cohort_short) %>%
  summarise(female = sum(yf),
            male   = sum(ym),
            total  = sum(total_population),
            ) %>%
ungroup()

```

`summarise()` has grouped output by 'cohort_code'. You can override using the `.groups` argument.

```

pop_total <- sum(pop_targets_2030$total)

pop_targets_2030 <- pop_targets_2030 %>%
  mutate(pct_total = total / pop_total)

#writeClipboard(as_raw_html(gt(pop_targets_2030)))

```

And economic targets from our macroeconomic scenario data.

```

economic_targets_2030 <- macro_data %>%
  filter(year == 2030, Variant == "Medium", scenario_id == "baseline") %>%
  summarise(
    target_lab_agr = sum(lab_agr_1000p * 1000),
    target_lab_man = sum(lab_man_1000p * 1000),
    target_lab_ser = sum(lab_ser_1000p * 1000)
  )

```

For a better representation of the labor market, we will take into account the combination between labor status and economic sector of the employed and adjust that combination according to the macrodata so that we can accurately model changes in total employment, sector distribution of the employed and overall population changes.

```

pp_microsim <- pp_microsim %>%
  mutate(lmarket = case_when(
    lstatus == 1 & sector_w == 1 ~ 1, # Agriculture
    lstatus == 1 & sector_w == 2 ~ 2, # Manufactures
    lstatus == 1 & sector_w == 3 ~ 3, # Services
    lstatus == 2 & is.na(sector_w) ~ 4, # Unemployed
    lstatus == 3 & is.na(sector_w) ~ 4, # Unemployed
  ))

```

```
lstatus == 4 & is.na(sector_w) ~ 5,    # OLF

))
```

Note that the differences between the totals of the survey and the macro file for the base year are very much different. We'll adjust the survey only with relative growth instead of total numbers so that labor income doesn't change completely.

0.7.2 Reweighting

We use anesrake to calculate targets from known future proportions of sex, age, economic sector. We first create a target list.

```
# Target for each variable

gender_code <- c(
  sum(pop_targets_2030$male) /
  (sum(pop_targets_2030$male)+ sum(pop_targets_2030$female)),
  sum(pop_targets_2030$female) /
  (sum(pop_targets_2030$male)+ sum(pop_targets_2030$female)))

cohort_code <- pop_targets_2030$pct_total

# Four digits are better than two in this case, raking is quite accurate.
lmarket_baseline <- c(0.1341, 0.0494, 0.2611, 0.2472, 0.3082)
lmarket_dry_hot <- c(0.1368, 0.0489, 0.2593, 0.2472, 0.3078)
# Note how similar the scenarios are

# Target list baseline
targets_baseline <- list(gender_code
  , cohort_code
  , lmarket_baseline
  )

names(targets_baseline) <- c("gender_code",
  "cohort_code",
  "lmarket"
  )

# Target list Dry/Hot
targets_dry_hot <- list(gender_code
```

```

        , cohort_code
        , lmarket_dry_hot
      )

names(targets_dry_hot) <- c("gender_code",
                           "cohort_code",
                           "lmarket"
                          )

```

And now we perform the reweighting, using the original weights. Initially we had used the default option `type = "pctlim"` combined with `pctlim=0.05`, because the method recommends that if reweighting changes for one variable according to its target are not of at least 5%, then it's not worth burdening the procedure with it. It then ignored sex as a reweighting variable, leaving a small percentage difference between the target and the final population. However, we then tried removing this limitation and the procedure reached convergence in 33 iterations very efficiently.

```

# Since this uses base R, we need to turn the data frame into base R object
rakedata <- as.data.frame(pp_microsim)

anesrakefinder(targets_baseline, rakedata, choosemethod = "total")

```

```

gender_code cohort_code    lmarket
0.03626510  0.09677000  0.07212418

```

```

outsave <- anesrake(targets_baseline,
                    rakedata,
                    caseid = rakedata$pid,
                    #verbose = FALSE,
                    choosemethod = "total",
                    #type = "pctlim",
                    type = "nolim",
                    #cap = 100,
                    #pctlim = 0.05,
                    nlim = 3,
                    iterate = TRUE,
                    force1 = TRUE,
                    verbose = TRUE,
                    weightvec = rakedata$weight)

```

```
[1] "Raking...Iteration 1"
```

[1] "Current iteration changed total weights by 2365.37047462746"
 [1] "Raking...Iteration 2"
 [1] "Current iteration changed total weights by 345.629544201074"
 [1] "Raking...Iteration 3"
 [1] "Current iteration changed total weights by 51.129532012726"
 [1] "Raking...Iteration 4"
 [1] "Current iteration changed total weights by 15.8102078836608"
 [1] "Raking...Iteration 5"
 [1] "Current iteration changed total weights by 5.00226200109642"
 [1] "Raking...Iteration 6"
 [1] "Current iteration changed total weights by 1.58313448389485"
 [1] "Raking...Iteration 7"
 [1] "Current iteration changed total weights by 0.500820317613819"
 [1] "Raking...Iteration 8"
 [1] "Current iteration changed total weights by 0.158458854255416"
 [1] "Raking...Iteration 9"
 [1] "Current iteration changed total weights by 0.0501397739726498"
 [1] "Raking...Iteration 10"
 [1] "Current iteration changed total weights by 0.0158655682184549"
 [1] "Raking...Iteration 11"
 [1] "Current iteration changed total weights by 0.00502030487751332"
 [1] "Raking...Iteration 12"
 [1] "Current iteration changed total weights by 0.00158856388303248"
 [1] "Raking...Iteration 13"
 [1] "Current iteration changed total weights by 0.000502665741921302"
 [1] "Raking...Iteration 14"
 [1] "Current iteration changed total weights by 0.000159057405067636"
 [1] "Raking...Iteration 15"
 [1] "Current iteration changed total weights by 5.03301832327496e-05"
 [1] "Raking...Iteration 16"
 [1] "Current iteration changed total weights by 1.59258690392711e-05"
 [1] "Raking...Iteration 17"
 [1] "Current iteration changed total weights by 5.03938627684219e-06"
 [1] "Raking...Iteration 18"
 [1] "Current iteration changed total weights by 1.59460194727734e-06"
 [1] "Raking...Iteration 19"
 [1] "Current iteration changed total weights by 5.04577232413039e-07"
 [1] "Raking...Iteration 20"
 [1] "Current iteration changed total weights by 1.59661560861224e-07"
 [1] "Raking...Iteration 21"
 [1] "Current iteration changed total weights by 5.05214382690022e-08"
 [1] "Raking...Iteration 22"
 [1] "Current iteration changed total weights by 1.59870944677065e-08"

```

[1] "Raking...Iteration 23"
[1] "Current iteration changed total weights by 5.05728310618014e-09"
[1] "Raking...Iteration 24"
[1] "Current iteration changed total weights by 1.60276966698625e-09"
[1] "Raking...Iteration 25"
[1] "Current iteration changed total weights by 5.05979536047363e-10"
[1] "Raking...Iteration 26"
[1] "Current iteration changed total weights by 1.60390659087462e-10"
[1] "Raking...Iteration 27"
[1] "Current iteration changed total weights by 5.05322866883873e-11"
[1] "Raking...Iteration 28"
[1] "Current iteration changed total weights by 1.52227813687844e-11"
[1] "Raking...Iteration 29"
[1] "Current iteration changed total weights by 5.3808346667239e-12"
[1] "Raking...Iteration 30"
[1] "Current iteration changed total weights by 2.08032202575481e-12"
[1] "Raking...Iteration 31"
[1] "Current iteration changed total weights by 6.44706510399828e-13"
[1] "Raking...Iteration 32"
[1] "Current iteration changed total weights by 0"
[1] "Raking...Iteration 33"
[1] "Current iteration changed total weights by 0"
[1] "Raking converged in 33 iterations"

```

```
summary(outsave)
```

```
$convergence
```

```
[1] "Complete convergence was achieved after 33 iterations"
```

```
$base.weights
```

```
[1] "Using Base Weights Provided"
```

```
$raking.variables
```

```
[1] "gender_code" "cohort_code" "lmarket"
```

```
$weight.summary
```

Min.	1st Qu.	Median	Mean	3rd Qu.	Max.
0.1034	0.6701	0.9287	1.0000	1.2687	3.3900

```
$selection.method
```

```
[1] "variable selection conducted using _nolim_ - discrepancies selected using _total_."
```

```
$general.design.effect
[1] 1.244926
```

```
$gender_code
```

	Target	Old Weights	N	Old Weights	%	Wtd	N	Wtd	%	Change in %
<NA>	0.4514133		NA		NA	NA	NA	NA		NA
<NA>	0.5485867		NA		NA	NA	NA	NA		NA
Total	1.0000000		0		0	0	0	0		0

	Resid.	Disc.	Orig.	Disc.
<NA>	NA		NA	
<NA>	NA		NA	
Total	0		0	

```
$cohort_code
```

	Target	Old Weights	N	Old Weights	%	Wtd	N	Wtd	%	Change in %
<NA>	0.3638899		NA		NA	NA	NA	NA		NA
<NA>	0.1420277		NA		NA	NA	NA	NA		NA
<NA>	0.1630905		NA		NA	NA	NA	NA		NA
<NA>	0.1042513		NA		NA	NA	NA	NA		NA
<NA>	0.2267405		NA		NA	NA	NA	NA		NA
Total	1.0000000		0		0	0	0	0		0

	Resid.	Disc.	Orig.	Disc.
<NA>	NA		NA	
<NA>	NA		NA	
<NA>	NA		NA	
<NA>	NA		NA	
<NA>	NA		NA	
Total	0		0	

```
$lmarket
```

	Target	Old Weights	N	Old Weights	%	Wtd	N	Wtd	%	Change in %	Resid.	Disc.
<NA>	0.1341		NA		NA	NA	NA	NA		NA	NA	
<NA>	0.0494		NA		NA	NA	NA	NA		NA	NA	
<NA>	0.2611		NA		NA	NA	NA	NA		NA	NA	
<NA>	0.2472		NA		NA	NA	NA	NA		NA	NA	
<NA>	0.3082		NA		NA	NA	NA	NA		NA	NA	
Total	1.0000		0		0	0	0	0		0	0	

	Orig.	Disc.
<NA>	NA	
<NA>	NA	
<NA>	NA	
<NA>	NA	
<NA>	NA	

Total 0

```
# add weights to the dataset

rakedata$weight_2030_baseline <- unlist(outsave[1])
n <- length(rakedata$sector)

# Calculate the sum of original weights
original_weight_sum <- sum(rakedata$weight)

# # Target scaling for original weights
# In a first version, we used the population scaling from UN,
# But to match with the labor market given by the scenario, we take
# the total population from the macro scenario information. Differences are
# small anyway.

# original_weight_scaling_factor <-
#   pop_data$total_population[pop_data$year == 2030] /
#   pop_data$total_population[pop_data$year == 2022]

# For year 2030 (Calculated in Excel, but need a more elegant solution
# from macrodataset)
original_weight_scaling_factor <- 0.992805755

# Scaled original weights
original_weight_sum <- (original_weight_sum
                        * original_weight_scaling_factor)

# Calculate the sum of the new weights
new_weight_sum <- sum(rakedata$weight_2030_baseline)

# Scale the new weights to match the sum of the original weights
scaling_factor <- original_weight_sum / new_weight_sum
rakedata$weight_2030_baseline <- rakedata$weight_2030_baseline * scaling_factor

# Verify the adjustment
head(rakedata[, c("weight", "weight_2030_baseline")])
```

	weight	weight_2030_baseline
1	185.7685	175.1387
2	185.7685	188.3611
3	122.7176	101.5911

4	185.7685	191.9173
5	326.8796	264.6620
6	326.8796	337.6990

```
summary(rakedata$weight_2030_baseline)
```

	Min.	1st Qu.	Median	Mean	3rd Qu.	Max.
	15.87	102.91	142.63	153.57	194.84	520.60

```
summary(rakedata$weight)
```

	Min.	1st Qu.	Median	Mean	3rd Qu.	Max.
	21.48	109.82	156.33	154.68	192.16	326.88

```
hh_size <- rakedata %>%
  select(hhid, hhsize) %>%
  mutate(ones = 1,
         hhsize_old = hhsize) %>%
  group_by(hhid) %>%
  summarise(hhsize = sum(ones, na.rm = TRUE)) %>%
  ungroup()

rakedata <- rakedata %>%
  rename(hhsize_old = hhsize) %>%
  left_join(hh_size, join_by(hhid)) %>%
  relocate(weight, .before = weight_2030_baseline) %>%
  mutate(hh_weight_2030_baseline = weight_2030_baseline / hhsize)

pp_microsim <- tibble(rakedata)
rm(rakedata)
```

We now do the Dry/Hot Scenario. The efficient way of doing this is through a loop or sapply, but as we're strapped for time we will just repeat the code. (Needs rework.)

```
# Since this uses base R, we need to turn the data frame into base R object
rakedata <- as.data.frame(pp_microsim)

anesrakefinder(targets_dry_hot, rakedata, choosemethod = "total")
```

gender_code	cohort_code	lmarket
0.03626510	0.09677000	0.06672418


```

outsave <- anesrake(targets_dry_hot,
  rakedata,
  caseid = rakedata$pid,
  #verbose = FALSE,
  choosemethod = "total",
  #type = "pctlim",
  type = "nolim",
  #cap = 100,
  #pctlim = 0.05,
  nlim = 3,
  iterate = TRUE,
  force1 = TRUE,
  verbose = TRUE,
  weightvec = rakedata$weight)

```

```

[1] "Raking...Iteration 1"
[1] "Current iteration changed total weights by 2350.42100984824"
[1] "Raking...Iteration 2"
[1] "Current iteration changed total weights by 327.800824143871"
[1] "Raking...Iteration 3"
[1] "Current iteration changed total weights by 48.4646674908705"
[1] "Raking...Iteration 4"
[1] "Current iteration changed total weights by 15.0591332668451"
[1] "Raking...Iteration 5"
[1] "Current iteration changed total weights by 4.76527023673584"
[1] "Raking...Iteration 6"
[1] "Current iteration changed total weights by 1.50952971121123"
[1] "Raking...Iteration 7"
[1] "Current iteration changed total weights by 0.477918701816283"
[1] "Raking...Iteration 8"
[1] "Current iteration changed total weights by 0.151329791876323"
[1] "Raking...Iteration 9"
[1] "Current iteration changed total weights by 0.0479208345301924"
[1] "Raking...Iteration 10"
[1] "Current iteration changed total weights by 0.015175102858"
[1] "Raking...Iteration 11"
[1] "Current iteration changed total weights by 0.0048055174821354"
[1] "Raking...Iteration 12"
[1] "Current iteration changed total weights by 0.00152176932434214"
[1] "Raking...Iteration 13"
[1] "Current iteration changed total weights by 0.000481900638637872"
[1] "Raking...Iteration 14"

```

[1] "Current iteration changed total weights by 0.000152604092209838"
[1] "Raking...Iteration 15"
[1] "Current iteration changed total weights by 4.83253346107576e-05"
[1] "Raking...Iteration 16"
[1] "Current iteration changed total weights by 1.53032442354595e-05"
[1] "Raking...Iteration 17"
[1] "Current iteration changed total weights by 4.8460990282051e-06"
[1] "Raking...Iteration 18"
[1] "Current iteration changed total weights by 1.5346211032774e-06"
[1] "Raking...Iteration 19"
[1] "Current iteration changed total weights by 4.85968348479249e-07"
[1] "Raking...Iteration 20"
[1] "Current iteration changed total weights by 1.53894348695061e-07"
[1] "Raking...Iteration 21"
[1] "Current iteration changed total weights by 4.87326087122986e-08"
[1] "Raking...Iteration 22"
[1] "Current iteration changed total weights by 1.54319526879387e-08"
[1] "Raking...Iteration 23"
[1] "Current iteration changed total weights by 4.8878960184906e-09"
[1] "Raking...Iteration 24"
[1] "Current iteration changed total weights by 1.54612000979881e-09"
[1] "Raking...Iteration 25"
[1] "Current iteration changed total weights by 4.91729171270272e-10"
[1] "Raking...Iteration 26"
[1] "Current iteration changed total weights by 1.54891197090556e-10"
[1] "Raking...Iteration 27"
[1] "Current iteration changed total weights by 4.90309043366111e-11"
[1] "Raking...Iteration 28"
[1] "Current iteration changed total weights by 1.57319296478775e-11"
[1] "Raking...Iteration 29"
[1] "Current iteration changed total weights by 5.07691111373276e-12"
[1] "Raking...Iteration 30"
[1] "Current iteration changed total weights by 2.15254203350668e-12"
[1] "Raking...Iteration 31"
[1] "Current iteration changed total weights by 5.62244695245795e-13"
[1] "Raking...Iteration 32"
[1] "Current iteration changed total weights by 0"
[1] "Raking...Iteration 33"
[1] "Current iteration changed total weights by 0"
[1] "Raking converged in 33 iterations"

```
summary(outsave)
```

```
$convergence
```

```
[1] "Complete convergence was achieved after 33 iterations"
```

```
$base.weights
```

```
[1] "Using Base Weights Provided"
```

```
$raking.variables
```

```
[1] "gender_code" "cohort_code" "lmarket"
```

```
$weight.summary
```

	Min.	1st Qu.	Median	Mean	3rd Qu.	Max.
	0.1032	0.6670	0.9308	1.0000	1.2690	3.3817

```
$selection.method
```

```
[1] "variable selection conducted using _nolim_ - discrepancies selected using _total_."
```

```
$general.design.effect
```

```
[1] 1.24362
```

```
$gender_code
```

	Target	Old Weights	N	Old Weights	% Wtd	N	Wtd %	Change in %
<NA>	0.4514133		NA		NA	NA	NA	NA
<NA>	0.5485867		NA		NA	NA	NA	NA
Total	1.0000000		0		0	0	0	0
	Resid. Disc.	Orig. Disc.						
<NA>	NA	NA						
<NA>	NA	NA						
Total	0	0						

```
$cohort_code
```

	Target	Old Weights	N	Old Weights	% Wtd	N	Wtd %	Change in %
<NA>	0.3638899		NA		NA	NA	NA	NA
<NA>	0.1420277		NA		NA	NA	NA	NA
<NA>	0.1630905		NA		NA	NA	NA	NA
<NA>	0.1042513		NA		NA	NA	NA	NA
<NA>	0.2267405		NA		NA	NA	NA	NA
Total	1.0000000		0		0	0	0	0
	Resid. Disc.	Orig. Disc.						
<NA>	NA	NA						
<NA>	NA	NA						

<NA>	NA	NA
<NA>	NA	NA
<NA>	NA	NA
Total	0	0

\$lmarket

	Target	Old Weights	N	Old Weights	% Wtd	N	Wtd	%	Change in %	Resid.	Disc.
<NA>	0.1368		NA		NA	NA	NA		NA	NA	
<NA>	0.0489		NA		NA	NA	NA		NA	NA	
<NA>	0.2593		NA		NA	NA	NA		NA	NA	
<NA>	0.2472		NA		NA	NA	NA		NA	NA	
<NA>	0.3078		NA		NA	NA	NA		NA	NA	
Total	1.0000		0		0	0	0		0	0	

Orig. Disc.

<NA>	NA
<NA>	NA
<NA>	NA
<NA>	NA
<NA>	NA
Total	0

```
# add weights to the dataset

rakedata$weight_2030_dry_hot <- unlist(outsave[1])

# Calculate the sum of original weights
original_weight_sum <- sum(rakedata$weight)

# # Target scaling for original weights
# In a first version, we used the population scaling from UN,
# But to match with the labor market given by the scenario, we take
# the total population from the macro scenario information. Differences are
# small anyway.

# original_weight_scaling_factor <-
#   pop_data$total_population[pop_data$year == 2030] /
#   pop_data$total_population[pop_data$year == 2022]

# For year 2030 (Calculated in Excel, but need a more elegant solution
# from macrodataset)
# It's the same as the baseline
original_weight_scaling_factor <- 0.992805755
```

```
# Scaled original weights
original_weight_sum <- (original_weight_sum
                        * original_weight_scaling_factor)

# Calculate the sum of the new weights
new_weight_sum <- sum(rakedata$weight_2030_dry_hot)

# Scale the new weights to match the sum of the original weights
scaling_factor <- original_weight_sum / new_weight_sum
rakedata$weight_2030_dry_hot <- rakedata$weight_2030_dry_hot * scaling_factor

# Verify the adjustment
head(rakedata[, c("weight", "weight_2030_dry_hot")])
```

	weight	weight_2030_dry_hot
1	185.7685	174.2201
2	185.7685	188.4009
3	122.7176	101.8206
4	185.7685	190.6847
5	326.8796	263.9341
6	326.8796	335.5302

```
summary(rakedata$weight_2030_dry_hot)
```

Min.	1st Qu.	Median	Mean	3rd Qu.	Max.
15.85	102.44	142.95	153.57	194.88	519.34

```
summary(rakedata$weight)
```

Min.	1st Qu.	Median	Mean	3rd Qu.	Max.
21.48	109.82	156.33	154.68	192.16	326.88

```
rakedata <- rakedata %>%
  mutate(hh_weight_2030_dry_hot = weight_2030_dry_hot / hhsize)
```

Weights for the household database

```

# We calculate new weights for households in the hh database
weights_scenarios <- rakedata %>%
  group_by(hhid) %>%
  summarise(
    hh_weight_2030_baseline =
      sum(hh_weight_2030_baseline, na.rm = TRUE),
    hh_weight_2030_dry_hot =
      sum(hh_weight_2030_dry_hot, na.rm = TRUE)
  )

# We return rakedata to data frame pp_microsim and get rid of rakedata
pp_microsim <- tibble(rakedata)
rm(rakedata)

```

0.7.3 Rescaling labor income according to changes to the wage bill

As a last step, we rescale labor income according to changes to the wage bill in the macro scenario.

```

# Wage rescale factor by sector from macro (Agriculture, Manufacturing, Services)
wrf_2030_baseline <- c(1.269821454, 1.284834838, 1.328623737)
wrf_2030_dry_hot   <- c(1.279274540, 1.258485855, 1.302350464)

# We check the wage bill by sector
wages_by_sector <- pp_microsim %>%
  filter(!is.na(sector_w)) %>%
  group_by(sector_w, .drop = TRUE) %>%
  summarise(
    wages_2022 = sum(annual_labor_total * weight, na.rm = TRUE),
    wages_2030_baseline =
      sum(annual_labor_total * weight_2030_baseline, na.rm = TRUE),
    wages2030_dry_hot =
      sum(annual_labor_total * weight_2030_dry_hot, na.rm = TRUE)
  )

# Compare how much it changed with reweighting with how it should have changed
# Derive coefficients (wtc_2030) from that
wages_by_sector <- wages_by_sector %>%
  mutate(
    wages_target_2030_baseline = case_when(

```

```

    sector_w == 1 ~ wages_2022 * wrf_2030_baseline[1],
    sector_w == 2 ~ wages_2022 * wrf_2030_baseline[2],
    sector_w == 3 ~ wages_2022 * wrf_2030_baseline[3],
    .default = NA
  ),
  wages_target2030_dry_hot = case_when(
    sector_w == 1 ~ wages_2022 * wrf_2030_dry_hot[1],
    sector_w == 2 ~ wages_2022 * wrf_2030_dry_hot[2],
    sector_w == 3 ~ wages_2022 * wrf_2030_dry_hot[3],
    .default = NA
  ),
  wtc_2030_baseline = wages_target_2030_baseline / wages_2030_baseline,
  wtc_2030_dry_hot = wages_target2030_dry_hot / wages2030_dry_hot
)

wages_by_sector %>%
  gt()

```

sector_w	wages_2022	wages_2030_baseline	wages2030_dry_hot	wages_target_2030_baseline	wages2030_dry_hot
1	329980600	328684330	335432397	419016446	335432397
2	250074262	259221426	256676453	321304124	256676453
3	1255196730	1303470504	1294801936	1667684171	1294801936

We then add the coefficient to rescale each wage by sector

```

# Assign rescale the annual and monthly wage depending on the sector
# Quick way, but needs to be put in a supply statement or loop
pp_microsim <- pp_microsim %>%
  rename(monthly_labor_income_2022 = monthly_labor_income,
    annual_labor_total_2022 = annual_labor_total) %>%
  mutate(
    monthly_labor_income_2030_baseline = case_when(
      sector_w == 1 ~ monthly_labor_income_2022 * wages_by_sector$wtc_2030_baseline[1],
      sector_w == 2 ~ monthly_labor_income_2022 * wages_by_sector$wtc_2030_baseline[2],
      sector_w == 3 ~ monthly_labor_income_2022 * wages_by_sector$wtc_2030_baseline[3],
      TRUE ~ NA
    ),
    annual_labor_total_2030_baseline = case_when(
      sector_w == 1 ~ annual_labor_total_2022 * wages_by_sector$wtc_2030_baseline[1],
      sector_w == 2 ~ annual_labor_total_2022 * wages_by_sector$wtc_2030_baseline[2],

```

```

    sector_w == 3 ~ annual_labor_total_2022 * wages_by_sector$wtc_2030_baseline[3],
    TRUE ~ NA
  ),
  monthly_labor_income_2030_dry_hot = case_when(
    sector_w == 1 ~ monthly_labor_income_2022 * wages_by_sector$wtc_2030_dry_hot[1],
    sector_w == 2 ~ monthly_labor_income_2022 * wages_by_sector$wtc_2030_dry_hot[2],
    sector_w == 3 ~ monthly_labor_income_2022 * wages_by_sector$wtc_2030_dry_hot[3],
    TRUE ~ NA
  ),
  annual_labor_total_2030_dry_hot = case_when(
    sector_w == 1 ~ annual_labor_total_2022 * wages_by_sector$wtc_2030_dry_hot[1],
    sector_w == 2 ~ annual_labor_total_2022 * wages_by_sector$wtc_2030_dry_hot[2],
    sector_w == 3 ~ annual_labor_total_2022 * wages_by_sector$wtc_2030_dry_hot[3],
    TRUE ~ NA
  )
)

# This takes care of different household members coming from different sectors
hh_li <- pp_microsim %>%
  group_by(hhid) %>%
  summarise(mli_2022 = sum(monthly_labor_income_2022),
            mli_2030_baseline = sum(monthly_labor_income_2030_baseline),
            mli_2030_dry_hot = sum(monthly_labor_income_2030_dry_hot),
            mli_coef_2030_baseline = mli_2030_baseline / mli_2022,
            mli_coef_2030_dry_hot = mli_2030_dry_hot / mli_2022,
            )%>%
  select(hhid, mli_coef_2030_baseline, mli_coef_2030_dry_hot)

ic_microsim <- ic %>%
  left_join(hh_li, join_by(interview__key == hhid)) %>%
  rename(inc2_2022 = inc2,
         inc3_2022 = inc3,
         totalinc_2022 = totalinc) %>%
  mutate(
    mli_coef_2030_baseline =
      if_else(
        is.na(mli_coef_2030_baseline), 1, mli_coef_2030_baseline),
    mli_coef_2030_dry_hot =
      if_else(
        is.na(mli_coef_2030_dry_hot), 1, mli_coef_2030_dry_hot)
  ) %>%
  mutate(

```



```

inc2_2030_baseline = inc2_2022 * mli_coef_2030_baseline,
inc3_2030_baseline = inc3_2022 * mli_coef_2030_baseline,
inc2_2030_dry_hot  = inc2_2022 * mli_coef_2030_dry_hot,
inc3_2030_dry_hot  = inc3_2022 * mli_coef_2030_dry_hot
) %>%
mutate(
  totalinc_2030_baseline =
    totalinc_2022 - coalesce(inc2_2022,0) - coalesce(inc3_2022,0) +
    coalesce(inc2_2030_baseline,0) + coalesce(inc3_2030_baseline,0),
  totalinc_2030_dry_hot =
    totalinc_2022 - coalesce(inc2_2022,0) - coalesce(inc3_2022,0) +
    coalesce(inc2_2030_dry_hot,0) + coalesce(inc3_2030_dry_hot,0)
) %>%
mutate(
  totinc_coef_2030_baseline =
    if_else(
      totalinc_2022 == 0,
      1,
      totalinc_2030_baseline / totalinc_2022),
  totinc_coef_2030_dry_hot =
    if_else(
      totalinc_2022 == 0,
      1,
      totalinc_2030_dry_hot / totalinc_2022)
) %>%
mutate(
  totinc_coef_2030_baseline =
    if_else(
      is.na(totinc_coef_2030_baseline),
      1,
      totinc_coef_2030_baseline),
  totinc_coef_2030_dry_hot =
    if_else(
      is.na(totinc_coef_2030_dry_hot),
      1,
      totinc_coef_2030_dry_hot)
)

ic_coef_scenarios <- ic_microsim %>%
select(
  interview__key,
  totinc_coef_2030_baseline,

```

```
totinc_coef_2030_dry_hot
)
```

We check that our reweighting was successful

```
table <- pp_microsim %>%
  group_by(cohort) %>%
  # group_by(lmarket,sector_w) %>%
  # group_by(gender) %>%
  summarise(total_pp = sum(weight_2030_baseline, na.rm = TRUE)) %>%
  ungroup()

table %>%
  gt() %>%
  fmt_number(columns = total_pp, decimals = 0)
```

cohort	total_pp
P0029	1,031,260
P3039	402,505
P4049	462,197
P5059	295,447
P60up	642,580

```
# write.table(
#   table,
#   "clipboard", sep="\t", row.names=FALSE
# )
```

0.8 Microsimulation

We now implement different shocks according to various scenarios.

0.8.1 Macro scenarios without additional impacts

For the baseline we only adjust labor income according to the reweighting procedure and rescaling of the wage bill.

```

ca_microsim <- ca %>%
  left_join(weights_scenarios, join_by(hhid == hhid)) %>%
  left_join(ic_coef_scenarios, join_by(hhid == interview_key)) %>%
  # We adjust total consumption by the income coefficient
  rename(
    totc_2022 = totc,
    poor_Avpovln2022_2022 = poor_Avpovln2022
  ) %>%
  mutate(
    totc_2030_baseline = totc_2022 * totinc_coef_2030_baseline,
    totc_2030_dry_hot = totc_2022 * totinc_coef_2030_dry_hot
  )

```

And recalculate poverty.

```

ca_microsim <- ca_microsim %>%
  rename(
    aec_r_2022 = aec_r,
    weight_2022 = weight,
    weight_2030_baseline = hh_weight_2030_baseline,
    weight_2030_dry_hot = hh_weight_2030_dry_hot
  ) %>%
  mutate(
    aec_r_2030_baseline =
      totc_2030_baseline / ae_r / PI,
    aec_r_2030_dry_hot =
      totc_2030_dry_hot / ae_r / PI,
  ) %>%
  # Official poverty line
  mutate(
    poor_Avpovln2022_2030_baseline =
      if_else(aec_r_2030_baseline < 52883, 1, 0),
    poor_Avpovln2022_2030_dry_hot =
      if_else(aec_r_2030_dry_hot < 52883, 1, 0)
  )

```

Test

```

test_baseline <- ca_microsim %>%
  rename(
    poor_original = poor_Avpovln2022_2022,

```

```

    poor_2030_baseline = poor_Avpovln2022_2030_baseline,
    poor_2030_dry_hot = poor_Avpovln2022_2030_dry_hot
  ) %>%
group_by(poor_2030_baseline) %>%
summarise(
  no_hh_baseline = round(sum(weight_2030_baseline, na.rm = TRUE)),
  no_pp_baseline = round(sum(weight_2030_baseline * hhsize, na.rm = TRUE)),
  no_hh_dry_hot = round(sum(weight_2030_dry_hot, na.rm = TRUE)),
  no_pp_dry_hot = round(sum(weight_2030_dry_hot * hhsize, na.rm = TRUE))
) %>%
ungroup()

test_baseline %>%
  gt()

```

poor_2030_baseline	no_hh_baseline	no_pp_baseline	no_hh_dry_hot	no_pp_dry_hot
0	644051	2136703	643543	2136057
1	139817	697287	139909	697933

```
##write.table(test_baseline, "clipboard", sep="\t", row.names=FALSE)
```

0.8.2 Climate change

In the climate change scenario, we ask ourselves, what would happen if agriculture revenues from crops and livestock are reduced due to losses in productivity due to heat? For this, we use crops data.

We add a moving window average and max value for our labor productivity data.

```

# First calculate moving window average
heat_l_pdcty <- heat_l_pdcty %>%
  group_by(ADM1_EN,
            clim_scenario) %>%
  arrange(year) %>%
  # Moving window average 5 years before, 5 after
  mutate(
    moving_avg = rollapply(
      pct_change_productivity,
      width = 11,
      FUN = mean,

```

```

    partial = TRUE,
    align = "center",
    fill = NA,
    na.rm = TRUE
  ),
  # Moving window max value 5 years before, 5 after
  # Since it's expressed in negative values (min) is the maximum
  moving_max = rollapply(
    pct_change_productivity,
    width = 11,
    FUN = min,
    partial = TRUE,
    align = "center",
    fill = NA,
    na.rm = TRUE
  )
) %>%
ungroup()

# Clim scenarios to select
cs <- unique(heat_l_pdcty$clim_scenario)

# Moving average for year of interest
lab_loss_avg <- heat_l_pdcty %>%
  filter(clim_scenario == cs[1], year == yearsto[1]) %>%
  select(-pct_change_productivity,
    -ADM1_PCODE,
    -year,
    -clim_scenario,
    -moving_max) %>%
  pivot_wider(names_from = sector, values_from = moving_avg) %>%
  rename(agr_avg = Agriculture,
    man_avg = Manufacturing,
    ser_avg = Services)

# Max value for year of interest
lab_loss_max <- heat_l_pdcty %>%
  filter(clim_scenario == cs[1], year == yearsto[1]) %>%
  select(-pct_change_productivity,
    -ADM1_PCODE,
    -year,
    -clim_scenario,

```

```

      -moving_avg) %>%
pivot_wider(names_from = sector, values_from = moving_max) %>%
rename(agr_max = Agriculture,
       man_max = Manufacturing,
       ser_max = Services)

```

We add a moving window average and max value for our crops and livestock productivity data.

```

# First calculate moving window average
crops_productivity <- crops_productivity %>%
  group_by(NAM_1, climate_scenario) %>%
  arrange(year) %>%
  # Moving window average
  mutate(
    moving_avg = rollapply(
      pct_change_prod,
      width = 11,
      # 5 years before, 5 after + reference year = 11
      FUN = mean,
      partial = TRUE,
      align = "center",
      fill = NA,
      na.rm = TRUE
    ),
    # Moving window max value 5 years before, 5 after
    # Since it's expressed in negative values (min) is the maximum
    moving_max = rollapply(
      pct_change_prod,
      width = 11,
      FUN = min,
      partial = TRUE,
      align = "center",
      fill = NA,
      na.rm = TRUE
    )
  ) %>%
  ungroup()

# Clim scenarios to select
cs <- unique(crops_productivity$climate_scenario)

```

```
# Moving average for year of interest
crops_pdcvty_loss <- crops_productivity %>%
  filter(climate_scenario == cs[1],
         year == yearsto[1]) %>%
  select(-pct_change_prod,
         -GID_1,
         -year,
         -climate_scenario) %>%
  rename(crops_avg_loss = moving_avg,
         crops_max_loss = moving_max)
```

And we do the same for livestock productivity. In this case, there is no disaggregation by Marz.

```
# First calculate moving window average
livestock_productivity <- livestock_productivity %>%
  group_by(NAM_1, climate.scenario) %>%
  arrange(year) %>%
  # Moving window average
  mutate(
    moving_avg = rollapply(
      pct_change_prod,
      width = 11,
      # 5 years before, 5 after + reference year = 11
      FUN = mean,
      partial = TRUE,
      align = "center",
      fill = NA,
      na.rm = TRUE
    ),
    # Moving window max value 5 years before, 5 after
    # Since it's expressed in negative values (min) is the maximum
    moving_max = rollapply(
      pct_change_prod,
      width = 11,
      FUN = min,
      partial = TRUE,
      align = "center",
      fill = NA,
      na.rm = TRUE
    )
  ) %>%
```

```

ungroup()

# Clim scenarios to select
cs <- unique(livestock_productivity$climate.scenario)

# Moving average for year of interest
lvstk_pdcvty_loss <- livestock_productivity %>%
  filter(climate.scenario == cs[1],
         year == yearsto[1]) %>%
  select(-pct_change_prod,
         -year,
         -climate.scenario) %>%
  rename(lvstk_avg_loss = moving_avg,
         lvstk_max_loss = moving_max)

```

And then we introduce these values in our ag income and labor income data. First, we attach the percentage losses to the appropriate data set.

```

# Persons processed dataset
pp_microsim_cc <- pp_microsim %>%
  left_join(lab_loss_avg,
            join_by(NAM_1 == ADM1_EN)) %>%
  left_join(lab_loss_max,
            join_by(NAM_1 == ADM1_EN))

# Household income processed dataset
ic_microsim_cc <- ic_microsim %>%
  left_join(crops_pdcvty_loss,
            join_by(NAM_1 == NAM_1)) %>%
  left_join(lvstk_pdcvty_loss,
            join_by(NAM_1))

```

And we first shock labor income.

```

# Labor income according to sector
pp_microsim_cc <- pp_microsim_cc %>%
  mutate(sector = as.numeric(sector)) %>%
  mutate(
    mli_2030_baseline_lab_avg =
      case_when(
        sector == 1 ~

```



```

    monthly_labor_income_2030_baseline *
    (1 + agr_avg),
  sector == 2 ~
    monthly_labor_income_2030_baseline *
    (1 + man_avg),
  sector == 3 ~
    monthly_labor_income_2030_baseline *
    (1 + ser_avg),
  TRUE ~ NA
)
) %>%
mutate(
  mli_2030_baseline_lab_max =
    case_when(
      # * 1000 because its thousands of Dram
      sector == 1 ~
        monthly_labor_income_2030_baseline *
        (1 + agr_max),
      sector == 2 ~
        monthly_labor_income_2030_baseline *
        (1 + man_max),
      sector == 3 ~
        monthly_labor_income_2030_baseline *
        (1 + ser_max),
      TRUE ~ NA
    )
)

```

We aggregate at household level and take note of the percent difference between the two labor incomes, so that we can impact labor income by that amount. We don't do it with absolute numbers because we don't know the assumptions made by the poverty team to construct the income variable.

```

ic_new_incomes <- pp_microsim_cc %>%
  group_by(hhid) %>%
  summarise(
    mli_2030_baseline_lab_avg =
      sum(mli_2030_baseline_lab_avg, na.rm = TRUE),
    mli_2030_baseline_lab_max =
      sum(mli_2030_baseline_lab_max, na.rm = TRUE),
    mli_original =
      sum(monthly_labor_income_2030_baseline, na.rm = TRUE)
  )

```

```

) %>%
mutate(
  mli_2030_baseline_lab_avg_coef =
    if_else(
      mli_original == 0 | is.na(mli_original),
      1,
      mli_2030_baseline_lab_avg / mli_original
    ),
  mli_2030_baseline_lab_max_coef =
    if_else(
      mli_original == 0 | is.na(mli_original),
      1,
      mli_2030_baseline_lab_max / mli_original
    )
) %>%
ungroup()

ic_microsim_cc <- ic_microsim_cc %>%
  left_join(ic_new_incomes,
            join_by(interview__key == hhid)) %>%
  mutate(
    inc2_2030_baseline_lab_avg =
      inc2_2030_baseline * mli_2030_baseline_lab_avg_coef,
    inc2_2030_baseline_lab_max =
      inc2_2030_baseline * mli_2030_baseline_lab_max_coef,
    inc3_2030_baseline_lab_avg =
      inc3_2030_baseline * mli_2030_baseline_lab_avg_coef,
    inc3_2030_baseline_lab_max =
      inc3_2030_baseline * mli_2030_baseline_lab_max_coef
  )

```

And now we impact agricultural income `cropinc` and livestock income `lvstk`.

```

ic_microsim_cc <- ic_microsim_cc %>%
  mutate(
    cropinc_2030_baseline_cc_avg =
      cropinc * (1 + crops_avg_loss),
    cropinc_2030_baseline_cc_max =
      cropinc * (1 + crops_max_loss),
    lvstk_2030_baseline_cc_avg =
      lvstk * (1 + lvstk_avg_loss),
    lvstk_2030_baseline_cc_max =

```

```
lvstk * (1 + lvstk_max_loss)
)
```

And recalculate total income.

```
ic_microsim_cc <- ic_microsim_cc %>%
  mutate(
    totalinc_2030_baseline_lab_avg =
      totalinc_2030_baseline -
      rowSums(select(., c(inc2_2030_baseline,
                          inc3_2030_baseline)), na.rm = TRUE) +
      rowSums(select(
        ., c(inc2_2030_baseline_lab_avg,
              inc3_2030_baseline_lab_avg)), na.rm = TRUE),
    totalinc_2030_baseline_lab_max =
      totalinc_2030_baseline -
      rowSums(select(., c(inc2_2030_baseline,
                          inc3_2030_baseline)), na.rm = TRUE) +
      rowSums(select(
        ., c(inc2_2030_baseline_lab_max,
              inc3_2030_baseline_lab_max)), na.rm = TRUE)
  ) %>%
  mutate(
    totalinc_2030_baseline_lab_avg_coef =
      if_else(totalinc_2030_baseline == 0,
              1, totalinc_2030_baseline_lab_avg /
                totalinc_2030_baseline),
    totalinc_2030_baseline_lab_max_coef =
      if_else(totalinc_2030_baseline == 0,
              1, totalinc_2030_baseline_lab_max /
                totalinc_2030_baseline)
  ) %>%
  mutate(
    totalinc_2030_baseline_lab_avg_coef =
      if_else(is.na(totalinc_2030_baseline_lab_avg_coef),
              1, totalinc_2030_baseline_lab_avg_coef),
    totalinc_2030_baseline_lab_max_coef =
      if_else(is.na(totalinc_2030_baseline_lab_max_coef),
              1, totalinc_2030_baseline_lab_max_coef)
  )
```

We do the same for agriculture and livestock income alone

```

ic_microsim_cc <- ic_microsim_cc %>%
  mutate(
    totalinc_2030_baseline_cc_avg =
      totalinc_2030_baseline -
      rowSums(select(., c(cropinc,
                          lvstk)), na.rm = TRUE) +
      rowSums(select(
        ., c(cropinc_2030_baseline_cc_avg,
              lvstk_2030_baseline_cc_avg)), na.rm = TRUE),
    totalinc_2030_baseline_cc_max =
      totalinc_2030_baseline -
      rowSums(select(., c(cropinc,
                          lvstk)), na.rm = TRUE) +
      rowSums(select(
        ., c(cropinc_2030_baseline_cc_max,
              lvstk_2030_baseline_cc_max)), na.rm = TRUE)
  ) %>%
  mutate(
    totalinc_2030_baseline_cc_avg_coef =
      if_else(totalinc_2030_baseline == 0,
              1, totalinc_2030_baseline_cc_avg
                / totalinc_2030_baseline),
    totalinc_2030_baseline_cc_max_coef =
      if_else(totalinc_2030_baseline == 0,
              1, totalinc_2030_baseline_cc_max
                / totalinc_2030_baseline)
  ) %>%
  mutate(
    totalinc_2030_baseline_cc_avg_coef =
      if_else(is.na(totalinc_2030_baseline_cc_avg_coef),
              1, totalinc_2030_baseline_cc_avg_coef),
    totalinc_2030_baseline_cc_max_coef =
      if_else(is.na(totalinc_2030_baseline_cc_max_coef),
              1, totalinc_2030_baseline_cc_max_coef)
  )

```

And yet again for the combined impacts

```

ic_microsim_cc <- ic_microsim_cc %>%
  mutate(
    totalinc_2030_baseline_lab_cc_avg =
      totalinc_2030_baseline -

```

```

    rowSums(select(., c(inc2_2030_baseline,
                        inc3_2030_baseline,
                        cropinc,
                        lvstk))), na.rm = TRUE) +
    rowSums(select(
      ., c(inc2_2030_baseline_lab_avg,
            inc3_2030_baseline_lab_avg,
            cropinc_2030_baseline_cc_avg,
            lvstk_2030_baseline_cc_avg)), na.rm = TRUE),
    totalinc_2030_baseline_lab_cc_max =
      totalinc_2030_baseline -
      rowSums(select(., c(inc2_2030_baseline,
                          inc3_2030_baseline,
                          cropinc,
                          lvstk))), na.rm = TRUE) +
      rowSums(select(
        ., c(inc2_2030_baseline_lab_max,
              inc3_2030_baseline_lab_max,
              cropinc_2030_baseline_cc_max,
              lvstk_2030_baseline_cc_max)), na.rm = TRUE)
  ) %>%
  mutate(
    totalinc_2030_baseline_lab_cc_avg_coef =
      if_else(totalinc_2030_baseline == 0,
              1, totalinc_2030_baseline_lab_cc_avg /
                totalinc_2030_baseline),
    totalinc_2030_baseline_lab_cc_max_coef =
      if_else(totalinc_2030_baseline == 0,
              1, totalinc_2030_baseline_lab_cc_max /
                totalinc_2030_baseline)
  ) %>%
  mutate(
    totalinc_2030_baseline_lab_cc_avg_coef =
      if_else(is.na(totalinc_2030_baseline_lab_cc_avg_coef),
              1, totalinc_2030_baseline_lab_cc_avg_coef),
    totalinc_2030_baseline_lab_cc_max_coef =
      if_else(is.na(totalinc_2030_baseline_lab_cc_max_coef),
              1, totalinc_2030_baseline_lab_cc_max_coef)
  )

```

We assume that the loss in income translates into a loss of expenditure.

```

income_losses <- ic_microsim_cc %>%
  select(interview__key,
         totalinc_2030_baseline_lab_avg_coef,
         totalinc_2030_baseline_lab_max_coef,
         totalinc_2030_baseline_cc_avg_coef,
         totalinc_2030_baseline_cc_max_coef,
         totalinc_2030_baseline_lab_cc_avg_coef,
         totalinc_2030_baseline_lab_cc_max_coef)

ca_microsim_cc <- ca_microsim %>%
  left_join(income_losses, join_by(hhid == interview__key))

# And now reduce total consumption

ca_microsim_cc <- ca_microsim_cc %>%
  mutate(totc_2030_baseline_lab_avg = totc_2030_baseline *
         totalinc_2030_baseline_lab_avg_coef,
         totc_2030_baseline_lab_max = totc_2030_baseline *
         totalinc_2030_baseline_lab_max_coef,
         totc_2030_baseline_cc_avg = totc_2030_baseline *
         totalinc_2030_baseline_cc_avg_coef,
         totc_2030_baseline_cc_max = totc_2030_baseline *
         totalinc_2030_baseline_cc_max_coef,
         totc_2030_baseline_lab_cc_avg = totc_2030_baseline *
         totalinc_2030_baseline_lab_cc_avg_coef,
         totc_2030_baseline_lab_cc_max = totc_2030_baseline *
         totalinc_2030_baseline_lab_cc_max_coef
         ) %>%
  mutate(aec_r_2030_baseline_lab_avg =
         totc_2030_baseline_lab_avg / ae_r / PI,
         aec_r_2030_baseline_lab_max =
         totc_2030_baseline_lab_max / ae_r / PI,
         aec_r_2030_baseline_cc_avg =
         totc_2030_baseline_cc_avg / ae_r / PI,
         aec_r_2030_baseline_cc_max =
         totc_2030_baseline_cc_max / ae_r / PI,
         aec_r_2030_baseline_lab_cc_avg =
         totc_2030_baseline_lab_cc_avg / ae_r / PI,
         aec_r_2030_baseline_lab_cc_max =
         totc_2030_baseline_lab_cc_max / ae_r / PI) %>%
  mutate(poor_2030_baseline_lab_avg =

```

```

    if_else(aec_r_2030_baseline_lab_avg < 52883, 1, 0),
  poor_2030_baseline_lab_max =
    if_else(aec_r_2030_baseline_lab_max < 52883, 1, 0),
  poor_2030_baseline_cc_avg =
    if_else(aec_r_2030_baseline_cc_avg < 52883, 1, 0),
  poor_2030_baseline_cc_max =
    if_else(aec_r_2030_baseline_cc_max < 52883, 1, 0),
  poor_2030_baseline_lab_cc_avg =
    if_else(aec_r_2030_baseline_lab_cc_avg < 52883, 1, 0),
  poor_2030_baseline_lab_cc_max =
    if_else(aec_r_2030_baseline_lab_cc_max < 52883, 1, 0)
)

# We make a table to see who became poor.

test <- ca_microsim_cc %>%
  rename(poor_original = poor_Avpovln2022_2030_baseline,
         poor_cc = poor_2030_baseline_lab_avg) %>%
  group_by(poor_Avpovln2022_2030_dry_hot) %>%
  summarise(no_hh = round(sum(weight_2030_dry_hot, na.rm = TRUE)),
           no_pp = round(sum(weight_2030_dry_hot * hhsize, na.rm = TRUE))) %>%
  ungroup()

test %>%
  gt()

```

poor_Avpovln2022_2030_dry_hot	no_hh	no_pp
0	643268	2135222
1	140184	698768

```
##write.table(test, "clipboard", sep="\t", row.names=FALSE)
```

0.8.3 Food prices

We start by looking at the differences of food prices between scenarios.

```

# We extract and reformat the price data
price_data <- macro_data %>%
  select(year, scenario_id, starts_with( c("fpi" , "epi") )) %>%

```

```

rename(scenario = scenario_id) %>%
pivot_longer(starts_with( c("fpi" , "epi") ),
              names_to = "type_decile",
              values_to = "index") %>%
mutate(decile = parse_number(type_decile)) %>%
mutate(commodity_group =
       case_when(
         str_starts(type_decile, "fpi") ~ "food",
         str_starts(type_decile, "epi") ~ "energy",
         TRUE ~ NA_character_
       )) %>%
select(-type_decile) %>%
relocate(index, .after = commodity_group)

# We take a look at price information in 2030
price_data %>%
  filter(year == 2030) %>%
  group_by(commodity_group, scenario) %>%
  summarise(index = mean(index, na.rm = TRUE)) %>%
  gt()

```

`summarise()` has grouped output by 'commodity_group'. You can override using the `.groups` argument.

scenario	index
energy	
baseline	1.129182
dry_hot	1.124883
food	
baseline	1.009986
dry_hot	1.075696

So, we will assign a price index depending on which decile the household belonged to in the base year 2022. We will have a column for each scenario. So we manipulate our price data according to our years of interest (in this case, only 2030).

```

# Filter `price_data` for the years of interest
price_data_yearsto <- price_data %>%
  filter(year %in% yearsto)

```



```

# Create a named vector for scenario indices
scenario_indices <- setNames(seq_along(scenarios), scenarios)

# Create the composite string column
price_data_yearsto <- price_data_yearsto %>%
  mutate(
    scenario_index = scenario_indices[scenario],
    composite_column = paste( scenario,year,commodity_group, sep = "_")
  ) %>%
  select(decile,index,composite_column)

composite_column_names <- unique(price_data_yearsto$composite_column)

price_data_yearsto <- price_data_yearsto %>%
  pivot_wider(names_from="composite_column", values_from = index)

```

So in this particular case, we don't want to use the price index from the `dry_hot` scenario, but we want to use the difference between the baseline and that scenario, so we are going to do those columns by hand, but we actually have to find a way to do it programmatically against the baseline.

```

price_data_yearsto <- price_data_yearsto %>%
  mutate(food_PI = dry_hot_2030_food - baseline_2030_food +1)

```

And we join with our household's dataset.

```

# PP microsim already has decile information from previous join
ca_microsim_cc <- ca_microsim_cc %>%
  left_join(price_data_yearsto, join_by(decile==decile))

```

Since we don't have quantities for the aggregate food expenditure category or for the aggregate energy bundle, we assume a price of 1 in the survey year.

We will estimate price elasticities for a single "food" commodity from the consumption aggregate `FOOD_with_prices` dataset. We add decile data to the original.

```

food_summary <- food_with_prices %>%
  left_join(deciles, join_by(hhid))

# Step 1: Summarize the data at the household level
food_summary <- food_summary %>%

```

```

group_by(hhid, decile) %>%
  summarise(
    total_quantity = sum(q, na.rm = TRUE),
    weighted_price = sum(avrpr_mean * q, na.rm = TRUE) / sum(q, na.rm = TRUE),
    .groups = 'drop'
  )

# Define a function to fit the model and extract the elasticity
fit_model <- function(data) {
  model <- lm(log(total_quantity) ~ log(weighted_price), data = data)
  coef(model)["log(weighted_price)"]
}

# Apply the model fitting function by decile
decile_models <- food_summary %>%
  group_by(decile) %>%
  nest() %>%
  mutate(price_elasticity = map_dbl(data, fit_model)) %>%
  select(decile, price_elasticity) %>%
  mutate(price_elasticity = if_else(price_elasticity > 0,
    price_elasticity * (-1),
    price_elasticity))

decile_models

```

```

# A tibble: 10 x 2
# Groups:   decile [10]
  decile price_elasticity
  <dbl>         <dbl>
1     10         -0.206
2      8         -0.00939
3      2         -0.360
4      3         -0.428
5      1         -0.483
6      9         -0.118
7      6         -0.116
8      4         -0.299
9      5         -0.253
10     7         -0.0598

```

Let's add back the elasticity data to the analysis dataset.

```
ca_microsim_cc <- ca_microsim_cc %>%
  left_join(decile_models, by = "decile")
```

Let's apply the elasticities to the new data.

```
# Calculate the implicit price
# Assuming implicit_price can be calculated from the expenditure (food1)
# If we assume baseline quantity consumed is proportional to expenditure/price
ca_microsim_cc <- ca_microsim_cc %>%
  mutate(implicit_price = food1 / food1, # This is 1 as we don't have baseline price
         food_quantity = food1 / implicit_price)

# Calculate the percentage change in prices for each decile
ca_microsim_cc <- ca_microsim_cc %>%
  mutate(food_1_dprice = (baseline_2030_food - 1),
         food_2_dprice = (dry_hot_2030_food - 1),
         food_PI_dprice = (food_PI - 1))

# Estimate the new food consumption levels
ca_microsim_cc <- ca_microsim_cc %>%
  mutate(
    food_q1_sim = food_quantity *
      (1 + food_1_dprice * price_elasticity),
    food_q2_sim = food_quantity *
      (1 + food_2_dprice * price_elasticity),
    food_qPI_sim = food_quantity *
      (1 + food_PI_dprice * price_elasticity))

# Calculate the new expenditure levels
ca_microsim_cc <- ca_microsim_cc %>%
  mutate(food_exp1_sim = food_q1_sim * baseline_2030_food,
         food_exp2_sim = food_q2_sim * dry_hot_2030_food,
         food_exp3_sim = food_qPI_sim * food_PI)

# View the results
print(ca_microsim_cc %>% select(decile, food1, baseline_2030_food, food_1_dprice, food_q1_sim, food_exp1_sim))
```

A tibble: 5,184 x 10


	decile	food1	baseline_2030_food	food_1_dprice	food_q1_sim	food_exp1_sim
	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
1	9	92178.	1.01	0.00973	92073.	92969.

2	7	105290.	1.01	0.00963	105229.	106243.
3	2	22733.	1.01	0.0102	22650.	22881.
4	2	163379.	1.01	0.0102	162778.	164442.
5	4	102718.	1.01	0.0104	102400.	103461.
6	10	208995.	1.01	0.0104	208548.	210712.
7	8	116151.	1.01	0.00995	116140.	117296.
8	5	67911.	1.01	0.00965	67745.	68398.
9	6	152144.	1.01	0.00978	151971.	153457.
10	8	80033.	1.01	0.00995	80025.	80822.

```
# i 5,174 more rows
# i 4 more variables: food_2_dprice <dbl>, food_q2_sim <dbl>,
#   food_exp2_sim <dbl>, food_PI_dprice <dbl>
```

Let's plot the distributions to see changes:

```
# Basic density plot comparing food1 and food_exp_sim
ggplot(ca_microsim_cc, aes(x = food1, fill = 'Initial Food Expenditure')) +
  geom_density(alpha = 0.3) +
  geom_density(
    data = ca_microsim_cc,
    aes(x = food_exp3_sim, fill = 'Baseline + Dry-Hot prices'),
    alpha = 0.3) +
  labs(
    fill = "Consumption Type",
    title = "Comparison of Food Expenditure Distributions",
    x = "Food Expenditure",
    y = "Density") +
  theme_minimal() +
  coord_cartesian(xlim = c(0, 300000)) + # Adjust the xlim for zoom
  scale_x_continuous(labels = scales::comma) +
  scale_y_continuous(labels = scales::comma)
```



Calculate losses in consumer surplus and purchasing power loss.

```
# Calculate Consumer Surplus loss for food1 and food2 scenarios
ca_microsim_cc <- ca_microsim_cc %>%
  mutate(food1_CSloss = ((food_quantity * implicit_price) /
    totc_2030_baseline) * food_1_dprice * (
    1 + (price_elasticity / 2) * food_1_dprice),
    food2_CSloss = ((food_quantity * implicit_price) /
    totc_2030_dry_hot) * food_2_dprice * (
    1 + (price_elasticity / 2) * food_2_dprice),
    foodPI_CSloss = ((food_quantity * implicit_price) /
    totc_2030_baseline_lab_cc_avg) * food_PI_dprice * (
    1 + (price_elasticity / 2) * food_PI_dprice),
    ttl_CSloss_1 = food1_CSloss,
    ttl_CSloss_2 = food2_CSloss,
    ttl_CSloss_PI = foodPI_CSloss)

# Calculate Purchasing Power loss for food1 and food2 and PI scenarios
ca_microsim_cc <- ca_microsim_cc %>%
  mutate(food1_PPloss = (food1 /
    totc_2030_baseline) * food_1_dprice,
    food2_PPloss = (food1 /
    totc_2030_dry_hot) * food_2_dprice,
```

```

    foodPI_PPloss = (food1 /
                      totc_2030_baseline_lab_cc_avg) * food_PI_dprice,
    ttl_PPloss_1 = food1_PPloss,
    ttl_PPloss_2 = food2_PPloss,
    ttl_PPloss_PI = foodPI_PPloss
  )

# Adjust total expenditure (totc) based on the purchasing power loss
ca_microsim_cc <- ca_microsim_cc %>%
  mutate(totc_2030_baseline_food1 = totc_2030_baseline * (1 - ttl_PPloss_1),
         totc_2030_dry_hot_food2 = totc_2030_dry_hot * (1 - ttl_PPloss_2),
         totc_2030_baseline_lab_cc_foodPI = totc_2030_baseline_lab_cc_avg * (1 - ttl_PPloss_PI))

# View the results
print(ca_microsim_cc %>% select(decile, totc_2030_baseline, totc_2030_baseline_food1, totc_2030_dry_hot_food2, totc_2030_baseline_lab_cc_foodPI))

```

```

# A tibble: 5,184 x 5
  decile totc_2030_baseline totc_2030_baseline_food1 totc_2030_dry_hot_food2
  <dbl>         <dbl>         <dbl>         <dbl>
1     9      298269.      297372.      291365.
2     7      268114.      267100.      260288.
3     2       98284.       98051.       96553.
4     2      302036.      300366.      289603.
5     4      215294.      214230.      207347.
6    10      404041.      401871.      387804.
7     8      232452.      231296.      223637.
8     5      247204.      246549.      242165.
9     6      363337.      361849.      351936.
10    8      149196.      148400.      143123.
# i 5,174 more rows
# i 1 more variable: totc_2030_baseline_lab_cc_foodPI <dbl>

```

Okay so now we estimate new welfare and poverty.

```

ca_microsim_cc <- ca_microsim_cc %>%
  mutate(aec_r_2030_baseline_food1 = totc_2030_baseline_food1 / ae_r / PI,
         aec_r_2030_dry_hot_food2 = totc_2030_dry_hot_food2 / ae_r / PI,
         aec_r_2030_baseline_foodPI = totc_2030_baseline_lab_cc_foodPI / ae_r / PI) %>%
  mutate(poor_2030_baseline_food1 =
    if_else(aec_r_2030_baseline_food1 < 52883, 1, 0),
         poor_2030_dry_hot_food2 =

```

```

    if_else(aec_r_2030_dry_hot_food2 < 52883, 1, 0),
    poor_2030_baseline_lab_cc_foodPI =
    if_else(aec_r_2030_baseline_foodPI < 52883, 1, 0))

```

And now we see who became poor

```

# We make a table to see who became poor.
test <- ca_microsim_cc

test <- test%>%
  rename(poor_original = poor_Avpovln2022_2030_baseline,
         poor_cc = poor_2030_baseline_lab_cc_avg,
         poor_food1 = poor_2030_baseline_food1,
         poor_food2 = poor_2030_dry_hot_food2,
         poor_foodPI = poor_2030_baseline_lab_cc_foodPI) %>%
  group_by(poor_original) %>%
  summarise(no_hh = round(sum(weight_2030_baseline, na.rm = TRUE)),
            no_pp = round(sum(weight_2030_baseline*hhsize, na.rm = TRUE)))

test %>%
  gt()

```

poor_original	no_hh	no_pp
0	644051	2136703
1	139817	697287

```
##write.table(test, "clipboard", sep="\t", row.names=FALSE)
```

And we map these results.

```

# foodpoor <- ca_microsim_cc %>%
#   mutate(new_poor_food_base = if_else(
#     poor_cc_avg_food2 == 1 & poor_cc_avg == 0, 1, 0),
#     new_poor_food_dryhot = if_else(
#       poor_cc_avg_food1 == 1 & poor_cc_avg == 0, 1, 0),
#     NAM_1 = as_factor(marz)) %>%
#   mutate(NAM_1 = if_else(NAM_1 == "VayotsDzor", "Vayots Dzor", NAM_1)) %>%
#   mutate(NAM_1 = if_else(NAM_1 == "Sjunik", "Syunik", NAM_1)) %>%
#   select(NAM_1, poor_Avpovln2022, poor_cc_avg, poor_cc_max,

```

```

#       poor_cc_avg_food1, poor_cc_avg_food2, new_poor_food_base,
#       new_poor_food_dryhot, weight, hhsize)
#
# fp <-foodpoor %>%
#   group_by(NAM_1) %>%
#   summarise(new_poor = round(sum(new_poor_food_dryhot * weight*hhsize, na.rm = TRUE))) %>%
#   mutate(label = paste0(NAM_1," (", new_poor, ")"))
#
#
# ##write.table(fp, "clipboard", sep="\t", row.names=FALSE)
# fp_map <- adm1 |>
#   left_join(fp, join_by(NAM_1 == NAM_1))
#
# fp_map <-tm_shape(fp_map)+
#   tm_polygons("new_poor", legend.show = FALSE) +
#   tm_text("label", size = .7, col = "black")+
#   tm_layout(legend.position = c("right", "top"),
#             title= "Additional Poor Dry-Hot Scenario",
#             title.position = c('left', 'bottom'),
#             title.size = 0.9)
#
# fp_map

```

Let's plot how the distribution moves with all these measures.

```

# Basic density plot comparing equivalized consumption per capita
ggplot(ca_microsim_cc,
       aes(x = aec_r_2030_baseline_foodPI, fill = 'Baseline + LP/CC + Food Prices (D/H)')) +
  geom_density(alpha = 0.5) +
  # geom_density(
  #   data = ca_microsim_cc,
  #   aes(x = aec_r_2030_dry_hot, fill = 'Dry/Hot'),
  #   alpha = 0.5) +
  # geom_density(
  #   data = ca_microsim_cc,
  #   aes(x = aec_r_2030_dry_hot_food2, fill = 'Dry/Hot + Food Price'),
  #   alpha = 0.5) +
  geom_density(
    data = ca_microsim_cc,
    aes(x = aec_r_2030_baseline_lab_cc_avg, fill = 'Baseline + LP/CC'),
    alpha = 0.5) +
  geom_density(


```



```

data = ca_microsim_cc,
aes(x = aec_r_2030_baseline, fill = 'Baseline'),
alpha = 0.5) +
labs(
  fill = "Consumption Distribution\nby Scenario Variant",
  # title = "Comparison of Consumption Distributions",
  x = "Equivalized consumption (Dram)",
  y = "Probability") +
theme_minimal()+
coord_cartesian(xlim = c(40000, 110000),
                ylim = c(0.000010,0.0000140)) + # Zoom in without removing data
scale_x_continuous(labels = scales::comma) +
scale_y_continuous(labels = scales::comma)+
geom_vline(xintercept = 55883,
           color = "red",
           linetype = "dotted",
           linewidth =0.8) +
annotate("text",
        x = 55883,
        y = 0.0000110,
        #label = "Poverty line\nAMD 55,883",
        label = "Poverty line",
        color = "black",
        hjust = -0.1,
        # vjust = -3.5,
        #angle = 90,
        size = 3)


```



And we also plot the cumulative distributions.

```
# Plot the cumulative distribution with left-facing arrows
ggplot(ca_microsim_cc,
       aes(x = aec_r_2030_baseline_foodPI, color = 'Baseline + LP/CC + Food Prices (D/H)')) +
  stat_ecdf(geom = "step") +
  # stat_ecdf(data = ca_microsim_cc,
  #          aes(x = aec_r_2030_baseline_lab_avg, color = 'Baseline + Labor Productivity')) +
  stat_ecdf(data = ca_microsim_cc,
            aes(x = aec_r_2030_baseline_lab_cc_avg, color = 'Baseline + LP/CC')) +
  stat_ecdf(data = ca_microsim_cc,
            aes(x = aec_r_2030_baseline, color = 'Baseline')) +
  labs(
    color = "Cumulative Consumption\nby Scenario Variant",
    # title = "Comparison of Cumulative Consumption Distributions",
    x = "Equivalentized consumption (Dram)",
    y = "Cumulative Probability") +
  theme_minimal() +
  coord_cartesian(xlim = c(40000, 110000)) +
  scale_x_continuous(labels = scales::comma) +
  # geom_vline(xintercept = 55883,
  #            color = "red",
  #            linetype = "dotted",
```

```
#           linewidth = 0.8) +
# annotate("text",
#         x = 55883,
#         y = 0.5,
#         label = "Poverty line",
#         color = "black",
#         hjust = -0.1,
#         size = 3) +
annotate("segment", x = 70000, xend = 65000, y = 0.2, yend = 0.2,
        arrow = arrow(length = unit(0.3, "cm")), color = "black") +
annotate("text", x = 72500, y = 0.2, label = "Shift due to shocks", hjust = 0)
```



```
# annotate("segment", x = 80000, xend = 75000, y = 0.4, yend = 0.4,
#         arrow = arrow(length = unit(0.3, "cm")), color = "black") +
# annotate("text", x = 82500, y = 0.4, label = "Shift due to shocks", hjust = 0)
```

We bring back poverty to the people's dataset.

```
# We extract household poverty designations from the data
new_poor <- ca_microsim_cc %>%
  select(hhid,
         weight_2030_baseline,
```

```

weight_2030_dry_hot,
poor_Avpovln2022_2022,
poor_Avpovln2022_2030_baseline,
poor_Avpovln2022_2030_dry_hot,
poor_2030_baseline_lab_avg,
poor_2030_baseline_lab_max,
poor_2030_baseline_cc_avg,
poor_2030_baseline_cc_max,
poor_2030_baseline_lab_cc_avg,
poor_2030_baseline_lab_cc_max,
poor_2030_baseline_food1,
poor_2030_dry_hot_food2,
poor_2030_baseline_lab_cc_foodPI
)

# And merge them back into the people dataset
pp_microsim_cc <- pp_microsim_cc %>%
  select(-c(poor_Avpovln2022,
            weight_2030_baseline,
            weight_2030_dry_hot)) %>%
  left_join(new_poor, join_by(hhid)) %>%
  mutate(female = if_else(gender == 2, 1, 0),
         youth = if_else(age < 15, 1, 0))

```

0.8.4 Disaggregation of poverty measures

We make a table to see who became poor.

```

test <- pp_microsim_cc

test <- test%>%
  rename(poor_original = poor_Avpovln2022_2030_baseline,
         poor_lab = poor_2030_baseline_lab_avg,
         poor_cc = poor_2030_baseline_cc_avg,
         poor_lab_cc = poor_2030_baseline_lab_cc_avg,
         poor_foodPI = poor_2030_baseline_lab_cc_foodPI
         ) %>%
  group_by(poor_original) %>%
  summarise(no_pp = round(sum(weight_2030_baseline, na.rm = TRUE)),
            female = round(sum(female*weight_2030_baseline, na.rm = TRUE)),
            male = no_pp - female,

```

```

    youth = round(sum(youth*weight_2030_baseline, na.rm = TRUE)),
    non_youth = no_pp - youth,
    rural = round(sum(rural *weight_2030_baseline, na.rm = TRUE)),
    urban = no_pp - rural
  )

test %>%
  gt()

```

poor_original	no_pp	female	male	youth	non_youth	rural	urban
0	2136703	1145528	991175	375694	1761009	818438	1318265
1	697287	374064	323223	174675	522612	321846	375441

```
##write.table(test, "clipboard", sep="\t", row.names=FALSE)
```

```

# foodpoor <- ca_microsim_cc %>%
#   mutate(new_poor_food_base = if_else(
#     poor_2030_baseline_lab_cc_foodPI == 1 &
#     poor_2030_baseline_lab_cc_avg == 0, 1, 0),
#     new_poor_food_dryhot = if_else(
#       poor_cc_avg_food1 == 1 & poor_cc_avg == 0, 1, 0),
#     NAM_1 = as_factor(marz)) %>%
#   mutate(NAM_1 = if_else(NAM_1 == "VayotsDzor", "Vayots Dzor", NAM_1)) %>%
#   mutate(NAM_1 = if_else(NAM_1 == "Sjunik", "Syunik", NAM_1)) %>%
#   select(NAM_1, poor_Avpovln2022_2022,
#     poor_Avpovln2022_2030_baseline,
#     poor_Avpovln2022_2030_dry_hot,
#     poor_2030_baseline_lab_avg,
#     poor_2030_baseline_lab_max,
#     poor_2030_baseline_cc_avg,
#     poor_2030_baseline_cc_max,
#     poor_2030_baseline_lab_cc_avg,
#     poor_2030_baseline_lab_cc_max,
#     poor_2030_baseline_food1,
#     poor_2030_dry_hot_food2,
#     poor_2030_baseline_lab_cc_foodPI,
#     weight_2030_baseline,
#     weight_2030_dry_hot,
#     hhsize)
#

```

```

# fp <-foodpoor %>%
#   group_by(NAM_1) %>%
#   summarise(new_poor = round(sum(new_poor_food_dryhot * weight*hhsize, na.rm = TRUE))) %>%
#   mutate(label = paste0(NAM_1," (", new_poor, ")"))
#
#
# ##write.table(fp, "clipboard", sep="\t", row.names=FALSE)
# fp_map <- adm1 |>
#   left_join(fp, join_by(NAM_1 == NAM_1))
#
# fp_map <-tm_shape(fp_map)+
#   tm_polygons("new_poor", legend.show = FALSE) +
#   tm_text("label", size = .7, col = "black")+
#   tm_layout(legend.position = c("right", "top"),
#             title= "Additional Poor Dry-Hot Scenario",
#             title.position = c('left', 'bottom'),
#             title.size = 0.9)
#
# fp_map

```

```

new_poor_scenarios <- pp_microsim_cc %>%
  mutate(
    poor_baseline = poor_Avpovln2022_2030_baseline,
    new_poor_lab_cc = if_else(
      poor_Avpovln2022_2030_baseline == 0 &
      poor_2030_baseline_lab_cc_avg == 1,
      1,
      0
    ),
    new_poor_lab_cc_foodPI = if_else(
      poor_Avpovln2022_2030_baseline == 0 &
      poor_2030_baseline_lab_cc_foodPI == 1,
      1,
      0
    )
  ) %>%
  group_by(NAM_1) %>%
  summarise(
    total_population = round(sum(weight_2030_baseline, na.rm = TRUE)),
    poor_baseline =
      round(sum(
        poor_baseline * weight_2030_baseline, na.rm = TRUE

```

```

    )),
    new_p_lab_cc =
      round(sum(
        new_poor_lab_cc * weight_2030_baseline, na.rm = TRUE
      )),
    new_p_lab_cc_foodPI =
      round(
        sum(new_poor_lab_cc_foodPI * weight_2030_baseline, na.rm = TRUE))
  )

new_poor_map <- adm1 %>%
  left_join(new_poor_scenarios, join_by(NAM_1)) %>%
  mutate(
    new_p_lab_cc_pct = new_p_lab_cc / total_population *
      100,
    new_poor_lab_cc_foodPI_pct = new_p_lab_cc_foodPI /
      total_population * 100
  ) %>%
  mutate(
    new_p_lab_cc_label = paste0(NAM_1, "\n(", sprintf("%.1f%%", new_p_lab_cc_pct), ")"),
    new_p_lab_cc_foodPI_label = paste0(NAM_1, "\n(", sprintf("%.1f%%", new_poor_lab_cc_foodPI_pct), ")")
  )

# test <- as.data.frame(new_poor_map)[,c(1,2,4,5,6,7,8,9)]

##write.table(test, "clipboard", sep="\t", row.names=FALSE)
##write.table(new_poor_scenarios, "clipboard", sep="\t", row.names=FALSE)


```

Let's map different scenarios.

```


tm_shape(new_poor_map)+
  tm_polygons("new_p_lab_cc_pct", title="Percent", legend.show = TRUE) +
  tm_text(c("new_p_lab_cc_label"), size = .7, col = "black")+
  tm_layout(legend.position = c("right", "top"),
    #legend.outside = TRUE,
    title= "New poor as a percentage of Marz population\nBaseline + LP/CC",
    title.position = c('left', 'bottom'),
    title.size = 0.9)

```



And the second variant

```
tm_shape(new_poor_map)+
  tm_polygons("new_poor_lab_cc_foodPI_pct",
    title="Percent",
    legend.show = TRUE) +
  tm_text(c("new_p_lab_cc_foodPI_label"), size = .7, col = "black")+
  tm_layout(legend.position = c("right", "top"),
    title= "New poor as a percentage of Marz population\nBaseline + LP/CC + Food Pri
#
    outer.margins=c(.10,.10, .10, .10),
    title.position = c('left', 'bottom'),
    title.size = 0.9)
```

Now let's show average losses by decile as a percentage of total spending.

```
avg_scenario_losses <- ca_microsim_cc %>%
  mutate(
    totc_loss_lab_cc = if_else(
      (totc_2030_baseline_lab_cc_avg - totc_2030_baseline) < 0,
      (totc_2030_baseline_lab_cc_avg - totc_2030_baseline) /
        totc_2030_baseline, NA),
    totc_loss_lab_cc_foodPI = if_else(
      (totc_2030_baseline_lab_cc_foodPI - totc_2030_baseline) < 0,
      (totc_2030_baseline_lab_cc_foodPI - totc_2030_baseline) /
        totc_2030_baseline, NA)
  ) %>%
  group_by(decile) %>%
  summarise(no_hh =
    round(
      sum(
        weight_2030_baseline, na.rm = TRUE), digits = 0
      ),
    avg_totc =
      round(
        weighted.mean(
          totc_2030_baseline, weight_2030_baseline, na.rm = TRUE), digits = 2
```

```

    ),
    avg_totc_usd =
      round(
        weighted.mean(
          totc_2030_baseline, weight_2030_baseline, na.rm = TRUE)*er, digits = 1
        ),
    avg_loss_lab_cc =
      round(
        weighted.mean(
          totc_loss_lab_cc,
          weight_2030_baseline,
          na.rm = TRUE),
        digits = 4
      ),
    avg_loss_lab_cc_foodPI =
      round(
        weighted.mean(
          totc_loss_lab_cc_foodPI,
          weight_2030_baseline,
          na.rm = TRUE), digits = 4))

##write.table(avg_scenario_losses, "clipboard", sep="\t", row.names=FALSE)

avg_scenario_losses %>%
  gt()

```

Decile of aec_r, with pweight	no_hh	avg_totc	avg_totc_usd	avg_loss_lab_cc	avg_loss_lab_cc_foodPI
1	54383	128475.5	296.8	-0.0091	-0.0091
2	59989	148602.4	343.3	-0.0112	-0.0112
3	61811	168331.2	388.8	-0.0104	-0.0104
4	67022	176428.9	407.6	-0.0094	-0.0094
5	73365	179992.2	415.8	-0.0113	-0.0113
6	80825	183949.5	424.9	-0.0116	-0.0116
7	80332	202849.9	468.6	-0.0101	-0.0101
8	88224	208982.8	482.8	-0.0122	-0.0122
9	96982	222294.9	513.5	-0.0092	-0.0092
10	120934	275965.9	637.5	-0.0107	-0.0107

ARMSTAT. (2023). *Integrated Living Conditions Survey 2022*.