Tools

Map with Bowtie for Illumina

Map with BWA for Illumina

Map with BWA for SOLiD

Megablast compare short reads against htgs, nt, and wgs databases

Parse blast XML output

Map with BWA-MEM - map medium and long reads (> 100 bp) against reference genome

Map with BWA - map short reads (< 100 bp) against reference genome

Bowtie2 - map reads against reference genome

TopHat Gapped-read mapper for RNA-seq data

NGS: RNA-seq

NGS: SAMtools

NGS: BAM Tools

NGS: Picard Tools

Genome Visualization

Workflows

- All workflows

TopHat Gapped-read mapper for RNA-seq data (Galaxy Tool Version 2.1.0) — Options

Is this single-end or paired-end data?

Paired-end (as individual datasets)

RNA-Seq FASTQ file, forward reads

3: SRR388738_1.fastq

Must have Sanger-scaled quality values with ASCII offset 33

RNA-Seq FASTQ file, reverse reads

4: SRR388738_2.fastq

Must have Sanger-scaled quality values with ASCII offset 33

Mean Inner Distance between Mate Pairs

300

-r/--mate-inner-dist; This is the expected (mean) inner distance between mate pairs. For, example, for paired end runs with fragments selected at 300bp, where each end is 50bp, you should set -r to be 200. The default is 50bp.

Std. Dev for Distance between Mate Pairs

20

--mate-std-dev; The standard deviation for the distribution on inner distances between mate pairs. The default is 20bp.

Report discordant pair alignments?

Yes

--no-discordant

Use a built in reference genome or own from your history

Use a built-in genome

History

search datasets

Galaxy exercise

6 shown

2.3 GB

6: SRR388749_2.fastq

5: SRR388749_1.fastq

4: SRR388738_2.fastq

3: SRR388738_1.fastq

2: refGene.gtf

1: clf.fna