Tools

Tophat Fusion Post post-processing to identify fusion genes

Filter Combined Transcripts using tracking file

Cuffquant Precompute gene expression levels

Cuffnorm Create normalized expression levels

Cuffmerge merge together several Cufflinks assemblies

gffread Filters and/or converts GFF3/GTF2 records

Cufflinks transcript assembly and FPKM (RPKM) estimates for RNA-Seq data

Cuffcompare compare assembled transcripts to a reference annotation and track Cufflinks transcripts across multiple experiments

StringTie transcript assembly and quantification

Cuffdiff find significant changes in transcript expression, splicing, and promoter use

Cufflinks transcript assembly and FPKM (RPKM) estimates for RNA-Seq data (Galaxy Tool Version 2.2.1.0) — Options

SAM or BAM file of aligned RNA-Seq reads

11: TopHat on data 1, data 4, and data 3: accepted_hits

Max Intron Length

300000

ignore alignments with gaps longer than this

Min Isoform Fraction

0.1

suppress transcripts below this abundance level

Pre MRNA Fraction

0.15

suppress intra-intronic transcripts below this level

Use Reference Annotation

Use reference annotation

Reference Annotation

2: refGene.gtf

Gene annotation dataset in GTF or GFF3 format.

Count hits compatible with reference RNAs only

No

With this option, Cufflinks counts only those fragments compatible with some reference transcript towards the number of mapped hits used in the FPKM denominator. This option can only be used in combination with --GTF.

History

search datasets

Galaxy exercise

11 shown

2.3 GB

11: TopHat on data 1, data 4, and data 3: accepted_hits

10: TopHat on data 1, data 4, and data 3: splice junctions

9: TopHat on data 1, data 4, and data 3: deletions

8: TopHat on data 1, data 4, and data 3: insertions

7: TopHat on data 1, data 4, and data 3: align_summary

6: SRR388749_2.fastq

5: SRR388749_1.fastq

4: SRR388738_2.fastq