

Free Models Router

[openrouter/free](#)[Compare](#)[Playground](#)

The simplest way to get free inference. `openrouter/free` is a router that selects free models at random from the models available on OpenRouter. The router smartly filters for models that support features needed for your request such as imag...



Personal ▾

All free-variant models currently available on OpenRouter.

📖 Quick Start

Drop-in code to call this model. OpenRouter's API is OpenAI-compatible — most SDKs work by just swapping the base URL. The only thing that changes between models is the model slug below.

1 Get your API key

Create an API key from your OpenRouter dashboard and set it as an environment variable:

Create API Key

```
export OPENROUTER_API_KEY=sk-or-v1- ...
```

📋 Copy

2 Make your first request

Use `openrouter/free` with the OpenRouter API:

OpenRouter supports reasoning-enabled models that can show their step-by-step thinking process. Use the `reasoning` parameter in your request to enable reasoning, and access the `reasoning_details` array in the response to see the model's internal reasoning before the final answer. When continuing a conversation, preserve the complete `reasoning_details` when passing messages back to the model so it can continue reasoning from where it left off. [Learn more about reasoning tokens.](#)

1.		MiniMax M3 by minimax	327.1B 9.2%
2.		Hy3 by tencent	317.2B 8.9%
3.		Nemotron 3 Super by nvidia	277.3B 7.8%
4.		MiniMax M2.7 by minimax	256.1B 7.2%
5.		gpt-oss-120b by openai	244.9B 6.9%
6.	+	Others	2.1T 60.1%

TypeScript SDK Python TypeScript (fetch) cURL Python (Open.

```
import { OpenRouter } from "@openrouter/sdk";  
  
const openrouter = new OpenRouter({  
  apiKey: "<OPENROUTER_API_KEY>"  
});  
  
// Stream the response to get reasoning tokens in usage  
const stream = await openrouter.chat.send({  
  chatRequest: {  
    model: "openrouter/free",  
    messages: [  
      {  
        role: "user",
```

Copy

Using third-party SDKs

For information about using third-party SDKs and frameworks with OpenRouter, please see our [frameworks documentation](#).

3 Enable streaming

Add `"stream": true` to your request body to receive responses as server-sent events:

```
curl -N https://openrouter.ai/api/v1/chat/completions \\  
  -H "Content-Type: application/json" \\  
  -H "Authorization: Bearer $OPENROUTER_API_KEY" \\  
  -d '{  
    "model": "openrouter/free",
```

Copy

```
]
}'
```

Endpoint

Sends a request for a model response for the given chat conversation.
Supports both streaming and non-streaming modes.

POST <https://openrouter.ai/api/v1/chat/completions>

Authorization	Bearer \$OPENROUTER_API_KEY
Content-Type	application/json
HTTP-Referer	optional – your site URL, for rankings
X-Title	optional – your site name, for rankings
Model	openrouter/free

Creates a streaming or non-streaming response using the OpenAI Responses API format.

Docs

POST <https://openrouter.ai/api/v1/responses>

Authorization	Bearer \$OPENROUTER_API_KEY
Content-Type	application/json
HTTP-Referer	optional – your site URL, for rankings
X-Title	optional – your site name, for rankings

Creates a message using the Anthropic Messages API format. Supports text, images, PDFs, tools, and extended thinking.

Docs

POST `https://openrouter.ai/api/v1/messages`

Authorization	Bearer <code>\$OPENROUTER_API_KEY</code>
Content-Type	<code>application/json</code>
HTTP-Referer	optional – your site URL, for rankings
X-Title	optional – your site name, for rankings
Model	<code>openrouter/free</code>

Frequently asked questions

What is Free Models Router?

Is Free Models Router free?

What is the context length of Free Models Router?

What inputs and outputs does Free Models Router support?

When was Free Models Router released?

Explore more models

AI Models with Vision: Multimodal LLMs for Image Understanding Collection

AI Model Rankings Ranking

More models from OpenRouter

Auto Router

Auto Router (Beta) is a task-aware router from OpenRouter. It classifies each ...

Text 2M context

Fusion

Fusion turns your prompt into a model deliberation. A panel of e

Text 1M context



Personal ▾

[Rankings](#)

[Benchmarks](#)

[Apps](#)

[Discover](#)

[Models](#)

[Collections](#)

[Providers](#)

[Pricing](#)

[Enterprise](#)

[Labs](#)

[Blog](#)

[Careers](#) [Hiring](#)

[Privacy](#)

[Terms of Service](#)

[Trust Center](#)

[Support](#)

[Works With OR](#)

[Data](#)

[Brand](#)

[API Reference](#)

[Developer Platform](#)

[Status](#)

[GitHub](#)

[LinkedIn](#)

[X](#)

[YouTube](#)



Personal ▾





Personal ▾