

INFORME DE LABORATORIO

(formato estudiante)

INFORMACIÓN BÁSICA					
ASIGNATURA:	Desarrollo de aplicaciones web				
TÍTULO DE LA PRÁCTICA:	JavaScript				
NÚMERO DE PRÁCTICA:	03	AÑO LECTIVO:	2026 A	NRO. SEMESTRE:	V
GRUPO:		Subgrupo		No. Informe	
FECHA DE PRESENTACIÓN	20 04 2026	HORA DE PRESENTACIÓN	9.00		
INTEGRANTE (s): A Condori Idme Raul Wilfredo B C				NOTA: 00.00	
DOCENTE(s): Mg. Ing. Corrales					

SOLUCIÓN Y RESULTADOS
I. SOLUCIÓN DE EJERCICIOS/PROBLEMAS – (considerar hasta 5 páginas para los resultados, considerando descripciones breves.) 1

Exercise: JS Introduction

True or False.
JAVA is short for JavaScript.

☐ True

☒ False

rwci

2

Exercise: JS Introduction

Who invented JavaScript?

☐ Tim Berners-Lee

☒ Brendan Eich

☐ Haakon Wium Lie

- raul wilfredo condori
idme

3.

Exercise: JS Introduction

Select the correct JavaScript method for finding the specified HTML element:

document.`getElementById`('demo').innerHTML

`findHTMLById`

`HTMLbyId`

4

Exercise: JS Where To

In HTML, JavaScripts must be inserted inside which HTML tags?

- ☒ `<script>` and `</script>`
- ☐ `<javascript>` and `</javascript>`
- ☐ `<head></head>`

5

Exercise: JS Where To

What is the correct file extension for JavaScript files?

- ☐ `.jvs`
- ☐ `.jv`
- ☒ `.js`

6

Exercise: JS Where To

What is a correct syntax for including a JavaScript in an HTML document?

- ☐ `<script href='myScript.js'></script>`
- ☐ `<script type='myScript.js'></script>`
- ☒ `<script src='myScript.js'></script>`

7

Exercise: JS Output

What is NOT a correct syntax for writing output in JavaScript?

- ☐ `window.alert()`
- ☒ `console.log()`
- ☐ `body.html()`
- ☐ `document.write()`

8

Exercise: JS Output

True or False.

`alert(8);` is the same as `window.alert(8);`.

- ☒ True
- ☐ False

9

Exercise: JS Output

Select the correct syntax for writing 'Hello':

document

.

write

(

'Hello'

)

body

console

getElementById

print

10

Exercise: JS Statements

How many statements can you find in this line of code:

```
let a = 5; let b = 6; c = a + b;
```

☐ 1

☐ 2

☒ 3

☐ 4

11

Exercise: JS Statements

True or False.

A semicolons is required after a statement in JavaScript.

- ☐ True
- ☒ False

12

Exercise: JS Statements

How many statements are present inside the function block?

```
function genie() {  
  let a, b, c;  
  a = 5;  
  b = 9;  
  c = a + b;  
}
```

- ☒ 4
- ☐ 5
- ☐ 6
- ☐ 7

13 syntax

Exercise: JS Syntax

Which one is NOT a legal variable name?

- ☐ FirstName
- ☐ \$FirstName
- ☐ _FirstName
- ☒ -FirstName

14

True or False.

JavaScript variable names are case in-sensitive, meaning **name** is the same as **NAME**

- ☐ True
- ☒ False

15 commnets

What is a correct syntax for creating a comment in JavaScript?

- ☐ # this is a comment
- ☒ // this is a comment
- ☐ '' this is a comment
- ☐ ## this is a comment

Submit Answer »

16

Exercise: JS Comments

Select the correct syntax for commenting out the entire section of the code.

```
/*  
This code will  
be ignored by JavaScript  
and will NOT be executed  
*/
```

// ## ' ' ' ' //

17

Exercise: JS Comments

What will be the value of `x`?

```
x = 5;  
//x = 7;
```

☒ 5

☐ 7

18 variables

Exercise: JS Variables

What is NOT a correct syntax for declaring variables?

☐ `let x;`

☒ `dim x;`

☐ `var x;`

☐ `const x;`

19

Exercise: JS Variables

Consider the following code:

```
let x = 5;  
x = 7;  
x = x + x;  
alert(x);
```

What will be the alerted result?

☐ 10

☒ 12

☐ 14

20

Exercise: JS Variables

Consider the following code:

```
let x = 5;  
x = 7;  
x = x + x;  
alert(x);
```

What will be the alerted result?

☐ 10

☐ 12

☒ 14

21

Exercise: JS Variables

Which one is NOT a legal variable name?

- ☒ first-name
- ☐ first_name
- ☐ first\$name
- ☐ first3name

22

Exercise: JS Variables

Create a variable called `carName`, assign the value `Volvo` to it.

```
let carName = "Volvo";
```

Show Answer

23

EXERCISE: JS variables

Create a variable called `x`, assign the value `50` to it.

```
let x = 50
```

Show Answer

24

Exercise: JS Variables

Display the sum of `5 + 10`, using two variables: `x` and `y`.

```
let x = 5;  
let y = 10;  
document.getElementById("demo").innerHTML = x + y;
```

Show Answer

25

Exercise: JS variables

On one single line, declare three variables named `fname`, `lname`, and `age`, with the values John, Doe, and 46.

```
let fname = 'John' , lname = 'Doe' , age = 46
```

```
const : John .  
fname 'age' Doe  
( ) var
```

26 let

What is a correct use of the `let` keyword?

☒ `let x = 5;`

☐ `x let 5;`

☐ `let 5 into x;`

☐ `x = 5(let);`

27

Exercise: JS Let

True or False.

Variables created with the `let` keyword can never change their value.

☐ True

☒ False

28

Exercise: JS Let

True or False.

With the `let` keyword, you can declare variables with the same name in the same block.

☐ True

☒ False

29 const

Exercise: JS Const

True or False.

Variables of type String or Number, created with the `const` keyword, can never change their value.

☐ True

☒ False

30

Exercise: JS Const

What is a correct use of the `const` keyword?

☐ `x const 5;`

☐ `const 5 into x;`

☒ `const x = 5;`

☐ `const(x, 5);`

31

Exercise: JS Const

True or False.

If you create an Array with the `const` keyword, you cannot change the item values.

☐ True

☒ False

32 operators

Exercise: JS Operators

Consider the following code:

```
let x = 5;  
let y = '8';  
let z = x + y;
```

What will be the result of `z`?

☐ undefined

☒ 58

☐ 13

Exercise: JS Operators

Multiply 10 with 5, and alert the result:

```
alert(10 * 5);
```

Show A

34

Insert the correct operator to divide 10 by 2:

```
let x = 10 / 2
```

x

*

-

\

#

%

35 operaciones aritmeticas

Exercise: JS Arithmetic Operators

Consider the following code:

```
let x = 5;  
x++;
```

What will be the result of `x`?

55

25

10

6

36

Exercise: JS Arithmetic Operators

Insert the correct operator to return the remainder when 15 is divided by 9:

```
let x = 15  9
```

#

-

/

\

*

37

Exercise: JS Arithmetic Operators

Consider the following code:

```
let x = 100 + 50 * 3;
```

What will be the result of `x`?

☐ 450

☒ 250

38

Exercise: JS Assignment Operators

Consider the following code:

```
let x = 5;  
x += 10;
```

What will be the result of `x`?

☐ 5

☐ 10

☒ 15

☐ 50

39



Exercise: JS Assignment Operators

Use the correct **assignment operator** that will result in `x` being `15` (same as `x = x + y`).

```
x = 10;  
y = 5;  
x  y;
```

Show Answer

40



Exercise: JS Assignment Operators

Use the correct **assignment operator** that will result in `x` being `50` (same as `x = x * y`).

```
x = 10;  
y = 5;  
x  y;
```

41 data types

Exercise: JS Data Types

In JavaScript, what is the data type of the following variable?

```
let x = 7.5
```

- ☐ Decimal
- ☒ Number
- ☐ Integer
- ☐ Float

42

Exercise: JS Data Types

True or False.

If a variable is declared using the `let` keyword, it can never change its type.

- ☐ True
- ☒ False

Exercise: JS Data Types

Insert the correct data type for each variable:

```
let a = 10;    //
```

Number

```
let b = 'Sally'; //
```

String

```
let c = true;  //
```

Boolean

Dictionary

Float

Object

44 functions

Ejercicio: Funciones de JavaScript

¿Qué palabra clave se utiliza para definir una función en JavaScript?

- ☐ def
- ☐ func
- ☒ function

Ejercicio: Funciones de JavaScript

Ejecuta la función llamada `myFunction`.

```
función myFunction() {  
  alert("¡Hola mundo!");  
}  
myFunction();
```

Mostrar respuesta

46

Ejercicio: Funciones de JavaScript

Crea una función llamada "myFunction".

```
function myFunction() {  
  alert("¡Hola mundo!");  
}
```

Mostrar respuesta

47

```
function myFunction() {  
  return "Hello";  
}  
document.getElementById("demo").innerHTML = myFunction();
```

Show Answer

48

Exercise: JS Functions

Complete the code to make the function display 'Hello' in the inner HTML of an element with the ID 'demo':

```
function myFunction() {  
  document.getElementById('demo').innerHTML = 'Hello'  
}
```

getId

49 Objects

Exercise: JS Objects

Consider the following object:

```
const car = {  
  brand: 'Volvo',  
  model: 'EX90'  
};
```

How many properties do the object have?

☐ 0

☐ 1

☒ 2

☐ 3

Exercise: JS Objects

Alert "John" by extracting information from the person object.

```
const person = {  
  firstName: "John",  
  lastName: "Doe"  
};  
  
alert(person.firstName);
```

Show Answer

51

Exercise: JS Objects

Add the following property and value to the person object: country: Norway.

```
const person = {  
  firstName: "John",  
  lastName: "Doe",  
  country: "Norway"  
};
```

Show Answer

52

Exercise: JS Objects

Consider the following object:

```
const person = {  
  name: 'John', age: 50  
};
```

Insert the missing parts to alert 'John is 50'.

```
alert( person . name + ' is ' + person . age );
```

John . 50
[age] object const Person

Exercise: JS Object Properties

Consider the following object:

```
const car = {  
  brand : 'Volvo',  
  model : 'EX90'  
};
```

What is NOT a correct syntax to alert 'Volvo'?

- ☐ alert(car[brand])
- ☐ alert(car.brand)
- ☒ alert(car['brand'])


Exercise: JS Object Properties

True or False:

You are allowed to insert new properties to existing objects.

☒ True

☐ False



Te Apuesto te lleva a la final 2026

Participa en el sorteo de uno de los paquetes para la final, semis o cuartos.

Más información

Submit Answer »

Exercise: JS Object Properties

What is a correct syntax to delete the property `model` from an object named `car`?

- ☐ `del car.model`
- ☐ `del model from car`
- ☐ `delete car.model`
- ☒ `car.model = NULL`

Submit Answer »

Exercise: JS Object Methods

Consider the following object:

```
const person = {  
  firstname: 'Jane',  
  lastname: 'Doe',  
  fullname: function() {  
    return this.firstname + ' ' + this.lastname;  
  }  
};
```

How many methods do the object have?

☐ 0

☒ 1

☐ 2

☐ 3

Exercise: JS Object Methods

Consider the following object:

```
const person = {  
  firstname: 'Jane',  
  lastname: 'Doe',  
  fullname: function() {  
    return this.firstname + ' ' + this.lastname;  
  }  
};
```

Insert the missing parts to alert 'Jane Doe'.

rt(Person . fullname ());

Jane : person . fullname () = person name

Exercise. JS Object Methods

True or False:

You are allowed to insert new methods to existing objects.

☒ True

☐ False

TE APUESTO



Te Apuesto te lleva a la final 2026

Participa en el sorteo de uno de los paquetes para la final, semis o cuartos.

Más info

Submit Answer »

59 display objects

Ejercicio: Visualización de objetos en JavaScript

Solo uno de los siguientes métodos es un método integrado de un objeto JavaScript, ¿cuál es?

- ☒ `return()`
- ☐ `all()`
- ☐ `entries()`
- ☐ `methods()`

60

Exercise: JS Display Objects

What method can be used to convert JavaScript Objects into JSON str

- ☐ `JSON.toString()`
- ☐ `JSON.stringify()`
- ☒ `JSON.string()`

61

Exercise: JS Display Objects

When using `Object.values()` on a JavaScript Object, what will be the data type of the returned result?

- ☐ Array
- ☐ String
- ☐ JSON
- ☒ Object

62 constructor objects

Ejercicio: Constructores de objetos JS

¿Cuál es la sintaxis correcta para agregar una nueva propiedad al `Person` constructor del objeto?

- ☒ `Person.hometown = 'Roma';`
- ☐ `Person.prototype.hometown = 'Roma';`
- ☐ `new Person.hometown = 'Roma';`
- ☐ `Person['hometown'] = 'Roma';`

Ejercicio: Constructores de objetos JS

Es común usar estos literales de objeto en lugar de `new Object()`, ¿cuáles?

☐ `()`

☐ `{}`

☒ `[]`

64

Ejercicio: Constructores de objetos JS

Inserta las partes que faltan para completar el constructor del objeto:

```
function Person(fname) {  
  this.firstname = fname;  
}
```

```
    ;  
    ,  
    : new ( )
```

65 eventos de js

Ejercicio: Eventos de JavaScript

¿Cuál es el atributo de evento HTML correcto para ejecutar algo cuando un usuario hace clic en un elemento?

- ☐ ontap
- ☐ onmouseclick
- ☐ clickme
- ☒ onclick

66

Ejercicio: Eventos de JavaScript

Al hacer clic en el botón, se debe ejecutar la función "myFunction".

```
<botón onclick="myfunction()">Haz clic aquí.</button>
```

67

Exercise: JS Events

The <div> element should turn red when someone moves the mouse over it.

```
<div onmouseover="this.style.backgroundColor='red'">myDIV.</div>
```

Show Answer

68 strings

Ejercicio: Cadenas de caracteres en JavaScript

¿Cuál de las siguientes opciones no es una cadena de JavaScript válida?

- ☐ "Hello world!"
- ☐ ""Hello world!""
- ☐ 'Hello world!'
- ☒ `Hello world!`

69

Ejercicio: Cadenas de caracteres en JavaScript

Utilice la propiedad `length` para alertar sobre la longitud de `txt`.

```
let txt = "¡Hola Mundo!";  
let x = txt.length;  
alert(x);
```

70

Exercise: JS Strings

Use escape characters to alert `We are "Vikings"`.

```
let txt = "We are \"Vikings\"";  
alert(txt);
```

71

Ejercicio: Cadenas de caracteres

Concatena las dos cadenas para mostrar "

```
let str1 = "Hola ";  
let str2 = ";Mundo!";  
alerta(str1 + str2);
```

72 string methods

Exercise: JS String Methods

Consider the following string:

```
let x = 'Having fun?';
```

Which one of the following statements returns 'fun'?

- ☐ x.slice(7, 10)
- ☐ x.substring(7, 9)
- ☒ x.substr(7, 10)

73

Exercise: JS String Methods

Convert the text into an UPPERCASE text:

```
let txt = "Hello World!";  
txt = txt.toUpperCase();
```

74

Exercise: JS String Methods

Use the slice method to return the word "bananas".

```
let txt = "I can eat bananas all day";  
let x = txt.slice(10, 17);
```

75

Exercise: JS String Methods

Use the correct String method to replace the word "Hello" with the word "Welcome".

```
let txt = "Hello World";  
txt = txt.replace("Hello", "Welcome");
```

76

Exercise: JS String Methods

Convert the value of `txt` to lower case.

```
let txt = "Hello World";  
txt = txt.toLowerCase();
```

77 string search

Exercise: JS String Search

Consider the following code:

```
let x = 'Hello world!';  
alert(x.indexOf('Hello'));
```

What will be the alerted result?

- ☐ -1
- ☐ 0
- ☒ 1
- ☐ true

78

Exercise: JS String Search

Consider the following code:

```
let x = 'JavaScript is fun!';  
alert(x.includes('fun'));
```

What will be the alerted result?

- ☐ 13
- ☐ 14
- ☒ true

79

Exercise: JS String Search

Which one is NOT a legal JavaScript method?

- ☐ `indexOf()`
- ☐ `instr()`
- ☐ `lastIndexOf()`
- ☒ `search()`

80

Exercise: JS String Search

Find the position of the character `h` in the string `txt`

```
let txt = "abcdefghijklm";  
let pos = txt.indexOf("h");
```

81 string templates

Exercise: JS String Templates

What do the back-ticks used for template strings in JavaScript look like

☐ " "

☐ ' '

☒ ` `

☐ ()

82

Exercise: JS String Templates

Insert the missing parts to alert 'Hello John Doe!':

```
let firstname = 'John';
```

```
let lastname = 'Doe';
```

```
alert(`Hello ${firstname} ${lastname} !`);
```

83

Exercise: JS String Templates

True or False.

Template strings allows multi line strings.

☒ True

☐ False

Exercise: JS Numbers

Consider the following code:

```
let x = 10;  
let y = 20;  
let z = x + y;
```

What will be the result of `z`?

- ☒ 30
- ☐ 1020
- ☐ 30.00

Exercise: JS Numbers

Consider the following code:

```
let x = 10;  
let y = 20;  
let z = 'The prize is ' + x + y;
```

What will be the result of `z`?

- ☒ The prize is 30
- ☐ The prize is 1020

Exercise: JS Numbers

True or False.

In JavaScript `4` and `1.8` has the same data type.

☐ True

☒ False

87 big int

Exercise: JS BigInt

What is a legal JavaScript syntax for creating a BigInt number?

☐ `1234567890123456789m`

☒ `1234567890123456789max`

☐ `1234567890123456789n`

88

Exercise: JS BigInt

What is *also* a legal JavaScript syntax for creating a BigInt number?

- ☐ `1234567890123456789.toBigInt()`
- ☒ `BigInt(1234567890123456789)`
- ☐ `Int64+(1234567890123456789)`

89

Exercise: JS BigInt

True or False.

BigInt numbers can have decimals.

- ☒ True
- ☐ False

90 numbers methods

Exercise: JS Number Methods

What is a legal JavaScript method for returning a number as a string?

- ☐ `intToString()`
- ☒ `toString()`
- ☐ `stringify()`

Exercise: JS Number Methods

Consider the following code:

```
let x = 2.7;  
let z = x.toFixed(2);
```

What will be the result of `z`?

- ☒ 2
- ☐ 3
- ☐ 2.7
- ☐ 2.70

Exercise: JS Number Methods

Consider the following code:

```
let x = 'Tobias';  
let z = Number(x);
```

What will be the result of `z`?

- ☐ false
- ☐ -1
- ☒ NaN
- ☐ undefined

Exercise: JS Number Properties

What is the name of the property for returning the largest number possible in JavaScript?

- ☐ POSSIBLE_MAX
- ☐ MAX_POSSIBLE
- ☒ MAX_VALUE
- ☐ MAX_POSITIVE

What is the name of the property for returning the largest INTEGER possible in JavaScript?

- ☒ MAX_INTEGER
- ☐ MAX_SAFE_INTEGER
- ☐ MAX_VALUE
- ☐ MAX_POSITIVE_INTEGER

Exercise: JS Number Properties

Consider the following code:

```
let a = Number.POSITIVE_INFINITY;
```

If you try to write the result of `a`, what will be the result?

- ☐ Infinity
- ☒ undefined
- ☐ NaN

96 arrays

¿Cuál NO es una forma legal de crear una matriz?

- ☐ `const fruits = ['Orange', 'Banana', 'Apple'];`
- ☐ `const fruits = new Array ('Orange', 'Banana', 'Apple');`
- ☒ `const fruits = ('Orange', 'Banana', 'Apple');`

97

Exercise: JS Arrays

Get the value "Volvo" from the `cars` array

```
const cars = ["Saab", "Volvo", "BMW"];  
let x = cars[1];
```

98

Exercise: JS Arrays

Change the first item of cars to "Ford".

```
const cars = ["Volvo", "Jeep", "Mercedes"];  
cars[0] = "Ford";
```

99

Exercise: JS Arrays

Alert the number of items in an array, using the correct Array property.

```
const cars = ["Volvo", "Jeep", "Mercedes"];  
alert(cars.length);
```

100 arrays methods

Exercise: JS Array Methods

After executing the following code:

```
const fruits = ['Banana', 'Orange', 'Apple'];  
fruits.pop();
```

What will the `fruits` array look like?

- ☐ [' ', 'Banana', 'Orange', 'Apple']
- ☐ ['Banana', 'Orange']
- ☒ ['Orange', 'Apple']

101

Exercise: JS Array Methods

Use the correct Array method to add "Kiwi" to the `fruits`

```
const fruits = ["Banana", "Orange", "Apple"];  
fruits.push("Kiwi");
```

102

Exercise: JS Array Methods

Use the `splice()` method to remove "Orange" and "Apple" from `fruits`

```
const fruits = ["Banana", "Orange", "Apple", "Kiwi"];  
fruits.splice(1, 2);
```

Exercise: JS Array Search

Consider the following code:

```
const fruits = ['Apple', 'Orange', 'Mango'];  
let x = fruits.indexOf('Orange');
```

What will the result of `x`?

- ☐ 0
- ☒ 1
- ☐ true

Consider the following code:

```
const fruits = ['Apple', 'Orange', 'Mango'];  
let x = fruits.includes('Orange');
```

What will the result of `x`?

- ☐ 0
- ☒ 1
- ☐ true

Exercise: JS Array Search

Consider the following code:

```
const fruits = ['Apple', 'Orange', 'Mango'];  
let x = fruits.indexOf('Banana');
```

What will the result of `x`?

- ☐ 0
- ☐ -1
- ☒ false

106 sorting arrays

Exercise: JS Sorting Arrays

Consider the following code:

```
const fruits = ['Apple', 'Orange', 'Banana'];  
fruits.reverse();
```

What will the result of the `fruits` array?

- ☐ ['Orange', 'Banana', 'Apple']
- ☒ ['Banana', 'Orange', 'Apple']
- ☐ ['Apple', 'Banana', 'Orange']
- ☐ ['Orange', 'Apple', 'Banana']

107

Exercise: JS Sorting Arrays

Use the correct Array method to sort the `fruits` array alphabetically.

```
const fruits = ["Banana", "Orange", "Apple", "Kiwi"];  
fruits.sort();
```

108

True or False?

The `reverse()` method returns a new array, the original array is not affected.

☒ True

☐ False

109 array iteration

Consider the following code:

```
const x = [45, 4, 9, 16, 25];  
let y = x.every(myfunc);  
function myfunc(val) {  
  return val > 20;  
}
```

What will the result of the `y`?

- ☐ [45, 25]
- ☐ false
- ☐ []
- ☒ NaN

Exercise: JS Array iteration

Consider the following code:

```
const x = [45, 4, 9, 16, 25];  
let y = x.some(myfunc);  
function myfunc(val) {  
  return val > 20;  
}
```

What will the result of the `y`?

- ☒ [45, 25]

Consider the following code:

```
const x = [45, 4, 9, 16, 25];  
let y = x.map(myfunc);  
function myfunc(val) {  
  return val > 20;  
}
```

What will the result of the `y`?

- ☐ [45, 25]
- ☐ false
- ☐ true
- ☒ [true, false, false, false, true]

112 array const

Exercise: JS Array Const

True or False.

you declare an array with the `const` keyword, you cannot change the items later.

- ☐ True
- ☒ False

113

Exercise: JS Array Const

Consider the following code:

```
const x = ['Apple', 'Banana', 'Cherry'];  
{  
  const x = ['Audi', 'BMW', 'Chevrolet'];  
}  
alert(x[1]);
```

What will be the alerted result?

- ☒ You will get an error.
- ☐ Banana
- ☐ BMW

114

Exercise: JS Array Const

Is the following redeclaring of the `fruits` array allowed?

```
const fruits = ['Apple', 'Banana', 'Cherry'];  
var fruits = ['Kiwi', 'Lemon', 'Mango'];
```

- ☒ Yes, it's allowed
- ☐ No it's not allowed

115 dates

Exercise: JS Dates

What date is created with the following code:

```
const d = new Date(2024, 10, 18);
```

- ☐ October 18. 2024
- ☒ November 18. 2024
- ☐ October 19. 2024
- ☐ November 19. 2024

116

Exercise: JS Dates

Create a Date object and alert the current date and time

```
const d = new Date();  
alert(d);
```

117

EXERCISE: JS Dates

What date is created with the following code:

```
const d = new Date(24, 10, 18);
```

- ☐ October 18. 2024
- ☒ November 18. 2024
- ☐ October 18. 1924
- ☐ November 18. 1924

118 date formats

Exercise: JS Date Formats

What date is created with the following code:

```
const d = new Date('2024');
```

- ☐ A random date in 2024
- ☒ January 1. 2024
- ☐ December 31. 2024

Exercise: JS Date Formats

True or False.

UTC (Universal Time Coordinated) is the same as GMT (Greenwich Mean Time).

- ☐ True
- ☒ False

120

Exercise: JS Date Formats

Consider the following code:

```
let x = Date.parse('March 30, 2011');
```

What will be the result `x` ?

- ☒ The number of milliseconds between March 30, 2011 and January 1, 1900
- ☐ The number of milliseconds between March 30, 2011 and January 1, 1970
- ☐ The number of milliseconds between March 30, 2011 and January 1, 2000

121 date get methods

Exercise: JS Date Get Methods

What is the return value of the `getDay()` ?

- ☐ A number between 1 and 31
- ☐ A number between 0 and 30
- ☒ A number between 1 and 7
- ☐ A number between 0 and 6

122

Exercise: JS Date Get Methods

Use the correct Date method to extract the year (four digits) out of a object.

```
const d = new Date();  
year = d.getFullYear();
```

123

Exercise: JS Date Get Methods

Use the correct Date method to get the month (0-11) out of a date object

```
const d = new Date();  
month = get.month();
```

124 date set methods

Exercise: JS Date Set Methods

What is expected format of the argument in the `setDate()` method?

- ☐ A number between 1 and 31
- ☒ A number between 0 and 30
- ☐ A number between 1 and 7
- ☐ A number between 0 and 6

125

Exercise: JS Date Set Methods

Use the correct Date method to set the year of a date object to 2020.

```
const d = new Date();  
d.setFullYear(2020);
```

126

Exercise: JS Date Set Methods

What is expected format of the `setTime()` method?

- ☒ A number between 0 and 23
- ☐ A date with the time specified
- ☐ Milliseconds since January 1, 1970

Ejercicio: Matemáticas JS

¿Cuál es la sintaxis correcta para redondear un número hacia abajo más cercano?

- ☒ `Math.roundDown(4.9)`
- ☐ `Math.floor(4.9)`
- ☐ `Math.abs(4.9)`
- ☐ `Math.min(4.9)`

Exercise: JS Math

Use the correct Math method to return the largest number of 10 and 20.

```
let x = Math.max(10, 20);
```

Exercise: JS Math

Use the correct Math method to round a number to the nearest integer

```
let x = Math.round(5.3);
```

Exercise: JS Math Random

How many parameters can the `Math.random()` method take?

☐ 0

☐ 1

☒ 2

Exercise: JS Math Random

Use the correct Math method to create a random number.

```
let r = Math.dandom();
```


Exercise: JS Math Random

What is a correct syntax for returning a random number between 0 and 100?

- ☐ `Math.random()`
- ☒ `Math.random() * 10`
- ☐ `Math.random() * 100`

134 booleans

Exercise: JS Booleans

Consider the following code:

```
let x = 5 < 2;
```

What will be the value of `x`?

- ☒ `true`
- ☐ `false`

135

Exercise: JS Booleans

Consider the following code:

```
let x = 5 == 5;
```

What will be the value of `x`?

☒ true

☐ false

136

Exercise: JS Booleans

Consider the following code:

```
let x = Boolean(0);
```

What will be the value of `x`?

☐ true

☒ false

137 comparisons

Exercise: JS Comparisons

Consider the following code:

```
let x = (5 == 5 || 5 < 2);
```

What will be the value of `x`?

- ☒ true
- ☐ false

138

Choose the correct comparison operator to alert `true`, when `x` is greater than `y`.

```
x = 10;  
y = 5;  
alert(x > y);
```

139

Exercise: JS Comparisons

Choose the correct comparison operator to alert `true`, when `x` is equal to `y`.

```
x = 10;  
y = 10;  
alert(x == y);
```

140

Choose the correct comparison operator to alert `true` , when `x` is NOT equal to `y` .

```
x = 10;  
y = 5;  
alert(x  y);
```

141

Exercise: JS Comparisons

Choose the correct conditional (ternary) operator to alert "Too young" is less than 18, otherwise alert "Old enough".

```
var age = n;  
var voteable = (age > 18) ? "Too young" : "Old enough";  
alert(voteable);
```

142

Fix the if statement to alert "Hello World" if `x` is greater than `y` .

```
if (x > y) {  
    alert("Hello World");  
}
```

Exercise: JS If Else

Fix the if statement to alert "Hello World" if `x` is greater than `y`, otherwise alert "Goodbye".

```
if (x > y) {  
  alert("Hello World");  
} else {  
  alert("Goodbye");  
}
```

142 switch

Exercise: JS Switch

Which one is NOT a keyword in the `switch` statement?

- ☐ switch
- ☐ break
- ☐ continue
- ☒ default

Create a `switch` statement that will alert "Hello" if `fruits` is "banana", and "Welcome" if `fruits` is "apple".

```
switch(fruits) {  
  case "Banana":  
    alert("Hello")  
    break;  
  case "Apple":  
    alert("Welcome")  
    break;  
}
```

144

Add a section that will alert("Neither") if `fruits` is neither "banana" nor "apple".

```
switch(fruits) {  
  case "Banana":  
    alert("Hello")  
    break;  
  case "Apple":  
    alert("Welcome")  
    break;  
  default  
    alert("Neither");  
}
```

145 for loops

Consider the following code:

```
let i, x = '';  
for (i = 0; i <= 5; i++) {  
  x += i;  
}
```

What will be the result of `x`?

- ☐ 01234
- ☒ 012345
- ☐ 1234
- ☐ 12345

146

Create a loop that runs from 0 to 9.

```
let i;  
for (i = 0; i < 9; i++) {  
  console.log(i);  
}
```

147

Consider the following code:

```
let i, x = '';  
for (i = 0; i < 5; i = i + 2) {  
  x += i;  
}
```

What will be the result of `x`?

- ☐ 0123456
- ☐ 01234567
- ☒ 02468
- ☐ 024

148

Exercise: JS For In Loops

True or False.

The `for in` loop cannot be used on Arrays.

- ☐ True
- ☒ False

149

Exercise: JS For In Loops

Complete the following code to make a **for in** loop:

```
for in let x { person is end  
alert(person[x]);  
}
```

150

Ejercicio: Bucles for-in en JavaScript

Existe un método Array que puedes usar para recorrer los elementos de un array, ¿cuál?

- ☐ `Array.for()`
- ☒ `Array.in`
- ☐ `Array.forEach`
- ☐ `Array.iterate()`

151 for of loops

Exercise: JS For Of Loops

Consider the following code:

```
const fruits = ['Apple', 'Banana', 'Orange'];  
for (x of fruits) {  
  console.log(x);  
}
```

What will be the result in the console?

☐

1
2
3

☐

0
1
2

☒

Apple
Banana
Orange

Exercise: JS For Of Loops

Create a loop that runs through each item in the `fruits` array.

```
const fruits = ["Apple", "Banana", "Orange"];  
for (x of fruits) {  
  console.log(x);  
}
```

153

Exercise: JS For Of Loops

Consider the following code:

```
const fruits = ['Apple', 'Banana', 'Orange'];  
for (x in fruits) {  
  console.log(x);  
}
```

What will be the result in the console?



1
2
3



0
1
2



Apple
Banana
Orange

Exercise: JS While Loops

Consider the following code:

```
let i = 15, x = '';  
do {  
  x += 'The number is ' + i;  
}  
while (i < 10);
```

Which one of these statements will be true?

- ☒ `x` will be an empty string
- ☐ `x` will be a string with the value 'The number is 15'
- ☐ The loop will never end

Exercise: JS While Loops

Create a loop that runs as long as `i` is less than 10.

```
let i = 0;  
while (i < 10) {  
  console.log(i);  
  i++;  
}
```

Exercise: JS While Loops

Create a loop that runs as long as `i` is less than 10, but increase `i` with 2 each time.

```
let i = 0;
while (i < 10) {
  console.log(i);
  i = i + 2;
}
```

157 break and continue

Exercise: JS Break and Continue

Consider the following code:

```
const fruits = ['Apple', 'Banana', 'Cherry'];
let x = '';
myfavorite: {
  x = fruits[0];
  break myfavorite;
  x = fruits[1];
  x = fruits[2];
}
alert(x);
```

What will be the alerted result?

☒ Apple

☐ Banana

☐ Cherry

158

Make the loop stop when **i** is 5.

```
for (i = 0; i < 10; i++) {  
  console.log(i);  
  if (i == 5) {  
    break;  
  }  
}
```

159

Make the loop jump to the next iteration when **i** is 5.

```
for (i = 0; i < 10; i++) {  
  if (i == 5) {  
    continue;  
  }  
  console.log(i);  
}
```

160 iterables

Consider the following code.

```
let firstname = 'Jim', i = 0;  
for (const x of firstname) {  
  i++;  
}
```

What will be the value of `i`?

☐ 0

☐ 1

☒ 2

☐ 3

161

Consider the following code:

```
const fruits = ['Apple', 'Banana', 'Cherry'];  
let txt = '';  
for (const x of fruits) {  
  txt += x;  
}
```

What will be the value of `txt`?

☐ Apple

☐ Banana

☐ Cherry

☒ AppleBananaCherry

Consider the following code:

```
const fruits = ['Apple', 'Banana', 'Cherry'];  
let txt = '';  
for (const x in fruits) {  
  txt += x;  
}
```

What will be the value of `txt`?

- ☒ 012
- ☐ AppleBananaCherry

Exercise: JS Sets

True or False.

Each value can only occur once in a Set.

- ☒ True
- ☐ False

Which method can be used to add a value to a set?

- ☐ add()
- ☐ insert()
- ☒ push()
- ☐ attach()

165

What happens if you try to add a value that already exists?

- ☐ An error will occur
- ☐ The Set will not add the new value, but keep the first occurrence
- ☒ The Set will add the new value and delete the first occurrence

166 methods

EXERCISE: JS SET METHODS

Which method can be used to check if a Set contains a specified value?

- ☒ contains()
- ☐ indexOf()
- ☐ has()
- ☐ inSet()

Exercise: JS Set Methods

Which method can be used to execute a function for each Set item?

- ☐ function
- ☐ run()
- ☐ forEach()
- ☐ next()

Which method returns an Iterator object with all the values in a Set

- ☐ all()
- ☐ values()
- ☐ items()
- ☒ iterator()

Which method can be used to add elements to a Map?

- ☐ add()
- ☒ insert()
- ☐ push()
- ☐ set()

170

Which method can be used to get elements from a Map?

- ☐ key()
- ☐ value()
- ☒ get()
- ☐ select()

171

True or False.
The Map key must be a String.

☒ True

☐ False

172 math methods

Exercise: JS Map Methods

Which property can be used to return the number of elements in a Map?

☐ length

☒ size

☐ count

☐ numberOf

173

Exercise: JS Map Methods

Which method can be used to check if a Map contains a specified element?

- ☐ contains()
- ☐ indexOf()
- ☒ has()
- ☐ inSet()

174

Exercise: JS Map Methods

Which method returns an Iterator object with all the keys in a Map

- ☐ all()
- ☐ keys()
- ☐ items()
- ☒ iterator()

175 type off

Exercise: JS TypeOf

Consider the following code:

```
x = typeof('John' + 35);
```

What will be the value of `x`?

- ☒ string
- ☐ undefined
- ☐ number
- ☐ boolean

176

Exercise: JS TypeOf

Consider the following code:

```
x = typeof(['Apple', 'Banana']);
```

What will be the value of `x`?

- ☐ string
- ☒ array
- ☐ object

177

Consider the following code:

```
x = ['Apple', 'Banana'];  
y = (x instanceof Array);
```

What will be the value of **y**?

- ☐ string
- ☐ array
- ☒ true

178 type conversion

Consider the following code:

```
let x = Number(55.21);
```

What will be the value of **x**?

- ☒ 55
- ☐ 55.2
- ☐ 55.21

179

Exercise. JS Type Conversion

Consider the following code:

```
let x = Number('John');
```

What will be the value of `x`?

- ☐ 0
- ☐ John
- ☒ NaN

180

Consider the following code:

```
let x = typeof(Number('John'));
```

What will be the value of `x`?

- ☐ string
- ☒ NaN
- ☐ undefined
- ☐ number

181 destructuring

Consider the following code:

```
const fruits = ['Apple', 'Banana', 'Cherry'];  
let [x, y] = fruits;
```

What will be the value of `x`?

- ☐ ['Apple', 'Banana', 'Cherry']
- ☐ ['Apple']
- ☒ Apple

182

Insert the missing syntax to make the `leftover` variable contain the rest of the Array.

```
const numbers = [10, 20, 30, 40, 50, 60, 70];  
const [a,b, = leftover] = numbers;
```

:

...

===

,,,

183

Use destructuring to swap fName and lName. Meaning, fName should get the value 'Doe' and lName 'John'.

```
let fName = 'John';  
let lName = 'Doe';  
[fName, lName] = new { lName, fName };
```

this { [] :
()

184 bit wise

EXERCISE: 95 BITWISE

What number does the binary number 010 represent?

- ☐ 1
- ☒ 2
- ☐ 10

185

When working with binary numbers, what is the result of the following operation?

`1111 & 0001`

- ☐ 0000
- ☒ 0001
- ☐ 1110
- ☐ 1111

186

When working with binary numbers, what is the result of the following operation?

`1111 | 0001`

- ☐ 0000
- ☐ 0001
- ☐ 1110
- ☒ 1111

187 regular expresion

Exercise: JS Regular Expressions

What does the `i` modifier represent in Regular Expressions?

- ☐ Perform global matching (find all occurrences)
- ☐ Perform case-sensitive matching
- ☒ Perform case-insensitive matching

188

```
let pattern = /e/;  
let x = pattern.test('Ladies and gentlemen');
```

What will be the value of `x`?

- ☐ e
- ☒ 4
- ☐ true
- ☐ false

189

Exercise: JS Regular Expressions

Consider the following code:

```
let txt = 'Ladies and gentlemen';  
let x = txt.match(/[abc]/ig);
```

How many matches will the regular expression get?

☒ 0

☐ 1

☐ 2

☐ 3

190 operator precedence

Exercise: JS Operator Precedence

Consider the following code:

```
let x = 10 + 50 * 3;
```

What will be the result of `x`?

☒ 160

☐ 180

☐ 250

191

Consider the following code:

```
let x = 10 / 2 * 5;
```

What will be the result of `x`?

- ☐ 1
- ☐ 10
- ☐ 20
- ☒ 25

192

Exercise 35 Operator Precedence

Consider the following code:

```
let x = 20 + 5 * (5 + 5);
```

What will be the result of `x`?

- ☐ 250
- ☒ 70

193 error handling

Exercise: JS Error Handling

Only one of the following words is a legal JavaScript statement, which one?

- ☐ find
- ☐ check
- ☒ try
- ☐ execute

194

Insert the missing syntax to complete the error handling:

```
    if {  
      let x = 'Hello';  
    }  
    catch (err) {  
      alert('Something wen wrong');  
    }
```

195

Insert the missing syntax to complete the error handling:

```
try {  
  let x = 'Hello';  
}  
catch (err) {  
  alert('Something wen wrong');  
}
```

196

```
try {  
  let x = 'Hello';  
}  
catch (err) {  
  alert('Something went wrong');  
  finally {  
    alert('Everything went fine');  
  }  
}
```

197 scope


```
let x = 5;  
{  
  let x = 3;  
}  
alert(x);
```

What will be the alerted result?

☒ 5

198

Consider the following code:

```
let x = 5;  
function myfunc() {  
  x = 3;  
}  
myfunc();  
alert(x);
```

What will be the alerted result?

☒ 5

☐ 3

199

Consider the following code.

```
let x = 5;  
function myfunc() {  
  const x = 3;  
}  
myfunc();  
alert(x);
```

What will be the alerted result?

☐ 5

☒ 3

200 hoisting

```
x = 5;  
alert(x);  
var x;
```

What will be the alerted result?

☐ 5

☒ undefined

Consider the following code:

```
x = 5;  
var x;  
alert(x);
```

What will be the alerted result?

5

undefined

201

202

Exercise: JS Hoisting

Consider the following code:

```
var x = 5;  
var y;  
alert(y);  
y = 7;
```

What will be the alerted result?

☒ 7

☐ undefined

203 strict mode

How do we define that JavaScript code should be executed in 'strict mode'?

- ☐ "use strict";
- ☒ use strict;
- ☐ "strict mode";
- ☐ strict mode;

204

True or False.

"strict mode" can only be defined at the very beginning of a JavaScript?

- ☐ True
- ☒ False

205

Will the following code cause an error?

```
"use strict";  
var x = 5;
```

- ☒ No it will not cause an error
- ☐ Yes it will cause an error

206

Will the following code cause an error?

```
"use strict";  
x = 'Hello';
```

- ☒ No it will not cause an error
- ☐ Yes it will cause an error

207

True or False.

You cannot change the value of **this**.

- ☒ True
- ☐ False

208

Exercise: JS The this Keyword

What does **this** refer to when used in an object method?

- ☐ The global object [object Window]
- ☒ The object that the method belongs to.

209

`<button onclick='this.style.display="none"'>OK</button>`

What object does `this` refer to?

- ☐ The global object [object Window]
- ☒ The button element
- ☐ The body element

210

Exercise: JS Arrow Function

Which one of the following is a correct JavaScript arrow function?

- ☒ `greeting => 'Hello World!';`
- ☐ `greeting = return => 'Hello World!';`
- ☐ `greeting = () => 'Hello World!';`

211

Insert the missing parts to complete the arrow function:

```
myfunc == ==> () {  
  let x = 5;  
  return x;  
}
```

212

EXERCISE: JS ARROW FUNCTION

True or False.

You are not allowed to use parameters in arrow functions.

☐ True

☒ False

213

There is one method all classes should have, which one?

☐ `init()`

☒ `constructor()`

☐ `onerror()`

214

What keyword do we use when we create a class?

☒ `class`

☐ `object`

☐ `function`

215

EXERCISE: JS CLASSES

True or False.

You are not allowed to send parameters into class methods.

☐ True

☒ False

216

EXERCISE: JS MODULES

What attribute and value are required on the `<script>` tag when importing a module?

☐ `<script type='module'>`

☒ `<script module='name of module'>`

☐ `<script link='module'>`

217

```
const name = 'Tobias';
```

```
const age = 18;
```

```
export {name, age};
```

return

values

218

Exercise: JS Modules

True or False.

You can only have one 'default export' in a module file.

- ☐ True
- ☒ False

219 json

Exercise: JS JSON

What does JSON stand for?

- ☐ JavaScript Organized Nodes
- ☒ JavaScript Object Notation
- ☐ JavaScript Original Numbers

220

What is a correct JavaScript function to convert a string into a JavaScript object?

- ☒ `JSON.toObject()`
- ☐ `JSON.objectify()`
- ☐ `JSON.parse()`

221

Exercise: JS JSON


Which one is a legal JSON object?

- ☐ `{"firstName":"John", "lastName":"Doe"}`
- ☐ `{"firstName"="John", "lastName"="Doe"}`
- ☐ `{firstName="John", lastName="Doe"}`

222

225

Exercise: JS HTML DOM




What does DOM stand for?

- ☒ Document Object Model
- ☐ Document Order Manager
- ☐ Document Organize Manager

226

Exercise: JS HTML DOM



Who has created the DOM standard?

- ☒ Microsoft
- ☐ Apple
- ☐ W3C

227

Exercise: JS HTML DOM

True or False.

With the HTML Dom, you can use JavaScript to access HTML elements.

☒ True

☐ False

228 dom methods

Exercise: JS HTML DOM Methods

What is a legal HTML DOM method for accessing HTML elements?

☐ fetchId

☒ getElementById()

☐ element()

229

What is a legal HTML DOM property for changing the value of an HTML element?

☐ content

☐ tagValue

☒ innerHTML

230

Exercise: JS HTML DOM Document

Insert the missing syntax to change the content of the HTML element with the id 'demo'.

```
document . getElementById ('demo'). innerHTML = 'Hello!';
```

valueHTML []

element []

231 dom document

Exercise: JS HTML DOM Document

What is a NOT a legal HTML DOM document method?

- ☐ `getElementsByClassName()`
- ☒ `getElementsByTagName()`
- ☐ `getElementsByAttributeName()`

232

Exercise: JS HTML DOM Document

What is a correct syntax for returning the title of an HTML document?

- ☐ `document.name`
- ☐ `document.title`
- ☐ `document.getTitle`
- ☒ `document.getElementsByTagName('title')`

233

Exercise: JS HTML DOM Document

Insert the missing syntax to alert the value of the element with the id 'demo'.

```
alert( document . getElementById ( 'demo' ) . valueHTML );
```

```
    [ ] innerHTML [ ]  
    element [ ]
```

234

Exercise: JS HTML DOM HTML

What is a legal syntax for changing the content of an Element

- ☐

```
let x = document.getElementById('demo')  
x.content = 'Welcome';
```
- ☒

```
let x = document.getElementById('demo')  
x.innerHTML = 'Welcome';
```
- ☐

```
let x = document.getElementById('demo')  
x.changeContent('Welcome');
```

235

Exercise: JS HTML DOM HTML

Change the text of the first element that has the class name "test".

```
<p class="test"></p>  
<p class="test"></p>
```

```
<script>  
document.getElementsByClassName("test")[0].innerHTML = "Hello";  
</script>
```

Show Answer

236

Use HTML DOM to change the value of the image's src attribute.

```


<script>
document.getElementById("image").src = "pic_mountain.jpg";
</script>
```

237

Exercise: JS HTML DOM Form Validation

What is a legal syntax for returning all the form elements of a document?

- ☐ document.forms;
- ☐ document.all('form');
- ☒ document.getForms();

238

Exercise: JS HTML DOM Form Validation

Use HTML DOM to change the value of the input field.

```
<input type="text" id="myText" value="Hello">

<script>
document.getElementById("myText").value = "Have a nice day!";
</script>
```


Exercise: JS HTML DOM Form Validation

What is a legal JavaScript syntax for setting a form field as REQUIRED?

- ☐ `document.forms['myForm']['fname'].type = 'required'`
- ☒ `document.forms['myForm']['fname'].required = true`
- ☐ `document.forms['myForm']['fname'].value = 'required'`

Exercise: JS HTML DOM CSS

What is a legal JavaScript syntax for returning the background color of an element?

- ☐ `document.getElementById('demo').layout.backgroundColor;`
- ☐ `document.getElementById('demo').css.backgroundColor;`
- ☒ `document.getElementById('demo').style.backgroundColor;`

Change the text color of the `<p>` element to "red".

```
<p id="demo"></p>
```

```
<script>
```

```
document.getElementById("demo").style.color = "red";
```

```
</script>
```

242

Exercise: JS HTML DOM CSS

Change the font size of the `p` element to 40 pixels.

```
<p id="demo"></p>
```

```
<script>
```

```
document.getElementById("demo").style.fontSize = "40px";
```

```
</script>
```

243

Use the CSS `display` property to hide the `p` element.

```
<p id="demo"></p>
```

```
<script>
```

```
document.getElementById("demo").style.display = "none";
```

```
</script>
```

EXERCISE: JS HTML DOM EVENTS

What is a legal HTML attribute used for adding some action when a button is clicked?

- ☒ `<button onclick='alert(10) '>Click me</button>`
- ☐ `<button click='alert(10) '>Click me</button>`
- ☐ `<button press='alert(10) '>Click me</button>`

Exercise: JS HTML DOM Events

What is a legal JavaScript syntax for adding some action when a button is clicked?

- ☐ `document.getElementById('x').click = alert(5);`
- ☒ `document.getElementById('x').onclick = alert(5);`
- ☐ `document.getElementById('x').onmouseclick = alert(5);`

EXERCISE: JS HTML DOM EVENTS

Insert the correct event attribute to add some action when the mouse moves over an element.

```
<div onmouseover='console.log('Entered');'
```

247 dom events

Exercise: JS HTML DOM Event Listener

What is a legal syntax for executing a function called 'myfunc' when the browser window resizes?

- ☐ window.listen('resize', myfunc);
- ☒ window.addEventListener('resize', myfunc);
- ☐ window.addEvent('resize', myfunc);
- ☐ window.execute(myfunc, 'resize');

248

Use the `addEventListener` to assign an onclick event to the `<button>` element.

```
<button id="demo">Click me1</button>
```

```
<script>  
document.getElementById("demo").addEventListener("click", myFunction);  
</script>
```

249

Insert the missing syntax for a function to execute when an element is clicked.

```
document.getElementById('demo').execute('click',  
function(){  
  alert('Hello');});
```

250 dom navigation

Consider the following code:

```
<body>  
  <h1>Welcome</h1>  
  <p>Read this.</p>  
</body>
```

Which one of the following statements is true?

- ☒ <body> is the sibling of <h1>
- ☐ <body> is the child of <h1>
- ☐ <body> is the parent of <h1>

Exercise: JS HTML DOM Navigation

Consider the following code:

```
<div>
  <h1>Welcome</h1>
</div>
```

```
<div>
  <h1>Welcome</h1>
</div>
```

True or False.

The two <h1> elements are siblings.

True

False

252

Insert the missing syntax for returning the parent of the <h1> element.

```
let x = document.getElementsByTagName('h1')[0].parent;
```

253 dom modules

Exercise: JS HTML DOM Nodes

What is a correct syntax for creating a new `<h1>` element?

- ☐ `document.appendChild('h1');`
- ☐ `document.newElement('h1');`
- ☒ `document.createElement('h1');`

254

Exercise: JS HTML DOM Nodes

Insert the missing syntax to:

1. Create a paragraph
2. Create a Text Node
3. Append the Text Node to the paragraph
4. Append the paragraph to the body element

```
let a = document.createElement('p');  
let b = document.my text node('a');  
a.createText(b);document.body.appendChild(appendChild);
```

255

Exercise: JS HTML DOM Nodes

Insert the missing syntax to:

1. Create a paragraph
2. Create a Text Node
3. Append the Text Node to the paragraph
4. Append the paragraph to the body element

```
let a = document.createElement('p');  
let b = document.createTextNode('my text node.');
```

a. `appendChild`(b); document.body.appendChild(a)

256 dom collections

Exercise: JS HTML DOM Collections

What is a correct syntax for returning all <p> element?

- ☒ `document.getElementsByTagName('p')`
- ☐ `document.getElements('p')`
- ☐ `document.all('p')`

257

Exercise: JS HTML DOM Collections

What is a correct property for returning the number of elements in a collection?

☐ count

☒ length

☐ nth

258

Exercise: JS HTML DOM Collections

True or False.

The first element in a collection has the index 1

☐ True

☒ False

259 dom node list

Exercise: JS HTML DOM Node List

What is a correct syntax for returning all <p> element?

☒ `document.getElementsByTagName('p')`

☐ `document.getElements('p')`

☐ `document.all('p')`

260

Exercise: JS HTML DOM Node List

What is a correct property for returning the number of elements in a Node List?

☐ `count`

☒ `length`

☐ `numberOfItems`

261

Exercise: JS HTML DOM Node List

Only one of the following statements return a Node List. Which one?

☐ `getElementsByClassName()`

☐ `getElementsByTagName`

☒ `querySelectorAll`

262

Exercise: JS HTML DOM Node List

Congratulations!

You completed the JS HTML DOM Node List Exercises from W3Schools.com


Share on:

in

X

f

Close



II. SOLUCIÓN DEL CUESTIONARIO
III. CONCLUSIONES – (A las que llega el grupo respecto a los resultados obtenidos, van relacionadas respecto a los objetivos) Conclusión 1.- Conclusión 2,-

--

RETROALIMENTACIÓN GENERAL

(NO LLENAR – Lo realiza el Docente de Laboratorio en su Informe que se les hace llegar al subgrupo)

REFERENCIAS Y BIBLIOGRAFÍA

(Incluir las principales contempladas en el desarrollo de su Informe.)
--