

PSC4375: Visualizing Distributions

Week 3: Lecture 5

Prof. Weldzius

Villanova University

Slides Updated: 2025-01-27

Studying political efficacy

- 2002 WHO survey of people in China and Mexico

Studying political efficacy

- 2002 WHO survey of people in China and Mexico
- Goal: determine feelings of political efficacy

Studying political efficacy

- 2002 WHO survey of people in China and Mexico
- Goal: determine feelings of political efficacy
- Question: “How much say do you have in getting the government to address issues that interest you?”

Studying political efficacy

- 2002 WHO survey of people in China and Mexico
- Goal: determine feelings of political efficacy
- Question: “How much say do you have in getting the government to address issues that interest you?”
 - 1 No say at all
 - 2 little say
 - 3 some say
 - 4 a lot of say
 - 5 unlimited say

Data

- Load the data:

```
library(tidyverse)
data(vignettes, package = "qss")
head(vignettes)
```

```
##      self alison jane moses china age
## 1      1      5     5     2     0  31
## 2      1      1     5     5     0  54
## 3      2      3     1     1     0  50
## 4      2      4     2     1     0  22
## 5      2      3     3     3     0  52
## 6      1      3     1     5     0  50
```

```
## Also works if you downloaded the data:
# vignettes <- read.csv("data/vignettes.csv")
```

Contingency table

- `count()` shows how many units are in each category of a variable:

```
vignettes %>%  
  count(self)
```

```
##    self    n  
## 1     1 327  
## 2     2 210  
## 3     3 130  
## 4     4  56  
## 5     5  58
```


Contingency table (continued)

- using `group_by` we can convert these counts into proportions of units:

```
vignettes %>%  
  group_by(self) %>%  
  count() %>%  
  ungroup() %>%  
  mutate(prop = n / sum(n))
```

```
## # A tibble: 5 x 3  
##   self      n  prop  
##   <int> <int> <dbl>  
## 1     1    327 0.419  
## 2     2    210 0.269  
## 3     3    130 0.166  
## 4     4     56 0.0717  
## 5     5     58 0.0743
```


Useful way to visualize this information: barplot



Barplots in R

- The `barplot()` function can help us visualize a categorical variable:

```
vignettes %>%  
  ggplot(aes(x = as.factor(self), y = ..prop.., group = 1)) +  
  geom_bar() +  
  scale_x_discrete(labels = c("None", "A little",  
                              "Some", "A lot", "Unlimited")) +  
  xlab("Self-reported political efficacy") +  
  ylab("Proportion of Respondents") +  
  theme_bw()
```

- Arguments:
 - `aes()`: the aesthetic mapping of the plot (what you see)

Barplots in R

- The `barplot()` function can help us visualize a categorical variable:

```
vignettes %>%  
  ggplot(aes(x = as.factor(self), y = ..prop.., group = 1)) +  
  geom_bar() +  
  scale_x_discrete(labels = c("None", "A little",  
                              "Some", "A lot", "Unlimited")) +  
  xlab("Self-reported political efficacy") +  
  ylab("Proportion of Respondents") +  
  theme_bw()
```

- Arguments:
 - `aes()`: the aesthetic mapping of the plot (what you see)
 - `scale_x_discrete()`: changes the scale of the axis

Barplots in R

- The `barplot()` function can help us visualize a categorical variable:

```
vignettes %>%  
  ggplot(aes(x = as.factor(self), y = ..prop.., group = 1)) +  
  geom_bar() +  
  scale_x_discrete(labels = c("None", "A little",  
                              "Some", "A lot", "Unlimited")) +  
  xlab("Self-reported political efficacy") +  
  ylab("Proportion of Respondents") +  
  theme_bw()
```

- Arguments:
 - `aes()`: the aesthetic mapping of the plot (what you see)
 - `scale_x_discrete()`: changes the scale of the axis
 - `xlab()`, `ylab()` are axis labels

Barplots in R

- The `barplot()` function can help us visualize a categorical variable:


```
vignettes %>%  
  ggplot(aes(x = as.factor(self), y = ..prop.., group = 1)) +  
  geom_bar() +  
  scale_x_discrete(labels = c("None", "A little",  
                              "Some", "A lot", "Unlimited")) +  
  xlab("Self-reported political efficacy") +  
  ylab("Proportion of Respondents") +  
  theme_bw()
```

- Arguments:
 - `aes()`: the aesthetic mapping of the plot (what you see)
 - `scale_x_discrete()`: changes the scale of the axis
 - `xlab()`, `ylab()` are axis labels
 - `theme_bw()` removes grey background

Histogram

- **Histograms** visualize density of a continuous/numeric variable

Distribution of Respondent's Age



How to create histograms?

- How to create a histogram by hand:

How to create histograms?

- How to create a histogram by hand: 1. create bins along the variable of interest

How to create histograms?

- How to create a histogram by hand: 1. create bins along the variable of interest 2. count number of observations in each bin

How to create histograms?

- How to create a histogram by hand: 1. create bins along the variable of interest 2. count number of observations in each bin 3. **density** = bin height

$$\text{density} = \frac{\text{proportion of observations in bin}}{\text{bin width}}$$

How to create histograms?

- How to create a histogram by hand: 1. create bins along the variable of interest 2. count number of observations in each bin 3. **density** = bin height

$$\text{density} = \frac{\text{proportion of observations in bin}}{\text{bin width}}$$

- The areas of the bins = proportion of observations in those bins.

How to create histograms?

- How to create a histogram by hand: 1. create bins along the variable of interest 2. count number of observations in each bin 3. **density** = bin height

$$\text{density} = \frac{\text{proportion of observations in bin}}{\text{bin width}}$$

- The areas of the bins = proportion of observations in those bins.
 - \rightsquigarrow area of the blocks sum to 1 (100%)

How to create histograms?

- How to create a histogram by hand: 1. create bins along the variable of interest 2. count number of observations in each bin 3. **density** = bin height

$$\text{density} = \frac{\text{proportion of observations in bin}}{\text{bin width}}$$

- The areas of the bins = proportion of observations in those bins.
 - \rightsquigarrow area of the blocks sum to 1 (100%)
 - Can lead to confusion: height of block can go above 1!

How to create histograms?

- How to create a histogram by hand: 1. create bins along the variable of interest 2. count number of observations in each bin 3. **density** = bin height

$$\text{density} = \frac{\text{proportion of observations in bin}}{\text{bin width}}$$

- The areas of the bins = proportion of observations in those bins.
 - \rightsquigarrow area of the blocks sum to 1 (100%)
 - Can lead to confusion: height of block can go above 1!
 - With equal-width bins, height is proportional to proportion in bin.


Histograms in R

- In ggplot, we use `geom_histogram()`:

```
vignettes %>%  
  ggplot(aes(x = age,  
             y = ..density..)) +  
  geom_histogram(binwidth = 5, # how wide for each bin  
                boundary = 0, # bin position  
                alpha=0.75) + # reduces opaqueness  
  scale_x_continuous(breaks = seq(20, 80, by = 10)) +  
  labs(title = "Distribution of Respondent's Age",  
       y = "Density",  
       x = "Age") +  
  theme_bw()
```

- Other arguments: -`labs` sets the titles for the plot (used `xlab` and `ylab` in previous plot) -`scale_x_continuous` sets the scale for the

Histograms in R: adding a vertical median line




Histograms in R: adding a vertical median line

```
vignettes %>%  
  ggplot(aes(x = age,  
             y = ..density..)) +  
  geom_histogram(binwidth = 5, # how wide for each bin  
                boundary = 0, # bin position  
                alpha=0.75) + # reduces opaqueness  
  geom_vline(xintercept = median(vignettes$age)) +  
  annotate(geom = "text", x = median(vignettes$age),  
         y=.03, label = "Median", hjust = -0.1) +  
  scale_x_continuous(breaks = seq(20, 80, by = 10)) +  
  labs(title = "Distribution of Respondent's Age",  
       y = "Density",  
       x = "Age") +  
  theme_bw()
```

Boxplot

- A **boxplot** can characterize the distribution of continuous variables



Boxplots in R

- “Box” represents range between lower and upper quartile
- “Whiskers” represents either:
 - $1.5 \times \text{IQR}$ or max/min of the data, whichever is smaller
 - Points beyond whiskers are outliers
- Use `geom_boxplot()` in `ggplot`

Boxplots in R

```
vignettes %>%  
  ggplot(aes(y = age)) +  
  geom_boxplot() +  
  scale_y_continuous(breaks = seq(20, 80, by = 10)) +  
  xlim(-.75, .75) +  
  labs(title = "Distribution of Age", y = "Age") +  
  theme_bw() +  
  theme(axis.text.x=element_blank(),  
        axis.ticks.x=element_blank())
```

- Added options:
 - `scale_y_continuous`: scale the y axis
 - `xlim`: alter range of x-axis so box is less wide
 - `theme_bw`: removes grey background
 - `theme`: allows you to adjust other parts of figure

Review

- Visualizing single discrete/categorical variables: **barplots**

Review

- Visualizing single discrete/categorical variables: **barplots**
- Visualizing continuous variables: **histograms, boxplots**