# Dual-Thread Aerators

# **FEATURES AND BENEFITS**

N3210



# **Needle Spray Model** 18 individual streams with

the perfect amount of pressure



#### **Bubble Spray Model**

Air-inducted providing a full stream of bubble spray while using less water



#### Constant Output Regardless of Pressure









#### Finishes & Flow Rates

	1.0 GPM	
Bubble	N3210B-PC	

# **Patented Pressure Compensating Device**

# **Water Savings Without Sacrificing Performance**

- Choose 0.5, 1.0 or 1.5 GPM Water-Saving Flow Rates, Needle Spray or Bubble Spray (only needle spray available on 0.5 GPM)
- 1.0 GPM saves 55% over standard faucets\*
- Dual-thread brass connection, Male: 15/16-27, Female: 55/64-27
- Housing constructed of solid, low-lead brass with high-polished chrome finish
- Niagara's patented pressure compensating technology guarantees a consistent flow rate across wide range of pressure
- Installs easily without tools
- Stylish, modern fits most faucets, works well in both kitchens and baths
- Limited lifetime warranty\*\*

### **POTENTIAL SAVINGS\***

	Water (Gallons)	Electric (kWh)	Gas (therms)	Dollars
Water Savings	3,285			\$26
Energy Savings with Electric Water Heater		482		\$64
Energy Savings with Gas Water Heater			16	\$16

\*Factors in calculating savings potential:

- 3-person households each using a bathroom faucet 2.5 minutes per day, 365 days per year
- Comparing water use with this 1.0 GPM aerator vs. a standard 2.2 GPM unit
- Water and sewer cost of \$8 per 1,000 gallons
- 8.34 BTUs to raise the temperature of 1 gallon 1°
- 500.4 BTUs to raise the temperature of 1 gallon 60° (i.e. 50° to 110° F)
- 1 million BTUs = 293 kWh
- Average cost of electricity \$0.133 per kWh (Bureau of Labor Statistics Sept 2012)
- Average cost of gas \$0.953 per therm (Bureau of Labor Statistics Sept 2012)

## **Corporate HQ**

4200 Diplomacy Road Fort Worth, TX 76155 USA Toll Free: 800.831.8383

Phone: 817.391.0800 Fax: 817.391.0801

Email: info@nccgreen.com


© 2013 Niagara Conservation MSS3205 3104 3210 3215-04




# Dual-Thread Aerators

# **SPECIFICATIONS**


N3215






\*Dimensions are subject to change

#### **Consistent Flow Rate Across Wide Range of Pressure**




0.5 Pressure
Compensated Spray

Non-Pressure
Compensated Spray









#### 1. N3205N-PC is not WaterSense Labeled.

### \*\*WARRANTY FOR AERATORS PURCHASED AT RETAIL:

Limited Lifetime Warranty for aerators purchased at retail for as long as the original purchaser owns the product. Niagara will replace any part that, in our opinion has proved defective, provided it has not been abused, misused, altered or damaged after its purchase.

For complete product warranty details, call Niagara Conservation at 1-800-831-8383.

WARRANTY FOR AERATORS OBTAINED THROUGH WHOLESALE, MUNICIPALITIES, UTILITIES OR OTHER COMMERCIAL CHANNELS:

10-year Limited Warranty to the purchaser from the date of purchase. Niagara will replace any part that, in our opinion has proved defective, provided it has not been abused, misused, altered or damaged after its purchase.

For complete product warranty details, call Niagara Conservation at 1-800-831-8383.

## **Corporate HQ**

4200 Diplomacy Road Fort Worth, TX 76155 USA Toll Free: 800.831.8383

Phone: 817.391.0800 Fax: 817.391.0801

Email: info@nccgreen.com

© 2013 Niagara Conservation MSS3205\_3104\_3210\_3215-04



For more information please visit: www.NiagaraConservation.com

# Dual Spray Swivel Aerator



Our Niagara Conservation branded Dual Spray Swivel Aerator allows for directing the water flow where it's needed most providing greater efficiencies. It offers two stream options: a full force multiple stream and a splash-free bubble stream. The aerator also contains a 360° swivel which helps to reduce water use by directing the water flow where it's needed.

#### **Features**

- Dual threaded
- Fits most male and female threaded faucets, Male: 15/16-27, Female: 55/64-27
- Housing constructed of durable ABS plastic with high-polish chrome finish, does not contain any unplated brass parts
- 10 Year Warrantv\*\*


## Certification and Performance Requirements







Dimensions	



\*Dimensions are subject to change

Model #	Spray	Finish	Flow Rate	Watersense	Case Qty
N3115-P	Aerated Bubble/Needle	Chrome	1.5 GPM	No	200

### Potential Annual Savings<sup>1</sup>

	Flow Rate	Water	Electric Heating	Gas Heating	
Dollar Savings	1.5 GPM	\$51	\$39	\$21	
Utility Savings	1.5 GPM	6,132 Gallons	347 kWh	19 Therms	

1Factors in calculating savings potential:

- 3-person households each person using a faucet 8 minutes per day, 365 days per year (AWWARF Residential Study)
- Comparing water use with these aerator vs. a standard 2.2 GPM unit
- . US city average water and sewer cost of \$8.3 per 1,000 gallons (study done by NUS Consulting Group 2011)
- Average cost of electricity 0.113¢ per kWh (Energy Star Nov. 2013 Lightbulb Calculator — http://www.energystar.gov/?c=cfls.pr\_cfls\_savings)

  Average cost of gas \$1.137 per therm (Bureau of Labor Statistics April 2014)
- · Calculations done by http://www.fishnick.com/savewater/tools/watercalculator

AM Conservation Group, Inc. guarantees to the original purchaser or recipient of an aerator that it is free from defects in material and workmanship for a period of 10 years. AM Conservation Group. Inc. will at our choice replace any part of the aerator which is in our opinion defective provided that the product has not been abused, misused, altered, or damaged after its purchase. This includes damage due to the use of tools or harsh chemicals. In the event a product has been discontinued, AM Conservation Group, Inc. will replace it with what we determine to be the closest product. AM Conservation Group, Inc. is not responsible for labor charges, installation, or other consequential cost. AM Conservation Group, Inc.'s responsibility shall not exceed the original cost of the product.






# arth Handheld Showerhead

N2935









Easy Turn Dial

#### Constant Output Regardless of Pressure





Low Water Pressure

High Water Pressure

#### Finishes & Flow Rates

	2.0 GPM
Chrome	N2935CH
White	

#### **Corporate HQ**

4200 Diplomacy Road Fort Worth, TX 76155 USA Toll Free: 800.831.8383

Phone: 817.391.0800 Fax: 817.391.0801

Email: info@nccgreen.com

© 2013 Niagara Conservation MSS2935-01

## Earth® Showerhead

## **Water Savings Without Sacrificing Performance**

- Three spray settings: 9-jet spray, shower and combo
- Niagara's patented pressure compensating technology guarantees a consistent flow rate across wide range of pressure
- Non-removable flow compensator
- Non-aerated spray means less temperature loss with maximum energy savings
- Steady stream with a large spray diameter
- Corrosion-resistant, high-impact ABS thermoplastic body
- Includes 72-inch tangle-free, high-quality stainless steel hose and mounting bracket
- Installs easily, by hand and without tools
- EPA WaterSense labeled
- Limited lifetime warranty\*\*

#### POTENTIAL SAVINGS\* with 1.5 GPM Model

	Water (Gallons)	Electric (kWh)	Gas (therms)	Dollars
Water Savings	10,959			\$88
Energy Savings with Electric Water Heater		1,607		\$214
Energy Savings with Gas Water Heater			55	\$52

\*Factors in calculating savings potential:


- · 3-person households each using a shower 10 minutes per day, 365 days per year Comparing water use with this 1.5 GPM showerhead vs. a standard 2.5 GPM unit
- Water and sewer cost of \$8 per 1,000 gallons
  8.34 BTUs to raise the temperature of 1 gallon of water 1°
- 500.4 BTUs to raise the temperature of 1 gallon 60° (i.e. 50° to 110°)
- 1 million BTUs = 293 kWh
   Average cost of electricity \$0.133 per kWh (Bureau of Labor Statistics Sept 2012)
- Average cost of gas \$0.953 per therm (Bureau of Labor Statistics Sept 2012)



# Earth Handheld Showerhead


# **SPECIFICATIONS**

N2935



#### **Consistent Flow Rate Across Wide Range of Pressure**

# 1.5 GPM Flow Rate 2.00 1.60 1.60 1.20 0.80 0.80 0.40 0.00 1.5 Pressure (psi) Non-Pressure Compensated Spray Non-Pressure Compensated Spray



Overall Dimensions	Diameter: 2.688" Length: 8.6"
Materials	Body: Chrome plated ABS plastic or white color durable ABS plastic
	Bracket Ball Joint: White color durable ABS plastic or chrome plated ABS thermoplastic
	Internal Parts: Chrome plated brass, ABS and POM plastics & high heat rubber gaskets and pressure compensator
	Hose: 72" (183.9 cm) nylon reinforced PVC hose with durable chrome-plated or white color BS connectors
Threads	Inlet size: 1/2-14 NPSM female straight pipe thread
Certifications	Meets or exceeds: ASME A112.18.1 / CSA B125.1; ANSI/NSF 61 WaterSense labeled



Item Number	Max. Flow Rate	Min. Flow Rate @ 45psi				
N2945	Max. 1.5 GPM (5.7 LPM)	Min. 1.13 GPM (4.3 LPM)				
N2945CH	Max. 1.5 GPM (5.7 LPM)	Min. 1.13 GPM (4.3 LPM)				
N2935CH	Max. 2.0 GPM (7.6 LPM)	Min. 1.5 GPM (5.7 LPM)				

Niagara will replace any part that, in our opinion has proved defective, provided it has not been abused, misused, altered or damaged after its purchase.

For complete product warranty details, call Niagara Conservation at 1-800-831-0800.

#### **Corporate HQ**

4200 Diplomacy Road Fort Worth, TX 76155 USA Toll Free: 800.831.8383

Phone: 817.391.0800 Fax: 817.391.0801

Email: info@nccgreen.com

© 2013 Niagara Conservation MSS2935-01



<sup>\*\*</sup>WARRANTY FOR SHOWERHEADS OBTAINED THROUGH WHOLESALE, MUNICIPALITIES, UTILITIES OR OTHER COMMERCIAL CHANNELS:

<sup>10-</sup>year Limited Warranty to the purchaser from the date of purchase.

	SPECIFICATIONS N						D					
	AC RATING					125V/60HZ						
	HOUSING					ABS Plastic						
	COLOR					White						
			LIGHT I	PIPE REFLECTO	R /	Acrylic o	r Crys	tal Styre	ne			
				LE		mm						
				OUTPU		).5W						
				COLO		Cool Wh						
				PHOTOCEL			ssive F	Photo-Re	sistor			
		0'	VERLO/	AD PROTECTIO	_	N/A						
				SWITC		No						
				AC PLUG STYL				ght Angle	<del>.</del>			
				CKAGING STYL		Sealed Po	olybag	g				
		DAD COD		ARRANTY SHEE		N/A						
		BAK COD		ON CASE PAC		BD O Bos - I	Macta	r Carton				
	c-	LVNUVBU EA		CARTON DESIG		es	iviaste	: Carton				
	3			CERTIFICATION		-UL-us						
		Α.	JE: VOI (	CERTIFICATION	-	, <b>UL</b> U3						
	Г											
BITS#	NL-CL4DD	Unit		Unit Dims (cr	n)	Inner Qty. Inner Carton Dims (cm)			(cm)	G. W		
		Polybag	L	W	Н	р	CS	L	W	Н	Cube	KGS
DESC	CRIPTION	1	10	4.3	2.7	-	-	-	-	-	-	-
		Unit		Unit Dims (in)			ster rton	Master Carton Dims (cm)		G.W.		
		Polybag	L	W	Н	р	cs	L	W	Н	Cube	KGS
		1	4	1.63	1	5	50	24.9	24.4	12.7	0.0085	1.7
is the state of th		CONTAIN 20'	IER -	QTY	TBD		ner ty.	In	ner Car	ton Dim	s (in)	G.W.
			IER -	QTY		pe	)CS	L	W	Н	Cube	LBS
							-	-	-	-	-	-
			Dusk-to-Dawn Night Light with				ster rton	I Master (arton Dims (in) I (a )			G.W.	
				l Styrene Light		р	CS	L	W	Н	Cube	LBS
				eflector	•		50	9.8	9.6	5.5	0.3	3.75