Shell Scripting Set 1

Rwithik Manoj

March 18, 2019

- 1. Write a shell script to show various system configuration like
 - (a) Currently logged user and his login name
 - (b) Your current shell
 - (c) Your home directory
 - (d) Your operating system type
 - (e) Your current path setting
 - (f) Your current working directory
 - (g) Number of users currently logged in

#!/bin/bash

```
echo -e "Current User : $USER (Login Name: $LOGNAME)"
echo -e "Current Shell : $SHELL"
echo -e "Home Directory : $HOME"
echo -e "OS Type : $OSTYPE"
echo -e "Path : $PATH"
echo -e "Current Working Directory : $PWD"
echo -e "Number of Users Logged in : `who | wc -l`"
```

- 2. Write a shell script to show various system configurations like
 - Your OS and version, release number, kernel version
 - All available shells
 - Computer CPU information like processor type, speed etc
 - Memory information
 - Hard disk information like size of hard-disk, cache memory, model etc
 - File system (Mounted)

#!/bin/bash

```
echo -e "OS Details: `uname -a`\n"
echo -e "Available Shells"
echo -e "------"
cat /etc/shells | grep -e "^/"
echo -e "\nCPU Info"
echo -e "------"
lscpu | grep "Architecture\|Model name\|MHz"
echo -e "\nMemory Info"
echo -e "------"
free -mh
echo -e "\nHard Disk Info"
echo -e "\nHounted Filesystems"
echo -e "\nMounted Filesystems"
echo -e "------"
lsblk
```

```
### Architecture: x86_64
Model name: Intel(R) Core(TM) i3-7100U CPU @ 2.40GHz
CPU MHz: 666.149
CPU min MHz: 400.0000

Memory Info

total used free shared buff/cache available
Mem: 3.66i 1.36i 1.36i 84Mi 1.16i 2.06i
Swap: 7.66i 3.0Mi 7.66i

Hard Disk Info

Filesystem 1K-blocks Used Available Use% Mounted on dev 1904660 0 1904660 0 % /dev run 191248 1252 1911296 1% /run
/dev/sda2 78218924 14127908 60074632 20% /
```

- 3. Write a shell script to implement a menu driven calculator with following functions
 - (a) Addition
 - (b) Subtraction
 - (c) Multiplication
 - (d) Division
 - (e) Modulus

```
#!/bin/bash
echo -e "Enter the operator:\n\
               + for addition\n\
                - for subtraction\n\
                * for multiplication\n\
                / for division\n\
                % for modulus"
read CHOICE
if [[ $CHOICE == '+' ]] || [[ $CHOICE == '-' ]]\
                || [[ $CHOICE == '*' ]] || [[ $CHOICE == '/' ]]\
                || [[ $CHOICE == '%' ]]
then
        echo -e "Enter two numbers:"
        read A
        read B
        echo -e "Result: $[${A}${CHOICE}${B}]"
else
        echo -e "Invalid Choice"
fi
```

- 4. Write a script called addnames that is to be called as follows ./addnames ulist username. Here ulist is the name of the file that contains list of user names and username is a particular student's username. The script should
 - (a) Check that the correct number of arguments was received and print a message, in case the number of arguments is incorrect
 - (b) Check whether the ulist file exists and print an error message if it does not
 - (c) Check whether the username already exists in the file. If the username exists, print a message stating that the name already exists. Otherwise, add the username to the end of the list.

```
rwithik@Zeus foss-lab/Scripts (master *%)
» ./Expt7.sh
Wrong usage!
rwithik@Zeus foss-lab/Scripts (master *%)
» ./Expt7.sh ulist rwithik
rwithik@Zeus foss-lab/Scripts (master *%)
» ./Expt7.sh ulist rwithik
Name already exists in list!
rwithik@Zeus foss-lab/Scripts (master *%)
» ./Expt7.sh ulist rahul
rwithik@Zeus foss-lab/Scripts (master *%)
» ./Expt7.sh ulist rahul
rwithik@Zeus foss-lab/Scripts (master *%)
» ./Expt7.sh ulist rahul
```

5. Write a Shell script which starts on system boot up and kills every process which uses more than a specified amount of memory or CPU. Script:

```
#!/bin/bash
CHECK_MEM_VAL=10.0
CHECK_CPU_VAL=10.0
while true
do
        ps -e -o pmem=,pcpu=,pid=,user=,comm= --sort=-pmem \mid
          while read SIZE CPU PID USER COMM
          do
            KILL_MEM=0
            KILL_CPU=0
            if [ "$USER" != "root" ]
              if [ `echo "$SIZE>$CHECK_MEM_VAL" | bc` = "1" ]
              then
                       echo "kill $COMM due to mem usage"
                kill $pid
              elif [ `echo "$CPU>$CHECK_CPU_VAL" | bc` = "1" ]
                echo "kill $COMM due to cpu usage"
                kill $pid
              fi
            fi
        done
        sleep 10
done
```

```
rwithik@Zeus foss-lab/Scripts (master *%)
» ./Expt8.sh
kill Web Content due to mem usage
kill firefox due to mem usage
```