ALUCA – TECHNICAL SOUND RIDER

SOUND

• PA system suitable for the venue and expected audience capacity, high-end range (D&B;, L'Acoustics, TW Audio, Nexo, Adamson or equivalent). The system must be properly tuned by a qualified person before soundcheck.

• If a sound limiter is inserted in the system, it must be installed before soundcheck.

• Digital PA mixing console with a minimum of 8 channels: Allen & Heath SQ series, Yamaha CL, Midas Pro, Midas HD96, Midas M32. The mixing console must be centered with respect to the stage and at the same height as the audience.

• No monitor mixing console is required. Monitors will preferably be mixed from FOH control.

• 4x stage monitors arranged as sidefills (with speaker stands): 2 at the front of the stage and 2 halfway along the stage, one on each side. (D&B; E8, E12, NEXO PS10, P12 or equivalent).

• 1 assistant sound technician at FOH is required.

• 3x wireless headset systems: Sennheiser EW, EWD, Shure QLXD, Axient, with DPA4066 (omnidirectional) microphone bodypack.

• A detailed counter-rider must be sent sufficiently in advance, indicating the PA system, PA mixing console and microphone alternatives (if applicable), to allow sufficient room for adjustments.

MONITOR AUX SENDS

AUX 1	Stage front L. Sidefill monitor with speaker stand.
AUX 2	Stage front R. Sidefill monitor with speaker stand.
AUX 3	Mid-stage L. Sidefill monitor with speaker stand.
AUX 4	Mid-stage R. Sidefill monitor with speaker stand.

CHANNEL AND MICROPHONE LIST

CH	INSTRUMENT	MIC / DI
1	Voice 1	DPA 4066 (omni), wireless
2	Voice 2	DPA 4066 (omni), wireless
3	Voice 3	DPA 4066 (omni), wireless
4	Table percussion	Shure B91