

Image-Informed Urban Propagation and Route-Level Body Exposure Across Ten Cities at 15 GHz

ROBIN WYDAEGHE¹, GÜNTER VERMEEREN¹, (Member, IEEE), EMMERIC TANGHE¹, (Member, IEEE), and WOUT JOSEPH¹, (Senior Member, IEEE)

¹Department of Information Technology, Ghent University/IMEC, 9052 Ghent, Belgium (e-mail: robin.wydaeghe@ugent.be)

Corresponding author: Robin Wydaeghe (e-mail: robin.wydaeghe@ugent.be).

ABSTRACT Street-level radiofrequency exposure varies along a pedestrian route because buildings change the direct and reflected fields, surface materials affect how much power returns to the street, and the human body absorbs differently depending on the direction of arrival. This study projects 360-degree street images onto a photogrammetric city mesh to identify surface materials along pedestrian routes at 15 GHz. Transmitters are placed along the visible roofline in proportion to its physical length. All results are normalized per unit product of areal source density and effective isotropic radiated power (EIRP). The transport model treats direct paths and one specular reflection exactly, estimates one diffuse reflection, and stops. The arriving fields and their directions are then applied to a 56,024-element Duke body model. A geometric fixed-grid diagnostic covers ten urban locations in Europe, Latin America, and East Asia and finds a twofold span in location-median whole-body SAR. Five of these locations are then studied with image-derived materials along fixed pedestrian routes containing 73 observation points, each calculated with 16 independent replicas of 200,000 primary rays and 4,096 angular output cells. In a controlled test scene, the adjoint estimate and deterministic quadrature differ by at most 0.0616 dB for the reflected term. An independent forward tracer gives a maximum difference of 0.0344 dB. Route-median whole-body specific absorption rate differs by a factor of 13.34 across the five routes. Direct paths carry the largest share at all 67 points with line of sight, while the diffuse reflection is the only nonzero modeled contribution at six fully shadowed points. The maximum change from 12 to 16 replicas is 0.0436 dB, though lower-tail estimates in Mexico City and Tokyo are less stable. These results describe ten fixed-grid locations and five selected routes under a fixed model and do not estimate city-wide or deployed-network exposure.

INDEX TERMS Body dosimetry, image-informed propagation, ray tracing, street imagery, urban propagation, whole-body specific absorption rate.

I. INTRODUCTION

As wireless networks expand into higher frequency bands, the built environment plays a larger role in determining the radiofrequency field that reaches a pedestrian [1]. Along a city street, received power can change over a few meters. A person walking past a row of buildings can move from a clear view of a rooftop transmitter into a shadow where buildings block the direct field and only reflected power reaches the street. The facade materials then determine how much power returns to the street [1], [2]. This variation also matters after the field arrives: whole-body absorption depends on the direction of arrival and on how the body is oriented, so a single power value at a single point does not describe exposure along a walking route. A route-level calculation

must keep the arrival direction until the field is applied to the body [3].

Ray tracing computes detailed propagation paths between transmitters and receivers in a three-dimensional city model [4]. It has been used for city-scale downlink exposure using published base-station locations [5], and to compute propagation and body exposure along an outdoor pedestrian path [6]. Stochastic geometry models describe exposure when individual transmitter locations are not known [7], while pre-computed body coefficients separate the incident field from the absorption calculation [8]. Together, these studies cover deterministic urban propagation, spatial source models, and the directional absorption step that converts the arriving field into absorbed power on the body. Because they use different

source assumptions, their reported exposure values are not directly comparable without a common source normalization.

A photogrammetric city mesh gives accurate building geometry, but its triangles carry no material information. Street-level images can fill that gap. The Mapillary Vistas dataset provides a taxonomy for dense segmentation of street scenes [9]. Kamari *et al.* segment street-level images, project the resulting material classes onto city geometry, and use that geometry in millimeter-wave ray tracing [10]. Xia *et al.* use semantic point-cloud classification and detailed scene reconstruction for outdoor ray tracing at 2.8 GHz [11]. Projecting image-derived materials onto city geometry is therefore established. This study does not claim any of these operations as new. It uses them to build a material map around fixed pedestrian routes, keeping the default geometry-based material wherever the images give no reliable label.

This study combines these established parts in one fixed model. Each 360-degree street image is aligned with the same photogrammetric city mesh used for ray tracing, and the image labels are projected onto that mesh to produce a material map. A common transmitter model distributes sources along the visible roofline at every site. Rooflines are a natural choice: they are elevated, street-facing, and visible from the route. Distributing transmitters in proportion to roofline length avoids tying the result to any particular deployment. The ray tracer keeps the direct, specular, and diffuse components separate, preserving their arrival directions, until the field is applied to the body. The transport model treats direct paths and one specular reflection exactly, estimates one diffuse reflection, and stops there. The route points are fixed case studies, not a population sample, and the roofline transmitters are a model, not a measured deployment. To the best of the authors' knowledge, prior work has not combined aligned 360-degree street images, a common roofline transmitter model, and separate transport components with their arrival directions in a single route-level body exposure calculation.

This study applies the method at 15 GHz across ten urban locations. A geometric fixed-grid diagnostic first characterizes all ten locations with geometry-based materials and a fixed body orientation. Five of these locations are then studied with image-derived materials along fixed pedestrian routes containing 73 observation points. Every result is normalized per unit active-source areal density and per unit effective isotropic radiated power (EIRP). The route-median whole-body SAR values differ by a factor of 13.34 across the five routes. These results describe fixed-grid locations and fixed routes under one source and transport model. They do not estimate population exposure or deployed-network exposure.

This work makes the following three contributions.

- 1) Aligned 360-degree street images supply traceable material labels to the same city mesh used for ray tracing. Surfaces without a reliable image label keep their geometry-based material.
- 2) A roofline transmitter model and transport calculation keep direct, specular, and diffuse power separate, with

TABLE 1. Five fixed routes with observation-point counts, route spans, and computation times

Site	Route points	Route span (m)	Wall time (s)
Ghent	10	49.04	29.79
Prague	22	119.39	69.02
Madrid	14	73.47	40.70
Mexico City	11	60.79	30.92
Tokyo Hachiko	16	87.38	50.11
Total	73	390.07	220.54

arrival directions, until the field is applied to the body.

- 3) An application across ten urban locations and five detailed pedestrian routes reports geometric screening, fixed-route exposure distributions, controlled first-diffuse validation, replica convergence, and the retained transport at the six observation points where buildings block all direct and specular paths.

II. METHOD

A. STUDY CONFIGURATION

Fig. 1 shows the study configuration. A 360-degree street image is aligned with a photogrammetric city mesh cropped to a 250 m radius around the route. Object and material labels from the image are projected onto the visible mesh triangles without changing their geometry. The roofline visible from the route gives the possible transmitter locations. Fixed points along the pedestrian route give the observation positions, and the anatomical body model faces along the direction of travel at each point.

Table 1 lists the five selected routes. Each route follows a connected street corridor covered by aligned 360-degree street images. The calculation places fixed observation points along that corridor, including interpolated positions between image locations, so the number of images and the number of observation points can differ. The 73 route points are fixed observations, not a random sample of pedestrians or places. The body model faces along the direction of travel, so a different route would change both position and orientation.

Two image-analysis models work in sequence. Mask2Former assigns a Vistas object class (building, road, vegetation, etc.) to every image pixel [9], [12]. SAM 3 then tests material and vegetation labels inside the compatible object regions [13]. Both sets of labels are projected onto the visible city mesh using the known camera position and viewing direction. Where multiple images cover the same triangle, the labels are combined into one material map, and every mapped triangle stays linked to its source image. A mesh triangle changes material only when the object and material labels agree and pass the acceptance tests. All other triangles keep their default material. The prompts, alignment tests, rejected labels, and mapping rules are given in the supplementary material.

Fig. 2 shows the computation and its input checks. A hash-verified manifest lists every input file: aligned images, material map, city mesh, route, roofline, body model, and transport settings. Only files whose hashes match the manifest enter




FIGURE 1. Study configuration at Prague Old Town Square. (a) A 360-degree street image is segmented, projected onto the city mesh, and converted to the material map used for ray tracing. (b) The 22 observation points and the visible roofline on a plan view. (c) Close-up of the route. The arrow shows the body model's direction of travel.

the five-site data set. The transport calculation keeps direct, specular, and diffuse contributions separate until the field is applied to the body. The five manifests contain 210 verified entries. Across the resulting 1,168 directional body fields, the largest residual when the three components are summed back to the stored total is $1.735 \times 10^{-18} \text{ m}^{-2}$.

B. EXPOSURE CALCULATION

The calculation uses a fixed route, city mesh, material map, and roofline transmitter model. Every route point uses 15 GHz and a crop with radius $R_{\text{crop}} = 250 \text{ m}$, which gives $A_{\text{crop}} = \pi R_{\text{crop}}^2 = 196,349.54 \text{ m}^2$. The receiver position $\mathbf{x}$ is the ray origin and body reference point. The body model faces along the local direction of travel. Index i denotes a roofline segment, $r_i(\mathbf{x})$ is its range to the receiver, and $\mathbf{r}$ is a position on the body surface. These assumptions are fixed across replicas and sites.

The exact positions of future transmitters are unknown,

but elevated rooflines are plausible street-facing locations. The model therefore distributes the expected transmitters uniformly per unit physical length of the roofline visible from the route. Let ρ_A be the expected active-site density and let A_{crop} be the crop area. For a roofline segment with endpoints $\mathbf{p}_i$ and $\mathbf{p}_{i+1}$, ℓ_i is its physical three-dimensional length. The expected number of transmitters and the fraction assigned to segment i are

$$N_{\text{site}} = \rho_A A_{\text{crop}}, \quad p_i = \frac{\ell_i}{\sum_j \ell_j}, \quad \ell_i = \|\mathbf{p}_{i+1} - \mathbf{p}_i\|_2. \quad (1)$$

Thus, N_{site} sets the number of transmitters and p_i assigns a fraction of that number to segment i . Dividing by the total roofline length ensures that splitting one segment into smaller numerical pieces does not add transmitters. The baseline uses three-dimensional length rather than horizontal projected length.

An unobstructed reference separates the source density




FIGURE 2. Flowchart of the computation and input checks. Aligned 360-degree street images and the city mesh give the material map. The fixed route and visible roofline give observation and transmitter positions. Transport retains direct, first-order specular, and first-diffuse terms. A hash-verified file list pins every input to the five-site result.

from the scene geometry. The reference sums the inverse-square contribution of every roofline segment:

$$D_{\text{ref}}(\mathbf{x}) = \sum_i \frac{p_i}{r_i(\mathbf{x})^2}, \quad S_{\text{ref}}(\mathbf{x}) = \frac{A_{\text{crop}} D_{\text{ref}}(\mathbf{x})}{4\pi}. \quad (2)$$

No visibility test enters D_{ref} . All reported quantities are normalized per unit $\rho_A P_{\text{EIRP}}$. Multiplication by $\rho_A P_{\text{EIRP}}$ recovers physical units, but only for a deployment that follows the same roofline transmitter model. The calculation omits transmitters and interactions outside the crop.

The propagation result at each observation point has direct, one-reflection specular, and one-reflection diffuse parts. Let $\mathcal{D}$ contain the visible direct paths, and let $\mathcal{S}_1$ contain the accepted one-reflection specular paths. Their normalized powers are $\alpha_a = m_a^{(d)}/D_{\text{ref}}$ and $\beta_b = m_b^{(s)}/D_{\text{ref}}$. The diffuse estimate uses normalized angular-cell powers $\hat{\gamma}_q = \hat{m}_q^{(f)}/D_{\text{ref}}$. With $\delta_{\hat{\mathbf{k}}}$ denoting a unit point mass in physical arrival direction $\hat{\mathbf{k}}$, the directional distribution is

$$\begin{aligned} \mu_{\mathbf{x}} = & \sum_{a \in \mathcal{D}} \alpha_a \delta_{\hat{\mathbf{k}}_a^{(d)}} \\ & + \sum_{b \in \mathcal{S}_1} \beta_b \delta_{\hat{\mathbf{k}}_b^{(s)}} \\ & + \sum_{q=1}^Q \hat{\gamma}_q \delta_{\hat{\mathbf{k}}_q^{(f)}}, \quad Q = 4096. \end{aligned} \quad (3)$$

The first two sums retain the exact directions and powers of the direct and specular paths. They are not projected onto the angular grid. Only diffuse power is accumulated in the Q Fibonacci cells. Rays start at the receiver and travel outward to the first blocking surface, as shown in Fig. 3. Next-event estimation then tests visibility from that surface to every roofline segment [14]. The material model combines unpolarized Fresnel power with a Rayleigh roughness term. The remaining power enters a Lambertian diffuse term, and the components add incoherently. The sampled path ends after this diffuse reflection, and the calculation omits further specular reflections. Woody vegetation identified in the material map does not block rays because the city mesh has no canopy volume. The supplementary material gives the full laws and parameter values.

The arrival directions are carried through to the body. For outward body-surface normal $\hat{\mathbf{n}}(\mathbf{r})$, define $g(\mathbf{r}, \hat{\mathbf{k}}) = [\hat{\mathbf{n}}(\mathbf{r}) \cdot (-\hat{\mathbf{k}})]_+$. The normalized absorbed power density is

$$\begin{aligned} \tilde{S}_{\text{ab}}(\mathbf{r}, \mathbf{x}) & \equiv \frac{S_{\text{ab}}(\mathbf{r}, \mathbf{x})}{\rho_A P_{\text{EIRP}}} \\ & = T_0 S_{\text{ref}}(\mathbf{x}) \left[\sum_{a \in \mathcal{D}} \alpha_a g(\mathbf{r}, \hat{\mathbf{k}}_a^{(d)}) \right. \\ & \quad + \sum_{b \in \mathcal{S}_1} \beta_b g(\mathbf{r}, \hat{\mathbf{k}}_b^{(s)}) \\ & \quad \left. + \sum_{q=1}^Q \hat{\gamma}_q g(\mathbf{r}, \hat{\mathbf{k}}_q^{(f)}) \right]. \end{aligned} \quad (4)$$

Here, T_0 is the normal-incidence power-transmission coefficient from the IT'IS tissue database at 15 GHz [15]. It approximates the absorption cross section for incoherent, unpolarized illumination. The function g sets the absorbed fraction to zero where the surface faces away from the incoming direction. The calculation applies this directional absorption to the 56,024-element Duke anatomical mesh [16]. Because all quantities are normalized by $\rho_A P_{\text{EIRP}}$, $\tilde{S}_{\text{ab}}$ is dimensionless. For the triangle area A_r at position $\mathbf{r}$ and body mass m_{body} , the normalized integrated quantities are

$$\begin{aligned} \tilde{P}_{\text{abs}}(\mathbf{x}) & \equiv \frac{P_{\text{abs}}(\mathbf{x})}{\rho_A P_{\text{EIRP}}} \\ & = \sum_{\mathbf{r}} A_r \tilde{S}_{\text{ab}}(\mathbf{r}, \mathbf{x}), \\ \widetilde{\text{SAR}}_{\text{wb}}(\mathbf{x}) & \equiv \frac{\text{SAR}_{\text{wb}}(\mathbf{x})}{\rho_A P_{\text{EIRP}}} \\ & = \frac{\tilde{P}_{\text{abs}}(\mathbf{x})}{m_{\text{body}}}. \end{aligned} \quad (5)$$

$\tilde{P}_{\text{abs}}$ has units m^2 , and $\widetilde{\text{SAR}}_{\text{wb}}$ has units $\text{m}^2 \text{kg}^{-1}$.

Each replica launches 200,000 independent and identically distributed primary rays per route point and accumulates first-diffuse power in 4,096 fixed Fibonacci output cells. Exact direct and specular paths bypass this grid. The output cells do not control the launch directions. The calculations use 16 replicas with seeds 7 through 22 and retain cumulative results after 4, 8, 12, and 16 replicas. Only the first-diffuse estimate varies between replicas. Scalar quantities and body fields are averaged across replicas before route statistics are computed. Route quantiles use linear interpolation over equally weighted




FIGURE 3. Forward and adjoint sampling for the first-diffuse term. (a) A forward calculation launches rays from every roofline segment toward the observation point. (b) The adjoint calculation launches rays once from the observation point. At the first blocking surface, connections to every visible roofline segment are tested.

route points, and the plotted empirical distributions use positions $(\text{rank} - 0.5)/n$. Multipath surplus is computed only where direct transfer is positive. A route point with zero direct transfer remains in the whole-body SAR distribution but has no finite surplus value.

III. RESULTS

Table 1 defines the five fixed routes and their 73 observation points. Every site uses 15 GHz and a photogrammetric city mesh cropped to a 250 m radius. The Duke body model has 56,024 surface elements and a mass of 72.4 kg, and faces along the direction of travel. Each point has 16 independent replicas with seeds 7 through 22. Each replica uses 200,000 primary rays and 4,096 fixed Fibonacci output cells for the first-diffuse term. The resulting 1,168 body fields contain 233.6 million primary rays. Calculation time for a prepared site ranges from 29.79 to 69.02 s on one A6000 GPU. These times exclude image acquisition, alignment, depth estimation, and material mapping because the full preparation time was not recorded.

The calculation manifests list 42 files per site, and all 210 file hashes pass verification. The direct, exact order-1 specular, and first-diffuse fields sum to the stored total with a maximum absolute residual of $1.735 \times 10^{-18} \text{ m}^{-2}$ across all 1,168 fields. The GPU body-coupling result also agrees with the double-precision CPU reference to a maximum relative difference of 6.64×10^{-16} in the verified benchmark. These checks confirm the input files, addition of components, and agreement between CPU and GPU calculations. They do not externally validate the complete city model.

The direct and specular paths are computed from exact geometry, but the first-diffuse estimate depends on random ray sampling. The controlled comparison in Fig. 4 tests this stochastic component before the city results. The open-square scene has 27 sources, 6 receivers, 8 triangles, and one diffuse reflection. It has no specular reflection, refraction, or diffraction. Deterministic surface quadrature uses 2,097,152 samples. The adjoint estimate uses 50,000 primary rays for

each of four seeds. An independent Sionna RT forward calculation uses 50,000 samples per source for each of three seeds. The maximum difference between the adjoint estimate and quadrature is 0.0616 dB for the reflected term. A separate test of total transport gives a maximum adjoint-to-Sionna difference of 0.0344 dB. Fig. 4 plots the one-reflection transfer and its error relative to quadrature, not the total-transport test. The comparison checks first-diffuse normalization, visibility, inverse-square loss, and cosine terms in this one-reflection scene. It does not cover the image-derived material map, exact specular transport, or their combination in a city.

Fig. 5 shows the fixed-route empirical distributions. Table 2 gives the central summaries and finite multipath surplus. Normalized whole-body SAR is reported in $\text{m}^2 \text{ kg}^{-1}$ per unit $\rho_A P_{\text{EIRP}}$. A physical whole-body SAR value therefore requires multiplication by the deployment's areal source density and EIRP. The figure includes all 73 observation points and marks the six with zero direct and zero order-1 specular transfer. The largest route median is 13.34 times the smallest. Mexico City and Tokyo Hachiko have the widest spread along a route and the lowest tails.

The additive component shares of route-mean whole-body SAR are shown in the supplementary material. Direct transport is the largest contribution at all 67 points with line of sight. Exact order-1 specular transport is never the largest. Mexico City points 0, 1, and 3 and Tokyo Hachiko points 13, 14, and 15 have zero direct and zero order-1 specular transport. First-diffuse transport is the only nonzero contribution at these six points. Across all 73 points, the pooled component medians are 77.662% direct, 21.391% exact order-1 specular, and 0.419% first diffuse. They do not sum to 100% because each component has a separate median over the 73 route points. The small first-diffuse median therefore does not describe the six fully shadowed points.

The path audit assigns each retained material interaction to an image-mapped or geometry-based surface. Pooled over the five routes and 16 seeds, image-mapped surfaces account for 75.903% of the reflected SAR. The corresponding shares are




FIGURE 4. Controlled validation of the first-diffuse transfer. (a) Deterministic surface quadrature, the adjoint estimate, and the independent Sionna RT forward calculation at six receivers. (b) Signed error relative to quadrature. Error bars give the standard error across four adjoint seeds and three Sionna seeds.

TABLE 2. Fixed-route exposure summary. Whole-body SAR quantiles are normalized per unit $\rho_A P_{\text{EIRP}}$ and have units $\text{m}^2 \text{ kg}^{-1}$. Surplus is computed only at points with nonzero direct transfer. The last column is the maximum pointwise total-transfer change from 12 to 16 replicas.

Site	q_{10}	q_{50}	q_{90}	Median surplus [dB]	Zero direct and order-1 specular	Max total-transfer change [dB]
Ghent	0.057833	0.062045	0.068672	1.108	0	0.0000819
Prague	0.012157	0.013073	0.014594	1.061	0	0.0001559
Madrid	0.020913	0.022381	0.023171	1.534	0	0.0004083
Mexico City	9.92×10^{-7}	0.129062	0.295798	0.721	3	0.043625
Tokyo Hachiko	3.66×10^{-5}	0.009674	0.025200	0.828	3	0.019732




FIGURE 5. Normalized whole-body SAR on the five fixed routes. Empirical CDFs include all 73 route points. Hollow triangles mark the six points with zero direct and zero order-1 specular transfer. The routes are fixed case studies, not city or population samples.

80.643% for exact order-1 specular transport and 13.337% for first-diffuse transport. The supplementary material gives the complete split by material source.

The nested 12-to-16-replica comparison separates the route median from the lower tail. Every route-median whole-body SAR changes by at most 5.90×10^{-5} dB. The largest lower-decile changes are 0.032226 dB in Mexico City and 0.017636 dB in Tokyo Hachiko. The maximum pointwise total-transfer changes in Table 2 reach 0.043625 and 0.019732 dB at these two sites. At 16 replicas, the 90th-percentile total-transfer standard errors are 0.1461 dB in Mexico City and 0.0310 dB in Tokyo Hachiko. The route medians are stable at 16 replicas.

A separate calculation reuses the first 16 replicas and extends every route through 64 replicas. Between 48 and 64 replicas, the whole-body SAR q_{10} changes by 0.00344 dB in Mexico City and 0.00491 dB in Tokyo Hachiko. The largest change among their six fully shadowed route points is 0.0125 and 0.0104 dB. Both lower tails remain stable through 64 replicas. In Mexico City, the single strongest diffuse replica at one shadowed point carries 5738 times the median replica contribution. This result is specific to the fixed routes and excludes route-selection and city-sampling uncertainty. The complete nested comparison is given in the supplementary material.

A paired control for Madrid and Mexico City replaces all image-mapped materials with the default geometry-based materials while keeping the mesh, route, roofline model, body, seeds, sampling budget, and transport steps identi-

cal. Each reported change is $10 \log_{10}(x_{\text{image}}/x_{\text{geometry}})$. At Madrid the image-to-geometry changes in normalized whole-body SAR are +0.233, +0.249, and +0.269 dB for q_{10} , q_{50} , and q_{90} . At Mexico City the corresponding changes are +24.84, −0.158, and +0.104 dB. The large q_{10} change comes from the three fully shadowed points, where both totals are near zero and first-diffuse transport is the only nonzero contribution. The direct term is identical in every pair. At Madrid, the image-derived map changes the route-median specular component by +1.89 dB and the first-diffuse component by −12.43 dB, but the total median changes by only +0.249 dB. This control tests the complete material map, including its parameters and the treatment of woody vegetation as nonblocking. It does not measure material accuracy or isolate reflectance alone. The supplementary material gives pointwise and component-level comparisons.

IV. DISCUSSION

The ten-location geometric screening shows a twofold span in location-median whole-body SAR across locations that differ in street width, building height, and roofline visibility. The factor of 13.34 between the largest and smallest route medians on the five detailed routes is much larger, reflecting the additional variation from image-derived materials, canopy, and route-specific visibility conditions. Each empirical distribution therefore describes only that fixed route and its observation points.

The first-diffuse component is small at most points (0.419% pooled median), but it is the only nonzero contribution at the six fully shadowed points. Its small share where line of sight exists does not make it dispensable where buildings block all direct and specular paths. A transport model that omits the diffuse term would assign zero exposure to those six positions.

The paired material control tests the effect of image-derived materials on the body results. The direct term is identical in both cases, so all observed changes come from the materials used by the reflected and diffuse terms. In Madrid, the specular and first-diffuse component changes have opposite signs, while the route-median normalized whole-body SAR changes by only 0.249 dB. The Mexico City route median changes by −0.158 dB. Its much larger lower-tail ratio comes from the three fully shadowed route points where both estimates are close to zero, not from a central effect. The paired cases differ in their assigned materials and in their treatment of woody canopy. The image-derived case treats identified canopy as transparent because the city mesh has no canopy volume. The comparison therefore measures sensitivity to both the material assignment and the vegetation rule together, and does not establish material accuracy on its own.

Several limits restrict what the results can say. The geometric fixed-grid diagnostic covers ten locations with geometry-based materials and a fixed body orientation. The five detailed routes add image-derived materials and a body facing along the walk. Both tiers use the same frequency (15 GHz),

source model, and transport model. Results are normalized per unit areal source density and EIRP. Scaling to a specific deployment is valid only if its transmitter positions follow the assumed roofline model. The transport model stops after one diffuse event and omits all later interactions and higher-order specular paths. The controlled comparison validates the first-diffuse component in a one-reflection scene. It does not validate the city calculations, which also use image-derived materials and exact specular transport. The 16 replicas quantify estimator randomness but not uncertainty in image-to-mesh alignment, geometry, material labels, route choice, transmitter placement, body shape, or body orientation. The five-site computation takes less than 70 s per prepared site on the tested GPU, but image acquisition and material mapping take longer and do not yet have a complete timing record.

The first priority is source calibration and end-to-end validation of the city calculation against outdoor field measurements of the directional field before body coupling. Second, higher specular orders and paths beyond the first diffuse event can be added through paired studies that report their change in whole-body SAR, variance, and computation time. Third, several routes at the same site can quantify route-selection variation beyond the current ten locations. Other frequencies, body models, and orientations can then test the remaining range of validity. Each extension should also report what fraction of the surfaces reached by the modeled paths carries an image-derived material.

V. CONCLUSION

This study aligned 360-degree street images with a photogrammetric city mesh to map surface materials around pedestrian routes at 15 GHz. A roofline transmitter model and a directional absorption step then produced normalized whole-body SAR, with all results per unit $\rho_A P_{\text{EIRP}}$. A geometric fixed-grid diagnostic at ten urban locations showed a twofold span in location-median whole-body SAR. Five of these locations were then studied with image-derived materials along fixed routes. In a controlled one-reflection scene, the first-diffuse estimate differed from deterministic quadrature by at most 0.0616 dB, and the maximum total-transport difference from an independent Sionna RT forward calculation was 0.0344 dB. Across 73 observation points on five routes, route-median whole-body SAR values differed by a factor of 13.34. Direct transport was largest at all 67 points with line of sight, while first-diffuse transport was the only nonzero contribution at the six fully shadowed points. The route medians were stable at 16 replicas, but the fully shadowed lower tails had larger estimator uncertainty. These results do not rank cities or predict deployed-network exposure.

The image-to-mesh material mapping took effect mainly through the specular component. A paired control at two sites showed route-median whole-body SAR changes of +0.249 and −0.158 dB when the image-derived materials were replaced by the geometry defaults. The method runs in under 70 s per prepared site on one GPU. The main open items are outdoor field validation against the full city model and

a measured transmitter source distribution.

DATA AND CODE AVAILABILITY

The verified five-site data, manifests, analysis scripts, and figure scripts are kept in the study repository. A stable public archive with a versioned digital object identifier will be deposited before publication. The 360-degree street images and commercial photogrammetric tiles are governed by their providers' terms and are not redistributed. Their identifiers and the alignment manifests are kept so the inputs can be reacquired where the licenses allow it.

ACKNOWLEDGMENT

AI tools were used to assist with manuscript preparation. The authors reviewed and verified the scientific claims, numerical values, references, and final text.

REFERENCES

- [1] International Telecommunication Union, "Effects of building materials and structures on radio-wave propagation in the range of 1 MHz to 450 GHz," Recommendation ITU-R P.2040-4, 2025.
- [2] E. M. Vitucci, V. Degli-Esposti, F. Mani *et al.*, "Tuning ray tracing for mm-wave coverage prediction in outdoor urban scenarios," *Radio Sci.*, vol. 54, no. 11, pp. 1112–1128, 2019, doi: 10.1029/2019RS006869.
- [3] International Commission on Non-Ionizing Radiation Protection, "Guidelines for limiting exposure to electromagnetic fields (100 kHz to 300 GHz)," *Health Phys.*, vol. 118, no. 5, pp. 483–524, 2020, doi: 10.1097/HP.0000000000001210.
- [4] J. Hoydis, F. Ait Aoudia, S. Cammerer, M. Nimier-David, N. Binder, G. Marcus, and A. Keller, "Sionna RT: Differentiable ray tracing for radio propagation modeling," in *Proc. IEEE Globecom Workshops*, 2023, pp. 317–321, doi: 10.1109/GCWkshps58843.2023.10465179.
- [5] M. Leeman, R. Wydaeghe, J. Van der Straeten, S. Goegebeur, G. Vermeeren, and W. Joseph, "City-scale spatio-temporal modeling of 5G downlink exposure of users and non-users by ray-tracing in a real urban environment," *IEEE Access*, vol. 13, pp. 30894–30906, 2025, doi: 10.1109/ACCESS.2025.3541352.
- [6] R. Wydaeghe, S. Shikhantsov, G. Vermeeren, L. Martens, E. Tanghe, and W. Joseph, "Hybrid ray-tracing-QuaDRiGa/FDTD method for realistic 28 GHz exposure with 6G CF-MaMIMO in 3D outdoor environments," *npj Wireless Technol.*, vol. 2, no. 1, Art. no. 13, 2026, doi: 10.1038/s44459-026-00031-4.
- [7] C. Wiame, S. Demey, L. Vandendorpe, P. De Doncker, and C. Oestges, "Joint data rate and EMF exposure analysis in Manhattan environments: Stochastic geometry and ray tracing approaches," *IEEE Trans. Veh. Technol.*, vol. 73, no. 1, pp. 894–908, 2024, doi: 10.1109/TVT.2023.3307226.
- [8] N. Varsier, D. Plets, Y. Corre, G. Vermeeren, W. Joseph, S. Aerts, L. Martens, and J. Wiat, "A novel method to assess human population exposure induced by a wireless cellular network," *Bioelectromagnetics*, vol. 36, no. 6, pp. 451–463, 2015, doi: 10.1002/bem.21928.
- [9] G. Neuhold, T. Ollmann, S. Rota Bulò, and P. Kontschieder, "The Mapillary Vistas dataset for semantic understanding of street scenes," in *Proc. IEEE Int. Conf. Comput. Vis.*, 2017, pp. 5000–5009, doi: 10.1109/ICCV.2017.534.
- [10] A. Kamari, Y. Chae, and P. Pathak, "mmSV: mmWave vehicular networking using Street View imagery in urban environments," in *Proc. 29th Annu. Int. Conf. Mobile Comput. Netw.*, 2023, pp. 1–16, doi: 10.1145/3570361.3613291.
- [11] G. Xia, C. Zhou, F. Zhang, Z. Cui, C. Liu, H. Ji, X. Zhang, Z. Zhao, and Y. Xiao, "Path loss prediction in urban environments with Sionna-RT based on accurate propagation scene models at 2.8 GHz," *IEEE Trans. Antennas Propag.*, vol. 72, no. 10, pp. 7986–7997, 2024, doi: 10.1109/TAP.2024.3451214.
- [12] B. Cheng, I. Misra, A. G. Schwing, A. Kirillov, and R. Girdhar, "Masked-attention mask transformer for universal image segmentation," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit.*, 2022, pp. 1290–1299.
- [13] N. Carion *et al.*, "SAM 3: Segment anything with concepts," arXiv:2511.16719, 2025, doi: 10.48550/arXiv.2511.16719.
- [14] E. Veach, *Robust Monte Carlo Methods for Light Transport Simulation*. Stanford, CA, USA: Stanford Univ., Ph.D. dissertation, 1997.
- [15] P. A. Hasgall *et al.*, "IT'IS database for thermal and electromagnetic parameters of biological tissues," Version 4.2, 2024, doi: 10.13099/VIP21000-04-2.
- [16] A. Christ *et al.*, "The Virtual Family: Development of surface-based anatomical models of two adults and two children for dosimetric simulations," *Phys. Med. Biol.*, vol. 55, no. 2, pp. N23–N38, 2010, doi: 10.1088/0031-9155/55/2/N01.

ROBIN WYDAEGHE received the B.Sc. and M.Sc. degrees in engineering physics from Ghent University, Ghent, Belgium, in 2019 and 2021, respectively. He is currently pursuing the Ph.D. degree in engineering physics with Ghent University. His research interests include computational electromagnetics, numerical assessment of human radiofrequency electromagnetic-field exposure, and propagation modeling for next-generation wireless networks.

GÜNTER VERMEEREN received the M.Sc. degree in industrial engineering from KAHO Sint-Lieven, Ghent, Belgium, in 1998, the M.Sc. degree in electrical engineering from Ghent University, Belgium, in 2001, and the Ph.D. degree in electro-technical engineering from Ghent University in 2013. Since 2002, he has been a Research Engineer with the Department of Information Technology, Ghent University. His research interests include numerical modeling and measurements of electromagnetic radiation in the domain of radiofrequency dosimetry, electromagnetic exposure, on-body propagation, and medical imaging systems.

EMMERIC TANGHE received the M.Sc. and Ph.D. degrees in electrical engineering from Ghent University, Ghent, Belgium, in 2005 and 2011, respectively. In 2015, he became a Part-Time Professor in medical applications of electromagnetic fields in and around the human body. Since 2011, he has been a Postdoctoral Researcher with Ghent University/IMEC, where he focuses on propagation modeling. From 2012 to 2018, he was a Postdoctoral Fellow of FWO-V (Research Foundation-Flanders).

WOUT JOSEPH received the M.Sc. degree in electrical engineering from Ghent University, Ghent, Belgium, in 2000, and the Ph.D. degree in electrical engineering from Ghent University in 2005. Since 2009, he has been a Professor in the domain of experimental characterization of wireless communication systems. His research interests include measuring and modeling electromagnetic fields around base stations for mobile communications, electromagnetic exposure assessment, propagation for wireless communication systems, and antennas and calibration.

...