

CPSC 319 – Assignment 2



**UNIVERSITY OF
CALGARY**

Name: Omar Ahmed

UCID: 30154382

GRADING SUMMARY

Name: Omar Ahmed

ID: 30154382

PROGRAM:		/13.0 pts
REPORT:		/2.0 pts
TOTAL		/15.0pts

PROGRAM

Program builds correctly	Yes	No
Runs: completes with zero run-time errors	Yes	No

IMPORTANT: Source code that does not compile or produces run-time errors will receive 0%

USE THE SKELETON CODE PROVIDED

Functionality + Output: Produces the <u>correct</u> output	Correct 1.0	Fail 0.0	TOTAL	
OUTPUT from Input DATA 1				/1.0 pt
OUTPUT from Input DATA 2				/1.0 pt
OUTPUT from Input DATA 3				/1.0 pt
OUTPUT from Input DATA 4				/1.0 pt
TOTAL				/4.0 pts

REPORT	Correct 1.0	Fail 0.0	TOTAL	
Question #1:				/1.0 pt
Question #2:				/1.0 pt
TOTAL				/2.0 pts

IF Functionality NOT equal to zero:

TODOs in your code:	Correct 1.0	Fail 0.0	TOTAL	
TODO-1				/1.0 pt
TODO-2				/1.0 pt
TODO-3				/1.0 pt
TODO-4				/1.0 pt
TODO-5				/1.0 pt
TODO-6				/1.0 pt
TOTAL				/6.0 pts

Readability Is your code:	Correct 1.0	Fail 0.0	TOTAL	
Clear?				/1.0 pt
Commented?				/1.0 pt
Credited ?				/1.0 pt
TOTAL				/3.0 pts

Report

Question 1:

Sorting Method for LIST A (Array of Words): The program uses a custom implementation of the Merge Sort algorithm to sort the array of all words from the input file. Merge Sort is a divide-and-conquer algorithm that breaks the array into smaller arrays, sorts those arrays, and then merges them back together in sorted order. This method is particularly effective for sorting because it is efficient for large datasets, and I don't know how big the input files used to test my code will be.

Sorting Method for Letters within Words: To determine if two words are anagrams, the program sorts the characters within each word using the same Merge Sort algorithm. This sorting standardizes each word to its alphabetically sorted form, allowing for easy comparison between words to check for anagrams.

Question 2:

The overall time complexity of the program can be estimated by considering the two main operations: sorting the list of words (LIST A) and sorting the characters within each word.

- Sorting LIST A: Sorting N words using Merge Sort has a time complexity of $O(N \log N)$.
- Sorting Characters within Each Word: Each word is sorted individually, with a time complexity of $O(L \log L)$ for each word, where L is the length of the longest word. Since each of the N words undergoes this process, the total time complexity for this part is $O(N * L \log L)$.

Combining these two operations, the total estimated time complexity of the program is $O(N \log N + N * L \log L)$. In scenarios where N is significantly larger than L , the $N \log N$ term dominates. Conversely, if L is large (but still much smaller than N), the $N * L \log L$ term can become significant, especially for very long words. However, for practical purposes and typical datasets where L is much smaller than N , the overall running time can be closely approximated by $O(N \log N)$, acknowledging that the sorting of characters within words adds an additional factor based on the length of the words.

Final answer: $O(N \log N)$