MOBSF

ANDROID STATIC ANALYSIS REPORT

EWUmate (1.0.3)

File Name: app-release.apk

Package Name:	com.rxxeron.ewumate
Scan Date:	March 6, 2026, 7:26 p.m.
App Security Score:	56/100 (MEDIUM RISK)
Grade:	B

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT

2	11	2	3	1

FILE INFORMATION

File Name: app-release.apk
Size: 61.54MB
MD5: 9b25e09edbe3fd85749e7f0f6296c760
SHA1: 2ef32ae9d35b88301d7b8aae8cdf3ee6112f3025
SHA256: 4fa1622a741961e3a35ea9821eff16c5418dc8d2953626da56a4b804eec6996a

APP INFORMATION

App Name: EWUmate
Package Name: com.rxxeron.ewumate
Main Activity: com.rxxeron.ewumate.MainActivity
Target SDK: 36
Min SDK: 24
Max SDK:
Android Version Name: 1.0.3
Android Version Code: 14

APP COMPONENTS

Activities: 4
Services: 7
Receivers: 4
Providers: 4
Exported Activities: 0
Exported Services: 0
Exported Receivers: 3
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: C=BD, ST=Dhaka, L=Dhaka, O=Rxxeron, OU=Development, CN=EWUmate
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2026-03-06 19:12:21+00:00
Valid To: 2053-07-22 19:12:21+00:00
Issuer: C=BD, ST=Dhaka, L=Dhaka, O=Rxxeron, OU=Development, CN=EWUmate
Serial Number: 0xfc046d29fb95ec3d
Hash Algorithm: sha256
md5: 8956cb7292213a0a20d01e872b960b3b
sha1: cee6959b84b69d2cea10050a130d4ca33225be76
sha256: 0e246088b889edbf42c49b8c2a8273d9af8ddac9f276c9a0948ea18e63fac7f3
sha512: be431b8d8eeb287aaafb4b23bfb84cda4f17c6301135d17bf24a7986a98136c95bc2499bedc3fdac641464470ce1f3655c5614038be944d2c242d1b682b60b42
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 15e7739fe02f040ee11d85599237bf2e2b444ffa392732bfddc7c799d31c23e3
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.CAMERA	dangerous	take pictures and videos	Allows application to take pictures and videos with the camera. This allows the application to collect images that the camera is seeing at any time.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.SCHEDULE_EXACT_ALARM	normal	permits exact alarm scheduling for background work.	Allows an app to use exact alarm scheduling APIs to perform timing sensitive background work.
android.permission.USE_EXACT_ALARM	normal	allows using exact alarms without user permission.	Allows apps to use exact alarms just like with SCHEDULE_EXACT_ALARM but without needing to request this permission from the user. This is only intended for use by apps that rely on exact alarms for their core functionality. You should continue using SCHEDULE_EXACT_ALARM if your app needs exact alarms for a secondary feature that users may or may not use within your app. Keep in mind that this is a powerful permission and app stores may enforce policies to audit and review the use of this permission. Such audits may involve removal from the app store if the app is found to be misusing this permission.
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.
android.permission.ACCESS_FINE_LOCATION	dangerous	fine (GPS) location	Access fine location sources, such as the Global Positioning System on the phone, where available. Malicious applications can use this to determine where you are and may consume additional battery power.
android.permission.ACCESS_COARSE_LOCATION	dangerous	coarse (network-based) location	Access coarse location sources, such as the mobile network database, to determine an approximate phone location, where available. Malicious applications can use this to determine approximately where you are.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
com.google.android.c2dm.permission.RECEIVE	normal	recieve push notifications	Allows an application to receive push notifications from cloud.
com.rxxeron.ewumate.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS
classes.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check Build.TAGS check ro.build.type check ro.kernel.qemu check possible ro.secure check emulator file check</td></tr><tr><td>Compiler</td><td>r8</td></tr></table>

<table>
<tr><th>FILE</th><th>DETAILS</th></tr>
<tr><td>classes2.dex</td><td><table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>Compiler</td><td>r8</td></tr></table></td></tr>
<tr><td>lib/arm64-v8a/libtoolChecker.so</td><td><table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>anti_root</td><td>RootBeer</td></tr></table></td></tr>
<tr><td>lib/armeabi-v7a/libtoolChecker.so</td><td><table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>anti_root</td><td>RootBeer</td></tr></table></td></tr>
<tr><td>lib/x86_64/libtoolChecker.so</td><td><table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>anti_root</td><td>RootBeer</td></tr></table></td></tr>
</table>

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

MANIFEST ANALYSIS

HIGH: 1 | WARNING: 3 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version 7.0, [minSdk=24]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Broadcast Receiver (io.flutter.plugins.firebase.messaging.FlutterFirebaseMessagingReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
3	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
4	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

CODE ANALYSIS

HIGH: 1 | WARNING: 7 | INFO: 2 | SECURE: 1 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
				A2/c.java A3/a.java A3/d.java B/C0016p.java B/K.java B/O.java B0/i.java B0/k.java B1/b.java C/c.java D/l.java D1/a.java D1/b.java D3/d.java E/e.java E/g.java E/h.java E/i.java E/j.java E/l.java E/m.java E0/d.java E1/l.java E3/g.java E3/m.java F0/a.java G1/b.java G2/b.java G2/d.java G2/g.java H1/b.java H2/c.java H3/d.java I2/c.java I3/C0019a.java I3/L.java J/e.java J3/f.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				K/d.java K/l.java K0/a.java K1/h.java L2/AbstractC0039e.java L2/AbstractServiceC0042h.java L2/B.java L2/C.java L2/C0045k.java L2/C0046l.java L2/C0051q.java L2/D.java L2/E.java L2/F.java L2/G.java L2/H.java L2/K.java L2/L.java L2/M.java L2/O.java L2/Q.java L2/u.java N/C0053b.java N/C0060i.java N/I.java N/J.java N/U.java N/a0.java Q/j.java R/d.java T/e.java T1/d.java U1/a.java W1/g.java Y1/e.java Y2/a.java Y2/b.java Y2/c.java a/AbstractC0129a.java a3/C0135a.java b1/d.java b1/k.java c0/C0224b.java c0/d.java c0/h.java com/dexterous/flutterlocalnotifications/ActionBroadcastReceiver.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/dexterous/flutterlocalnotifications/ScheduledNotificationReceiver.java d3/C0273e.java d3/C0282n.java d3/RunnableC0279k.java d3/RunnableC0281m.java e0/DialogInterfaceOnCancelListenerC0286c.java e0/j.java f/AbstractC0295a.java f/AbstractC0297c.java f0/c.java f0/e.java f0/g.java h2/C0309b.java h2/C0310c.java i1/C0313b.java i1/d.java i1/e.java i1/f.java i1/j.java i1/k.java i1/l.java i1/m.java i2/q.java io/flutter/embedding/engine/FlutterJNI.java io/flutter/embedding/engine/renderer/FlutterRenderer$ImageTextureRegistryEntry.java io/flutter/embedding/engine/renderer/f.java io/flutter/plugin/editing/f.java io/flutter/plugin/editing/j.java io/flutter/plugin/platform/p.java io/flutter/plugins/GeneratedPluginRegistrant.java io/flutter/plugins/firebase/messaging/FlutterFirebaseMessagingInitProvider.java io/flutter/plugins/firebase/messaging/FlutterFirebaseMessagingReceiver.java io/flutter/view/AccessibilityViewEmbedder.java io/flutter/view/l.java j/C0331d.java j/C0332e.java j1/d.java j1/e.java j1/g.java j1/i.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				j1/k.java k/MenuC0346h.java k/ViewOnKeyListenerC0343e.java k0/e.java l/AbstractC0393l0.java l/AbstractC0405s.java l/C0402q.java l/C0404r0.java l/H0.java l/K.java l/K0.java l/O.java l/P0.java l/a1.java l/b1.java l/e1.java l1/C0426e.java l1/m.java l1/w.java l1/x.java m0/C0451q.java m1/C0453B.java m1/C0457d.java m1/C0459f.java m1/D.java m1/m.java m1/n.java m1/v.java m1/w.java m1/y.java n3/AbstractActivityC0504c.java n3/C0503b.java n3/C0507f.java n3/C0508g.java n3/C0510i.java n3/C0512k.java n3/C0516o.java n3/s.java n3/t.java o3/C0521d.java p1/b.java p3/C0539b.java p3/i.java q1/d.java q2/f.java s/c.java s1/a.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				s3/b.java s3/e.java t2/d.java u/C0572e.java v0/C0589f.java v2/C0593a.java x/AbstractC0606b.java x/C0610f.java x/C0613i.java x/m.java y0/n.java y3/C0633a.java
2	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	A3/d.java G3/g.java c0/h.java
3	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	D3/d.java G2/g.java L2/C0051q.java b1/i.java b1/j.java b1/k.java c1/j.java d3/C0273e.java
4	This App may have root detection capabilities.	secure	OWASP MASVS: MSTG-RESILIENCE-1	K1/c.java W1/e.java f/AbstractC0297c.java f3/b.java
5	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/dexterous/flutterlocalnotifications/models/NotificationDetails.java
6	This App may request root (Super User) privileges.	warning	CWE: CWE-250: Execution with Unnecessary Privileges OWASP MASVS: MSTG-RESILIENCE-1	b3/AbstractC0193a.java f/AbstractC0297c.java
7	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	C/e.java H3/d.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
8	SHA-1 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	H2/c.java I2/c.java i2/q.java
9	The App uses the encryption mode CBC with PKCS5/PKCS7 padding. This configuration is vulnerable to padding oracle attacks.	high	CWE: CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-3	B0/i.java
10	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	io/flutter/plugin/editing/c.java l/P0.java
11	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	k0/f.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	arm64-v8a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__fwrite_chk', '__read_chk', '__write_chk', '__memcpy_chk', '__strcpy_chk', '__pread_chk', '__strlen_chk', '__memmove_chk', '__poll_chk', '__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	arm64-v8a/libtoolChecker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	arm64-v8a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	armeabi-v7a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	armeabi-v7a/libtoolChecker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	armeabi-v7a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	x86_64/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__fwrite_chk', '__read_chk', '__write_chk', '__memcpy_chk', '__strcpy_chk', '__pread_chk', '__strlen_chk', '__memmove_chk', '__poll_chk', '__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	x86_64/libtoolChecker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	x86_64/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	arm64-v8a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__fwrite_chk', '__read_chk', '__write_chk', '__memcpy_chk', '__strcpy_chk', '__pread_chk', '__strlen_chk', '__memmove_chk', '__poll_chk', '__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	arm64-v8a/libtoolChecker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	arm64-v8a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	armeabi-v7a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
18	armeabi-v7a/libtoolChecker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
20	armeabi-v7a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	x86_64/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__fwrite_chk', '__read_chk', '__write_chk', '__memcpy_chk', '__strcpy_chk', '__pread_chk', '__strlen_chk', '__memmove_chk', '__poll_chk', '__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
22	x86_64/libtoolChecker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
23	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
24	x86_64/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00161	Perform accessibility service action on accessibility node info	accessibility service	io/flutter/view/AccessibilityViewEmbedder.java io/flutter/view/h.java
00013	Read file and put it into a stream	file	A3/d.java E/h.java E/i.java K0/a.java U/C.java X/d.java Y/f.java c0/h.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java k0/C0353a.java k0/e.java k0/k.java
00022	Open a file from given absolute path of the file	file	G3/g.java H3/d.java I0/a.java K0/a.java P0/a.java U/N.java U/Q.java U/S.java U/W.java c0/h.java io/flutter/embedding/engine/FlutterJNI.java s3/c.java
00202	Make a phone call	control	A3/d.java
00203	Put a phone number into an intent	control	A3/d.java
00014	Read file into a stream and put it into a JSON object	file	A3/d.java

RULE ID	BEHAVIOUR	LABEL	FILES
00063	Implicit intent(view a web page, make a phone call, etc.)	control	A3/d.java B0/i.java E0/d.java G3/g.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java j1/e.java s1/a.java
00004	Get filename and put it to JSON object	file collection	A3/d.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	A3/d.java B0/i.java E0/d.java j1/e.java
00036	Get resource file from res/raw directory	reflection	A3/d.java B0/i.java E0/d.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java j1/e.java l/H0.java s1/a.java
00091	Retrieve data from broadcast	collection	L2/C0046l.java io/flutter/plugins/firebase/messaging/FlutterFirebaseMessagingReceiver.java s1/a.java
00125	Check if the given file path exist	file	s1/a.java
00175	Get notification manager and cancel notifications	notification	com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java
00209	Get pixels from the latest rendered image	collection	n3/C0508g.java
00210	Copy pixels from the latest rendered image into a Bitmap	collection	n3/C0508g.java

RULE ID	BEHAVIOUR	LABEL	FILES
00023	Start another application from current application	reflection control	B0/i.java
00089	Connect to a URL and receive input stream from the server	command network	D3/d.java I2/c.java
00109	Connect to a URL and get the response code	network command	D3/d.java I2/c.java
00173	Get bounds in screen of an AccessibilityNodeInfo and perform action	accessibility service	io/flutter/view/AccessibilityViewEmbedder.java
00026	Method reflection	reflection	a/AbstractC0129a.java
00096	Connect to a URL and set request method	command network	D3/d.java
00191	Get messages in the SMS inbox	sms	l/H0.java
00012	Read data and put it into a buffer stream	file	c0/h.java
00001	Initialize bitmap object and compress data (e.g. JPEG) into bitmap object	camera	O0/a.java

FIREBASE DATABASES ANALYSIS

TITLE	SEVERITY	DESCRIPTION
Firebase Remote Config disabled	secure	Firebase Remote Config is disabled for https://firebaseremoteconfig.googleapis.com/v1/projects/10908876468/namespaces/firebase:fetch?key=AIzaSyCnFHdMw4PhHj81mY9gx2cqCDun5J-NCSo. This is indicated by the response: {'state': 'NO_TEMPLATE'}

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	10/25	android.permission.INTERNET, android.permission.ACCESS_NETWORK_STATE, android.permission.CAMERA, android.permission.VIBRATE, android.permission.RECEIVE_BOOT_COMPLETED, android.permission.READ_EXTERNAL_STORAGE, android.permission.WRITE_EXTERNAL_STORAGE, android.permission.ACCESS_FINE_LOCATION, android.permission.ACCESS_COARSE_LOCATION, android.permission.WAKE_LOCK
Other Common Permissions	1/44	com.google.android.c2dm.permission.RECEIVE

Malware Permissions:
Top permissions that are widely abused by known malware.

Other Common Permissions:
Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
ns.adobe.com	ok	No Geolocation information available.
www.w3.org	ok	**IP:** 104.18.22.19 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
firebase.google.com	ok	**IP:** 142.250.206.142 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
firebaseinstallations.googleapis.com	ok	**IP:** 142.251.220.106 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
issuetracker.google.com	ok	**IP:** 142.250.195.46 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.unicode.org	ok	**IP:** 172.67.74.23 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
api.flutter.dev	ok	**IP:** 199.36.158.100 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
github.com	ok	**IP:** 20.205.243.166 **Country:** United States of America **Region:** Washington **City:** Redmond **Latitude:** 47.682899 **Longitude:** -122.120903 **View:** Google Map
docs.flutter.dev	ok	**IP:** 199.36.158.100 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
dartbug.com	ok	**IP:** 216.239.32.21 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
jwygjihrbwxhehijldiz.supabase.co	ok	**IP:** 172.64.149.246 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.783058 **Longitude:** -96.806671 **View:** Google Map
fonts.gstatic.com	ok	**IP:** 142.251.221.99 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
developer.android.com	ok	**IP:** 142.251.43.46 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
youtrack.jetbrains.com	ok	**IP:** 63.33.88.220 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map

EMAILS

EMAIL	FILE
u0013android@android.com u0013android@android.com0	j1/j.java
appro@openssl.org	apktool_out/lib/arm64-v8a/libflutter.so
_link@16069316.fromrawpat _imagefilter@35065589.blur _httpparser@17463476.responsepa _list@0150898._ofarray _assertionerror@0150898._create _semanticsgeometry@27266271.root _growablelist@0150898._literal7 _timer@1026248.periodic _list@0150898._ofother _growablelist@0150898._literal4 _list@0150898.of ngstreamsubscription@5048458.zoned	

EMAIL	FILE
_double@0150898.fromintege _bigintimpl@0150898.from _imagefilter@35065589.fromcolorf _list@0150898.empty _uri@0150898.file _file@16069316.fromrawpat _colorfilter@35065589.srgbtoline storationinformation@39124995.fromserial _assetmanifestbin@348287047.fromstanda _list@0150898.generate _growablelist@0150898._literal2 _nativesocket@16069316.normal _future@5048458.immediatee _growablelist@0150898._ofother _list@0150898._ofefficie _list@0150898._ofgrowabl _bytebuffer@8027147._new _colorfilter@35065589.mode _timer@1026248._internal _growablelist@0150898._literal6 _growablelist@0150898._ofgrowabl _receiveportimpl@1026248.fromrawrec _colorfilter@35065589.lineartosr _compressednode@248137193.single _growablelist@0150898._literal5 _growablelist@0150898._literal1 _growablelist@0150898._ofefficie _uri@0150898.notsimple _growablelist@0150898._literal3 _growablelist@0150898.generate _imagefilter@35065589.composed authenticationscheme@17463476.fromstring _future@5048458.immediate _growablelist@0150898._ofarray _typeerror@0150898._create _growablelist@0150898.of _growablelist@0150898.withcapaci _hashcollisionnode@248137193.fromcollis _growablelist@0150898._literal8 _future@5048458.zonevalue _invocationmirror@0150898._withtype _uri@0150898.directory _growablelist@0150898._literal _directory@16069316.fromrawpat	apktool_out/lib/armeabi-v7a/libapp.so

EMAIL	FILE
appro@openssl.org	apktool_out/lib/x86_64/libflutter.so
appro@openssl.org	lib/arm64-v8a/libflutter.so
_link@16069316.fromrawpat _imagefilter@35065589.blur _httpparser@17463476.responsepa _list@0150898._ofarray _assertionerror@0150898._create _semanticsgeometry@27266271.root _growablelist@0150898._literal7 _timer@1026248.periodic _list@0150898._ofother _growablelist@0150898._literal4 _list@0150898.of ngstreamsubscription@5048458.zoned _double@0150898.fromintege _bigintimpl@0150898.from _imagefilter@35065589.fromcolorf _list@0150898.empty _uri@0150898.file _file@16069316.fromrawpat _colorfilter@35065589.srgbtoline storationinformation@39124995.fromserial _assetmanifestbin@348287047.fromstanda _list@0150898.generate _growablelist@0150898._literal2 _nativesocket@16069316.normal _future@5048458.immediatee _growablelist@0150898._ofother _list@0150898._ofefficie _list@0150898._ofgrowabl _bytebuffer@8027147._new _colorfilter@35065589.mode _timer@1026248._internal _growablelist@0150898._literal6 _growablelist@0150898._ofgrowabl _receiveportimpl@1026248.fromrawrec _colorfilter@35065589.lineartosr _compressednode@248137193.single _growablelist@0150898._literal5 _growablelist@0150898._literal1	lib/armeabi-v7a/libapp.so

EMAIL	FILE
_growablelist@0150898._ofefficie _uri@0150898.notsimple _growablelist@0150898._literal3 _growablelist@0150898.generate _imagefilter@35065589.composed authenticationscheme@17463476.fromstring _future@5048458.immediate _growablelist@0150898._ofarray _typeerror@0150898._create _growablelist@0150898.of _growablelist@0150898.withcapaci _hashcollisionnode@248137193.fromcollis _growablelist@0150898._literal8 _future@5048458.zonevalue _invocationmirror@0150898._withtype _uri@0150898.directory _growablelist@0150898._literal _directory@16069316.fromrawpat	
appro@openssl.org	lib/x86_64/libflutter.so

🔑 HARDCODED SECRETS

POSSIBLE SECRETS
"google_api_key" : "AIzaSyCnFHdMw4PhHj81mY9gx2cqCDun5J-NCSo"
"google_crash_reporting_api_key" : "AIzaSyCnFHdMw4PhHj81mY9gx2cqCDun5J-NCSo"
VGhpcyBpcyB0aGUgcHJlZml4IGZvciBhIHNlY3VyZSBzdG9yYWdlCg
VGhpcyBpcyB0aGUgcHJlZml4IGZvciBCaWdJbnRlZ2Vy
VGhpcyBpcyB0aGUga2V5IGZvciBhIHNlY3VyZSBzdG9yYWdlIEFFUyBLZXkK
VGhpcyBpcyB0aGUga2V5IGZvcihBIHNlY3XyZZBzdG9yYWdlIEFFUyBLZXkK

SCAN LOGS

Timestamp	Event	Error
2026-03-06 19:26:57	Generating Hashes	OK
2026-03-06 19:26:57	Extracting APK	OK
2026-03-06 19:26:57	Unzipping	OK
2026-03-06 19:26:57	Parsing APK with androguard	OK
2026-03-06 19:26:57	Extracting APK features using aapt/aapt2	OK
2026-03-06 19:26:58	Getting Hardcoded Certificates/Keystores	OK
2026-03-06 19:27:01	Parsing AndroidManifest.xml	OK
2026-03-06 19:27:01	Extracting Manifest Data	OK
2026-03-06 19:27:01	Manifest Analysis Started	OK
2026-03-06 19:27:01	Performing Static Analysis on: EWUmate (com.rxxeron.ewumate)	OK

2026-03-06 19:27:02	Fetching Details from Play Store: com.rxxeron.ewumate	OK
2026-03-06 19:27:03	Checking for Malware Permissions	OK
2026-03-06 19:27:03	Fetching icon path	OK
2026-03-06 19:27:03	Library Binary Analysis Started	OK
2026-03-06 19:27:03	Analyzing apktool_out/lib/arm64-v8a/libflutter.so	OK
2026-03-06 19:27:03	Analyzing apktool_out/lib/arm64-v8a/libtoolChecker.so	OK
2026-03-06 19:27:03	Analyzing apktool_out/lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-03-06 19:27:03	Analyzing apktool_out/lib/arm64-v8a/libapp.so	OK
2026-03-06 19:27:03	Analyzing apktool_out/lib/armeabi-v7a/libflutter.so	OK
2026-03-06 19:27:03	Analyzing apktool_out/lib/armeabi-v7a/libtoolChecker.so	OK
2026-03-06 19:27:03	Analyzing apktool_out/lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-03-06 19:27:03	Analyzing apktool_out/lib/armeabi-v7a/libapp.so	OK

2026-03-06 19:27:04	Analyzing apktool_out/lib/x86_64/libflutter.so	OK
2026-03-06 19:27:04	Analyzing apktool_out/lib/x86_64/libtoolChecker.so	OK
2026-03-06 19:27:04	Analyzing apktool_out/lib/x86_64/libdatastore_shared_counter.so	OK
2026-03-06 19:27:04	Analyzing apktool_out/lib/x86_64/libapp.so	OK
2026-03-06 19:27:04	Analyzing lib/arm64-v8a/libflutter.so	OK
2026-03-06 19:27:04	Analyzing lib/arm64-v8a/libtoolChecker.so	OK
2026-03-06 19:27:04	Analyzing lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-03-06 19:27:04	Analyzing lib/arm64-v8a/libapp.so	OK
2026-03-06 19:27:04	Analyzing lib/armeabi-v7a/libflutter.so	OK
2026-03-06 19:27:05	Analyzing lib/armeabi-v7a/libtoolChecker.so	OK
2026-03-06 19:27:05	Analyzing lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-03-06 19:27:05	Analyzing lib/armeabi-v7a/libapp.so	OK

2026-03-06 19:27:05	Analyzing lib/x86_64/libflutter.so	OK
2026-03-06 19:27:05	Analyzing lib/x86_64/libtoolChecker.so	OK
2026-03-06 19:27:05	Analyzing lib/x86_64/libdatastore_shared_counter.so	OK
2026-03-06 19:27:05	Analyzing lib/x86_64/libapp.so	OK
2026-03-06 19:27:05	Reading Code Signing Certificate	OK
2026-03-06 19:27:06	Running APKiD 3.0.0	OK
2026-03-06 19:27:11	Detecting Trackers	OK
2026-03-06 19:27:12	Decompiling APK to Java with JADX	OK
2026-03-06 19:27:19	Converting DEX to Smali	OK
2026-03-06 19:27:19	Code Analysis Started on - java_source	OK
2026-03-06 19:27:20	Android SBOM Analysis Completed	OK
2026-03-06 19:27:22	Android SAST Completed	OK

2026-03-06 19:27:22	Android API Analysis Started	OK
2026-03-06 19:27:24	Android API Analysis Completed	OK
2026-03-06 19:27:24	Android Permission Mapping Started	OK
2026-03-06 19:27:26	Android Permission Mapping Completed	OK
2026-03-06 19:27:26	Android Behaviour Analysis Started	OK
2026-03-06 19:27:28	Android Behaviour Analysis Completed	OK
2026-03-06 19:27:28	Extracting Emails and URLs from Source Code	OK
2026-03-06 19:27:30	Email and URL Extraction Completed	OK
2026-03-06 19:27:30	Extracting String data from APK	OK
2026-03-06 19:27:30	Extracting String data from SO	OK
2026-03-06 19:27:31	Extracting String data from Code	OK
2026-03-06 19:27:31	Extracting String values and entropies from Code	OK

2026-03-06 19:27:32	Performing Malware check on extracted domains	OK
2026-03-06 19:27:36	Saving to Database	OK

Report Generated by - MobSF v4.4.5

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.