

1. (a) The fit was done by iteratively adding an additional order, starting with a 1st order chebyshev fit. The error was always taken to be the absolute value of the final coefficient, since we were truncating the series there. Thus the n-1 first coefficients would be the returned coefficients of the fit. This produced the following output:

```
Order 0 gives error 0.4923648
Order 1 gives error 0.0421532
Order 2 gives error 0.0048173
Order 3 gives error 0.0006197
Order 4 gives error 0.0000850
Order 5 gives error 0.0000122
Order 6 gives error 0.0000018
Order 7 gives error 0.0000003
```

Indicating that a 7 terms were needed. Comparing the errors resulted in:

Maximum Errors:

Cheby: 3.228338e-07

Poly: 3.507079e-07

RMS Errors:

Cheby: 1.932287e-07

Poly: 1.800043e-07

So we see that both fits performed rather well, with the polynomial winning in RMS, but the Chebyshev fit gave a smaller maximum error. This is visible in the residuals of Fig. 1 where the Chebyshev fit results in less deviation at the ends, but the regular polynomial looking better in the middle.

- (b) Any number > 0 can be expressed as $m * 2^x$ with m the mantissa $\in (0.5, 1]$ and x some integer exponent. The mantissa is always $> \frac{1}{2}$ Since otherwise we could just subtract one from x and multiply the mantissa by 2. Similarly, it won't be greater than 1 as we could then add one to x and divide the mantissa by 2.

With that in mind, we can then express the base 2 logarithm of any positive number as:

$$\log_2(m * 2^x) = \log_2(m) + \log_2(2^x) = \log_2(m) + x$$

We can thus use the previous fit for the logarithm between 0.5 and 1 and `np.frexp` to calculate $\log_2(x)$ for a number in any range, allowing us to produce Fig. 2.




Figure 1: Chebyshev polynomial fit vs regular polynomial fit for function $\log_2(x)$.




Figure 2: $\log_2(x)$ calculated using a chebyshev polynomial fit from 0.5 to 1 and `np.frexp`, compared to `np.log2`.

2. (a)
 - i. Since this model requires multiple parameters and a nonlinear function ($\exp(x)$) is involved, it is not a linear model.
 - ii. Since we are fixing the starting time t_0 , the model requires three parameters, an offset f_0 , an amplitude A and a time constant τ . The model function will then be a decaying exponential given by

$$f(x) = f_0 + A \exp\left\{-\frac{(t - t_0)}{\tau}\right\},$$

or in python code:

```
y = p[0] + p[1] * np.exp(-(t-t0)/p[2])
```

I took a starting offset of 1.0 an amplitude of 0.26 since the peak value looks a bit above 1.25 and a time constant of 0.05, since 0.25 seconds after the peak the exponent is already basically at 0 which should correspond to 5 time constants. See part (b) for plot with both initial guess and optimized fit.

- (b) After optimizing the optimal parameters are found to be

[1.00194174 0.26085036 0.01540617]




Figure 3: Initial guess and fit of decaying exponential to flare data.

(c) In class we saw that

$$\sigma_m^2 = \text{diag} \left(\langle (m - m_t)(m - m_t)^\top \rangle \right) = \text{diag} \left(\left(\frac{1}{2} \frac{\partial^2 \chi^2}{\partial m^2} \right)^{-1} \right).$$

Since in Newton's method we estimate that

$$\frac{\partial^2 \chi^2}{\partial m^2} \approx 2A'(m)^\top N^{-1} A'(m),$$

we can take the errors on the parameters to be

$$\sigma_m = \sqrt{\text{diag} \left((A'(m)^\top N^{-1} A'(m))^{-1} \right)}.$$

To get an idea of what N should be, I took the standard deviation of all the data before the flare time σ_d . N would then simply be $\sigma_d^2 I$, plugging this in results in

$$\sigma_m = \sigma_d \cdot \sqrt{\text{diag} \left((A'(m)^\top A'(m))^{-1} \right)}.$$

The script produces the following results:

```
With parameters: [1.    0.26 0.05],
Iteration 0 gives chi2 of 8245.470399
With parameters: [1.00367122 0.20254194 0.02291222],
Iteration 1 gives chi2 of 702.552041
With parameters: [1.00204386 0.25281272 0.01399754],
Iteration 2 gives chi2 of 210.257034
With parameters: [1.00197512 0.26099529 0.01535158],
Iteration 3 gives chi2 of 148.926113
With parameters: [1.00194174 0.26085036 0.01540617],
Iteration 4 gives chi2 of 148.885625
Converged!
With parameters: [1.00194089 0.26083417 0.01540966],
Iteration 4 gives chi2 of 148.885625
Errors on fit: [0.00032999 0.00285143 0.00030042].
Estimated data error: 0.003113.
```

These errors are relatively sensible compared to the parameters, they are a small but not insignificant fraction.

- (d) Since I already considered the error by looking at the data before the flare, these parameter errors seem reasonable since, with a few hundred points, the error on each fit parameter is roughly σ_d/\sqrt{N} .