

(p_0, p_1, p_2, p_3)	$\alpha.RTS$				$\alpha.RTS - FE$			
	Uniform	Distance	ERADE2025	D-Tracking	Uniform	Distance	ERADE2025	D-Tracking
(0.1, 0.1, 0.1, 0.1)	2.80%	1.00%	1.70%	0.90%	4.00%	1.70%	1.70%	1.50%
(0.3, 0.3, 0.3, 0.3)	4.30%	5.50%	3.80%	4.30%	4.90%	5.50%	4.70%	4.70%
(0.5, 0.5, 0.5, 0.5)	4.00%	4.90%	5.00%	4.00%	5.50%	5.30%	5.80%	6.20%
(0.7, 0.7, 0.7, 0.7)	4.30%	5.20%	3.80%	4.50%	4.90%	5.50%	4.70%	4.70%
(0.9, 0.9, 0.9, 0.9)	2.80%	1.00%	1.70%	1.00%	4.00%	1.70%	1.70%	1.50%
(0.9, 0.8, 0.7, 0.6)	87.70%	85.90%	85.50%	85.30%	87.50%	84.70%	83.80%	86.50%
(0.8, 0.7, 0.5, 0.4)	98.10%	98.40%	97.70%	98.20%	98.10%	98.40%	98.20%	98.10%
(0.7, 0.6, 0.4, 0.2)	99.90%	99.90%	99.70%	100.00%	99.90%	99.70%	99.80%	99.60%
(0.5, 0.4, 0.3, 0.2)	78.50%	81.60%	81.60%	81.50%	80.20%	79.80%	79.20%	78.30%
(0.4, 0.3, 0.2, 0.1)	86.40%	83.90%	84.70%	85.20%	88.90%	85.20%	85.20%	83.80%

Table 1: Type-1 error (%) for different targeting designs with fixed target allocation (Neyman), 1000 simulations, $n = 200$