# Reinforcing Bar B500B 16 mm

FRT-RST-B500B16 · Reinforcing steel

| Document | Revision | Issue date | Product code |
|---|---|---|---|
| DS-FRT-RST-B500B16 | A | 2025-01-15 | FRT-RST-B500B16 |

## Description

Ribbed weldable reinforcing bar for beams, columns and foundations in reinforced concrete.

## Technical properties

| Property | Value | Standard |
|---|---|---|
| Characteristic yield strength | 500 MPa | EN 10080 |
| Tensile strength | 540 MPa | ISO 15630-1 |
| Elongation at maximum force (Agt) | 5 % | ISO 15630-1 |
| Nominal diameter | 16 mm | EN 10080 |
| Mass per metre | 1.58 kg/m | EN 10080 |

## Handling and storage

- Store off the ground on timber bearers and keep free of mud, oil and loose rust.
- Cut and bend cold, to the minimum former diameters in EN 1992-1-1.
- Supplied in bundles tagged with the cast number for traceability.

## Revision history

| Revision | Date | Change |
|---|---|---|
| A | 2025-01-15 | First issue. |

Values are characteristic or declared values for the product as supplied and do not replace a design check by a qualified engineer. Sample document for demonstration only: the values are illustrative typical figures, not test results.