



Binary Search & Sorting

Part 4

1



Binary Search

Cutting the problem in half... many times

2

Binary Searching

- A *binary search* is a fast and efficient way to search an array
- Algorithm works like the classic "secret number game"
- Requires that the array is sorted before the search



Fall 2021

Secrets to Success - CS50.100

3

3

How it Works

- Starts knowing the max & min values
 - in the case of arrays, this is the min and max index
 - in the number game, it is the min and max value
- Algorithm continues
 - it looks at the midpoint between the first and last
 - if the value > target, the max is set to the midpoint
 - if the value < target, the min is set to the midpoint
 - *this eliminates half of the numbers each iteration*


Fall 2021

Secrets to Success - CS50.100

4

4

Binary Example: Find 30




Fall 2021

Secrets to Success - CS50.100

5

5

Binary Example: Find 30







Fall 2021

Secrets to Success - CS50.100

6

6



Benefits

- The binary search is incredibly efficient and **absolutely necessary** for large arrays
- Any item can be found only $\log_2(n)$ searches! It is $O(\log n)$
- However, since array must be sorted, sorting algorithms are equally vital

11

Maximum # of Searches

Array Size	Sequential	Binary
10	10	4
100	100	7
1,000	1,000	10
10,000	10,000	14
100,000	100,000	17
1,000,000	1,000,000	20
10,000,000	10,000,000	24
100,000,000	100,000,000	27
1,000,000,000	1,000,000,000	30

12

Sorting

Bringing Order of "Chaos"

13

Sorting

- It is useful (and efficient) to *sort* a list of data – to put it in specific order
- There are multiple sorting algorithms which get complex as they become more efficient

Fall 2021 Sacramento State - CSIS - CSIS 130 14

14

Sorting

- Examples:
 - sorting scores by highest to lowest
 - sorting filenames in alphabetical order
 - sorting students by their student-id

Fall 2021 Sacramento State - CSIS - CSIS 130 15

15

Sorting Algorithm Attributes

- Time Complexity
 - Big-O classification
 - naturally, the smallest classification is better
- Auxiliary space
 - how extra much memory is needed to run the algorithm
 - some algorithms require extra memory – *perhaps as large as the array itself*

Fall 2021 Sacramento State - CSIS - CSIS 130 16

16

Sorting Algorithm Attributes

- Stable
 - what happens when two array elements, *a* and *b*, have the same sort value?
 - if *a* is initially stored before *b*, a "stable" sort will not change their relative positions
- Online
 - elements can be added at the same time that the data is being sorted
 - data can be *streamed* into the array at runtime

Fall 2021 Sacramento State - CSIS - CSIS 130 17

17


Bubble Sort

Carbonated Sorting

18

Bubble Sort

- The *bubble sort* is one of the least efficient algorithms ...but it is easy to understand
- Basic approach
 - "lighter" elements "bubble up" to the top of the array
 - "heavier" items sink to the bottom



Fall 2021

Scenario: Data - Cook - CS51.10

19

19

How It Works

- Consists of two For Loops
- Outer loop runs from the first to the last
- Inner loop ...
 - runs from the bottom of the array *up* to the top (well, the position of the first loop)
 - it checks every two neighbor elements, if they are out of order, it swaps them
 - so, the smallest element moves up the array

Fall 2021

Scenario: Data - Cook - CS51.10

20

20

The Bubble Sort (Java-ish)

```
for(i = 0; i < count-1; i++)
{
    for(j = count-1; j > i; j--)
    {
        if (array[j-1] < array[j])
        {
            //swap array[j-1] and array[j]
        }
    }
}
```

Fall 2021


Scenario: Data - Cook - CS51.10

21

21

Bubble Sort Example

- Outer Loop
- Inner Loop



Fall 2021


Scenario: Data - Cook - CS51.10

22

22

Bubble Sort Example

- Outer Loop
- Inner Loop



Fall 2021


Scenario: Data - Cook - CS51.10

23

23

Bubble Sort Example

- Outer Loop
- Inner Loop




Fall 2021


Scenario: Data - Cook - CS51.10

24


24




25




26




27



28



29



30

Bubble Sort Example

Outer Loop
 Inner Loop

array	
0	5
1	11
2	42
3	73
4	58

Fall 2021 Sacramento State - CS&E - CS&E 130 31

31

Bubble Sort Example

Outer Loop
 Inner Loop

array	
0	5
1	11
2	42
3	58
4	73

Fall 2021 Sacramento State - CS&E - CS&E 130 32

32

Efficiency of the Bubble Sort

- The Bubble Sort is **extremely** inefficient and only good for tiny arrays
- Since Bubble Sort uses two embedded loops
 - the outer loop looks at all n items
 - the inner loop looks at basically n items
 - the resulting algorithm gets **exponentially** less efficient as n increases

Fall 2021 Sacramento State - CS&E - CS&E 130 33

33

Efficiency of the Bubble Sort

- The Bubble Sort $O(n^2)$
- ... two embedded loops that are based on n
- ... and all that swapping doesn't help either!

Fall 2021 Sacramento State - CS&E - CS&E 130 34

34

Bubble Sort Summary

Bubble Sort	
Time Average	$O(n^2)$
Time Best	$O(n^2)$
Time Worst	$O(n^2)$
Auxiliary space	$O(1)$
Stable	Yes – Equal element order preserved
Online?	No – Entire array in use

Fall 2021 Sacramento State - CS&E - CS&E 130 35

35

Selection Sort


The Human Way

Fall 2021 Sacramento State - CS&E - CS&E 130 36

36

Selection Sort

- The *Selection Sort* is a similar to the Bubble Sort
- However...
 - rather than "bubble up" smaller items, it scans the entire array
 - it finds the smallest element
 - only *then* does it swap the values



Fall 2021

Selection Sort - Deck - CS61B

37

37

Selection Sort

- Like the Bubble Sort, it consists of two For Loops – one outer and one inner
- Outer loop runs from the first to the last
- Inner loop ...
 - starts at the position of the outer loop
 - scans down and finds the *smallest* value
- Then, after the scan, do a single swap

Fall 2021

Selection Sort - Deck - CS61B

38

38

The Selection Sort

```
for(i = 0; i < count-1; i++)
{
    best = i;
    for(j = i; j < count; j++)
    {
        if (array[j] < array[best])
        {
            best = j;
        }
    }
    //swap array[i] and array[best]
}
```

Fall 2021


Selection Sort - Deck - CS61B

39

39

Selection Sort Example

- Outer Loop
- Inner Loop



Fall 2021


Selection Sort - Deck - CS61B

40

40

Selection Sort Example: New Best

- Outer Loop
- Inner Loop



Fall 2021


Selection Sort - Deck - CS61B

41

41

Selection Sort Example

- Outer Loop
- Inner Loop




Fall 2021


Selection Sort - Deck - CS61B

42


42




43




44




45




46




47




48




49




50




51



52



53



54

Selection Sort Example: No Swap

Outer Loop
 Inner Loop

55

Selection Sort Example: Search Again

Outer Loop
 Inner Loop

56

Selection Sort Example: No Swap

Outer Loop
 Inner Loop

57

Selection Sort Example: Done

Outer Loop
 Inner Loop

58

Selection Sort Summary

Selection Sort	
Time Average	$O(n^2)$
Time Best	$O(n^2)$
Time Worst	$O(n^2)$
Auxiliary space	$O(1)$
Stable	Yes – Equal element order preserved
Online?	No – Entire array in use

59


Insertion Sort

Building a sorted array... bit by bit
(er... byte by byte?)

60

Insertion Sort

- The *Insertion Sort* is a $O(n^2)$ sorting algorithm with several advantages over bubble-sort and selection-sort
- While it is still $O(n^2)$ is far more efficient than the other two



Fall 2021

Scatterplot: Data - CS51.10

61

61

Deck of Cards

- Often, it is compared to sorting a deck of cards
- This is how you would manually sort a row of cards
 - if you start sorting on the left side, you will find a card, move it, and shift the rest of the cards right
 - you build a sorted list a bit at a time – on the left side of your row



Fall 2021

Scatterplot: Data - CS51.10

62

62

How it Works

- The algorithm consists of two loops – one embedded within the other
- The outer loop starts at the top of the array and moves down
- The algorithm builds a sorted array *above* the outer loop.



Fall 2021

Scatterplot: Data - CS51.10

63

63

How it Works

- Current array value is saved into a temporary variable
- Inner loop then searches all the values that come *before* it in the array
- If the value, being looked at, is larger than the saved value, it's moved down



Fall 2021

Scatterplot: Data - CS51.10

64

64

The Insertion Sort

```
for (i = 1; i < count; i++)
{
    value = array[i];
    j = i - 1;
    while (j >= 0 && array[j] > value)
    {
        array[j + 1] = array[j];
        j --;
    }
    array[j + 1] = value;
}
```

Fall 2021


Scatterplot: Data - CS51.10

65

65

Insertion Sort Example

- Outer Loop
- Inner Loop















Fall 2021


Scatterplot: Data - CS51.10

66


66









79




80




81








82



83



84



- ### Advantages
- Because Insertion Sort creates a sorted array above the outer loop
 - inner loop, on average, only needs to move 1/2 positions up – far faster!
 - data can be sent during the sorting process
 - this means the algorithm is considered *"online"* – i.e. it can sort *streaming* data
- 90

Advantages

- Insertion sort does not "swap" values
 - most of the overhead of bubble and selection-sort is swapping
 - insertion sort moves data as it sorts, so, there is little unnecessary overhead
- Little to no auxiliary storage overhead
 - like Bubble-Sort and Selection-Sort, Insertion-Sort requires little storage overhead
 - so, in regards to n , storage complexity is $O(1)$

91

Advantages

- Insertion sort is $O(n)$ on sorted lists
 - inner loop **stops** when the current array value cannot be moved up
 - the more sorted the list, the more the inner loop approaches $O(1)$

92

Insertion Sort Summary

Insertion Sort	
Time Average	$O(n^2)$
Time Best	$O(n)$
Time Worst	$O(n^2)$
Auxiliary space	$O(1)$
Stable	Yes – Equal element order preserved
Online?	Yes – Can sort streamed data

93


Shell Sort

Insertion Sort with an identity crisis

94

Shell Sort


- *Shell-Sort* is a version of the Insertion-Sort created by *Donald Shell* in 1959
- Yes, it is named after the guy, *not a shell metaphor*
- But, ironically, that metaphor works



95

Shell Sort

- It was the first algorithm to break the $O(n^2)$ barrier
- For a few years, this was the fastest sort algorithm available – until $O(n \log n)$ was invented



96

What is Going On?

- With insertion sort, each time we insert an element, the rest are moved one step closer to where they belong
- Can we move elements a larger distance than just one?
- Yes...** Shell Sort works like Insertion Sort, but works on elements at large distances
- This distance is called the gap

Fall 2021

Sacramento State - CS&E - CS&E 130

97

97

What's Going On?

- Gap changes with each outer loop iteration
 - the distance between comparisons decreases as the sorting algorithm runs
 - in the last iteration, the gap is 1
 - so, at that point, adjacent elements are compared – so it is a regular Insertion Sort
- Shell Sort is also known as a "diminishing increment sort"

Fall 2021

Sacramento State - CS&E - CS&E 130

98

98

Sorting "Shells"

- Shell Sort orders elements that are spaced a relative distance from each other
- So, the red cells above are sorted relative to each other, as are the yellow, green, and blue cells



Fall 2021

Sacramento State - CS&E - CS&E 130

99

99

Sorting "Shells"

- The decreasing gaps are a sequence
- The notation $h_1, h_2, h_3, \dots, h_i$ represents a sequence of increasing integer values which will be used (from right to left)
- Any sequence works if it $h_n > h_{n-1}$ and $h_1 = 1$



Fall 2021

Sacramento State - CS&E - CS&E 130

100

100

Gap Mathematics

- h_k -sorted array - all elements with gap h_k are sorted relative to each other
- So, after each phase of h_k ...
 - for each i , we have $\text{array}[i] \leq \text{array}[i + h_k]$
 - all elements spaced h_k apart are sorted.



Fall 2021

Sacramento State - CS&E - CS&E 130

101

101

Gap Mathematics

- Shell-Sort only works because an array that is h_k -sorted...
- ...remains h_k -sorted when h_{k-1} -sorted.



Fall 2021

Sacramento State - CS&E - CS&E 130

102

102

So, What are Gap Values?

- For $h_1, h_2, h_3, \dots, h_t$ we need to determine what the actual values will be
- Some sequences are better than others
- Shell's original design...
 - starts at $N / 2$ (where N is the size of the array)
 - cuts the gap in half for each iteration
- There are several competing sequences

Fall 2021

Sacramento State - CS&E - CS&E 130

103

103

So, What are the Gap Values

- The algorithm is most efficient when...
 - the gap sequence are *relatively prime*
 - i.e. the sequence does not share any divisors
- However....
 - using a prime sequence is often not practical in a program – too much to store!
 - so, real, practical solutions attempt to approximate a relatively prime sequence

Fall 2021

Sacramento State - CS&E - CS&E 130

104

104

So, What are Gap Values?

Creator	Sequence
Shell	1, ..., (n / 8), (n / 4), (n / 2)
Hibbard	1, 3, 7, 15, 31, ..., $2^k - 1$
Knuth	1, 4, 13, 40, 121, ..., $(3^k - 1) / 2$
Sedgewick	1, 5, 19, 41, 109, ..., $(4^k - 3 * 2^k + 1)$

Fall 2021

Sacramento State - CS&E - CS&E 130

105

105

The Shell Sort: Original

```

for (gap = count / 2; gap > 0; gap /= 2)
{
    for (i = gap; i < count; i++)
    {
        value = array[i];
        j = i;
        while (j >= gap && array[j - gap] > value)
        {
            array[j] = array[j - gap];
            j -= gap;
        }
        array[j] = value;
    }
}
    
```


Fall 2021

Sacramento State - CS&E - CS&E 130

106

106

Gap = 4, First Outer Loop Pass




Fall 2021

Sacramento State - CS&E - CS&E 130

107

107

Gap = 4, Outer Loop starts at 4 (the gap)















Fall 2021


Sacramento State - CS&E - CS&E 130

108


108









121




122




123




124




125




126




127




128




129



130



131



132

... and so on....

- The example continues to sort for each h_k
- The outer loop continues to the bottom of the array
- Finally, gap will go to one and the sort acts just like an Insertion-Sort

Fall 2021

Shenoy's Data - CS6 - CS6 133

133

133

Time Complexity

- Time complexity of Shell Sort is up for debate
- Although the algorithm is fairly simple, proving its time complexity is not
- What is known...
 - it is approximately $O(n^r)$ where $1 < r < 2$
 - this is ultimately faster than $O(n^2)$ but worse than $O(n \log n)$

Fall 2021

Shenoy's Data - CS6 - CS6 133

134

134

Time Complexity

- Empirical analysis of the algorithm has given some widely accepted values for average, best, and worst times
- Worst case performance (using Hibbard's sequence) is $O(n^{3/2})$
- Average performance is thought to be about $O(n^{5/4})$

Fall 2021

Shenoy's Data - CS6 - CS6 133

135

135

Shell Sort Summary

Shell Sort	
Time Average	$\approx O(n^{5/4})$
Time Best	$\approx O(n \log n)$ – For a near sorted list
Time Worst	$\approx O(n^{3/2})$
Auxiliary space	$O(1)$
Stable	No – Equal element order not preserved
Online?	No – Entire array in use

Fall 2021

Shenoy's Data - CS6 - CS6 133

136

136