




Abstract Data Types

Part 2

1




Data Structures

Return to CSC 15 and CSC 20

2

Data Structures

- Arrays and linked-lists are both examples of *data structures*
- These are different *techniques* of storing and organizing data
- In other words, this is *how* data is stored



Fall 2021


Sebastian Seitz - CSE 151

3

3

Data Structures

- Depending on *how* data is accessed, some data structures can either excel and falter
- This is true of both arrays and linked lists



Fall 2021


Sebastian Seitz - CSE 151

4

4

Data Structures

- We will do a quick review of arrays and linked lists
- There are more data structures than these two
- We will cover them this semester – some which have *incredible* in features



Fall 2021

Sebastian Seitz - CSE 151

5

5



Array Data Structure

Hidden math = easy code

6

Array Data Structure

- The array data structure is found in practically every programming language
- This is also one of the fundamental ways data is stored in memory



Fall 2021

Scenario: State - Cook - CS5.110

7

7

Behind the Scenes...

- Arrays are just **continuous** blocks of memory containing multiple instances of the same type
- Since the instances are continuous, values can be accessed randomly in **$O(1)$**



Fall 2021

Scenario: State - Cook - CS5.110

8

8

Array Math Example: 32-bit int

- Let's assume the array starts at address **2000**
- Each array element will take 8 bytes (for 64-bit integers)
- Array elements are stored continuous

2000	446576696E20436F
2008	6F6B000000000000
2016	53616372616D656E
2024	746F205374617465
2032	4353433335000000

Fall 2021

Scenario: State - Cook - CS5.110

9

9

Array Math Example: 32-bit int

- **array[0]** is **2000**
- **array[1]** is **2008**
- **array[2]** is **2016**
- **array[3]** is **2024**
- **array[4]** is **2032**
- etc...

2000	446576696E20436F
2008	6F6B000000000000
2016	53616372616D656E
2024	746F205374617465
2032	4353433335000000

Fall 2021

Scenario: State - Cook - CS5.110

10

10

Behind the Scenes...

- So, when an array element is read, internally, a mathematical equation is used
- It uses the start array, the array index, and the size of each element

```
start + (index * element_size)
```

Fall 2021

Scenario: State - Cook - CS5.110

11

11

Behind the Scenes...

- *This is why the C Programming Language uses zero as the first array element*
- If zero is used with this formula, it gets the start of the array

```
start + (index * element_size)
```

Fall 2021

Scenario: State - Cook - CS5.110

12

12

Auxiliary Storage in arrays

- Also, because elements are calculated, there is no extra storage overhead based on the array size
- So, the *auxiliary storage* overhead is $O(1)$



Fall 2021

Scatterplot: Size - Cost - CS: 130

13

13

Resizing Arrays



- A *dynamically allocated array* is resized anytime an object is added or removed
- Because arrays require all elements to be stored continuously...

Fall 2021

Scatterplot: Size - Cost - CS: 130

14

14

Resizing Arrays



- ...the old block of memory (old array) needs to be copied to a new one
- This is extremely costly in both time and resources


Fall 2021

Scatterplot: Size - Cost - CS: 130

15

15

Arrays in Memory




Fall 2021

Scatterplot: Size - Cost - CS: 130

16

16

Copy Values to New Block



Fall 2021

Scatterplot: Size - Cost - CS: 130

17

17

Resizing Arrays is $O(n)$



- While reading / writing elements takes only $O(1)$...
- ... every time an array is resized, it will require $O(n)$ time to copy the old array to the new one

Fall 2021

Scatterplot: Size - Cost - CS: 130

18

18

Fixed-Sized Arrays

- Arrays can also have a fixed sized called a *capacity*
- In this case, the array is *never* resized
- The array is often only partially filled
- An "end" index is maintained




Fall 2021

Scenario: Size - Cost - CS:101

19

19

Fixed-Size Array



Fall 2021


Scenario: Size - Cost - CS:101

20

20

Fixed-Size Wrapping Around

- Sometimes, you might need an array that wraps
- These are useful if both the first and last items can be removed
- ... or older items can be discarded if space is needed



Fall 2021


Scenario: Size - Cost - CS:101

21

21

Fixed-Size Wrapping Around

- In addition to a "end" index, a "start" index is maintained
- Once the end of the array is reached, the array "wraps" to index 0
- ... and continues until end is reached




Fall 2021

Scenario: Size - Cost - CS:101

22

22

Fixed-Size Array



Fall 2021

Scenario: Size - Cost - CS:101

23

23



Linked List Data Structure

CSC 20's Revenge

24

Linked List Data Structure

- Linked lists are a fundamental data structure that was covered in CSC 20
- Data is stored in a series of nodes which are connected with links



Fall 2021

Sacramento State - CS&E - CSC 130

25

25

Linked List Data Structure

- Unlike arrays, where the element can be found using a calculation, linked-lists require the list to be traversed
- So, finding an item in a linked list requires $O(n)$




Fall 2021

Sacramento State - CS&E - CSC 130

26

26

Single-Linked List – Find D




Fall 2021

Sacramento State - CS&E - CSC 130

27

27

Single-Linked List – Find D




Fall 2021

Sacramento State - CS&E - CSC 130

28

28

Single-Linked List – Find D




Fall 2021

Sacramento State - CS&E - CSC 130

29

29

Single-Linked List – Find D



Fall 2021

Sacramento State - CS&E - CSC 130

30

30

Head and Tail Nodes



- Linked lists maintain a link to the head node
- Often, in well-written linked lists, a link to the tail node is also maintained
- Why? It has a huge impact on time complexity


Fall 2021

Sacramento State - CS&E - CS&E 130

31

31

Append Value – No Tail Node




Fall 2021

Sacramento State - CS&E - CS&E 130

32

32

Append Value – No Tail Node




Fall 2021

Sacramento State - CS&E - CS&E 130

33

33

Append Value – No Tail Node




Fall 2021

Sacramento State - CS&E - CS&E 130

34

34

Append Value – No Tail Node



Fall 2021

Sacramento State - CS&E - CS&E 130

35

35

Head and Tail Nodes



- Without a tail node, the entire list must be traversed to find the end
- This will require **$O(n)$**
- Adding a tail node, will decrease it to **$O(1)$**


Fall 2021

Sacramento State - CS&E - CS&E 130

36

36

Append Value – With Tail Node




Fall 2021

Scenario: State - Cook - CS6 130

37

37

Append Value – With Tail Node




Fall 2021

Scenario: State - Cook - CS6 130

38

38

Append Value – With Tail Node



Fall 2021

Scenario: State - Cook - CS6 130

39

39

Use a Tail Node!

- Unless you are only appending nodes at the head of a linked list, maintain a tail node
- For all the examples used in these slides... assume the linked list has a tail node



Fall 2021

Scenario: State - Cook - CS6 130

40

40

Auxiliary Storage in Linked Lists

- Unlike arrays, linked lists must store the "next" links between nodes
- So, the *auxiliary storage* overhead is $O(n)$
 - ...which is usually the size of an address
 - 64-bit system \rightarrow 8 bytes



Fall 2021

Scenario: State - Cook - CS6 130

41

41

Big-O: Test Your Might...

```

LinkedList list;

for(i = 0; i < list.Count; i++)
{
    total += list.Find(i);
}
  
```

$O(n)$

$O(n)$

$O(n^2)$

Fall 2021

Scenario: State - Cook - CS6 130

42

42

Iterators

- To avoid accidental $O(n^2)$, major programming languages support *iterator objects*
- They store information about the current state (e.g. a node) when data is being sequentially read



Fall 2021

Scenarios: State - Cook - CS51.10

43

43

Iterators

- Iterators maintain $O(n)$ for sequentially accessing all the list's elements
- This is the purpose of the For-Each Statement
- Notation varies greatly between languages (when they are supported)



Fall 2021

Scenarios: State - Cook - CS51.10

44

44

Array vs. Linked List

Operation	Array	Linked List
Find (to read or write)	$O(1)$	$O(n)$
Insert (arbitrary)	$O(n)$	$O(n)$
Add first/last	$O(n)$	$O(1)$
Remove first/last	$O(n)$	$O(1)$
Auxiliary storage	$O(1)$	$O(n)$

Fall 2021

Scenarios: State - Cook - CS51.10

45

45




Data Abstraction

Abstraction is power

46

Abstract Data Types

- *Data types* are used in practically all programming languages
- The core data types found in language is known as a *primitive data type*



Fall 2021


Scenarios: State - Cook - CS51.10

47

47

Data Types Specify 2 Things

1. Set of possible values
2. *Operations* on the data
 - these are alternatively called *functions* or *methods*
 - data types often define the errors can occur during each operation



Fall 2021

Scenarios: State - Cook - CS51.10

48

48

Integer Example

- *int* is a type (found in most languages)
- The 32-bit version can contain values from -2^{31} to $2^{31} - 1$

```
int n;
```

Fall 2021

Scenario: State - Cook - CS51.10

49

49

Integer Example

- Operations include: $+$, $*$, $-$, $/$, $\%$, and many more (e.g. comparisons)

```
int n;
```


Fall 2021

Scenario: State - Cook - CS51.10

50

50

Abstract Data Types



- An *abstract data type (ADT)* hides how it is implemented from the *client* (programmer)
- The client only interacts with the defined operations
- This layer of abstraction separates implementation from behavior


Fall 2021

Scenario: State - Cook - CS51.10

51

51

ADTs vs Data Structures



- An ADT is implementation independent
- Can, internally, use any data structure
 - array, linked list, etc...
 - depending how the ADT works, some are better than others


Fall 2021

Scenario: State - Cook - CS51.10

52

52

ADTs vs Data Structures



- ADT defines an *interface*
- It defines:
 - operations (public methods)
 - properties (public fields)


Fall 2021

Scenario: State - Cook - CS51.10

53

53

Data Structures



Fall 2021


Scenario: State - Cook - CS51.10

54

54

Example ADT: Cheese Trader

- Data stores orders of cheese
- The operations supported are
 - buy (cheese, count)
 - sell (cheese, count)
 - cancel (Order)
 - balance – current funds



Fall 2021


Sacramento State - CS&E - CS&E 130

55

55

Example ADT: Cheese Trader

- Error conditions:
 - nonexistent cheese
 - sell a cheese we don't have
 - count is not greater than 0



Fall 2021

Sacramento State - CS&E - CS&E 130

56

56

Cheese Trader API



```
public class CheeseTrader
{
    int buy(string name, int count) Returns order #
    int sell(string name, int count) Returns order #
    void cancel(int order)
    double balance ()
}
```

Fall 2021

Sacramento State - CS&E - CS&E 130

57

57

Bags



Just toss it in

58

Bags

- A bag is one of the most simplistic ADT that stores multiple objects
- It can only add items
- Order doesn't matter – nor is it expected to be maintained



Fall 2021

Sacramento State - CS&E - CS&E 130

59

59

Bags

- At its core, the class only requires one method: **add()**
- Other attributes, such as size, count, etc... and be inferred from return types (i.e. null)



Fall 2021

Sacramento State - CS&E - CS&E 130

60

60

Bag API

```
public class Bag
{
    Bag() Create an empty bag
    void add(Item item)
    bool isEmpty()
    int size()
}
```

Fall 2021

Scatterplot: Data - CS51.10

61

61

Bag Summary

Operation	Fixed Array	Resizable Array	Linked List
Add()	$O(1)$	$O(n)$	$O(1)$

Fall 2021

Scatterplot: Data - CS51.10

62

62

Stacks


Piles of... Data

63

63

Stack

- The *Stack ADT* stores objects based on the concept of a stack of items – like a stack of dishes
- Data can only be added to or removed from the top of the stack



Fall 2021


Scatterplot: Data - CS51.10

64

64

Stack

- This gives a **first-in-last-out** logic (aka FILO)
- Same concept is also called **last-in-first-out** (LIFO)



Fall 2021


Scatterplot: Data - CS51.10

65

65

Stack Operation: Push

- A value is added to the stack
- It is placed on the top location
- Rest of the items are "covered"



Fall 2021


Scatterplot: Data - CS51.10

66

66

Stack Operation: Pop

- Removes an item from the stack
- Last item added is removed
- 2nd item becomes the top



Fall 2021

Stacks: Error Conditions - CS61B

67

67

Stack API

```
public class Stack
{
    Stack() Create empty stack
    void push(Item item)
    Item pop()
    bool isEmpty()
    int size()
}
```

Fall 2021

Stacks: Error Conditions - CS61B

68

68

Stacks: Error Conditions

- The execution of an operation may sometimes cause an error condition, called an *exception*
- Exceptions are said to be “thrown” by an operation that cannot be executed
- In the Stack ADT, operations pop and top cannot be performed if the stack is empty

Fall 2021

Stacks: Error Conditions - CS61B

69

69

Resizing an Array-Based Stack

- For stacks, if a dynamically allocated array is used, each pop/push will require the entire array to be resized
- It will require $O(n)$
- So, a dynamic array is a poor choice



Fall 2021

Stacks: Error Conditions - CS61B

70

70

One Solution... Not a Great One

- The array *could* grow/shrink by a specific # of elements
- So, the array will resize only when a new “block” of elements is needed
- Like a fixed-capacity array, we need to keep an end index



Fall 2021


Stacks: Error Conditions - CS61B

71

71

Fixed-Capacity Stacks

- A fixed-capacity array can be used instead
- For a *fixed-capacity stack*, an array is an excellent choice – in specific situations...



Fall 2021

Stacks: Error Conditions - CS61B

72

72

Array-Based Fixed-Capacity Stack

- The stack would behave as normal until the capacity is reached
- In this case, one of two things will happen...



Fall 2021

Scenario: Stack - Data - CS51B

73

73

When the Stack is filled...

1. Stack throws an *Overflow Error*
2. Stack discards an object
 - the bottom of the stack is typically removed
 - this gives the space needed for the newly pushed object
 - e.g. the history feature of your web browser

Fall 2021

Scenario: Stack - Data - CS51B

74

74

Stack Summary


Operation	Fixed Array	Resizable Array	Linked List
Pop()	$O(1)$	$O(n)$	$O(1)$
Push()	$O(1)$	$O(n)$	$O(1)$
Top()	$O(1)$	$O(1)$	$O(1)$

Fall 2021

Scenario: Stack - Data - CS51B

75


75



76

Queues

- *Queue ADT* stores list of arbitrary objects
- Based on the concept of a line – e.g. when you buy groceries
- Objects enter the back of the line, and must wait for prior items to leave before they do



Fall 2021


Scenario: Stack - Data - CS51B

77

77

Queues

- In most parts of the World, they call a "line" a "queue"
- Main queue operations:
 - *enqueue* (object): place on item on the queue
 - *dequeue*: removes and returns the first inserted object



Fall 2021


Scenario: Stack - Data - CS51B

78

78

Queue Operation: Enqueue

- When an object is "enqueued", it is put on to the **end** of the queue
- The items on the top of the queue are not covered



Fall 2021


Scenario: Stack - Deck - CS6.193

79

79

Queue Operation: Dequeue

- Dequeue removes the item from the front of the queue
- Second item becomes the new first item
- This gives a first-in-first-out logic (aka FIFO)



Fall 2021

Scenario: Stack - Deck - CS6.193

80

80

Auxiliary Queue Operations

- Queues also tend to have some operations defined
- These are not necessary, but they are useful
- Auxiliary operations:
 - peek**: return the next object without removing it. This is also sometimes called "front"
 - size**: returns the number of objects on the queue
 - isEmpty**: indicates whether the queue contains no objects. This is an alternative to size()

Fall 2021

Scenario: Stack - Deck - CS6.193

81

81

Queue API



```
public class Queue
```

```
    Queue ()
```

Create empty queue

```
    void enqueue (Item item)
```

```
    Item dequeue ()
```

```
    bool isEmpty ()
```

```
    int size ()
```

Fall 2021

Scenario: Stack - Deck - CS6.193

82

82

Queue Summary

Operation	Fixed Array	Resizable Array	Linked List
Enqueue()	$O(1)$	$O(n)$	$O(1)$
Dequeue()	$O(1)$	$O(n)$	$O(1)$
Peek()	$O(1)$	$O(1)$	$O(1)$

Fall 2021

Scenario: Stack - Deck - CS6.193

83

83


The Deque ADT

Time to shuffle the "deck"

84

Deque ADT

- There is a variant of the queue called a *deque* (pronounced "deck")
- The name is derived from **d**ouble-**e**nded **q**ueue (sometimes it is shorted more to DQ)



Fall 2021


Sacramento State - CS&E - CS&E 130

85

85

Deque ADT

- As the name implies, it's a queue allows insertions and removals from both ends
- It is a merging of a stack and queue ADT and the operations are union of the two
- Be warned:** name of each operation varies *greatly* between programming languages



Fall 2021

Sacramento State - CS&E - CS&E 130

86

86

Deque ADT

- addFront**
 - place an object on the front of the deque
 - this is same as stack "push"
 - also called: offerFirst, pushFirst
- addBack**
 - place an object on the end of the deque
 - this is the same as queue "enqueue"
 - also called: offerLast, pushLast

Fall 2021

Sacramento State - CS&E - CS&E 130

87

87

Deque ADT

- removeFront**
 - remove an object from the front of the deque
 - same as: queue "dequeue" or stack "pop"
 - also called: pollFirst, popFront
- removeBack**
 - this is unique** – and not found in either a stack or queue ADT
 - also called: pollLast, popBack

Fall 2021

Sacramento State - CS&E - CS&E 130

88

88

Deque API

public class Deque		
	Deque ()	Create empty deque
void	addFront (Item item)	
void	addBack (Item item)	
Item	removeFront ()	
Item	removeBack ()	
bool	isEmpty ()	
int	size ()	

Fall 2021

Sacramento State - CS&E - CS&E 130

89

89

Deque Example

- addFront ('N')
- addBack ('E')
- addFront ('W')
- addBack ('D')
- addFront ('P')



Fall 2021

Sacramento State - CS&E - CS&E 130

90

90

Deque Advantages

- A deque can function as either a stack or queue
- "Add Front" operation can be used to "redo" or "undo" a queue removal – remove then put it back in line
- There are some scenarios where this logic is needed

Fall 2021

Sacramento State - CS&E - CS&E 130

91

91

Deque Disadvantages

- While, Stacks/Queues can be created with a single-linked-list, *a Deque requires a double-linked-list*
- ...otherwise, removing items from the end would require $O(n)$ – *even with a tail node*
- Also, the link overhead (memory requirements) is doubled

Fall 2021

Sacramento State - CS&E - CS&E 130

92

92

Deque Summary

Operation	Fixed Array	Resizable Array	Single Linked List	Double Linked List
addFront()	$O(1)$	$O(n)$	$O(1)$	$O(1)$
addBack()	$O(1)$	$O(n)$	$O(1)$	$O(1)$
removeFront()	$O(1)$	$O(n)$	$O(1)$	$O(1)$
removeBack()	$O(1)$	$O(n)$	$O(n)$	$O(1)$

Fall 2021

Sacramento State - CS&E - CS&E 130

93

93