




Trees

Part 8

1




Introduction to Trees

Let the data grow

2

Introduction to Trees

- In computer science, a tree is an abstract model of a hierarchical structure
- A tree consists of nodes with a parent-child relationship to zero *or more* nodes



Fall 2021


Recursive Data - CS61B, 10/1

3

3

Some Applications

- Organizational charts
- Class hierarchy
- Disk directory and subdirectories
- Structure of a program




Fall 2021

Recursive Data - CS61B, 10/1

4

4

Tree Example



Fall 2021


Recursive Data - CS61B, 10/1

5

5

Trees are Recursive

- Trees are recursive data structures
- They can be defined as smaller instances of trees
- So, using recursion is a natural approach



Fall 2021

Recursive Data - CS61B, 10/1

6

6

Linked Lists vs. Trees

- **Linked Lists**
 - linear - accessing all elements is $O(n)$
 - nodes can only have one predecessor and/or one successor node
- **Trees**
 - nonlinear and hierarchical
 - nodes can have *multiple* successors but only one predecessor

Fall 2021


Searcher's State - Cook - CS131

7

7

Tree Terminology

- **Node**
 - just like in linked lists, the units of linked data are called nodes
 - usually contain data
- **Root**
 - starting point of the tree
 - no nodes link to it
 - e.g. A



Fall 2021


Searcher's State - Cook - CS131

8

8

Tree Terminology

- **Branch**
 - links between nodes
 - often unidirectional
- **Branching-factor**
 - max number of branches any node can have
 - can be 2 to more



Fall 2021


Searcher's State - Cook - CS131

9

9

Tree Terminology

- **Internal node**
 - node with at least one child
 - e.g. A, B, C, G
- **Leaf**
 - aka *external node*
 - node without children
 - e.g. D, E, F, H, I, J



Fall 2021


Searcher's State - Cook - CS131

10

10

Tree Terminology

- **Ancestor node**
 - predecessors
 - human-like lineage names: parent, grandparent, etc.
- **Descendant node**
 - successors
 - e.g. child, grandchild, great-grandchild, etc.



Fall 2021


Searcher's State - Cook - CS131

11

11

Tree Terminology

- **Depth of a node**
 - # of ancestors to the root
 - e.g. depth of F is 2
- **Height of a tree**
 - maximum depth of any node
 - e.g. this tree is 3



Fall 2021

Searcher's State - Cook - CS131


12

12

Tree Terminology

Size of the tree

- total number of nodes
- this tree has a size of 10




Fall 2021

Scatterplot: Size - Count - CS510

13

13

Tree Terminology



Fall 2021

Scatterplot: Size - Count - CS510

14

14

General Tree Node ADT

```
class Node
  public Object value;    //Anything
  public Node[] branches;
end class
```


Array, or better, a linked list

Fall 2021

Scatterplot: Size - Count - CS510

15

15




Depth-First Tree Traversal

Climbing Down

16

Tree Traversal

- A *tree traversal* visits the nodes of a tree in a systematic manner
- Given that trees can be defined into smaller and smaller subtrees, *recursion is an eloquent solution*



Fall 2021


Scatterplot: Size - Count - CS510

17

17

Tree Traversal

- When a node is *"visited"*, its contents are analyzed
- This can be before or after its children are visited
- The order of recursion vs. visiting the current node has a *huge* impact on the algorithm



Fall 2021

Scatterplot: Size - Count - CS510

18

18

Depth-First Transversal

- In depth-first transversal, the algorithm travels down the tree
- This approach lends itself to recursion
 - root recurses into its children
 - each child recurses into each of its children
 - ... and so on...
- There are several approaches of when a node is "visited"


Fall 2021

Scenario: State - Cook - CS510

19

19

Depth First Traversal



Fall 2021


Scenario: State - Cook - CS510

20

20

Depth-first: Preorder

- In a *preorder traversal*, a node is visited **before** its descendants
- In the image to the right, nodes will be visited in the order they are numbered



Fall 2021


Scenario: State - Cook - CS510

21

21

Depth-first: Preorder

- Notice that each child was visited **after** its parent
- Some uses...
 - print a tree document
 - e.g. XML export



Fall 2021

Scenario: State - Cook - CS510

22

22

Preorder Traversal Logic

```
function preOrder(n)
  visit(n)

  for each child c in n
    preOrder(c)
  end for
end function
```

Fall 2021


Scenario: State - Cook - CS510

23

23

Depth First: Postorder

- In a *postorder traversal*, a node is visited **after** its descendants
- Notice that each child was visited **before** its parent



Fall 2021


Scenario: State - Cook - CS510

24

24

Some Uses for Postorder

- Compute space used child nodes
- Calculate folder space
- Expression evaluation (an alternative to the stack algorithm)



Fall 2021

Scatterplot: Size - Count - CDS 130

25

25

Depth First: Postorder

```

function postOrder(n)
  for each child c in n
    postOrder(c)
  end for

  visit(n)
end function
    
```

Fall 2021


Scatterplot: Size - Count - CDS 130

26

26

Breadth-first Traversal

- In a *breadth-first* traversal, nodes are visited by their level in the tree
- So, the traversal, looks at all the nodes at depth 1, then at 2, etc...



Fall 2021

Scatterplot: Size - Count - CDS 130

27

27

Breadth-first Traversal

```

function breadthFirst(n)
  for each child c in n
    visit(c)
  end for

  for each child c in n
    breadthFirst(c)
  end for
end function
    
```

Fall 2021

Scatterplot: Size - Count - CDS 130


28

28

Test Your Might

What is the order the nodes are visited using depth-first *pre-order* traversal?

ABECFIJGHD



Fall 2021

Scatterplot: Size - Count - CDS 130


29

29

Test Your Might

What is the order the nodes are visited using depth-first *post-order* traversal?

EBIJFGHCDA



Fall 2021

Scatterplot: Size - Count - CDS 130


30

30

Test Your Might

What is the order the nodes are visited using depth-first *breadth-first* traversal?

ABCDEF GHIJ



31


Binary Trees

The Power of Two!

32

Binary Trees


- The most common tree used in data structures is in the style of the binary tree
- As the name implies, nodes in a binary tree only have two successors



33

Binary Trees

- We call the children of an internal node *left child* and *right child*
- Binary trees can be represented by arrays and linked data structures



34

Binary Trees

- Binary Trees are extremely useful in data structures
- The two branches allow for efficient branching and is ideal for binary operations
- Applications:
 - storing arithmetic expressions
 - decision processes
 - searching
 - sorting


35

Boolean Decision Tree



36

Boolean Decision Tree



37

Binary Tree Node

```

class Node
  public Object value; //Can be anything
  public Node left;
  public Node right;
end class
  
```

Branches are much simpler

38

Attributes of a Binary Tree

- $v = i + 1$
- $n = 2v - 1$
- $h \leq i$
- $h \leq (n - 1) / 2$
- $v \leq 2h$
- $h \geq \log_2 v$
- $h \geq \log_2 (n + 1) - 1$

n	number of nodes
i	number of internal nodes
v	number of leaves
h	height of the tree

39




Depth-First
Traversing
Binary Trees

With simplicity, we have power!

40

Depth-First Traversing


- Because of the simplicity of binary trees, we have a very useful structure for tree traversal
- We can only traverse left and right
- This gives **three** possibilities for a depth first search



41

Post-order Depth-first Traversal


- In an *post-order traversal* a node is evaluated **after** its left branch and **after** its right branch
- In other words: recurse left, recurse right, then do something



42

Arithmetic Expression Tree

- Expressions can be represented with a tree
- How?
 - internal nodes: operators
 - leaves: operand



Fall 2021


Secretmario Stale - Gosh - CS51.103

43

43

Arithmetic Expression Tree

- It can be evaluated using a depth-first traversal
- ... notice that the node's children need a result before the node can be evaluated



Fall 2021

Secretmario Stale - Gosh - CS51.103

44

44

Post-order: Evaluate Expressions

- A post-order traversal can be used to evaluate the tree
- Each recursive call (left, right) returns a value – the result of its calculation
- The node that applies the operator to the two returned values

Fall 2021

Secretmario Stale - Gosh - CS51.103

45

45

Post-order: Evaluate Expressions

```
function evaluate(Node n)
  if n is a leaf
    return n.value
  else
    x ← evaluate(n.left)
    y ← evaluate(n.right)
    ⋄ ← operator stored at n
    return x ⋄ y
  end if
end function
```

Fall 2021


Secretmario Stale - Gosh - CS51.103

46

46

In-order Depth-first Traversal

- In an *in-order* traversal a node is visited after its left branch and before its right branch
- In other words: recurse left, do something, then recurse right



Fall 2021


Secretmario Stale - Gosh - CS51.103

47

47

Some In-order Applications

- Draw a binary tree
- Heap sorting
- Binary searching – $O(\log n)$ when sorted



Fall 2021

Secretmario Stale - Gosh - CS51.103

48

48


Depth First: In-order

```
function inOrder(n)
  inorder(n.left)
  visit(n)
  inorder(n.right)
end function
```

49

In-order: Print Expressions

- In-order can be used to easily print an expression stored in a tree
- Print....
 - "(" then traverse left
 - the node's operator
 - ")" then traverse right




50

In-order: Print Expressions

```
function print(Node n)
  if n is a leaf
    write n.value
  else
    write "("
    print(n.left)
    write n.operator
    print(n.right)
    write ")"
  end if
end function
```

51


In-order: Print Expressions



52

Pre-order Depth-first Traversal

- When a *pre-order* depth-first traversal is performed, the node is visited before the right or left child
- This is useful for copying a tree, but not much more



53