



## Binary Search Trees


- Binary Search Tree (BST) is a special type of binary tree that sorts nodes by value
- For each node...

3

5

- all the nodes on the <u>left</u> branch are <u>less than</u> it
- all the nodes on the <u>right</u> branch are greater than it

Sacramento State - Cook - CSc 130



Searching the Tree

- Since the tree divides the problem progressively by two, the time complexity is only O(log n)
- Which gives that all the benefits of a sorted array
- Worst case is O(n) if the tree is a list-like chain



2021 Sacramento State - Cook - CSc 130


4


## Search logic (looking for S)


- Looking for If S is equal to the current node, you found it
- If S is smaller than the current node, take the left branch
- If S is bigger than the current node, take the right branch
- If there are no branches, S was not found




\_\_\_\_\_












Inserting into the Tree Inserting is handled exactly like a search The only difference is that if the item is not found, the node is  $\mbox{\sc added}$ If we reach a leaf... · we are already at the max-depth of the tree · we are at the node that needs to be updated • so, add a left or right node (based on value) · ... wow, this is easy!

10







## Binary Search Trees vs. Arrays

- Insert into a Binary Search Tree
  - · traverses down the tree
  - · then add itself as a leaf
  - it requires only O(log n)
- Insert into an Array

14

16

- · must expanded when new elements are added
- · ...and compacted when elements are removed
- these requires O(n)

13


Deleting From a **BST** Not as easy as Heaps 15


Deleting From a BST Deleting from a BST is a tad more tricky When the node is deleted, the tree needs to be re-linked to still preserve the ordering


Deleting From a BST Fortunately, while the logic might seem a tad hard, it is fairly straight forward There are 3 different scenarios that must be taken into account based on the node being deleted


Case 1: The Node is a Leaf • If the node (to be deleted) is a leaf, it can simply be removed from the parent This is due to, the fact that, nothing is linked from the node

18 17













21 22






23 24









We need to find a value that is mathematically next to the deleted value
 There are two equally valid options
 Choose one:

 find the maximum node of the left (smaller) branch
 ... or find the minimum node of the right (larger) branch


Case 3: Two Children


27 28







29














33 34














This can easily occur of the data is not truly random (which is generally the case)
 When this happens, the time complexity slowly deteriorates to O(n)


39 40







41 42









45 46

## Sort in a Binary Search Tree?

- Unfortunately, while this might seem like a good idea, this is not a great solution
- Binary Search Trees can deteriorate into linked lists
- So
  - $O(log\ n)$  search can quickly deteriorate to O(n)
  - ...and O(n log n) sort can deteriorate to O(n²)

221 Sacramento State - Cook - CSc 130