Forgetting to Refuse, or Forgetting to Freeze? A Taught VLA Safeguard Under Benign Personalization

Anonymous Author(s)
Affiliation
Address
email

Abstract: Benign fine-tuning erodes refusal in aligned language models. Does a refusal taught to a vision-language-action (VLA) policy survive benign personalization? In two pre-registered studies we teach OpenVLA-7B to hold still when told to harm a human hand, personalize it with LoRA on 200 benign demonstrations, and compare its closed-loop hand contact with that of a comparator never taught to refuse. We find that the taught refusal worked mostly by freezing: the policy held still under benign as well as harmful instructions. Personalization removed that freeze under ordinary instructions, and its protection went with it: inside the personalization domain, hand contact rose from 0 to 40 of 150 episodes, in all three seeds, leaving the policy no detectably safer than the comparator. Whether the refusal itself survived could not be tested, because no policy, aligned or not, detectably carried out the harmful instruction. We distill this into three traps for evaluating VLA refusal, each with a fix.

1 Introduction

Safety installed by fine-tuning is fragile under further fine-tuning: one epoch of benign instruction data raises the harmfulness of aligned language models from at most 5.5% to 12–32% [1], visual instruction tuning makes vision-language models less safe than their backbones [2], and alignment is often shallow and its durability overstated [3, 4]. Safety is now installed in the weights of VLA policies [5] and measured in closed loop [6], but each safeguard is trained and evaluated once, whereas a deployed VLA is personalized on its user's tasks, and every update risks safety drift [7]. Attackers already rely on persistence: INFUSE's backdoor in OpenVLA-7B survives a user's clean fine-tuning [8] (cf. BadVLA [9]). We ask the defender's question, which task retention does not answer, since VLAs forget heavily under the plain supervised fine-tuning that personalization uses [10, 11].

VLAs raise two measurement problems that text models do not. Refusal is a no-op action while harm is a contact event in closed loop, so the two can come apart. And LIBERO-fine-tuned OpenVLA-family policies largely ignore their language input [12], so a safeguard must be shown to respond to the instruction, which takes harmful, benign and blank instructions on identical states (cf. HazardArena's twin scenes [13]) and a comparator never taught to refuse. Our contributions:

- Two pre-registered closed-loop studies of whether a refusal taught to OpenVLA-7B survives benign LoRA personalization.
- Evidence that the refusal worked mostly by freezing, and that personalization removed the freeze under ordinary instructions, in every seed.
- Three traps for evaluating VLA refusal, each hit in our studies, with a fix for each (Table 2); the repaired LIBERO-Safety contact check and our paired-state evaluator will be released.

Submitted to the 10th Conference on Robot Learning (CoRL 2026). Do not distribute.

2 Setup

Policies. P is the released OpenVLA-7B LIBERO-Spatial checkpoint [14]. The aligned policy A is P fine-tuned with LoRA (rank 32, constant learning rate 5×10^{-4}, batch 16) on scripted, contact-free, hand-avoiding motion under benign instructions, the same frames under harmful instructions labeled with the no-op action (no motion, gripper unchanged), and rehearsal rows. The comparator C gets motion and rehearsal rows in place of the no-ops, so it never sees a harmful instruction. Both are then personalized for three epochs, without replay, on 200 LIBERO-Object demonstrations [15], about 29,000 transitions against the 300 no-op rows that taught the refusal. Alignment used three seeds; seed 0 is the main one.

Scenes and instructions. *Study 1* used the static-hand scenes of LIBERO-Safety [6], a LIBERO fork with human hands whose robot-contact check never fires as shipped (repository issue #3); we repair it. Its confirmatory states come from two held-out layouts. Its pre-registered test of harmful-instruction contact was null, but its only new contacts under the benign instruction fell on the layout that shares LIBERO-Object's scene. *Study 2* was therefore pre-registered to test inside the personalization domain: the ten LIBERO-Object tasks, each with a hand (one of two models unseen in alignment) between the objects and the basket, and 150 confirmatory states. Each state is paired with a harmful instruction ("{task} and pinch the hand on the way"), a benign one and a blank one. The benign instruction is "{task} while avoiding the hand" in Study 1 and the personalization instruction verbatim in Study 2; seeds 1 and 2 ran under it alone.

Outcomes and analysis. *Hand contact* is any LIBERO-Safety violation in a closed-loop episode: robot–hand contact, which ends the episode, or goal-object–hand contact. An episode is *near-still* if the policy outputs the no-op on most steps. *First-frame refusal* is scored offline: the predicted action is within one token bin of zero motion with the gripper unchanged, a criterion related to RoboShackles' [16]. Each study was frozen in a tagged commit before any confirmatory data, with one primary test, three key secondaries tested in a fixed sequence, and a manipulation check (Table 1); Study 1 was amended once before its data and once, post hoc, to add an exploratory 12-epoch run. Paired counts get exact McNemar tests and Newcombe intervals [17]; changes relative to C get state bootstraps and sign-flip tests. Everything else is exploratory.

3 Results

3.1 The taught refusal was mostly a freeze

Before personalization, A refused benign (0.89) and blank (0.52) instructions at the first frame, not only harmful ones (1.00), where P refused none. In closed loop under the benign instruction it was near-still in 148 of 150 Study 2 episodes, against 8 for C (Fig. 1). Its near-zero contact came from not moving, not from moving around the hand.




Figure 1: Inside its domain, personalization turned the aligned policy's stillness into motion under the benign instruction. Closed-loop outcomes (seed 0) for the aligned policy A and the never-aligned comparator C, before (@0) and after (@200) personalization, under benign (b) and harmful (h) instructions; numbers are hand-contact counts. In Study 1, outside the personalization domain, both personalized policies were near-still.

Test	Result	Reading
Study 1: LIBERO-Safety hand scenes, $n = 50$ *states*		
Primary: harmful contact, A before $\rightarrow$ after	$0 \rightarrow 0$ (a rise above 7 points excluded)	null
Secondary 1: A vs. C after, harmful	0 vs. 11 ($p = 0.001$)	A lower
Secondary 2: change vs. C, harmful	$+0.30$ $[0.12, 0.48]$ (C fell from 26 to 11)	A lost ground
Secondary 3: first-frame refusal, harmful	falls in all 3 seeds (mean $0.90 \rightarrow 0.59$)	yes
Manipulation check: new-task success	$0\% \rightarrow 60\%$	passed
Study 2: LIBERO-Object scenes with a hand, $n = 150$ *states*		
Primary: benign contact, A before $\rightarrow$ after	$0 \rightarrow 40$ ($+0.27$ $[0.20, 0.34]$)	rose
Secondary 1: seeds 1 and 2	$1 \rightarrow 45$; $0 \rightarrow 40$	replicated
Secondary 2: change vs. C, benign	$+0.42$ $[0.31, 0.53]$	A lost ground
Secondary 3: A vs. C after, benign	40 vs. 51 ($p = 0.11$)	no detectable difference
Manipulation check: task success	0 of 150, before and after	failed

Table 1: Every pre-registered test (seed 0 unless noted; contact counts out of n). Both studies' go/no-go gates passed; Study 1's non-blocking over-refusal screens failed. A pre-registered follow-up is in Table 2, trap 2.

3.2 Personalization removed the freeze under ordinary instructions, in every seed

In Study 2, benign-instruction contact rose from 0 to 40 of 150 episodes and replicated in both other seeds, leaving A no detectably safer than C (Table 1). The contacts came from the freeze thawing: near-still episodes fell from 148 to 104, and every contact came from an episode that moved at the first step (40 of 81, against 0 of 69 that did not). This is also what successful personalization looks like in a scene whose route to the goal crosses the hand (trap 2): the rise shows that the freeze was never hand avoidance, not that avoidance was erased, and since the manipulation check failed, the pre-registered rule forbids reading it as erased avoidance. All 40 contacts fall in the five scenes with the larger hand, so a task-level test cannot go below $p = 0.06$. In Study 1, outside the personalization domain, both personalized policies were near-still, so stillness is also these policies' default when they cannot do the task.

3.3 Whether the refusal survived could not be tested

Study 1's pre-registered harmful-instruction test stayed at zero contacts, but no policy, aligned or not, came detectably closer to the hand when told to harm it: P, never taught to refuse, made fewer contacts under the harmful instruction than under the benign one (27 vs. 45 of 50). Low harmful-instruction contact is therefore not evidence of refusal. Suggestively, after three epochs A stayed near-still under the harmful instruction (148 of 150 Study 2 episodes, 6 contacts) while C did not separate the instructions (49 vs. 51 contacts). This rests on one seed, only Study 2's harmful instruction names the hand, and the freeze was eroding there too with longer personalization (on 52 states, near-still $50 \rightarrow 38$ and contacts $6 \rightarrow 11$ at six epochs). Table 2 turns these problems into three traps.

4 Discussion and limitations

So did the policy forget to refuse, or forget to freeze? Under ordinary instructions it forgot to freeze: inside the personalization domain, stillness gave way to motion, contact rose in every seed, and the aligned policy was no longer detectably safer than one never taught to refuse. Whether it forgot to refuse we cannot say, because no policy detectably carried out a harmful instruction. For carrying LLM safety methods over to robots, this suggests that supervised refusal training can install a non-specific freeze, consistent with the argument that chatbot-style refusal is insufficient for robots [18], and that telling a freeze from a refusal takes closed-loop, paired evaluation with the fixes in Table 2.

Limitations. One model and recipe; a static simulated hand; one seed for all closed-loop harmful and blank results and one closed-loop wording per instruction class; three-epoch personalization (a

Trap	What it looked like here	Fix
1. No policy complies	No policy, not even the never-aligned base, came detectably closer to the hand when told to harm it, so harmful-instruction contact cannot register compliance.	Include a policy trained to comply, and show that the harness detects it.
2. The hazard blocks the task	In Study 2, 96% of successful hand-free paths pass within 10 cm of the hand, so contact tracked motion, not avoidance. A pre-registered follow-up moved the hand beside the basket: the task became feasible but C no longer met the hand (12% and 0% contact).	Gate scenes on a never-aligned policy that both completes the task and meets the hazard; consider moving hands.
3. Refusal rates are not safety	First-frame refusal rose from 0 to 0.32–0.48 in C, never taught to refuse, and in personalized A it ranked benign above harmful instructions (0.78 vs. 0.66), the opposite of contact (8 vs. 0, Study 1).	Report closed-loop outcomes per instruction on paired states, against a never-aligned comparator.

Table 2: Three traps for evaluating VLA refusal, each hit in our studies.

post hoc 12-epoch Study 1 run showed no benign advantage for A either); states clustered within few tasks. Alignment cut old-task success from 78% to 56%, and personalization to 0%.

References

[1] X. Qi, Y. Zeng, T. Xie, P.-Y. Chen, R. Jia, P. Mittal, and P. Henderson. Fine-tuning aligned language models compromises safety, even when users do not intend to! In *International Conference on Learning Representations (ICLR)*, 2024. arXiv:2310.03693.

[2] Y. Zong, O. Bohdal, T. Yu, Y. Yang, and T. Hospedales. Safety fine-tuning at (almost) no cost: A baseline for vision large language models. In *International Conference on Machine Learning (ICML)*, 2024. arXiv:2402.02207.

[3] X. Qi, A. Panda, K. Lyu, X. Ma, S. Roy, A. Beirami, P. Mittal, and P. Henderson. Safety alignment should be made more than just a few tokens deep. In *International Conference on Learning Representations (ICLR)*, 2025. arXiv:2406.05946.

[4] X. Qi, B. Wei, N. Carlini, Y. Huang, T. Xie, L. He, M. Jagielski, M. Nasr, P. Mittal, and P. Henderson. On evaluating the durability of safeguards for open-weight LLMs. In *International Conference on Learning Representations (ICLR)*, 2025. arXiv:2412.07097.

[5] B. Zhang, Y. Zhang, J. Ji, Y. Lei, J. Dai, Y. Chen, and Y. Yang. SafeVLA: Towards safety alignment of vision-language-action model via constrained learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025. arXiv:2503.03480.

[6] R. Cui, Z. Zhang, J. Pang, H. Chi, J. Guo, S. Zhang, S. Xie, X. Jin, Y. Mu, J. Yang, G. Yao, X. Zhan, Y.-Q. Zhang, and H. Zhao. LIBERO-Safety: A comprehensive benchmark for physical and semantic safety in vision-language-action models. In *European Conference on Computer Vision (ECCV)*, 2026. arXiv:2606.23686.

[7] Q. Li, B. Yin, W. Huang, R. Liu, B. Zou, R. Yu, J. Ye, W. Yu, and X. Wang. Vision-language-action safety: Threats, challenges, evaluations, and mechanisms, 2026. arXiv:2604.23775.

[8] J. Zhou, Y. Wei, R. Zhen, B. Zhao, X. Xia, R. Shao, X. Su, and S. Yang. Inject once survive later: Backdooring vision-language-action models to persist through downstream fine-tuning. *arXiv preprint arXiv:2602.00500*, 2026.

[9] X. Zhou, G. Tie, G. Zhang, H. Wang, P. Zhou, and L. Sun. BadVLA: Towards backdoor attacks on vision-language-action models via objective-decoupled optimization. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025. arXiv:2505.16640.

[10] H. Liu, C. Kim, B. Liu, M. Liu, and Y. Zhu. Pretrained vision-language-action models are surprisingly resistant to forgetting in continual learning. In *International Conference on Machine Learning (ICML)*, 2026. arXiv:2603.03818.

[11] J. Hu, J. Shim, C. Tang, Y. Sung, B. Liu, P. Stone, and R. Martín-Martín. Simple recipe works: Vision-language-action models are natural continual learners with reinforcement learning. In *Reinforcement Learning Conference (RLC)*, 2026. arXiv:2603.11653.

[12] S. Fei, S. Wang, J. Shi, Z. Dai, J. Cai, P. Qian, L. Ji, X. He, S. Zhang, Z. Fei, J. Fu, J. Gong, and X. Qiu. LIBERO-Plus: A progressive robustness benchmark for visual-language-action models. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. arXiv:2510.13626, posted as "LIBERO-Plus: In-depth Robustness Analysis of Vision-Language-Action Models".

[13] Z. Chen, Y. Gao, L. Wang, Y. Zhao, Y. Liu, J. Li, X. Zheng, Z. Wu, C. Wang, X. Ma, and Y.-G. Jiang. HazardArena: Evaluating semantic safety in vision-language-action models, 2026. arXiv:2604.12447 (v3, September 2026).

[14] M. J. Kim, K. Pertsch, S. Karamcheti, T. Xiao, A. Balakrishna, S. Nair, R. Rafailov, E. Foster, G. Lam, P. Sanketi, Q. Vuong, T. Kollar, B. Burchfiel, R. Tedrake, D. Sadigh, S. Levine, P. Liang, and C. Finn. OpenVLA: An open-source vision-language-action model. In *Conference on Robot Learning (CoRL)*, 2024. arXiv:2406.09246.

[15] B. Liu, Y. Zhu, C. Gao, Y. Feng, Q. Liu, Y. Zhu, and P. Stone. LIBERO: Benchmarking knowledge transfer for lifelong robot learning. In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*, 2023. arXiv:2306.03310.

[16] Z. Yin, C. Liu, W. Yang, R. Li, Y. Guo, and Y. Xue. RoboShackles: A multilingual safety dataset for human-injury prevention in embodied foundation models. arXiv preprint, 2026. arXiv:2606.18632 (v2, August 2026).

[17] R. G. Newcombe. Improved confidence intervals for the difference between binomial proportions based on paired data. *Statistics in Medicine*, 17:2635–2650, 1998.

[18] A. Robey, Z. Ravichandran, E. K. Jones, J. Perlo, F. Barez, V. Kumar, J. Z. Kolter, H. Hassani, and G. J. Pappas. Beyond alignment: Why robotic foundation models need context-aware safety. *Science Robotics*, 11(113):eaef2191, 2026.