Executive Summary

The Problem

Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server. Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server.

Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server. Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server.

Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server. Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server.

Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server. Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server.

Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server. Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server.

Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server. Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server.

Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server. Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server.

Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server. Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server.

Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server. Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server.

Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server. Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server.

Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server. Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server.

Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server. Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server.

Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server. Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server.

Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server. Ember replaces static context files with a typed knowledge graph that populates itself from the tools a team already uses, and serves that knowledge to any AI coding agent on demand through a Model Context Protocol server.