

Recall Horn formulas are easy to solve

Recall Horn formulas are easy to solve

How about more general formulas: CNF (conjunction normal form)?

Recall Horn formulas are easy to solve

How about more general formulas: CNF (conjunction normal form)?

Definition

and

A **CNF formula** is a conjunction of clauses, where each clause is a disjunction of literals

or

Recall Horn formulas are easy to solve

How about more general formulas: CNF (conjunction normal form)?

Definition

A **CNF formula** is a conjunction of clauses, where each clause is a disjunction of literals

Example: $(v_1 \vee x_2 \vee \bar{x}_3 \vee x_4) \wedge (x_3 \vee \bar{x}_5 \vee x_6) \wedge (\bar{x}_4 \vee x_7)$

Recall Horn formulas are easy to solve

How about more general formulas: CNF (conjunction normal form)?

Definition

A **CNF formula** is a conjunction of clauses, where each clause is a disjunction of literals

Example: $(x_1 \vee x_2 \vee \bar{x}_3 \vee x_4) \wedge (x_3 \vee \bar{x}_5 \vee x_6) \wedge (\bar{x}_4 \vee x_7)$

Definition

A **k-CNF** is a CNF where each clause contains exactly k literals

3-CNF

The Satisfiability Problem

The Satisfiability Problem (SAT)

The Satisfiability Problem

The Satisfiability Problem (SAT)

Instance: A CNF ϕ

The Satisfiability Problem

The Satisfiability Problem (SAT)

Instance: A CNF Φ

Objective: Decide if Φ is satisfiable, i.e., is there an assignment so that Φ is true?

The Satisfiability Problem

The Satisfiability Problem (SAT)

Instance: A CNF Φ

Objective: Decide if Φ is satisfiable, i.e., is there an assignment so that Φ is true?

The k -Satisfiability Problem (k -SAT)

Instance: A k -CNF Φ

Objective: Decide if Φ is satisfiable

3-SAT and Independent Set

Theorem

$3\text{-SAT} \leq_P \text{Independent Set}$

3-SAT and Independent Set

Theorem

$3\text{-SAT} \leq_P \text{Independent Set}$

Proof.

3-SAT and Independent Set

Theorem

$3\text{-SAT} \leq_P \text{Independent Set}$

Proof. First consider an intuition for solving SAT:

$$\Phi = (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \bar{x}_3 \vee x_4) \wedge (x_3 \vee \bar{x}_1 \vee x_5)$$

3-SAT and Independent Set

Theorem

$3\text{-SAT} \leq_P \text{Independent Set}$

Proof. First consider an intuition for solving SAT:

- pick one literal from each clause

$$\Phi = (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \bar{x}_3 \vee x_4) \wedge (x_3 \vee \bar{x}_1 \vee x_5)$$

3-SAT and Independent Set

Theorem

$3\text{-SAT} \leq_P \text{Independent Set}$

Proof. First consider an intuition for solving SAT:

- pick one literal from each clause
- select an assignment that satisfies all selected literals

$$\Phi = (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \bar{x}_3 \vee x_4) \wedge (\bar{x}_3 \vee \bar{x}_1 \vee x_5)$$

$$x_1=1 \quad x_2=1 \quad x_3=1$$

$x_4 \quad x_5$

3-SAT and Independent Set

Theorem

$3\text{-SAT} \leq_P \text{Independent Set}$

Proof. First consider an intuition for solving SAT:

- pick one literal from each clause
- select an assignment that satisfies all selected literals
- make sure there's no conflict:

$$\Phi = (\underbrace{x_1}_{\text{selected}} \vee x_2 \vee x_3) \wedge (x_2 \vee \underbrace{\bar{x}_3}_{\text{selected}} \vee x_4) \wedge (\underbrace{x_3}_{\text{selected}} \vee \bar{x}_1 \vee x_5)$$

3-SAT and Independent Set

Theorem

$3\text{-SAT} \leq_P \text{Independent Set}$

Proof. First consider an intuition for solving SAT:

- pick one literal from each clause
- select an assignment that satisfies all selected literals
- make sure there's no conflict: Don't pick x from one clause and \bar{x} from another

$$\Phi = (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \bar{x}_3 \vee x_4) \wedge (x_3 \vee \bar{x}_1 \vee x_5)$$

3-SAT and Independent Set

Theorem

$3\text{-SAT} \leq_P \text{Independent Set}$

Proof. First consider an intuition for solving SAT:

- pick one literal from each clause
- select an assignment that satisfies all selected literals
- make sure there's no conflict: Don't pick x from one clause and \bar{x} from another

$$\Phi = (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \bar{x}_3 \vee x_4) \wedge (x_3 \vee \bar{x}_1 \vee x_5)$$

↑ good ↑ ↑

3-SAT and Independent Set

Theorem

$3\text{-SAT} \leq_P \text{Independent Set}$

Proof. First consider an intuition for solving SAT:

- pick one literal from each clause
- select an assignment that satisfies all selected literals
- make sure there's no conflict: Don't pick x from one clause and \bar{x} from another

$$\Phi = (\overset{\text{bad}}{\downarrow} \underbrace{x_1}_{\text{good}} \vee x_2 \vee x_3) \wedge (x_2 \vee \underbrace{\bar{x}_3}_{\uparrow} \vee x_4) \wedge (\overset{\downarrow}{x_3} \vee \bar{x}_1 \vee \underbrace{x_5}_{\uparrow})$$

$x_1 = 1$ $x_3 = 0$ $x_5 = 1$

3-SAT and Independent Set

Theorem

$3\text{-SAT} \leq_P \text{Independent Set}$

Proof. First consider an intuition for solving SAT:

- pick one literal from each clause
- select an assignment that satisfies all selected literals
- make sure there's no conflict: Don't pick x from one clause and \bar{x} from another

$$\Phi = (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \bar{x}_3 \vee x_4) \wedge (x_3 \vee \bar{x}_1 \vee x_5)$$

Diagram illustrating the formula Φ with annotations:

- Red arrow pointing down to x_1 labeled "bad"
- Green arrow pointing up to x_1 labeled "good"
- Red arrow pointing down to \bar{x}_3
- Green arrow pointing up to x_3
- Red arrow pointing down to x_3
- Green arrow pointing up to x_3

We encode a CNF as a graph, and encode an assignment as independent sets (to keep track of the conflicts)


Consider a 3-SAT instance with variables x_1, \dots, x_n , and clauses C_1, \dots, C_k

Consider a 3-SAT instance with variables x_1, \dots, x_n , and clauses C_1, \dots, C_k

We build a graphs $G = (V, E)$ with $3k$ vertices,

Consider a 3-SAT instance with variables x_1, \dots, x_n , and clauses C_1, \dots, C_k

We build a graphs $G = (V, E)$ with $3k$ vertices, grouped into k triangles.




Consider a 3-SAT instance with variables x_1, \dots, x_n , and clauses C_1, \dots, C_k

We build a graph $G = (V, E)$ with $3k$ vertices, grouped into k triangles.

Each triangle contains v_{i1}, v_{i2}, v_{i3} where v_{ij} corresponds to the j -th literal in C_i .


$$\phi = (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \bar{x}_3 \vee x_4) \wedge (x_3 \vee \bar{x}_1 \vee x_5)$$



Consider a 3-SAT instance with variables x_1, \dots, x_n , and clauses C_1, \dots, C_k

We build a graph $G = (V, E)$ with $3k$ vertices, grouped into k triangles.


Each triangle contains v_{i1}, v_{i2}, v_{i3} where v_{ij} corresponds to the j -th literal in C_i . Add edges for conflicts, i.e., x_j and \bar{x}_j :



Consider a 3-SAT instance with variables x_1, \dots, x_n , and clauses C_1, \dots, C_k

We build a graphs $G = (V, E)$ with $3k$ vertices, grouped into k triangles.

Each triangle contains v_{i1}, v_{i2}, v_{i3} where v_{ij} corresponds to the j -th literal in C_i . Add edges for conflicts, i.e., x_j and \bar{x}_j :




At most one vertex in each triangle can be in an independent set,

Consider a 3-SAT instance with variables x_1, \dots, x_n , and clauses C_1, \dots, C_k

We build a graphs $G = (V, E)$ with $3k$ vertices, grouped into k triangles.

Each triangle contains v_{i1}, v_{i2}, v_{i3} where v_{ij} corresponds to the j -th literal in C_i . Add edges for conflicts, i.e., x_j and \bar{x}_j :



At most one vertex in each triangle can be in an independent set, so the size of an independent set cannot be larger than k

- If there exists a satisfying assignment, there exists a satisfied literal in each clause (triangle).

- If there exists a satisfying assignment, there exists a satisfied literal in each clause (triangle). Pick such a literal and include it into the independent set

- If there exists a satisfying assignment, there exists a satisfied literal in each clause (triangle). Pick such a literal and include it into the independent set

There is no conflicts. It's in fact an independent set

- If there exists a satisfying assignment, there exists a satisfied literal in each clause (triangle). Pick such a literal and include it into the independent set

There is no conflicts. It's in fact an independent set

- If there exists an independent set S of size k , every triangle contains a vertex from S .

- If there exists a satisfying assignment, there exists a satisfied literal in each clause (triangle). Pick such a literal and include it into the independent set

There is no conflicts. It's in fact an independent set

- If there exists an independent set S of size k , every triangle contains a vertex from S . We can choose an assignment so that all literals (vertices of S) are satisfied — there's no conflicts

- If there exists a satisfying assignment, there exists a satisfied literal in each clause (triangle). Pick such a literal and include it into the independent set

There is no conflicts. It's in fact an independent set

- If there exists an independent set S of size k , every triangle contains a vertex from S . We can choose an assignment so that all literals (vertices of S) are satisfied — there's no conflicts

So the 3-CNF has a satisfying assignment if and only if G has an independent set of size k




Example of the reduction

Consider $\Phi = (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \bar{x}_3 \vee x_4) \wedge (x_3 \vee \bar{x}_1 \vee x_5)$


Example of the reduction

Consider $\Phi = (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \bar{x}_3 \vee x_4) \wedge (x_3 \vee \bar{x}_1 \vee x_5)$




Example of the reduction

Consider $\Phi = (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \bar{x}_3 \vee x_4) \wedge (x_3 \vee \bar{x}_1 \vee x_5)$



Example of the reduction

Consider $\Phi = (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \bar{x}_3 \vee x_4) \wedge (x_3 \vee \bar{x}_1 \vee x_5)$



Satisfying assignment: $x_1 = 0, x_2 = 1, x_3 = 0, x_4 = 0, x_5 = 1$

$$x_1=0, x_2=1, x_3=0, x_4=0, x_5=1$$

NP and Computational Hardness

P, NP, and NP-completeness
(Kleinberg-Tardos, Section 8.3, 8.4)

Problems and algorithms

We can encode the input (an instance) of any computational problem as a binary string

Problems and algorithms

We can encode the input (an instance) of any computational problem as a binary string

A **decision problem** X is the set of strings on which the answer is “yes”

Problems and algorithms

We can encode the input (an instance) of any computational problem as a binary string

A **decision problem** X is the set of strings on which the answer is “yes”

An **algorithm** A for a decision problem receives an input string s and

outputs $A(s) = \begin{cases} \text{yes} \\ \text{no} \end{cases}$

Problems and algorithms

We can encode the input (an instance) of any computational problem as a binary string $(x_{\text{yes}}, x_{\text{no}})$

A **decision problem** X is the set of strings on which the answer is “yes”

An **algorithm** A for a decision problem receives an input string s and

outputs $A(s) = \begin{cases} \text{yes} \\ \text{no} \end{cases}$

The algorithm A **solves** X if for all s , $A(s) = \text{yes}$ if and only if $s \in X$

Problems and algorithms

We can encode the input (an instance) of any computational problem as a binary string

A **decision problem** X is the set of strings on which the answer is “yes”

An **algorithm** A for a decision problem receives an input string s and outputs $A(s) = \begin{cases} \text{yes} \\ \text{no} \end{cases}$

The algorithm A **solves** X if for all s , $A(s) = \text{yes}$ if and only if $s \in X$

The algorithm A has **polynomial running time** if there is a polynomial p s.t. for all s , A terminates on s in at most $O(p(|s|))$ steps

Problems and algorithms

We can encode the input (an instance) of any computational problem as a binary string

A **decision problem** X is the set of strings on which the answer is “yes”

An **algorithm** A for a decision problem receives an input string s and

outputs $A(s) = \begin{cases} \text{yes} \\ \text{no} \end{cases}$

The algorithm A **solves** X if for all s , $A(s) = \text{yes}$ if and only if $s \in X$

The algorithm A has **polynomial running time** if there is a polynomial p s.t. for all s , A terminates on s in at most $O(p(|s|))$ steps

Computational class

P : the class of all problems for which there exists a polynomial-time algorithm

Checking vs solving

Definition

An algorithm B is an **efficient certifier** for a problem X if

Checking vs solving

Definition

An algorithm B is an **efficient certifier** for a problem X if

- B is a polynomial-time algorithm that takes two inputs s, t and

Checking vs solving

Definition

An algorithm B is an **efficient certifier** for a problem X if

- B is a polynomial-time algorithm that takes two inputs s, t , and
- there exists a polynomial p s.t. for all s , we have $s \in X$ if and only if there exists a string t s.t. $|t| \leq p(|s|)$ and $B(s, t) = \text{yes}$

Checking vs solving

Definition

An algorithm B is an **efficient certifier** for a problem X if

- B is a polynomial-time algorithm that takes two inputs s, t , and
- there exists a polynomial p s.t. for all s , we have $s \in X$ if and only if there exists a string t s.t. $|t| \leq p(|s|)$ and $B(s, t) = \text{yes}$

The string t is called a **certificate**

Checking vs solving

Definition

An algorithm B is an **efficient certifier** for a problem X if

- B is a polynomial-time algorithm that takes two inputs s, t , and
- there exists a polynomial p s.t. for all s , we have $s \in X$ if and only if there exists a string t s.t. $|t| \leq p(|s|)$ and $B(s, t) = \text{yes}$

The string t is called a **certificate**

Example:

Checking vs solving

Definition

An algorithm B is an **efficient certifier** for a problem X if

- B is a polynomial-time algorithm that takes two inputs s, t , and
- there exists a polynomial p s.t. for all s , we have $s \in X$ if and only if there exists a string t s.t. $|t| \leq p(|s|)$ and $B(s, t) = \text{yes}$

The string t is called a **certificate**

Example:

- 3-SAT:

Checking vs solving

Definition

An algorithm B is an **efficient certifier** for a problem X if

- B is a polynomial-time algorithm that takes two inputs s, t , and
- there exists a polynomial p s.t. for all s , we have $s \in X$ if and only if there exists a string t s.t. $|t| \leq p(|s|)$ and $B(s, t) = \text{yes}$

The string t is called a **certificate**

Example:

- 3-SAT: certificate: an assignment

Checking vs solving

Definition

An algorithm B is an **efficient certifier** for a problem X if

- B is a polynomial-time algorithm that takes two inputs s, t , and
- there exists a polynomial p s.t. for all s , we have $s \in X$ if and only if there exists a string t s.t. $|t| \leq p(|s|)$ and $B(s, t) = \text{yes}$

The string t is called a **certificate**

Example:

- 3-SAT: certificate: an assignment

instance s : $(\bar{x}_1 \vee x_2 \vee x_3) \wedge (x_1 \vee \bar{x}_2 \vee x_3) \wedge (x_1 \vee x_2 \vee x_4) \wedge (\bar{x}_1 \vee \bar{x}_3 \vee \bar{x}_4)$

Checking vs solving

Definition

An algorithm B is an **efficient certifier** for a problem X if

- B is a polynomial-time algorithm that takes two inputs s, t , and
- there exists a polynomial p s.t. for all s , we have $s \in X$ if and only if there exists a string t s.t. $|t| \leq p(|s|)$ and $B(s, t) = \text{yes}$

The string t is called a **certificate**

Example:

- 3-SAT: certificate: an assignment

instance s : $(\bar{x}_1 \vee x_2 \vee x_3) \wedge (x_1 \vee \bar{x}_2 \vee x_3) \wedge (x_1 \vee x_2 \vee x_4) \wedge (\bar{x}_1 \vee \bar{x}_3 \vee \bar{x}_4)$

certificate t : $x_1 = 1, x_2 = 1, x_3 = 0, x_4 = 1$

Checking vs solving

Definition

An algorithm B is an **efficient certifier** for a problem X if

- B is a polynomial-time algorithm that takes two inputs s, t , and
- there exists a polynomial p s.t. for all s , we have $s \in X$ if and only if there exists a string t s.t. $|t| \leq p(|s|)$ and $B(s, t) = \text{yes}$

The string t is called a **certificate**

Example:

- 3-SAT: certificate: an assignment
instance s : $(\bar{x}_1 \vee x_2 \vee x_3) \wedge (x_1 \vee \bar{x}_2 \vee x_3) \wedge (x_1 \vee x_2 \vee x_4) \wedge (\bar{x}_1 \vee \bar{x}_3 \vee \bar{x}_4)$
certificate t : $x_1 = 1, x_2 = 1, x_3 = 0, x_4 = 1$
- Independent set.

Checking vs solving

Definition

An algorithm B is an **efficient certifier** for a problem X if

- B is a polynomial-time algorithm that takes two inputs s, t , and
- there exists a polynomial p s.t. for all s , we have $s \in X$ if and only if there exists a string t s.t. $|t| \leq p(|s|)$ and $B(s, t) = \text{yes}$

The string t is called a **certificate**

Example:

- 3-SAT: certificate: an assignment
instance s : $(\bar{x}_1 \vee x_2 \vee x_3) \wedge (x_1 \vee \bar{x}_2 \vee x_3) \wedge (x_1 \vee x_2 \vee x_4) \wedge (\bar{x}_1 \vee \bar{x}_3 \vee \bar{x}_4)$
certificate t : $x_1 = 1, x_2 = 1, x_3 = 0, x_4 = 1$
- Independent set. certificate: a set of at least k vertices

Checking vs solving

Definition

An algorithm B is an **efficient certifier** for a problem X if

- B is a polynomial-time algorithm that takes two inputs s, t , and
- there exists a polynomial p s.t. for all s , we have $s \in X$ if and only if there exists a string t s.t. $|t| \leq p(|s|)$ and $B(s, t) = \text{yes}$

The string t is called a **certificate**

Example:

- 3-SAT: certificate: an assignment
instance s : $(\bar{x}_1 \vee x_2 \vee x_3) \wedge (x_1 \vee \bar{x}_2 \vee x_3) \wedge (x_1 \vee x_2 \vee x_4) \wedge (\bar{x}_1 \vee \bar{x}_3 \vee \bar{x}_4)$
certificate t : $x_1 = 1, x_2 = 1, x_3 = 0, x_4 = 1$
- Independent set. certificate: a set of at least k vertices
certifier: check if there's no edge joining them

Checking vs solving

Definition

An algorithm B is an **efficient certifier** for a problem X if

- B is a polynomial-time algorithm that takes two inputs s, t , and
- there exists a polynomial p s.t. for all s , we have $s \in X$ if and only if there exists a string t s.t. $|t| \leq p(|s|)$ and $B(s, t) = \text{yes}$

The string t is called a **certificate**

Example:

- 3-SAT: certificate: an assignment
instance s : $(\bar{x}_1 \vee x_2 \vee x_3) \wedge (x_1 \vee \bar{x}_2 \vee x_3) \wedge (x_1 \vee x_2 \vee x_4) \wedge (\bar{x}_1 \vee \bar{x}_3 \vee \bar{x}_4)$
certificate t : $x_1 = 1, x_2 = 1, x_3 = 0, x_4 = 1$
- Independent set. certificate: a set of at least k vertices
certifier: check if there's no edge joining them

We can use B to design an algorithm for X : use brute force to find a t .

Checking vs solving

Definition

An algorithm B is an **efficient certifier** for a problem X if

- B is a polynomial-time algorithm that takes two inputs s, t , and
- there exists a polynomial p s.t. for all s , we have $s \in X$ if and only if there exists a string t s.t. $|t| \leq p(|s|)$ and $B(s, t) = \text{yes}$

The string t is called a **certificate**

Example:

- 3-SAT: certificate: an assignment
instance s : $(\bar{x}_1 \vee x_2 \vee x_3) \wedge (x_1 \vee \bar{x}_2 \vee x_3) \wedge (x_1 \vee x_2 \vee x_4) \wedge (\bar{x}_1 \vee \bar{x}_3 \vee \bar{x}_4)$
certificate t : $x_1 = 1, x_2 = 1, x_3 = 0, x_4 = 1$
- Independent set. certificate: a set of at least k vertices
certifier: check if there's no edge joining them

We can use B to design an algorithm for X : use brute force to find a t .

But there might be exponentially many possible t 's

The computational class NP

Computational class

NP : the class of all problems for which there exists an efficient certifier

The computational class NP

Computational class

NP : the class of all problems for which there exists an efficient certifier

It is easy to see: 3-SAT \in **NP**

Independent set \in NP
Vertex cover \in NP

The computational class NP

Computational class

NP : the class of all problems for which there exists an efficient certifier

It is easy to see: 3-SAT \in **NP**

Lemma

P \subseteq **NP**

The computational class NP

Computational class

NP : the class of all problems for which there exists an efficient certifier

It is easy to see: 3-SAT \in **NP**

Lemma

P \subseteq **NP**

Proof.

For any problem in **P** with algorithm A , we construct a certifier B that just returns $A(s)$ with empty certificate t □

NP-completeness

Fundamental question in CS: is $\mathbf{P} = \mathbf{NP}$?

NP-completeness

Fundamental question in CS: is $\mathbf{P} = \mathbf{NP}$? i.e., does there exist a problem $X \in \mathbf{NP}$ but $X \notin \mathbf{P}$?

NP-completeness

Fundamental question in CS: is $\mathbf{P} = \mathbf{NP}$? i.e., does there exist a problem $X \in \mathbf{NP}$ but $X \notin \mathbf{P}$?

We don't know the answer, but we try to find the most difficult problems in \mathbf{NP} :

NP-completeness

Fundamental question in CS: is $\mathbf{P} = \mathbf{NP}$? i.e., does there exist a problem $X \in \mathbf{NP}$ but $X \notin \mathbf{P}$?

We don't know the answer, but we try to find the most difficult problems in \mathbf{NP} :

Definition

A problem X is **NP-complete** if

NP-completeness

Fundamental question in CS: is $\mathbf{P} = \mathbf{NP}$? i.e., does there exist a problem $X \in \mathbf{NP}$ but $X \notin \mathbf{P}$?

We don't know the answer, but we try to find the most difficult problems in \mathbf{NP} :

Definition

A problem X is **NP-complete** if

- $X \in \mathbf{NP}$ and

NP-completeness

Fundamental question in CS: is $\mathbf{P} = \mathbf{NP}$? i.e., does there exist a problem $X \in \mathbf{NP}$ but $X \notin \mathbf{P}$?

We don't know the answer, but we try to find the most difficult problems in \mathbf{NP} :

Definition

A problem X is **NP-complete** if

- $X \in \mathbf{NP}$ and
- for all $Y \in \mathbf{NP}$, $Y \leq_P X$

NP-completeness

Fundamental question in CS: is $\mathbf{P} = \mathbf{NP}$? i.e., does there exist a problem $X \in \mathbf{NP}$ but $X \notin \mathbf{P}$?

We don't know the answer, but we try to find the most difficult problems in \mathbf{NP} :

Definition

A problem X is **NP-complete** if

- $X \in \mathbf{NP}$ and
- for all $Y \in \mathbf{NP}$, $Y \leq_P X$

Lemma

If an NP-complete problem can be solved in polynomial time, then
 $\mathbf{P} = \mathbf{NP}$


Which problems are NP-complete?

A first **NP**-complete problem: Circuit Satisfiability

Which problems are NP-complete?

A first **NP**-complete problem: Circuit Satisfiability

A circuit consists of




Which problems are NP-complete?

A first **NP**-complete problem: Circuit Satisfiability

A circuit consists of

- inputs




Which problems are NP-complete?

A first **NP**-complete problem: Circuit Satisfiability

A circuit consists of

- inputs
- wires




Which problems are NP-complete?

A first **NP**-complete problem: Circuit Satisfiability

A circuit consists of

- inputs
- wires
- logical gates \vee, \wedge, \neg




Which problems are NP-complete?

A first **NP**-complete problem: Circuit Satisfiability

A circuit consists of

- inputs
- wires
- logical gates \vee, \wedge, \neg
- single output




Which problems are NP-complete?

A first **NP**-complete problem: Circuit Satisfiability

A circuit consists of

- inputs
- wires
- logical gates \vee, \wedge, \neg
- single output



The Circuit Satisfiability Problem (circuit-SAT)

Instance: A circuit C

Objective: Decide if C is satisfiable

The Cook-Levin Theorem

Theorem (Cook-Levin)

*circuit-SAT is **NP**-complete*