

Finding optimal schedule using matroid

How to find an optimal schedule?

1. Optimizing over tasks in the canonical form:

Finding optimal schedule using matroid

How to find an optimal schedule?

1. Optimizing over tasks in the canonical form:
 - 1.1 Find a set A of tasks that are early

Finding optimal schedule using matroid

How to find an optimal schedule?

1. Optimizing over tasks in the canonical form:
 - 1.1 Find a set A of tasks that are early
 - 1.2 Sort the tasks of A in increasing deadlines

Finding optimal schedule using matroid

How to find an optimal schedule?

1. Optimizing over tasks in the canonical form:
 - 1.1 Find a set A of tasks that are early
 - 1.2 Sort the tasks of A in increasing deadlines
 - 1.3 Add late tasks in any order

Finding optimal schedule using matroid

How to find an optimal schedule?

1. Optimizing over tasks in the canonical form:
 - 1.1 Find a set A of tasks that are early
 - 1.2 Sort the tasks of A in increasing deadlines
 - 1.3 Add late tasks in any order
2. Minimize penalties of late tasks \equiv maximize penalties of early tasks

Finding optimal schedule using matroid

How to find an optimal schedule?

1. Optimizing over tasks in the canonical form:
 - 1.1 Find a set A of tasks that are early
 - 1.2 Sort the tasks of A in increasing deadlines
 - 1.3 Add late tasks in any order
2. Minimize penalties of late tasks \equiv maximize penalties of early tasks

Modeled by a matroid $M = (S, \mathcal{I})$, where

Finding optimal schedule using matroid

How to find an optimal schedule?

1. Optimizing over tasks in the canonical form:
 - 1.1 Find a set A of tasks that are early
 - 1.2 Sort the tasks of A in increasing deadlines
 - 1.3 Add late tasks in any order
2. Minimize penalties of late tasks \equiv maximize penalties of early tasks

Modeled by a matroid $M = (S, \mathcal{I})$, where

$$S = \{a_1, \dots, a_n\}$$

Finding optimal schedule using matroid

How to find an optimal schedule?

1. Optimizing over tasks in the canonical form:
 - 1.1 Find a set A of tasks that are early
 - 1.2 Sort the tasks of A in increasing deadlines
 - 1.3 Add late tasks in any order
2. Minimize penalties of late tasks \equiv maximize penalties of early tasks

Modeled by a matroid $M = (S, \mathcal{I})$, where

$$S = \{a_1, \dots, a_n\}$$

$$\mathcal{I} = \{A \subseteq S : \exists \text{ a way to schedule the tasks in } A \text{ s.t. no task is late}\}$$

Finding optimal schedule using matroid

How to find an optimal schedule?

1. Optimizing over tasks in the canonical form:
 - 1.1 Find a set A of tasks that are early
 - 1.2 Sort the tasks of A in increasing deadlines
 - 1.3 Add late tasks in any order
2. Minimize penalties of late tasks \equiv maximize penalties of early tasks

Modeled by a matroid $M = (S, \mathcal{I})$, where

$$S = \{a_1, \dots, a_n\}$$

$$\mathcal{I} = \{A \subseteq S : \exists \text{ a way to schedule the tasks in } A \text{ s.t. no task is late}\}$$

w : penalty

Finding optimal schedule using matroid

How to find an optimal schedule?

1. Optimizing over tasks in the canonical form:
 - 1.1 Find a set A of tasks that are early
 - 1.2 Sort the tasks of A in increasing deadlines
 - 1.3 Add late tasks in any order
2. Minimize penalties of late tasks \equiv maximize penalties of early tasks

Modeled by a matroid $M = (S, \mathcal{I})$, where

$$S = \{a_1, \dots, a_n\}$$

$$\mathcal{I} = \{A \subseteq S : \exists \text{ a way to schedule the tasks in } A \text{ s.t. no task is late}\}$$

w : penalty

Finding an optimal schedule \equiv finding max-weighted indep. subset of M

Such M for task scheduling is a matroid

$M = (S, \mathcal{I})$ is a matroid

Such M for task scheduling is a matroid

$M = (S, \mathcal{I})$ is a matroid

- \mathcal{I} has the hereditary property:
if $A \subseteq B$ and $B \in \mathcal{I}$ then $A \in \mathcal{I}$

Such M for task scheduling is a matroid

$M = (S, \mathcal{I})$ is a matroid

- \mathcal{I} has the hereditary property:
if $A \subseteq B$ and $B \in \mathcal{I}$ then $A \in \mathcal{I}$
- Exchange property:
Say $A, B \in \mathcal{I}$ and $|B| > |A|$.

need to show $\exists x \in B - A$

s.t. $A \cup \{x\} \in \mathcal{I}$

Such M for task scheduling is a matroid

$M = (S, \mathcal{I})$ is a matroid

- \mathcal{I} has the hereditary property:
if $A \subseteq B$ and $B \in \mathcal{I}$ then $A \in \mathcal{I}$

- Exchange property:

Say $A, B \in \mathcal{I}$ and $|B| > |A|$.

Assume A and B are sorted in increasing order of deadlines

Such M for task scheduling is a matroid

$M = (S, \mathcal{I})$ is a matroid

- \mathcal{I} has the hereditary property:
if $A \subseteq B$ and $B \in \mathcal{I}$ then $A \in \mathcal{I}$

- Exchange property:

Say $A, B \in \mathcal{I}$ and $|B| > |A|$.

Assume A and B are sorted in increasing order of deadlines

Let k be the time when the last task in A is finished

Such M for task scheduling is a matroid

$M = (S, \mathcal{I})$ is a matroid

- \mathcal{I} has the hereditary property:
if $A \subseteq B$ and $B \in \mathcal{I}$ then $A \in \mathcal{I}$

- Exchange property:


Say $A, B \in \mathcal{I}$ and $|B| > |A|$.

Assume A and B are sorted in increasing order of deadlines

Let k be the time when the last task in A is finished

Let x be the first task in B that finished after k

then $A \cup \{x\} \in \mathcal{I}$



Such M for task scheduling is a matroid

$M = (S, \mathcal{I})$ is a matroid

- \mathcal{I} has the hereditary property:
if $A \subseteq B$ and $B \in \mathcal{I}$ then $A \in \mathcal{I}$

- Exchange property:

Say $A, B \in \mathcal{I}$ and $|B| > |A|$.

Assume A and B are sorted in increasing order of deadlines

Let k be the time when the last task in A is finished

Let x be the first task in B that finished after k

Then $A \cup \{x\} \subseteq \mathcal{I}$

Greedy algorithm for finding optimal scheduling

```
1 def GREEDY( $M = (S, \mathcal{I})$ , weights  $w$ ):
```


Greedy algorithm for finding optimal scheduling

```
1 def GREEDY( $M = (S, \mathcal{I})$ , weights  $w$ ):  
2   Set  $A := \{\}$ ;
```

Greedy algorithm for finding optimal scheduling

```
1 def GREEDY( $M = (S, \mathcal{I})$ , weights  $w$ ):  
2   Set  $A := \{\}$ ;  
3   Sort  $S$  in decreasing order of  $w$  ;           //  $O(n \log n)$ 
```

Greedy algorithm for finding optimal scheduling

```
1 def GREEDY( $M = (S, \mathcal{I})$ , weights  $w$ ):  
2   Set  $A := \{\}$ ;  
3   Sort  $S$  in decreasing order of  $w$  ;           //  $O(n \log n)$   
4   for  $x \in S$ :  
    |
```

Greedy algorithm for finding optimal scheduling

```
1 def GREEDY( $M = (S, \mathcal{I})$ , weights  $w$ ):  
2   Set  $A := \{\}$ ;  
3   Sort  $S$  in decreasing order of  $w$  ;           //  $O(n \log n)$   
4   for  $x \in S$ :  
5     if  $A \cup \{x\} \in \mathcal{I}$ :  
       |  
       |
```

Greedy algorithm for finding optimal scheduling

```
1 def GREEDY( $M = (S, \mathcal{I})$ , weights  $w$ ):  
2   Set  $A := \{\}$ ;  
3   Sort  $S$  in decreasing order of  $w$  ;           //  $O(n \log n)$   
4   for  $x \in S$ :  
5       if  $A \cup \{x\} \in \mathcal{I}$ :  
6            $A := A \cup \{x\}$ ;
```

Greedy algorithm for finding optimal scheduling

```
1 def GREEDY( $M = (S, \mathcal{I})$ , weights  $w$ ):  
2   Set  $A := \{\}$ ;  
3   Sort  $S$  in decreasing order of  $w$  ; //  $O(n \log n)$   
4   for  $x \in S$ :  
5     if  $A \cup \{x\} \in \mathcal{I}$ :  
6        $A := A \cup \{x\}$ ;  
7   return  $A$ ;
```


Greedy algorithm for finding optimal scheduling

```
1 def GREEDY( $M = (S, \mathcal{I})$ , weights  $w$ ):  
2     Set  $A := \{\}$ ;  
3     Sort  $S$  in decreasing order of  $w$  ;           //  $O(n \log n)$   
4     for  $x \in S$ :  
5         if  $A \cup \{x\} \in \mathcal{I}$ :  
6              $A := A \cup \{x\}$ ;  
7     return  $A$ ;
```

Running time: let $n = |S|$

Greedy algorithm for finding optimal scheduling

```
1 def GREEDY( $M = (S, \mathcal{I})$ , weights  $w$ ):  
2     Set  $A := \{\}$ ;  
3     Sort  $S$  in decreasing order of  $w$  ;           //  $O(n \log n)$   
4     for  $x \in S$ :  
5         if  $A \cup \{x\} \in \mathcal{I}$ :  
6              $A := A \cup \{x\}$ ;  
7     return  $A$ ;
```

Running time: let $n = |S|$

Assume checking if $A \cup \{x\} \in \mathcal{I}$ takes $O(f(n))$.

Greedy algorithm for finding optimal scheduling

```
1 def GREEDY( $M = (S, \mathcal{I})$ , weights  $w$ ):  
2   Set  $A := \{\}$ ;  
3   Sort  $S$  in decreasing order of  $w$  ; //  $O(n \log n)$   
4   for  $x \in S$ :  
5     if  $A \cup \{x\} \in \mathcal{I}$ :  
6        $A := A \cup \{x\}$ ;  
7   return  $A$ ;
```

$O(n \log n + n f(n))$

Running time: let $n = |S|$

Assume checking if $A \cup \{x\} \in \mathcal{I}$ takes $O(f(n))$. Lines 5-6 takes $O(n \cdot f(n))$

Greedy algorithm for finding optimal scheduling

```
1 def GREEDY( $M = (S, \mathcal{I})$ , weights  $w$ ):  
2   Set  $A := \{\}$ ;  
3   Sort  $S$  in decreasing order of  $w$  ; //  $O(n \log n)$   
4   for  $x \in S$ :  
5       if  $A \cup \{x\} \in \mathcal{I}$ :  
6            $A := A \cup \{x\}$ ;  
7   return  $A$ ;
```

Running time: let $n = |S|$

Assume checking if $A \cup \{x\} \in \mathcal{I}$ takes $O(f(n))$. Lines 5-6 takes $O(n \cdot f(n))$

Claim: $f(n) = O(n)$ for task scheduling problem (Homework)

Greedy algorithm for finding optimal scheduling

```
1 def GREEDY( $M = (S, \mathcal{I})$ , weights  $w$ ):  
2     Set  $A := \{\}$ ;  
3     Sort  $S$  in decreasing order of  $w$  ; //  $O(n \log n)$   
4     for  $x \in S$ :  
5         if  $A \cup \{x\} \in \mathcal{I}$ :  
6              $A := A \cup \{x\}$ ;  
7     return  $A$ ;
```

Running time: let $n = |S|$

Assume checking if $A \cup \{x\} \in \mathcal{I}$ takes $O(f(n))$. Lines 5-6 takes $O(n \cdot f(n))$

Claim: $f(n) = O(n)$ for task scheduling problem (Homework)

Total running time: $O(n^2)$

Greedy algorithms

Horn formulas (Textbook Section 5.3)

Consider the following puzzle

Consider the following puzzle

- If Alice has a dog, then Bob has a cat

Consider the following puzzle

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat

Consider the following puzzle

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Consider the following puzzle

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Question: what pets do they have?

Boolean formulas

Basics of boolean formulas

Basics of boolean formulas

- **Variables:** possibilities

Knowledge about variables is represented by a special type of boolean formulas

Basics of boolean formulas

- **Variables:** possibilities

Knowledge about variables is represented by a special type of boolean formulas

Goal; find a *consistent* explanation of the knowledge

Basics of boolean formulas

- **Variables:** possibilities

Knowledge about variables is represented by a special type of boolean formulas

Goal; find a *consistent* explanation of the knowledge

- **Boolean variable:** $x = 1$ (true) or $x = 0$ (false)

Boolean formulas

Basics of boolean formulas

- **Variables:** possibilities

Knowledge about variables is represented by a special type of boolean formulas

Goal; find a *consistent* explanation of the knowledge *when $x=1$*

- **Boolean variable:** $x = 1$ (true) or $x = 0$ (false) *$\bar{x} = 0$*
- **Literal:** x (positive literal), \bar{x} (negative literal) *or $\neg x$ when $x=0$
 $\bar{x}=1$*

Basics of boolean formulas

- **Variables:** possibilities

Knowledge about variables is represented by a special type of boolean formulas

Goal; find a *consistent* explanation of the knowledge

- **Boolean variable:** $x = 1$ (true) or $x = 0$ (false)
- **Literal:** x (positive literal), \bar{x} (negative literal)
- **Clause:** a clause consists of literals connected by \wedge (AND), \vee (OR), \implies (implies)

Boolean formulas

Basics of boolean formulas

x, y	$x \wedge \bar{y}$
0 0	0
0 1	0
1 0	1
1 1	0

- **Variables:** possibilities

Knowledge about variables is represented by a special type of boolean formulas

Goal; find a *consistent* explanation of the knowledge

- **Boolean variable:** $x = 1$ (true) or $x = 0$ (false)
- **Literal:** x (positive literal), \bar{x} (negative literal)
- **Clause:** a clause consists of literals connected by \wedge (AND), \vee (OR), \implies (implies)

Examples: $x \wedge \bar{y}$, $(x \wedge y) \implies z$

Horn formulas

In a Horn formula, there are only two types of clauses (**Horn clauses**):

Horn formulas

In a Horn formula, there are only two types of clauses (**Horn clauses**):

- **Implication:** $(x_1 \wedge x_2 \wedge \cdots \wedge x_n) \implies y$

Horn formulas

In a Horn formula, there are only two types of clauses (**Horn clauses**):

- **Implication:** $(x_1 \wedge x_2 \wedge \cdots \wedge x_n) \implies y$
LHS: AND of any number of positive literals

Horn formulas

In a Horn formula, there are only two types of clauses (**Horn clauses**):

- **Implication:** $(x_1 \wedge x_2 \wedge \cdots \wedge x_n) \implies y$
LHS: AND of any number of positive literals
RHS: single positive literal

Horn formulas

In a Horn formula, there are only two types of clauses (**Horn clauses**):

- **Implication:** $(x_1 \wedge x_2 \wedge \cdots \wedge x_n) \implies y$
LHS: AND of any number of positive literals
RHS: single positive literal
 - $(x \wedge \bar{y}) \implies z$

Horn formulas

In a Horn formula, there are only two types of clauses (**Horn clauses**):

- **Implication:** $(x_1 \wedge x_2 \wedge \cdots \wedge x_n) \implies y$
LHS: AND of any number of positive literals
RHS: single positive literal
 - $(x \wedge \bar{y}) \implies z$ ✗

Horn formulas

In a Horn formula, there are only two types of clauses (**Horn clauses**):

- **Implication:** $(x_1 \wedge x_2 \wedge \cdots \wedge x_n) \implies y$
LHS: AND of any number of positive literals
RHS: single positive literal
 - $(x \wedge \bar{y}) \implies z$ ✗
 - $(x \checkmark y) \implies z$

Horn formulas

In a Horn formula, there are only two types of clauses (**Horn clauses**):

- **Implication:** $(x_1 \wedge x_2 \wedge \cdots \wedge x_n) \implies y$
LHS: AND of any number of positive literals
RHS: single positive literal
 - $(x \wedge \bar{y}) \implies z$ ✗
 - $(x \vee y) \implies z$ ✗

Horn formulas

In a Horn formula, there are only two types of clauses (**Horn clauses**):

- **Implication:** $(x_1 \wedge x_2 \wedge \cdots \wedge x_n) \implies y$

LHS: AND of any number of positive literals

RHS: single positive literal

- $(x \wedge \bar{y}) \implies z$ ✗
- $(x \vee y) \implies z$ ✗
- $\implies z$ \Leftarrow $1 \Rightarrow z$

Horn formulas

In a Horn formula, there are only two types of clauses (**Horn clauses**):

- **Implication:** $(x_1 \wedge x_2 \wedge \cdots \wedge x_n) \implies y$

LHS: AND of any number of positive literals

RHS: single positive literal

- $(x \wedge \bar{y}) \implies z$ ✗
- $(x \vee y) \implies z$ ✗
- $\implies z$ ✓

$$(x \wedge y \wedge z) \implies (\bar{w}) \text{ ✗}$$

Horn formulas

In a Horn formula, there are only two types of clauses (**Horn clauses**):

- **Implication:** $(x_1 \wedge x_2 \wedge \cdots \wedge x_n) \implies y$
LHS: AND of any number of positive literals
RHS: single positive literal
 - $(x \wedge \bar{y}) \implies z$ ✗
 - $(x \vee y) \implies z$ ✗
 - $\implies z$ ✓
- **Pure negative clauses** $\bar{x}_1 \vee \bar{x}_2 \vee \cdots \vee \bar{x}_n$

Horn formulas

In a Horn formula, there are only two types of clauses (**Horn clauses**):

- **Implication:** $(x_1 \wedge x_2 \wedge \cdots \wedge x_n) \implies y$
LHS: AND of any number of positive literals
RHS: single positive literal
 - $(x \wedge \bar{y}) \implies z$ ✗
 - $(x \vee y) \implies z$ ✗
 - $\implies z$ ✓
- **Pure negative clauses** $\bar{x}_1 \vee \bar{x}_2 \vee \cdots \vee \bar{x}_n$
OR of any number of negative literals

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Define variables:

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Define variables:

- a : Alice has a dog

$a=1 \Rightarrow$ Alice has a dog

$a=0 \Rightarrow$ Alice doesn't have a dog

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Define variables:

- a : Alice has a dog
- b : Bob has a dog

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Define variables:

- a : Alice has a dog
- b : Bob has a dog
- c : Charlie has a dog

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Define variables:

- a : Alice has a dog
- b : Bob has a dog
- c : Charlie has a dog
- x : Alice has a cat

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Define variables:

- a : Alice has a dog
- b : Bob has a dog
- c : Charlie has a dog
- x : Alice has a cat
- y : Bob has a cat

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Define variables:

- a : Alice has a dog $0/1$
- b : Bob has a dog $0/1$
- c : Charlie has a dog $0/1$
- x : Alice has a cat $0/1$
- y : Bob has a cat $0/1$
- z : Charlie has a cat $0/1$

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Define variables:

- a : Alice has a dog
- b : Bob has a dog
- c : Charlie has a dog
- x : Alice has a cat
- y : Bob has a cat
- z : Charlie has a cat

Modelled by a set of Horn clauses:

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Define variables:

- a : Alice has a dog
- b : Bob has a dog
- c : Charlie has a dog
- x : Alice has a cat
- y : Bob has a cat
- z : Charlie has a cat

Modelled by a set of Horn clauses:

$$a \Rightarrow y$$

~~$$(c \wedge b) \vee (z \wedge y) \Rightarrow x$$~~

$$b \wedge c \Rightarrow x$$

$$y \wedge z \Rightarrow x$$

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Define variables:

- a : Alice has a dog
- b : Bob has a dog
- c : Charlie has a dog
- x : Alice has a cat
- y : Bob has a cat
- z : Charlie has a cat

Modelled by a set of Horn clauses:

$$a \implies y$$

$$(b \wedge c) \implies x$$

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Define variables:

- a : Alice has a dog
- b : Bob has a dog
- c : Charlie has a dog
- x : Alice has a cat
- y : Bob has a cat
- z : Charlie has a cat

Modelled by a set of Horn clauses:

$$a \implies y$$

$$(b \wedge c) \implies x$$

$$(y \wedge z) \implies x$$

A handwritten expression $\bar{a} \vee \bar{b} \vee \bar{x} \vee \bar{z}$ is enclosed in a blue rectangular box. To the right of the box is a large handwritten 'X' with a question mark above it, indicating that this expression is not a valid Horn clause.

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Define variables:

- a : Alice has a dog
- b : Bob has a dog
- c : Charlie has a dog
- x : Alice has a cat
- y : Bob has a cat
- z : Charlie has a cat

Modelled by a set of Horn clauses:

$$a \implies y$$

$$(b \wedge c) \implies x$$

$$(y \wedge z) \implies x$$

$$\bar{a} \vee \bar{c}$$

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Define variables:

- a : Alice has a dog 0
- b : Bob has a dog 6
- c : Charlie has a dog 6
- x : Alice has a cat 0
- y : Bob has a cat 6
- z : Charlie has a cat 0

Modelled by a set of Horn clauses:

- ✓ $a \implies y$
- ✓ $(b \wedge c) \implies x$
- ✓ $(y \wedge z) \implies x$
- ✓ $\bar{a} \vee \bar{c} \iff a \implies \bar{c}$
- ✓ $\bar{x} \vee \bar{z} \iff x \implies \bar{z}$

Horn formula example

Consider the puzzle:

- If Alice has a dog, then Bob has a cat
- If Charlie and Bob both have pets of the same species, then Alice has a cat
- Charlie and Alice don't share a pet of the same species

Define variables:

- a : Alice has a dog \cup
- b : Bob has a dog \downarrow
- c : Charlie has a dog \downarrow
- x : Alice has a cat \downarrow
- y : Bob has a cat \downarrow
- z : Charlie has a cat \cup

Modelled by a set of Horn clauses:

$$a \implies y$$

$$(b \wedge c) \implies x$$

$$(y \wedge z) \implies x$$

$$\bar{a} \vee \bar{c}$$

$$\bar{x} \vee \bar{z}$$

Question: satisfying assignment?

Greedy approach for Horn formulas

Problem (Horn Satisfiability)

Given a set of Horn clauses, determine whether or not there is a consistent explanation,

Greedy approach for Horn formulas

Problem (Horn Satisfiability)

Given a set of Horn clauses, determine whether or not there is a consistent explanation, i.e., an assignment of 0/1 to variables that satisfy all clauses

Greedy approach for Horn formulas

Problem (Horn Satisfiability)

Given a set of Horn clauses, determine whether or not there is a consistent explanation, i.e., an assignment of 0/1 to variables that satisfy all clauses

Example: $\underbrace{(x \wedge y)}_{\checkmark} \implies z, \underbrace{\bar{x} \vee \bar{w}}_{\checkmark}$

$$x=0, y=0, z=0, w=0$$

Greedy approach for Horn formulas

Problem (Horn Satisfiability)

Given a set of Horn clauses, determine whether or not there is a consistent explanation, i.e., an assignment of 0/1 to variables that satisfy all clauses

Example: $(x \wedge y) \implies z, \bar{x} \vee \bar{w}$ can be satisfied by

$x = 0, y = 0, z = 0, w = 0$

Greedy approach for Horn formulas

Problem (Horn Satisfiability)

Given a set of Horn clauses, determine whether or not there is a consistent explanation, i.e., an assignment of 0/1 to variables that satisfy all clauses

Example: $(x \wedge y) \implies z, \bar{x} \vee \bar{w}$ can be satisfied by

$x = 0, y = 0, z = 0, w = 0$

Greedy heuristic: start with all 0. Only set a variable to 1 if you need to, i.e., when an implication says you need to

$\bar{p} \implies q \implies a \quad 1 \implies a$
↑
< when $p=1$, then q must be 1 >

Greedy approach for Horn formulas

Problem (Horn Satisfiability)

Given a set of Horn clauses, determine whether or not there is a consistent explanation, i.e., an assignment of 0/1 to variables that satisfy all clauses

Example: $(x \wedge y) \implies z, \bar{x} \vee \bar{w}$ can be satisfied by

$x = 0, y = 0, z = 0, w = 0$

Greedy heuristic: start with all 0. Only set a variable to 1 if you need to, i.e., when an implication says you need to

$\Rightarrow a$

Recall: $p \implies q \iff \bar{p} \vee q$

Pseudocode

```
def GREEDY_HORN(set of Horn clauses):
```


Pseudocode

def GREEDY_HORN(*set of Horn clauses*):

 Set all variables to 0;

Pseudocode

def GREEDY_HORN(*set of Horn clauses*):

 Set all variables to 0;

while *there exists an " \implies " that is not satisfied:*

 |

Pseudocode

def GREEDY_HORN(*set of Horn clauses*):

 Set all variables to 0;

while *there exists an " \implies " that is not satisfied:*

 Set its RHS to 1;

Pseudocode

def GREEDY_HORN(*set of Horn clauses*):

 Set all variables to 0;

while *there exists an " \implies " that is not satisfied:*

 | Set its RHS to 1;

if *all pure negative clauses are 1:*

 |

Pseudocode

def GREEDY_HORN(*set of Horn clauses*):

 Set all variables to 0;

while *there exists an " \implies " that is not satisfied*:

 Set its RHS to 1;

if *all pure negative clauses are 1*:

return the assignment;

Pseudocode

def GREEDY_HORN(*set of Horn clauses*):

 Set all variables to 0;

while *there exists an " \implies " that is not satisfied:*

 | Set its RHS to 1;

if *all pure negative clauses are 1:*

 | **return** the assignment;

else:

 |

Pseudocode

def GREEDY_HORN(*set of Horn clauses*):

 Set all variables to 0;

while *there exists an " \implies " that is not satisfied*:

 Set its RHS to 1;

if *all pure negative clauses are 1*:

return the assignment;

else:

return "unsatisfiable";

\implies ~~X~~

Pseudocode

def GREEDY_HORN(*set of Horn clauses*):

 Set all variables to 0;

while *there exists an " \implies " that is not satisfied*:

 Set its RHS to 1;

if *all pure negative clauses are 1*:

return the assignment;

else:

return "unsatisfiable";

Example: $\implies x, x \implies y, (\bar{x} \vee \bar{y})$

Pseudocode

def GREEDY_HORN(*set of Horn clauses*):

 Set all variables to 0;

while *there exists an " \implies " that is not satisfied*:

 Set its RHS to 1;

if *all pure negative clauses are 1*:

return the assignment;

else:

return "unsatisfiable";

Example: $\implies x$, $x \implies y$ ($\bar{x} \vee \bar{y}$)

x	y
0	0

Pseudocode

def GREEDY_HORN(*set of Horn clauses*):

 Set all variables to 0;

while *there exists an " \implies " that is not satisfied*:

 Set its RHS to 1;

if *all pure negative clauses are 1*:

return the assignment;

else:

return "unsatisfiable";

Example: $\implies x, x \implies y \quad (\bar{x} \vee \bar{y})$

x y

0 0 $\implies x$ ✗

1 0

Pseudocode

def GREEDY_HORN(*set of Horn clauses*):

 Set all variables to 0;

while *there exists an " \implies " that is not satisfied*:

 Set its RHS to 1;

if *all pure negative clauses are 1*:

return the assignment;

else:

return "unsatisfiable";

Example: $\implies x, x \implies y, (\bar{x} \vee \bar{y})$

x y

0 0 $\implies x$ ✗

1 0 $x \implies y$ ✗

| |

Pseudocode

def GREEDY_HORN(*set of Horn clauses*):

 Set all variables to 0;

while *there exists an " \implies " that is not satisfied*:

 Set its RHS to 1;

if *all pure negative clauses are 1*:

return the assignment;

else:

return "unsatisfiable";

Example: $\implies x, x \implies y, (\bar{x} \vee \bar{y})$

x y

0 0 $\implies x$ ✗

1 0 $x \implies y$ ✗

1 1 $\implies x$ ✓, $x \implies y$ ✓, $(\bar{x} \vee \bar{y})$ ✗

Pseudocode

def GREEDY_HORN(*set of Horn clauses*):

 Set all variables to 0;

while *there exists an " \implies " that is not satisfied*:

 Set its RHS to 1;

if *all pure negative clauses are 1*:

return the assignment;

else:

return "unsatisfiable";

Example: $\implies x, x \implies y, (\bar{x} \vee \bar{y})$

x y

0 0 $\implies x$ ✗

1 0 $x \implies y$ ✗

1 1 $\implies x$ ✓, $x \implies y$ ✓, $(\bar{x} \vee \bar{y})$ ✗

Unsatisfiable

Correctness and running time

Correctness: If `GREEDY_HORN` finds an assignment, then the problem has a satisfying assignment

Correctness and running time

Correctness: If GREEDY_HORN finds an assignment, then the problem has a satisfying assignment

If it returns “unsatisfiable”, is it really unsatisfiable?

Correctness and running time

Correctness: If GREEDY_HORN finds an assignment, then the problem has a satisfying assignment

If it returns “unsatisfiable”, is it really unsatisfiable?

Theorem

*The variables set to 1 by GREEDY_HORN must be 1 in **any** satisfying assignment*

Correctness and running time

Correctness: If GREEDY_HORN finds an assignment, then the problem has a satisfying assignment

If it returns “unsatisfiable”, is it really unsatisfiable?

Theorem

*The variables set to 1 by GREEDY_HORN must be 1 in **any** satisfying assignment*

Exercise: Prove this by induction

Correctness and running time

Correctness: If GREEDY_HORN finds an assignment, then the problem has a satisfying assignment

If it returns “unsatisfiable”, is it really unsatisfiable?

Theorem

*The variables set to 1 by GREEDY_HORN must be 1 in **any** satisfying assignment*

Exercise: Prove this by induction

$$\bar{x}_1 \vee \bar{x}_2 \vee \bar{x}_3 \vee \dots \vee \bar{x}_n$$

How does this theorem help?

If all the pure negative clauses cannot be satisfied after the while loop, then there's no such assignment satisfying them

Correctness and running time

Correctness: If GREEDY_HORN finds an assignment, then the problem has a satisfying assignment

If it returns “unsatisfiable”, is it really unsatisfiable?

Theorem

*The variables set to 1 by GREEDY_HORN must be 1 in **any** satisfying assignment*

Exercise: Prove this by induction

How does this theorem help?

If all the pure negative clauses cannot be satisfied after the while loop, then there's no such assignment satisfying them

Running time: Let n be the size of the Horn formula, i.e., the number occurrences of literals.

n^2

Correctness and running time

Correctness: If GREEDY_HORN finds an assignment, then the problem has a satisfying assignment

If it returns “unsatisfiable”, is it really unsatisfiable?

Theorem

*The variables set to 1 by GREEDY_HORN must be 1 in **any** satisfying assignment*

Exercise: Prove this by induction

How does this theorem help?

If all the pure negative clauses cannot be satisfied after the while loop, then there's no such assignment satisfying them

Running time: Let n be the size of the Horn formula, i.e., the number occurrences of literals.

Total running time: $O(n^2)$.

Correctness and running time

Correctness: If GREEDY_HORN finds an assignment, then the problem has a satisfying assignment

If it returns “unsatisfiable”, is it really unsatisfiable?

Theorem

*The variables set to 1 by GREEDY_HORN must be 1 in **any** satisfying assignment*

Exercise: Prove this by induction

How does this theorem help?

If all the pure negative clauses cannot be satisfied after the while loop, then there's no such assignment satisfying them

Running time: Let n be the size of the Horn formula, i.e., the number occurrences of literals.

Total running time: $O(n^2)$. Can be improved to $O(n)$ (exercise)