

# Dynamic Programming

---

**All-pair shortest path (Textbook Section 6.6)**

# All-pair shortest path

Consider  $G = (V, E)$  weighted, directed graph without negative cycles

# All-pair shortest path

Consider  $G = (V, E)$  weighted, directed graph without negative cycles

How to compute the `shortest_path( $u, v$ )`?

# All-pair shortest path

Consider  $G = (V, E)$  weighted, directed graph without negative cycles

How to compute the  $\text{shortest\_path}(u, v)$ ?

Recall Bellman-Ford:  $\text{shortest\_path}(u, v)$  for fixed  $u$ , all  $v$  takes  $O(|V| \cdot |E|)$  time

# All-pair shortest path

Consider  $G = (V, E)$  weighted, directed graph without negative cycles

How to compute the  $\text{shortest\_path}(u, v)$ ?

Recall Bellman-Ford:  $\text{shortest\_path}(u, v)$  for fixed  $u$ , all  $v$  takes  $O(|V| \cdot |E|)$  time

If for all  $u, v$ , APSP takes  $O(|V|^2|E|)$  time

# All-pair shortest path

Consider  $G = (V, E)$  weighted, directed graph without negative cycles

How to compute the  $\text{shortest\_path}(u, v)$ ?

Recall Bellman-Ford:  $\text{shortest\_path}(u, v)$  for fixed  $u$ , all  $v$  takes  $O(|V| \cdot |E|)$  time

If for all  $u, v$ , APSP takes  $O(|V|^2|E|)$  time

When  $|E| = O(|V|^2)$ , its running time becomes  $O(|V|^4)$

# All-pair shortest path

Consider  $G = (V, E)$  weighted, directed graph without negative cycles

How to compute the  $\text{shortest\_path}(u, v)$ ?

Recall Bellman-Ford:  $\text{shortest\_path}(u, v)$  for fixed  $u$ , all  $v$  takes  $O(|V| \cdot |E|)$  time

If for all  $u, v$ , APSP takes  $O(|V|^2|E|)$  time

When  $|E| = O(|V|^2)$ , its running time becomes  $O(|V|^4)$

Rethink this problem using DP.

## Subproblem

$$|V| = n$$

WLOG, index the vertices as  $V = \{1, 2, \dots, n\}$



# Subproblem

WLOG, index the vertices as  $V = \{1, 2, \dots, n\}$

**Subproblem:** find the shortest path  $u \rightarrow v$  using intermediate vertices from  $\{1, \dots, k\} \subseteq V$ .

# Subproblem

WLOG, index the vertices as  $V = \{1, 2, \dots, n\}$

**Subproblem:** find the shortest path  $u \rightarrow v$  using intermediate vertices from  $\{1, \dots, k\} \subseteq V$ . Denote it by  $\text{sp}(u, v, k)$

optimal solution:  $\text{sp}(u, v, n)$

# Subproblem

WLOG, index the vertices as  $V = \{1, 2, \dots, n\}$

**Subproblem:** find the shortest path  $u \rightarrow v$  using intermediate vertices from  $\{1, \dots, k\} \subseteq V$ . Denote it by  $\text{sp}(u, v, k)$

**Optimal solution:** the entries  $\text{sp}(u, v, n)$  for all  $u, v$

# Subproblem

WLOG, index the vertices as  $V = \{1, 2, \dots, n\}$

**Subproblem:** find the shortest path  $u \rightarrow v$  using intermediate vertices from  $\{1, \dots, k\} \subseteq V$ . Denote it by  $\text{sp}(u, v, k)$

**Optimal solution:** the entries  $\text{sp}(u, v, n)$  for all  $u, v$


To find out the recurrence relation, we need to relate  $\text{sp}(u, v, k)$  to smaller subproblems  $\text{sp}(u, v, k - 1)$

# Recurrence

Suppose  $\text{sp}(u, v, k) = P$

# Recurrence


Suppose  $\text{sp}(u, v, k) = P$



- $k \notin P$   $\text{sp}(u, v, k)$   $\text{sp}(u, v, k-1)$

# Recurrence


Suppose  $\text{sp}(u, v, k) = P$



- if  $k \notin P$ , then  $\text{sp}(u, v, k) = \text{sp}(u, v, k - 1)$

# Recurrence

Suppose  $\text{sp}(u, v, k) = P$




- if  $k \notin P$ , then  $\text{sp}(u, v, k) = \text{sp}(u, v, k - 1)$
- if  $k \in P$ , then consider



# Recurrence

Suppose  $\boxed{\text{sp}(u, v, k)} = P$




- if  $k \notin P$ , then  $\text{sp}(u, v, k) = \text{sp}(u, v, k - 1)$
- if  $k \in P$ , then consider

$$P : u \xrightarrow{P_1} k \xrightarrow{P_2} v$$

$P_1 =$   $P_2 =$

# Recurrence

Suppose  $\text{sp}(u, v, k) = P$




- if  $k \notin P$ , then  $\text{sp}(u, v, k) = \text{sp}(u, v, k - 1)$
- if  $k \in P$ , then consider

$$P : u \xrightarrow{P_1} k \xrightarrow{P_2} v$$

$P_1, P_2$  are paths whose intermediate vertices are from  $\{1, \dots, k - 1\}$ .

# Recurrence

Suppose  $\text{sp}(u, v, k) = P$



- if  $k \notin P$ , then  $\text{sp}(u, v, k) = \text{sp}(u, v, k - 1)$
- if  $k \in P$ , then consider

$$P : u \xrightarrow{P_1} k \xrightarrow{P_2} v$$



$P_1, P_2$  are paths whose intermediate vertices are from  $\{1, \dots, k - 1\}$ .

Because there's no negative cycles, there's no repeated vertices in shortest path

$$P_1 = (u, k, k-1) \quad P_2 = (k, v, k-1)$$

# Recurrence

Suppose  $\text{sp}(u, v, k) = P$



- if  $k \notin P$ , then  $\text{sp}(u, v, k) = \text{sp}(u, v, k - 1)$
- if  $k \in P$ , then consider

$$P : u \xrightarrow{P_1} k \xrightarrow{P_2} v$$


$P_1, P_2$  are paths whose intermediate vertices are from  $\{1, \dots, k - 1\}$ .

Because there's no negative cycles, there's no repeated vertices in shortest path

$$\text{Hence, } P_1 = \text{sp}(u, k, k - 1), P_2 = \text{sp}(k, v, k - 1)$$

# Recurrence

Suppose  $\text{sp}(u, v, k) = P$



- if  $k \notin P$ , then  $\text{sp}(u, v, k) = \text{sp}(u, v, k - 1)$
- if  $k \in P$ , then consider

$$P : u \xrightarrow{P_1} k \xrightarrow{P_2} v$$

$P_1, P_2$  are paths whose intermediate vertices are from  $\{1, \dots, k - 1\}$ .

Because there's no negative cycles, there's no repeated vertices in shortest path

$$\text{Hence, } P_1 = \text{sp}(u, k, k - 1), P_2 = \text{sp}(k, v, k - 1)$$

Using  $k$  is better if

$$|\text{sp}(u, k, k - 1)| + |\text{sp}(k, v, k - 1)| \leq |\text{sp}(u, v, k - 1)|$$

Let  $\text{dist}(u, v, k) = |\text{sp}(u, v, k)|$

Let  $\text{dist}(u, v, k) = |\text{sp}(u, v, k)|$

- **Recurrence:**

$$\text{dist}(u, v, k) = \min\{\text{dist}(u, v, k-1), \text{dist}(u, k, k-1) + \text{dist}(k, v, k-1)\}$$

# Dynamic programming

Let  $\text{dist}(u, v, k) = |\text{sp}(u, v, k)|$

- **Recurrence:**

$$\text{dist}(u, v, k) = \min\{\text{dist}(u, v, k-1), \text{dist}(u, k, k-1) + \text{dist}(k, v, k-1)\}$$

- **Optimal solution:**  $\text{dist}(\overset{u}{\downarrow}, \overset{v}{\downarrow}, n)$

- Base case:

$$\text{dist}(u, v, 0) =$$



Let  $\text{dist}(u, v, k) = |\text{sp}(u, v, k)|$

- **Recurrence:**

$$\text{dist}(u, v, k) = \min\{\text{dist}(u, v, k-1), \text{dist}(u, k, k-1) + \text{dist}(k, v, k-1)\}$$

- **Optimal solution:**  $\text{dist}(\cdot, \cdot, n)$

- **Base case:**

$$\text{dist}(u, v, 0) = \begin{cases} w_{u,v} & \text{if } (u, v) \in E \\ \infty & \text{otherwise} \end{cases}$$

The Floyd-Warshall algorithm:

# Pseudocode

The Floyd-Warshall algorithm:

**def** FLOYD\_WARSHALL( $G, w$ ):

|

## Pseudocode

## The Floyd-Warshall algorithm:

```
def FLOYD_WARSHALL( $G, w$ ):
```

```
for  $u = 1 \dots n$ :
```

# Pseudocode

The Floyd-Warshall algorithm:

**def** FLOYD\_WARSHALL( $G, w$ ):

**for**  $u = 1 \dots n$ :

**for**  $v = 1 \dots n$ :

# Pseudocode

The Floyd-Warshall algorithm:

**def** FLOYD\_WARSHALL( $G, w$ ):

**for**  $u = 1 \dots n$ :

**for**  $v = 1 \dots n$ :

$$\text{dist}(u, v, 0) = \begin{cases} w_{u,v} & \text{if } (u, v) \in E; \\ \infty & \text{otherwise} \end{cases};$$

# Pseudocode

The Floyd-Warshall algorithm:

**def** FLOYD\_WARSHALL( $G, w$ ):

**for**  $u = 1 \dots n$ :

**for**  $v = 1 \dots n$ :

$$\text{dist}(u, v, 0) = \begin{cases} w_{u,v} & \text{if } (u, v) \in E; \\ \infty & \text{otherwise} \end{cases};$$

**for**  $k = 1 \dots n$ :

# Pseudocode

The Floyd-Warshall algorithm:

**def** FLOYD\_WARSHALL( $G, w$ ):

**for**  $u = 1 \dots n$ :

**for**  $v = 1 \dots n$ :

$$\text{dist}(u, v, 0) = \begin{cases} w_{u,v} & \text{if } (u, v) \in E; \\ \infty & \text{otherwise} \end{cases};$$

**for**  $k = 1 \dots n$ :

**for**  $u = 1 \dots n$ :

            |

        |

    |



# Pseudocode

The Floyd-Warshall algorithm:

**def** FLOYD\_WARSHALL( $G, w$ ):

**for**  $u = 1 \dots n$ :

**for**  $v = 1 \dots n$ :

$$\text{dist}(u, v, 0) = \begin{cases} w_{u,v} & \text{if } (u, v) \in E; \\ \infty & \text{otherwise} \end{cases};$$

**for**  $k = 1 \dots n$ :

**for**  $u = 1 \dots n$ :

**for**  $v = 1 \dots n$ :

# Pseudocode

The Floyd-Warshall algorithm:

**def** FLOYD\_WARSHALL( $G, w$ ):

**for**  $u = 1 \dots n$ :

**for**  $v = 1 \dots n$ :

$$\text{dist}(u, v, 0) = \begin{cases} w_{u,v} & \text{if } (u, v) \in E; \\ \infty & \text{otherwise} \end{cases};$$

**for**  $k = 1 \dots n$ :

**for**  $u = 1 \dots n$ :

**for**  $v = 1 \dots n$ :

$$\text{dist}(u, v, k) = \min\{\text{dist}(u, v, k-1), \text{dist}(u, k, k-1) + \text{dist}(k, v, k-1)\};$$

# Pseudocode

The Floyd-Warshall algorithm:

**def** FLOYD\_WARSHALL( $G, w$ ):

**for**  $u = 1 \dots n$ :

**for**  $v = 1 \dots n$ :

$\text{dist}(u, v, 0) = \begin{cases} w_{u,v} & \text{if } (u, v) \in E; \\ \infty & \text{otherwise} \end{cases};$

**for**  $k = 1 \dots n$ :

**for**  $u = 1 \dots n$ :

**for**  $v = 1 \dots n$ :

$\text{dist}(u, v, k) =$

$\min\{\text{dist}(u, v, k-1), \text{dist}(u, k, k-1) + \text{dist}(k, v, k-1)\};$

**return**  $\text{dist}(\cdot, \cdot, n)$ ;

How many entries :  $O(n^3)$

Running time :

time for each entry :  $O(1)$

# Pseudocode

The Floyd-Warshall algorithm:

```
def FLOYD_WARSHALL( $G, w$ ):  
    for  $u = 1 \dots n$ :  
        for  $v = 1 \dots n$ :  
             $\text{dist}(u, v, 0) = \begin{cases} w_{u,v} & \text{if } (u, v) \in E; \\ \infty & \text{otherwise} \end{cases};$   
        for  $k = 1 \dots n$ :  
            for  $u = 1 \dots n$ :  
                for  $v = 1 \dots n$ :  
                     $\text{dist}(u, v, k) =$   
                         $\min\{\text{dist}(u, v, k-1), \text{dist}(u, k, k-1) + \text{dist}(k, v, k-1)\};$   
    return  $\text{dist}(\cdot, \cdot, n);$ 
```

Running time:  $O(n^3) = O(|V|^3)$