

Programming Language Concepts

Gary Tan
Computer Science and Engineering
Penn State University

1

CH2 SYNTAX

2

BNF Example

- A simple arithmetic expression language
 - Non-terminals: e, n, d ; identify grammatical categories
 - Terminals: $+, -, 0, 1, 2, 3, 4, 5, \dots, 9$; identify the basic alphabet
 - Production rules
 - $\langle e \rangle \rightarrow \langle n \rangle \mid \langle e \rangle + \langle e \rangle \mid \langle e \rangle - \langle e \rangle$
 - $\langle n \rangle \rightarrow \langle d \rangle \mid \langle n \rangle \langle d \rangle$
 - $\langle d \rangle \rightarrow 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$
 - "|" indicates a choice
 - the right hand side of a rule can be a sequence of terminal or non-terminal symbols
 - Start symbol: e
 - Note: the grammar has **recursion**
- Example numbers: 4, 27, 704
- Example expressions: $27 - 4 + 704$

3

3

Derivations

- Derivation: a sequence of replacement steps
 - starting from the start symbol
 - Replace a nonterminal by the rhs (right hand side) of a rule
 - Keep doing it until resulting in a string of terminals
- $\langle e \rangle \rightarrow \langle e \rangle + \langle e \rangle \rightarrow \langle e \rangle - \langle e \rangle + \langle e \rangle \rightarrow \langle n \rangle - \langle n \rangle + \langle n \rangle \rightarrow$
 $\langle n \rangle \langle d \rangle - \langle d \rangle + \langle d \rangle \rightarrow \langle d \rangle \langle d \rangle - \langle d \rangle + \langle d \rangle$
 $\rightarrow \dots \rightarrow 27 - 4 + 3$

Grammar defines a language: any terminal string that can be derived belongs to the language of the grammar

4

4

Left vs. right-most derivations

- Left-most derivation
 - At each step, always replace the leftmost nonterminal by one of its alternatives
- Right-most derivation
 - At each step, replace the rightmost nonterminal by one of its alternatives
- An example
 - $4 + 3$
 - Both derivations correspond to the same parse tree


5

5

Parse tree

- Derivation represented by a tree

$\langle e \rangle \rightarrow \langle e \rangle + \langle e \rangle \rightarrow \langle e \rangle - \langle e \rangle + \langle e \rangle$
 $\rightarrow \dots \rightarrow \langle n \rangle - \langle n \rangle + \langle n \rangle$
 $\rightarrow \dots \rightarrow \langle d \rangle - \langle d \rangle + \langle d \rangle$
 $\rightarrow \dots \rightarrow 7 - 4 + 3$




- Parse tree ignores the detail about the order of replacing nonterminals
- Two derivations may correspond to the same parse tree
- Tree shows parenthesization of expressions: $7-4+3$ treated as $(7-4) + 3$

6

6

Parse Tree and Ambiguity

- The expression $7 - 4 + 3$ has two parse trees; another one



- Problem: $7 - (4 + 3) \neq (7 - 4) + 3$
- A grammar is **ambiguous** if some terminal string has more than one parse tree. Otherwise it is unambiguous
 - Note: not two derivations; to show a grammar is ambiguous, need to find one terminal string with two parse trees

7

7

Ways to resolve operator ambiguity

- One way: add parentheses explicitly
 - $\langle e \rangle \rightarrow \langle n \rangle \mid (\langle e \rangle + \langle e \rangle) \mid (\langle e \rangle - \langle e \rangle)$
 - $7 - 4 + 3$ is not an expression

8

8

Ways to resolve operator ambiguity

- Second way: design a new grammar that enforces associativity and precedence
 - $\langle e \rangle \rightarrow \langle n \rangle \mid \langle e \rangle + \langle n \rangle \mid \langle e \rangle - \langle n \rangle$
 - $27 - 4 + 3$ has only one parse tree in this grammar; which one it is?
- Q: how many parse trees for $27 - 4 + 3$
 - The grammar makes the $+/-$ operator left associative (by convention)
 - By using left recursion
 - Q: what if we want to make $+$ and $-$ right associative?
- However, what if we really want $27 - (4 + 3)$?
 - $\langle e \rangle \rightarrow \langle t \rangle \mid \langle e \rangle + \langle t \rangle \mid \langle e \rangle - \langle t \rangle$
 - $\langle t \rangle \rightarrow \langle n \rangle \mid (\langle e \rangle)$
 - Ex: parse tree for $27 - (4 + 3)$

9

9

Associativity & Precedence

- Associativity
 - Parenthesize operators of equal precedence to the left (or the right)
 - $+$ is left associative, parse $3 + 4 + 5$ as $(3 + 4) + 5$
 - Parse $3 - 4 + 5$ as $(3 - 4) + 5$
 - Example: the exponentiation operator is right associative
- Precedence: an operator has a higher precedence than another operator if the first one binds tighter
 - Group $*$ before $+$
 - Parse $2 + 3 * 4$ as $2 + (3 * 4)$

10

10

Examples of enforcing associativity and precedence

- Four operators: $+$, $-$, $*$, $/$
 - they are left associative
 - $*$, $/$ should have higher precedence than $+$ and $-$
- $\langle \text{exp} \rangle \rightarrow \langle \text{term} \rangle \mid \langle \text{exp} \rangle + \langle \text{term} \rangle \mid \langle \text{exp} \rangle - \langle \text{term} \rangle$
 - $\langle \text{term} \rangle \rightarrow \langle \text{factor} \rangle \mid \langle \text{term} \rangle * \langle \text{factor} \rangle \mid \langle \text{term} \rangle / \langle \text{factor} \rangle$
 - $\langle \text{factor} \rangle \rightarrow \langle \text{num} \rangle \mid (\langle \text{exp} \rangle)$
 - Example: $7 + 4 * 3$
 - Why can't it be parsed like $(7 + 4) * 3$?
 - The explicit parentheses allow the parsing of $(7 + 4) * 3$
 - More examples: $7 * 4 * (3 + 5)$

11

11

E-BNF (Extended BNF)

- Put alternative parts in parentheses and separate them with vertical bars
 - $\langle \text{exp} \rangle \rightarrow \langle \text{exp} \rangle (+ \mid -) \langle \text{exp} \rangle$
 - Really just an abbreviation for two BNF rules
 - Note: $($, $|$, and $)$ are meta-symbols, while $+$ and $-$ are terminals
- Put repetition (0 or more) in curly braces $\{ \}$
 - $\langle \text{num} \rangle \rightarrow \langle \text{digit} \rangle \{ \langle \text{digit} \rangle \}$
 - Example: 101
- Optional parts are placed in square brackets $[\]$
 - $\langle \text{if-stmt} \rangle \rightarrow \text{if } \langle \text{test} \rangle \text{ then } \langle \text{stmt} \rangle [\text{else } \langle \text{stmt} \rangle]$
- Examples:
 - $\langle \text{Expr} \rangle \rightarrow \langle \text{Term} \rangle \{ (+ \mid -) \langle \text{Term} \rangle \}$
 - $\langle \text{proc_call} \rangle \rightarrow \langle \text{id} \rangle ([\langle \text{expr_list} \rangle])$

12

12

E-BNF is no more powerful than BNF

- $\langle \text{exp} \rangle \rightarrow \langle \text{exp} \rangle (+ \mid -) \langle \text{exp} \rangle$
 - Same as
 $\langle \text{exp} \rangle \rightarrow \langle \text{exp} \rangle + \langle \text{exp} \rangle \mid \langle \text{exp} \rangle - \langle \text{exp} \rangle$
- $\langle \text{num} \rangle \rightarrow \langle \text{digit} \rangle \{ \langle \text{digit} \rangle \}$
 - Same as
 $\langle \text{num} \rangle \rightarrow \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{num} \rangle$
- $\langle \text{if-stmt} \rangle \rightarrow \text{if } \langle \text{test} \rangle \text{ then } \langle \text{stmt} \rangle [\text{else } \langle \text{stmt} \rangle]$
 - Same as
 $\langle \text{if-stmt} \rangle \rightarrow \text{if } \langle \text{test} \rangle \text{ then } \langle \text{stmt} \rangle$
 $\mid \text{if } \langle \text{test} \rangle \text{ then } \langle \text{stmt} \rangle \text{ else } \langle \text{stmt} \rangle$

13

Real Examples: Excerpt from Java Grammar

Variable declarations in Java

$\langle \text{var-dec} \rangle$	$\rightarrow \langle \text{type-name} \rangle \langle \text{declarator-list} \rangle ;$
$\langle \text{type-name} \rangle$	$\rightarrow \text{boolean} \mid \text{byte} \mid \text{short} \mid \text{int} \mid$ $\text{long} \mid \text{char} \mid \text{float} \mid \text{double}$
$\langle \text{declarator-list} \rangle$	$\rightarrow \langle \text{declarator} \rangle \mid$ $\langle \text{declarator} \rangle , \langle \text{declarator-list} \rangle$
$\langle \text{declarator} \rangle$	$\rightarrow \langle \text{variable-name} \rangle \mid$ $\langle \text{variable-name} \rangle = \langle \text{expr} \rangle$

Assume $\langle \text{variable-name} \rangle$ and $\langle \text{expr} \rangle$ are defined elsewhere

14