



Web Development Fundamentals

Vue CLI 与单文件组件

Vue CLI & Single-file components

Jun 2021

Microsoft Reactor | Ryan Chung

```

    self.load_image("kg.png")

    def __init__(self):
        # Initialize Dog object and create Text object
        self.image = Dog.image
        self.x = games.mouse.x
        self.bottom = games.screen.bottom

        self.score = games.Text(value = 0, size = 24,
                                top = 5, right = games.screen.right)
        self.screen.add(self.score)

        self.lives = games.Text(value = 0, size = 24,
                                top = 5, left = games.screen.left)
        self.screen.add(self.lives)

```



Ryan Chung

Instructor / DevelopIntelligence
Founder / MobileDev.TW

@ryanchung403 on WeChat
Ryan@MobileDev.TW





Reactor



developer.microsoft.com/reactor/
[@MSFTReactor](#) on Twitter



Vue.js 中的 Vue CLI 和单文件组件入门

3 分钟 剩余 • 模块 • 已完成 9 个单元, 共 11 个

★★★★★ 4.9 (10)

对其进行评级

中级

学生

开发人员

应用服务静态 Web 应用

Visual Studio Code

虽然可以仅使用 JavaScript 来创建 Vue.js 应用程序, 但大多数开发人员都需要更多的功能和灵活性。使用 Vue CLI 和单文件组件, 你可以利用更可靠的工具增强开发体验。我们将了解如何使用 Vue CLI 启动应用程序, 以及如何在 Vue 中创建可重用组件。

学习目标

本模块涉及以下内容:

- 使用 Vue CLI
- 创建组件

先决条件

了解 HTML/CSS、Git、npm、JavaScript, 并对 Vue.js 有一定了解

继续 >

⊕ 保存

学习目标

- 使用Vue CLI
- 建立组件

安装 Vue CLI

- 确认已安装Node与NPM

```
node -v
```

```
npm -v
```

- 安装 Vue CLI

```
npm install -g @vue/cli
```

使用Vue CLI建立应用程序

- 终端机，先移至想要放置项目的文件夹
- 建立应用程序
 - vue create reelecloud
 - 选择 Manually select features

```
Vue CLI v4.5.13 mslearn-vue-components-practice >
? Please pick a preset:
  Default ([Vue 2] babel, eslint)
  Default (Vue 3) ([Vue 3] babel, eslint)
> Manually select features
```

确认需要的项目

- 只留下 Choose Vue version
- 移动至不要的项目，按下 Space

```
Vue CLI v4.5.13 mslearn-vue-components-practice >
? Please pick a preset: Manually select features
? Check the features needed for your project:
>(*) Choose Vue version
  ( ) Babel
  ( ) TypeScript
  ( ) Progressive Web App (PWA) Support
  ( ) Router
  ( ) Vuex
  ( ) CSS Pre-processors
  ( ) Linter / Formatter
  ( ) Unit Testing
  ( ) E2E Testing
```


选择版本

- 选择 3.x

```
Vue CLI v4.5.13 mslearn-vue-components-practice >
? Please pick a preset: Manually select features
? Check the features needed for your project: Choose Vue version
? Choose a version of Vue.js that you want to start the project with
  2.x mslearn-vue-components 2021/5/30 下午 08:46 檔案資料夾
> 3.x
```

配置文件放置位置

- In dedicated config files

```
Vue CLI v4.5.13 mslearn-vue-components-practice
? Please pick a preset: Manually select features
? Check the features needed for your project: Choose Vue version
? Choose a version of Vue.js that you want to start the project with 3.x
? Where do you prefer placing config for Babel, ESLint, etc.? (Use arrow keys)
> In dedicated config files
  In package.json
```


是否作为预设设定

- 暂时先不储存(No)

```
Vue CLI v4.5.13 mslearn-vue-components-practice
? Please pick a preset: Manually select features
? Check the features needed for your project: Choose Vue version
? Choose a version of Vue.js that you want to start the project with 3.x
? Where do you prefer placing config for Babel, ESLint, etc.? In dedicated config files
? Save this as a preset for future projects? (y/N) █
```

项目检视与执行

- VS Code -> 档案 -> 开启文件夹... 开启 reelecloud
- 检视 -> 终端
 - `npm run serve`
- 打开浏览器
 - `http://localhost:8080/`



Vue Component 有三个section

- style
 - CSS样式
- script
 - data()
 - methods
 - components
- template
 - HTML界面

安裝 Vue 相關 Extension

- Vetur
- Vue VSCode Snippets




Vetur octref.vetur

Pine Wu | 7,555,439 | ★★★★★ | 儲存庫 | 授權 | v0.33.1

Vue tooling for VS Code

解除安裝 ▼ ⚙️

根據您最近開啟的檔案，建議您使用此延伸模組。



Vue VSCode Snippets sdras.vue-vscode-snippets

sarah.drasner | 970,869 | ★★★★★ | 儲存庫 | 授權 | v2.2.0

Snippets that will supercharge your Vue workflow

安裝 ⚙️

建立新的Component

- 在src/components路径下，新增档案
 - Host.vue
- 在Host.vue中，输入 vue
 - 选择 <vue> with default.vue

```
src > components > ▼ Host.vue
1  vue
  ▼<vue> with default.vue 🙌
  #<style> css.vue 🙌
  #<style> less.vue 🙌
  #<style> sass.vue 🙌
  #<style> scss.vue 🙌
  <><template> pug.vue 🙌
  #<style> stylus.vue 🙌
  <><template> html.vue 🙌
  #<style> postcss.vue 🙌
```

修改 script 区段

```
<script>
export default {
  data(){
    return {
      cruise:{
        name:'Cruise to the moon',
        description:'Cruise to the moon in our luxurious shuttle. Watch the astronauts
working outside the International Space Station.',
        cabins:[
          {name:'Coach',price:125000},
          {name:'Business',price:275000},
          {name:'First',price:430000}
        ]
      },
      bookings:[
        {name:'Sample',price:0}
      ]
    }
  },
  // TODO: Add components
  // TODO: Add methods
}
</script>
```

修改 template 区段

```
<template>
  <section>
    <div class="nav-bar"></div>
    <h1>Relecloud Galaxy Tours</h1>
    <div>
      <h2>{{cruise.name}}</h2>
      <div>{{cruise.description}}</div>
      <hr>
      <div class="row">
        <div> <!-- TODO: Add booking-form -->
        </div>
        <div> <!-- TODO: Add booking-list -->
        </div>
      </div>
    </div>
  </section>
</template>
```

修改 style 区段

```
<style>
  body{
    background-color: #f2f2f2;
    margin: 0,5%;
    font-family: tahoma;
  }
  .row{
    display: grid;
    grid-template-columns: 1fr 1fr;
    vertical-align: middle;
    margin: 2em;
  }
  .button{
    background-color: #39495c;
    border-radius: 5px;
    color: white;
    text-align: center;
  }
  .nav-bar{
    background: linear-gradient(-50deg, #010801, #0d0d60);
    height: 60px;
    margin-bottom: 25px;
  }
</style>
```

修改 main.js

- 换成载入刚刚制作的Host.vue

```
import { createApp } from 'vue'  
//import App from './App.vue'  
import Host from './components/Host.vue'  
  
//createApp(App).mount('#app')  
createApp(Host).mount('#app')
```

檢視網頁

Relecloud Galaxy Tours

Cruise to the moon

Cruise to the moon in our luxurious shuttle. Watch the astronauts working outside the International Space Station.

增加一个新的Component

- 在src/components 新增档案
BookingList.vue
- 输入 vue 选择样板
<vue> with default.vue

修改 script 区段

```
<script>
export default {
  props:{
    bookings:Array
  },
  computed:{
    totalDisplay(){
      let totalCost = 0;
      if(this.bookings && this.bookings.length>0){
        totalCost = this.bookings.map(x => x.price).reduce((prev,obj) => prev + obj);
      }
      return 'US$ ' + totalCost.toLocaleString('en-US');
    }
  }
}
</script>
```

修改 template 区段

```
<template>
  <section>
    <h2>Here's your current bookings:</h2>
    <div class="row" v-for="(booking,index) in bookings" :key="index">
      <div>{{booking.cabin}}</div>
    </div>
    <h3 class="row">Total:{{totalDisplay}}</h3>
  </section>
</template>
```

```
<script>
import BookingList from './BookingList.vue'
//TODO: Register next component
export default {
  data(){
    return {
      cruise:{
        name:'Cruise to the moon',
        description:'Cruise to the moon in our luxurious shuttle. Watch the astronauts working
outside the International Space Station.',
        cabins:[
          {name:'Coach',price:125000},
          {name:'Business',price:275000},
          {name:'First',price:430000}
        ]
      },
      bookings:[
        {name:'Sample',price:0}
      ]
    }
  },
  // TODO: Add components
  components:{
    BookingList,
    // TODO: Add next component
  }
  // TODO: Add methods
}
</script>
```

将BookingList组件加入主页面

- Host.vue
- script 区段

将BookingList组件加入主页面

<https://github.com/ryan403/reactor-sh-2021-vue>

```
<template>
  <section>
    <div class="nav-bar"></div>
    <h1>Relecloud Galaxy Tours</h1>
    <div>
      <h2>{{cruise.name}}</h2>
      <div>{{cruise.description}}</div>
      <hr>
      <div class="row">
        <div> <!-- TODO: Add booking-form -->
        </div>
        <div> <!-- TODO: Add booking-list -->
          <booking-list :bookings="bookings"></booking-list>
        </div>
      </div>
    </div>
  </section>
</template>
```

- Host.vue
- template 区域

檢視網頁

Relecloud Galaxy Tours

Cruise to the moon

Cruise to the moon in our luxurious shuttle. Watch the astronauts working outside the International Space Station.

Here's your current bookings:

Total:US\$ 0

增加客制化事件至组件

- 建立一个新的组件：BookingForm.vue
- 输入vue，使用样板<vue> with default.vue

BookingForm.vue

• 修改script区段

```
<script>
export default {
  props:{
    cabins:Array,
  },
  emits:[ 'bookingCreated' ],
  data(){
    return {
      cabinIndex:-1
    }
  },
  methods:{
    bookCabin(){
      if(this.cabinIndex<0) return;
      this.$emit('bookingCreated', this.cabinIndex);
      this.cabinIndex = -1;
    }
  }
}
</script>
```

BookingForm.vue

• 修改template区段

```
<template>
  <section>
    <h2>Book Now!</h2>
    <form>
      <div class="row">
        <label for="cruise-cabin">Select class:</label>
        <select id="cruise-cabin" v-model="cabinIndex">
          <option disabled value="-1">Select a cabin</option>
          <option v-for="(cabin, index) in cabins" :value="index" :key="index">
            {{cabin.name}} US${{cabin.price.toLocaleString('en-US')}}
          </option>
        </select>
      </div>
      <div class="row">
        <button class="button" type="button" @click="bookCabin">Book now!</button>
      </div>
    </form>
  </section>
</template>
```

将BookingForm加入主页面

- src/Host.vue
- 修改script区段

```
<script>
```

```
import BookingList from './BookingList.vue'
```

```
//TODO: Register next component
```

```
import BookingForm from './BookingForm.vue'
```

将BookinForm加入主页面

<https://github.com/ryan403/reactor-sh-2021-vue>

- src/Host.vue
- 修改script区段

```
// TODO: Add components
components:{
  BookingList,
  // TODO: Add next component
  BookingForm
},
// TODO: Add methods
methods:{
  addBooking(cabinIndex){
    const cabin = this.cruise.cabins[cabinIndex];
    const booking = {
      cabin:cabin.name,
      price:cabin.price
    };
    this.bookings.push(booking);
  }
}
```

将BookinForm加入主页面

- src/Host.vue
- 修改template区段

```
<div class="row">  
  <div> <!-- TODO: Add booking-form -->  
    <booking-form @bookingCreated="addBooking" :cabins="cruise.cabins"></booking-form>  
  </div>  
  <div> <!-- TODO: Add booking-list -->  
    <booking-list :bookings="bookings"></booking-list>  
  </div>  
</div>
```


测试网页

- 可新增多笔

Relecloud Galaxy Tours

Cruise to the moon

Cruise to the moon in our luxurious shuttle. Watch the astronauts working outside the International Space Station.

Book Now!

Select class:

Select a cabin

Book now!


Here's your current bookings:

Coach

Business

Total:US\$ 400,000

架构回顾



知识检查

1. 用于为组件注册自定义事件的属性是什么？

- ☐ events
- ☐ emits
- ☐ props
- ☐ methods

2. Vue CLI 中用于创建 Web 应用程序的命令是什么？

- ☐ create
- ☐ help
- ☐ info

3. 你使用什么字段来列出应用的可用组件？

- ☐ methods
- ☐ props
- ☐ data
- ☐ components

[s://github.com/ryan403/reactor-sh-2021-vue](https://github.com/ryan403/reactor-sh-2021-vue)

Summary 摘要

- 使用Vue CLI创建 Vue应用程序
- 建立单一档案组件
- 将组件加入页面



Reactor



developer.microsoft.com/reactor/
[@MSFTReactor](#) on Twitter



议程结束 感谢聆听



请记得填写课程回馈问卷 (Event ID : **XXXXXX**)
<https://aka.ms/Reactor/Survey>

© 2019 Microsoft Corporation. All rights reserved. The text in this document is available under the Creative Commons Attribution 3.0 License, additional terms may apply. All other content contained in this document (including, without limitation, trademarks, logos, images, etc.) are not included within the Creative Commons license grant. This document does not provide you with any legal rights to any intellectual property in any Microsoft product. You may copy and use this document for your internal, reference purposes.

This document is provided "as-is." Information and views expressed in this document, including URL and other Internet Web site references, may change without notice. You bear the risk of using it. Some examples are for illustration only and are fictitious. No real association is intended or inferred. Microsoft makes no warranties, express or implied, with respect to the information provided here.