Applied Numerical Methods I, 3450:427/527, Kreider, Fall 2012

Computing Project 4 – Tridiagonal Matrix Solver (50 points) Due date: Thursday 8 November

We're going to do several things in this project. First, we'll introduce a special version of Gauss Elimination to use with tridiagonal matrices. The inner loop is replaced by a simple calculation that speeds up the solution process tremendously. Mathematicians call this special version the Crout Algorithm, and engineers call it the Thomas Algorithm. Second, we'll get a preview of some topics in Applied Numerical Methods II – specifically, how to approximate derivatives and how to solve differential equations numerically.

Part 1. The algorithm we will use is trinumrec.m, on my web site. It is taken from Numerical Recipes, by WH Press et al, Cambridge University Press, 1992. The parameters are:

AL is the left subdiagonal (remember, AL(1) is not used, as discussed in class)

AM is the main diagonal

AR is the right superdiagonal

r is the right hand side

u is the output vector

To use algorithm on Au=r, script files typically have this structure:

```
{build x, spatial domain}
{build AL, AM, AR for i=1}
{build AL, AM, AR for i=2,...,N-1}
{build AL, AM, AR for i=N}
{build r}
u = tridiag(AL,AM,AR,r)
plot(x,u)
```

Download the routine. You don't need to submit anything for Part 1.

Part 2. Whenever you get an algorithm from an outside source, you should test it on a simple problem whose answer you know. Here is a system in augmented matrix form that you can use to test your algorithm. The solution to the system is u = (1, 1, 1, 1)' so it is easy to see whether you're using the function properly.

$$\left(\begin{array}{ccc|cccc}
2 & -1 & 0 & 0 & 1 \\
-1 & 2 & -1 & 0 & 0 \\
0 & -1 & 2 & -1 & 0 \\
0 & 0 & -1 & 2 & 1
\end{array}\right)$$

Turn in a copy of the script file you used to test the algorithm, and a print out of the results.

Part 3. We are now going to solve a differential equation. The problem is

$$y''(x) + 3y'(x) = x^2y(x) = e^{-x_i}$$

$$y(0) = 10$$
$$y(2) = -3$$

Think of y(x) as the steady state temperature of a thin wire that sits in $0 \le x \le 2$. We'll solve for y(x) at a grid of points x_i (i = 1, ..., N). The notation is $x_1 = 0$, $x_i = (i - 1) * h$, $x_N = 2$, with h = 2/(N - 1). This will give us a set of values $y_1, y_2, ..., y_N$ at each of the grid points. We'll let N = 2001, so that h = .001. At each of the interior points i = 2, ..., N - 1, we'll need to approximate the equation by discretizing the equations. At the 2 endpoints i = 1 and i = N, we'll use the boundary conditions: $y_1 = 10$ and $y_N = -3$.

To discretize the equation, we need approximations for the derivatives y'' and y'. We'll use standard forms developed in 428/528 ANM2:

$$y''(x) = \frac{y(x-h) - 2y(x) + y(x+h)}{h^2}$$
$$y'(x) = \frac{y(x+h) - y(x-h)}{2h}$$

If we let $x = x_i$, then $x + h = x_{i+1}$ and $x - h = x_{i-1}$, so we get

$$y''(x_i) = \frac{y_{i-1} - 2y_i + y_{i+1}}{h^2}$$
$$y'(x_i) = \frac{y_{i+1} - y_{i-1}}{2h}$$

When we discretize the equation at a point x_i , the result is

$$\frac{y_{i-1} - 2y_i + y_{i+1}}{h^2} + 3\frac{y_{i+1} - y_{i-1}}{2h} + x_i^2 y_i = e^{-x_i}$$

We need to combine terms to set this up as a tridiagonal system:

$$\left(\frac{1}{h^2} - \frac{3}{2h}\right)y_{i-1} + \left(x_i^2 - \frac{2}{h^2}\right)y_i + \left(\frac{1}{h^2} + \frac{3}{2h}\right)y_{i+1} = e^{-x_i}$$

For simplicity, denote the coefficients as A, B and C. This equation applies to x_i for i = 2, ..., N-1, which will form the interior rows of the matrix system. With the left boundary condition in the first row, and the right in the last row, we get a tridiagonal matrix:

$$\begin{bmatrix} 1 & 0 & 0 & 0 & \dots & 0 \\ A & B & C & 0 & \dots & 0 \\ 0 & A & B & C & 0 & 0 \\ 0 & 0 & \ddots & \ddots & \ddots & 0 \\ 0 & 0 & \dots & A & B & C \\ 0 & 0 & \dots & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} y_1 \\ y_2 \\ y_3 \\ \vdots \\ y_{N-1} \\ y_N \end{bmatrix} = \begin{bmatrix} 10 \\ e^{-x_2} \\ e^{-x_3} \\ \vdots \\ e^{-x_{N-1}} \\ -3 \end{bmatrix}$$

We'll talk in class about how to build this system in MATLAB and how to use the tridiagonal solver. You will solve the system and plot the solution for Part 3.

WHAT TO TURN IN. You do not have to write a summary. Make sure that what you turn in is easily readable, but don't go to extreme lengths to make it look pretty.

Part 2. A copy of the script file you used to test the algorithm, and a printout of the results. (1 or 2 pages)

Part 3. A copy of the script file you used to build and solve the system and plot of the solution. (1 or 2 pages)