

Partner: AVPro Edge
Models: MXNet
Device Type: Network Switching



GENERAL INFORMATION

SIMPLWINDOWS NAME:	AVPro Edge MXNet Decoder v2.6
CATEGORY:	AVPro Edge MXNet
VERSION:	2.6
SUMMARY:	This module works in conjunction with the AVPro MXNet CommandProcessor v2.6 module to control one decoder of an Edge MXNet system. The full suite of AVPro MXNet modules includes: • AVPro MXNet CommandProcessor v2.6 • AVPro MXNet Encoder v2.6 • AVPro MXNet Decoder v2.6 • AVPro MXNet SerialPort v2.6 • AVPro MXNet IRPort v2.6 • AVPro MXNet CEC v2.6 • AVPro MXNet DestinationRouter v2.6 • AVPro MXNet MultiDestinationRouter v2.6 • AVPro MXNet VW DecoderAssign v2.6 • AVPro MXNet VW Layout v2.6 • AVPro MXNet VW LayoutRecall v2.6 • AVPro MXNet 10G VW LayoutRecall v2.6 • AVPro MXNet Matrix PresetRecall v2.6 • AVPro MXNet Matrix Macro v2.6
GENERAL NOTES:	This module requires one instance of the AVPro MXNet CommandProcessor v2.6 module to register with and one instance of the AVPro MXNet Encoder module v2.6 to handle routing of a single input.
CRESTRON HARDWARE REQUIRED:	4-Series processor, 3-Series processor
SETUP OF CRESTRON HARDWARE:	N/A
VENDOR FIRMWARE:	MXNet 1G Control Box v2.4 MXNet 1G Encoder v3.39 MXNet 1G Decoder v4.21 MXNet 10G Control Box v3.28 MXNet 10G Encoder v1.25 MXNet 10G Decoder v1.25
VENDOR SETUP:	N/A

Partner: AVPro Edge
Models: MXNet
Device Type: Network Switching



PARAMETERS:

Command_Processor_ID	The unique identifier of the command processor module that this module registers with.
MAC_Address_or_Device_ID	The MAC Address or Device ID (Custom Name) of the decoder used to associate this component with.
Matrix_Destination_Index	The specific index of this decoder to be used on the Destination Router module. (Minimum = 1 Maximum = 256)

Partner: AVPro Edge
Models: MXNet
Device Type: Network Switching



CONTROL:

Reboot	D	Pulse to reboot the Decoder.
Screen_On	D	Pulse to turn on the Decoder display screen.
Screen_Flash	D	Pulse to flash the Decoder display screen.
Screen_Off	D	Pulse to turn off the Decoder display screen.
OSD_On	D	Pulse to set the on-screen display on. <i>10G does not support this.</i>
OSD_Off	D	Pulse to set the on-screen display off. <i>10G does not support this.</i>
Volume_Level_Up	D	Ramp volume up incrementally while signal is high. <i>1G does not support this.</i>
Volume_Level_Down	D	Ramp volume down incrementally while signal is high. <i>1G does not support this.</i>
Volume_Level	A	Integer value specifies the target volume level to set. Range is 0 to 100. <i>1G does not support this.</i>
Volume_Level_Set	D	Pulse to set the target volume specified by the Volume_Level analog signal. <i>1G does not support this.</i>
Volume_Mute_On	D	Pulse to set the volume to the lowest possible level. <i>1G does not support this.</i>
Volume_Mute_Off	D	Pulse to set the volume to the previous level prior to muting. <i>1G does not support this.</i>
Volume_Mute_Toggle	D	Pulse to alternate the volume mute state between on and off. <i>1G does not support this.</i>
Resolution	A	Analog value specifies the resolution to use from the defined resolution list. Possible values include: 0: passthrough, 1: 720P50, 2: 720P60, 3: 1080P24, 4: 1080P50, 5: 1080P60, 6: 4K30, 7: 4K50, 8: 4K60

Partner: AVPro Edge
Models: MXNet
Device Type: Network Switching

**Hot_Plug_Reset**

D Pulse to reset the hot plug on the device.

Partner: AVPro Edge
 Models: MXNet
 Device Type: Network Switching



FEEDBACK:

Is_Initialized	D	Digital high indicates this decoder block has been initialized with the command processor module.
Is_Online	D	Digital high indicates the decoder is online, or not online when the signal is low.
Screen_On_Fb	D	Digital high indicates the decoder front panel display screen is on, or not on when the signal is low.
Screen_Flash_Fb	D	Digital high indicates the decoder front panel display screen is flashing, or not flashing when the signal is low.
Screen_Off_Fb	D	Digital high indicates the decoder front panel display screen is off, or not off when the signal is low.
OSD_On_Fb	D	Digital high indicates the on-screen display is on, or not on when the signal is low, if applicable.
OSD_Off_Fb	D	Digital high indicates the on-screen display is off, or not off when the signal is low, if applicable.
Volume_Level_Fb	A	Integer value indicates the current extracted audio volume, if applicable. Range is 0 to 100. <i>1G does not support this.</i>
Volume_Mute_On_Fb	D	Digital high indicates the volume level is at the lowest possible value, if applicable. <i>1G does not support this.</i>
Resolution_Fb	A	Integer value indicates the currently selected resolution value.
VideoWall_Count_Fb	A	Integer value indicates the number of video wall layouts this decoder is included in.
Hot_Plug_Detect_Fb	D	Digital high indicates the hot plug is detected, or not detected when the signal is low.
Connection_Rating	S	Text value indicates the current connection speed rating.
Resolution_and_Timing	S	Text value indicates the current resolution and FPS. Format example: 3840x2160, 30.
Colorspace	S	Text value indicates the current colorspace reported.
Bit_Depth	S	Text value indicates the current bit depth reported.
HDR_Status	S	Text value indicates the current HDR status ON or OFF.
HDCP_Status	S	Text value indicates the current HDCP status ON or OFF.
Audio_Format_Fb	S	Text value indicates the current audio format reported.
Network_Connection_Fb	S	Text value indicates the current network connection reported.
Device_Id_Fb	S	Text value indicating the device meta data for Device ID.

Partner: AVPro Edge
Models: MXNet
Device Type: Network Switching



MAC_Address_Fb	S	Text value indicating the device meta data for MAC Address.
-----------------------	---	---

Partner: AVPro Edge
Models: MXNet
Device Type: Network Switching



TESTING:

	VC4 v4.0000.00007
OPS USED FOR TESTING:	CP4 v2.8001.00086.01
	CP3 v1.8001.0214.01
SIMPL WINDOWS USED FOR TESTING:	4.2500.04
CRES DB USED FOR TESTING:	219.0500.001.00
DEVICE DATABASE:	200.28000.002.00
SYMBOL LIBRARY USED FOR TESTING:	1191
SAMPLE PROGRAM:	AVPro Edge MXNet v2.6 Demo.smw

REVISION HISTORY:

- v1.0 – Initial Release
- v1.1 – Fixed SerialPort transmitted and received data.
 - Made updates to allow a Wallplate Encoder to initialize with this suite.
- v1.2 – Isolated serial communication queue to provide device control responsiveness.
 - Corrected unsolicited data parsing impacting hotplug detected and resolution.
- v2.0 – Added “Offline” functionality.
 - Polling will happen more frequently but will only poll for one component’s states at a time. This prevents serial control from getting backed up behind a global system poll.
- v2.1 – Added volume support for applicable 10G decoders.
 - Added support for 10G videowall support with “10G VW Layout”
- v2.2 - Change 1G video wall input select to new faster API command
- v2.3 – Added CEC support for Encoders.
- v2.4 – Added Matrix PresetRecall and Matrix Macro module.
- V2.5 – Added video preview urls to encoder module.
- v2.6 – Reconnect time increased from 30 seconds to 90 seconds.