

This document provides additional assistance with wiring your Extron IP Link Pro Control Processor to your device. Different components may require a different wiring scheme than those listed below.

For complete operating instructions, refer to the user's manual for the specific IP Link Pro Control Processor or the documentation supplied by the manufacturer of the controlled device.

For more information on using Global Scriptor Modules, refer to the "[Guide to Using Scriptor Modules](#)" document.

Device Specifications

Device Type: Video Projector
Manufacturer: BenQ
Firmware Version: N/A
Model(s): W1080ST, W1070

Tested on the Following Software and Firmware Versions

IP Link Pro Control Processor Firmware	Global Scriptor Version
3.04.0001-b002	2.3.1

Version History

Module Version	Date	Notes
1_0_0_0	10/7/2019	Initial Version

Module Notes

- Unidirectional variable must be set to 'True' if status is not required. Default value is 'False'.
Example: `InterfaceName.Unidirectional = 'True'`
- connectionCounter variable must be set to the number of queries that will be sent to the device before displaying 'Disconnected' if no response is received. Default value is 15.
Example: `InterfaceName.connectionCounter = 5`

Supported Classes and Examples

SerialClass
<code>InterfaceName = ModuleName.SerialClass(ProcessorName, 'COM1', Model='W1080ST')</code>
SerialOverEthernetClass
<code>InterfaceName = ModuleName.SerialOverEthernetClass('192.168.254.254', 2001, Model='W1080ST')</code>

Control Commands

Format with Qualifier:

```
InterfaceName.Set(Command, Value, {'Qualifier Key': 'Qualifier Value'})
```

Format with Qualifier:

```
InterfaceName.Set(Command, Value)
```

Command 3DMode	Value 'Off' 'Frame Packing'	Value 'Auto' 'Top Bottom'	Value 'Frame Sequential' 'Side by Side'
# 3DMode example InterfaceName.Set('3DMode', 'Off')			
Command AspectRatio	Value '4:3' 'Auto' 'Wide'	Value '16:9' 'Real' 'Anamorphic'	Value '16:10' 'Letterbox'
# AspectRatio example InterfaceName.Set('AspectRatio', '4:3')			
Command AudioMute	Value 'On'	Value 'Off'	
# AudioMute example InterfaceName.Set('AudioMute', 'On')			
Command AutoImage	Value None		
# AutoImage example InterfaceName.Set('AutoImage', None)			
Command DigitalZoom	Value 'In'	Value 'Out'	
# DigitalZoom example InterfaceName.Set('DigitalZoom', 'In')			
Command Freeze	Value 'On'	Value 'Off'	
# Freeze example InterfaceName.Set('Freeze', 'On')			
Command Input	Value 'HDMI 1' 'S-Video'	Value 'HDMI 2' 'Component'	Value 'Video' 'PC'
# Input example InterfaceName.Set('Input', 'HDMI 1')			
Command LampMode	Value 'Normal'	Value 'Eco'	Value 'Smart Eco'
# LampMode example InterfaceName.Set('LampMode', 'Normal')			
Command MenuNavigation	Value 'Menu On' 'Down' 'Enter'	Value 'Menu Off' 'Left'	Value 'Up' 'Right'
# MenuNavigation example InterfaceName.Set('MenuNavigation', 'Menu On')			
Command Power	Value 'On'	Value 'Off'	
# Power example InterfaceName.Set('Power', 'On')			

Global Scripter Module Communication Sheet

Command VideoMute	Value 'On'	Value 'Off'
# VideoMute example InterfaceName.Set('VideoMute', 'On')		
Command Volume	Value 'Up'	Value 'Down'
# Volume example InterfaceName.Set('Volume', 'Up')		

Status Available

For all commands, call Update to receive the latest status. ConnectionStatus does not support the Update function and is triggered by the device providing a successful response to other Update function calls.

Format with Qualifier:

```
InterfaceName.Update(Command, {'Qualifier Key': 'Qualifier Value'})
Value = InterfaceName.ReadStatus(Command, {'Qualifier Key': 'Qualifier Value'})
InterfaceName.SubscribeStatus(Command, {'Qualifier Key': 'Qualifier Value'},
```

FeedbackHandler)

FeedbackHandler will be called only when the specified qualifier gets a new status.

Format without Qualifier:

```
InterfaceName.Update(Command)
Value = InterfaceName.ReadStatus(Command)
InterfaceName.SubscribeStatus(Command, None, FeedbackHandler)
FeedbackHandler will be called when any qualifier gets a new status.
```

Command 3DMode	Value 'Off' 'Frame Packing'	Value 'Auto' 'Top Bottom'	Value 'Frame Sequential' 'Side by Side'
# 3DMode example InterfaceName.Update('3DMode') Value = InterfaceName.ReadStatus('3DMode') InterfaceName.SubscribeStatus('3DMode', None, FeedbackHandler)			
Command AspectRatio	Value '4:3' 'Auto' 'Wide'	Value '16:9' 'Real' 'Anamorphic'	Value '16:10' 'Letterbox'
# AspectRatio example InterfaceName.Update('AspectRatio') Value = InterfaceName.ReadStatus('AspectRatio') InterfaceName.SubscribeStatus('AspectRatio', None, FeedbackHandler)			
Command AudioMute	Value 'On'	Value 'Off'	
# AudioMute example InterfaceName.Update('AudioMute') Value = InterfaceName.ReadStatus('AudioMute') InterfaceName.SubscribeStatus('AudioMute', None, FeedbackHandler)			
Command ConnectionStatus	Value 'Connected'	Value 'Disconnected'	
# ConnectionStatus example Value = InterfaceName.ReadStatus('ConnectionStatus') InterfaceName.SubscribeStatus('ConnectionStatus', None, FeedbackHandler)			
Command Freeze	Value 'On'	Value 'Off'	
# Freeze example InterfaceName.Update('Freeze') Value = InterfaceName.ReadStatus('Freeze') InterfaceName.SubscribeStatus('Freeze', None, FeedbackHandler)			
Command Input	Value 'HDMI 1' 'S-Video'	Value 'HDMI 2' 'Component'	Value 'Video' 'PC'
# Input example InterfaceName.Update('Input') Value = InterfaceName.ReadStatus('Input') InterfaceName.SubscribeStatus('Input', None, FeedbackHandler)			

Global Scripter Module Communication Sheet

Command	Value	Value	Value
LampMode	'Normal'	'Eco'	'Smart Eco'
# LampMode example InterfaceName.Update('LampMode') Value = InterfaceName.ReadStatus('LampMode') InterfaceName.SubscribeStatus('LampMode', None, FeedbackHandler)			
Command	Value		
LampUsage	Hours		
# LampUsage example InterfaceName.Update('LampUsage') Value = InterfaceName.ReadStatus('LampUsage') InterfaceName.SubscribeStatus('LampUsage', None, FeedbackHandler)			
Command	Value	Value	
Power	'On'	'Off'	
# Power example InterfaceName.Update('Power') Value = InterfaceName.ReadStatus('Power') InterfaceName.SubscribeStatus('Power', None, FeedbackHandler)			
Command	Value	Value	
VideoMute	'On'	'Off'	
# VideoMute example InterfaceName.Update('VideoMute') Value = InterfaceName.ReadStatus('VideoMute') InterfaceName.SubscribeStatus('VideoMute', None, FeedbackHandler)			
Command	Value		
VolumeStatus	0 – 10		
# VolumeStatus example InterfaceName.Update('VolumeStatus') Value = InterfaceName.ReadStatus('VolumeStatus') InterfaceName.SubscribeStatus('VolumeStatus', None, FeedbackHandler)			

Cable and Adapter Requirements

Captive Screw to Female DB9 RS-232 Serial Cable


Notes for the Device

Serial communication


Port Type: RS-232
Baud Rate: 115200
Data Bits: 8

Parity: None
Stop Bits: One
Flow Control: None

Pin Assignments Diagram



Signal	Main Cable	Pin	Signal
TxD	→	2	RxD
RxD	←	3	TxD
GND	→	5	GND



Appendix A. Set Commands

3D Mode Auto	\x0D*3d=auto#\x0D
3D Mode Frame Packing	\x0D*3d=fp#\x0D
3D Mode Frame Sequential	\x0D*3d=fs#\x0D
3D Mode Off	\x0D*3d=off#\x0D
3D Mode Side by Side	\x0D*3d=sbs#\x0D
3D Mode Top Bottom	\x0D*3d=tb#\x0D
Aspect Ratio 16:10	\x0D*asp=16:10#\x0D
Aspect Ratio 16:9	\x0D*asp=16:9#\x0D
Aspect Ratio 4:3	\x0D*asp=4:3#\x0D
Aspect Ratio Anamorphic	\x0D*asp=ANAM#\x0D
Aspect Ratio Auto	\x0D*asp=AUTO#\x0D
Aspect Ratio Letterbox	\x0D*asp=LBOX#\x0D
Aspect Ratio Real	\x0D*asp=REAL#\x0D
Aspect Ratio Wide	\x0D*asp=WIDE#\x0D
Audio Mute Off	\x0D*mute=off#\x0D
Audio Mute On	\x0D*mute=on#\x0D
Auto Image None	\x0D*auto#\x0D
Digital Zoom In	\x0D*zoomI#\x0D
Digital Zoom Out	\x0D*zoomO#\x0D
Freeze Off	\x0D*freeze=off#\x0D
Freeze On	\x0D*freeze=on#\x0D
Input Component	\x0D*sour=yubr#\x0D
Input HDMI 1	\x0D*sour=hdm1#\x0D
Input HDMI 2	\x0D*sour=hdm2#\x0D
Input PC	\x0D*sour=RGB#\x0D
Input S-Video	\x0D*sour=svid#\x0D
Input Video	\x0D*sour=vid#\x0D
Lamp Mode Eco	\x0D*lamp=eco#\x0D
Lamp Mode Normal	\x0D*lamp=lnor#\x0D
Lamp Mode Smart Eco	\x0D*lamp=seco#\x0D
Menu Navigation Down	\x0D*down#\x0D
Menu Navigation Enter	\x0D*enter#\x0D
Menu Navigation Left	\x0D*left#\x0D
Menu Navigation Menu Off	\x0D*menu=off#\x0D
Menu Navigation Menu On	\x0D*menu=on#\x0D
Menu Navigation Right	\x0D*right#\x0D
Menu Navigation Up	\x0D*up#\x0D
Power Off	\x0D*pow=off#\x0D
Power On	\x0D*pow=on#\x0D
Video Mute Off	\x0D*blank=off#\x0D
Video Mute On	\x0D*blank=on#\x0D
Volume Down	\x0D*vol=-#\x0D

Volume Up	\x0D*vol=+#\x0D
------------------	-----------------

Appendix B. Update Commands

3D Mode	\x0D*3d=?#\x0D
Aspect Ratio	\x0D*asp=?#\x0D
Audio Mute	\x0D*mute=?#\x0D
Freeze	\x0D*freeze=?#\x0D
Input	\x0D*sour=?#\x0D
Lamp Mode	\x0D*lamp=?#\x0D
Lamp Usage	\x0D*ltim=?#\x0D
Power	\x0D*pow=?#\x0D
Video Mute	\x0D*blank=?#\x0D
Volume Status	\x0D*vol=?#\x0D