

This document provides additional assistance with wiring your Extron IP Link Pro Control Processor to your device. Different components may require a different wiring scheme than those listed below.

For complete operating instructions, refer to the user's manual for the specific IP Link Pro Control Processor or the documentation supplied by the manufacturer of the controlled device.

For more information on using Global Scriptor Modules, refer to the "[Guide to Using Scriptor Modules](#)" document.

Device Specifications

Device Type: Lighting Control
Manufacturer: Clipsal
Firmware Version: N/A
Model(s): CNI 5500CN2

Tested on the Following Software and Firmware Versions

IP Link Pro Control Processor Firmware	Global Scriptor Version
3.00.0000-b022	2.0.0

Version History

Module Version	Date	Notes
1_3_1_0	11/12/2018	Added status for DimLevel command. Added ApplicationAddress parameter to the commands. Removed LightingApplicationAddress module parameter.
1_2_1_0	7/30/2018	Added status for SwitchLight command, removed ConnectionStatus.
1_1_0_0	1/16/2018	Initial Version

Module Notes

- Checksum variable must be set accordingly. Default value is 'Enabled'. Checksum can be set to 'Enabled' and the module will send a checksum byte to the device. Checksum can be set to 'Disabled' and the device will not look for a checksum byte in the command strings.
Example: `InterfaceName.Checksum = 'Enabled'`

Supported Class and Example

EthernetClass
<code>InterfaceName = ModuleName.EthernetClass('192.168.254.254', 10001, Model='CNI 5500CN2')</code>

Control Commands

Format with Qualifier:

```
InterfaceName.Set(Command, Value, {'Qualifier Key': 'Qualifier Value'})
```

Format without Qualifier:

```
InterfaceName.Set(Command, Value)
```

Command DimLevel	Value 0 to 255 in steps of 1		
Qualifier Key 'Application Address'	Qualifier Value '48' – '255'		
Qualifier Key 'Group Address'	Qualifier Value '0' – '255'		
Qualifier Key 'Dimming Rate'	Qualifier Value 'Instantaneous'	Qualifier Value '4 seconds'	Qualifier Value '8 seconds'
	'12 seconds'	'20 seconds'	'30 seconds'
	'40 seconds'	'1 minute'	'1.5 minutes'
	'2 minutes'	'3 minutes'	'5 minutes'
	'7 minutes'	'10 minutes'	'15 minutes'
	'17 minutes'		
	# DimLevel example InterfaceName.Set('DimLevel', 255, {'Application Address': '48', 'Group Address': '0', 'Dimming Rate': 'Instantaneous'})		
Command SwitchLight	Value 'On'	Value 'Off'	
Qualifier Key 'Application Address'	Qualifier Value '48' – '255'		
Qualifier Key 'Group Address'	Qualifier Value '0' – '255'		
# SwitchLight example InterfaceName.Set('SwitchLight', 'On', {'Application Address': '48', 'Group Address': '0'})			

Status Available

Device does not support any Update command. All statuses are unsolicited responses from the device.

Format with Qualifier:

```
InterfaceName.Update(Command, {'Qualifier Key': 'Qualifier Value'})
Value = InterfaceName.ReadStatus(Command, {'Qualifier Key': 'Qualifier Value'})
InterfaceName.SubscribeStatus(Command, {'Qualifier Key': 'Qualifier Value'}, FeedbackHandler)
FeedbackHandler will be called only when the specified qualifier gets a new status.
```

Format without Qualifier:

```
InterfaceName.Update(Command)
Value = InterfaceName.ReadStatus(Command)
InterfaceName.SubscribeStatus(Command, None, FeedbackHandler)
FeedbackHandler will be called when any qualifier gets a new status.
```

Command DimLevel	Value 0 to 255 in steps of 1		
Qualifier Key 'Application Address'	Qualifier Value '48' – '255'		
Qualifier Key 'Group Address'	Qualifier Value '0' – '255'		
Qualifier Key 'Dimming Rate'	Qualifier Value 'Instantaneous'	Qualifier Value '4 seconds'	Qualifier Value '8 seconds'
	'12 seconds'	'20 seconds'	'30 seconds'
	'40 seconds'	'1 minute'	'1.5 minutes'
	'2 minutes'	'3 minutes'	'5 minutes'
	'7 minutes'	'10 minutes'	'15 minutes'
	'17 minutes'		
<pre># DimLevel examples Value = InterfaceName.ReadStatus('DimLevel', {'Application Address': '48', 'Group Address': '0', 'Dimming Rate': 'Instantaneous'}) InterfaceName.SubscribeStatus('DimLevel', None, FeedbackHandler)</pre>			
Command SwitchLight	Value 'On'		Value 'Off'
Qualifier Key 'Application Address'	Qualifier Value '48' – '255'		
Qualifier Key 'Group Address'	Qualifier Value '0' – '255'		
<pre># SwitchLight examples Value = InterfaceName.ReadStatus('SwitchLight', {'Application Address': '48', 'Group Address': '0'}) InterfaceName.SubscribeStatus('SwitchLight', None, FeedbackHandler)</pre>			

Network communication

When configuring the Ethernet module, be sure device settings match those of the Global Scripter ethernet interface

Port Type:	Ethernet
Default Port:	10001
Logon Credentials Supported:	No
Multi-Connection Capabilities:	No
Port Changeability:	No

Ethernet Module Configuration Description

Please refer to user manual for settings and changes to the network communication

Notes for the Device

Appendix A. Set Commands

Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 1 minute	\05FF003A0000C2\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 1.5 minutes	\05FF00420000BA\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 10 minutes	\05FF006A000092\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 12 seconds	\05FF001A0000E2\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 15 minutes	\05FF007200008A\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 17 minutes	\05FF007A000082\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 2 minutes	\05FF004A0000B2\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 20 seconds	\05FF00220000DA\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 3 minutes	\05FF00520000AA\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 30 seconds	\05FF002A0000D2\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 4 seconds	\05FF000A0000F2\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 40 seconds	\05FF00320000CA\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 5 minutes	\05FF005A0000A2\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 7 minutes	\05FF006200009A\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate 8 seconds	\05FF00120000EA\x0D
Dim Level 0 Group Address 0 Application Address 255 Dimming Rate Instantaneous	\05FF00020000FA\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 1 minute	\0530003A000091\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 1.5 minutes	\05300042000089\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 10 minutes	\0530006A000061\x0D

Global Scripter Module Communication Sheet

Revision: 11/12/2018

Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 12 seconds	\0530001A0000B1\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 15 minutes	\05300072000059\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 17 minutes	\0530007A000051\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 2 minutes	\0530004A000081\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 20 seconds	\053000220000A9\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 3 minutes	\05300052000079\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 30 seconds	\0530002A0000A1\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 4 seconds	\0530000A0000C1\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 40 seconds	\05300032000099\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 5 minutes	\0530005A000071\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 7 minutes	\05300062000069\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate 8 seconds	\053000120000B9\x0D
Dim Level 0 Group Address 0 Application Address 48 Dimming Rate Instantaneous	\053000020000C9\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 1 minute	\05FF003AFF00C3\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 1.5 minutes	\05FF0042FF00BB\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 10 minutes	\05FF006AFF0093\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 12 seconds	\05FF001AFF00E3\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 15 minutes	\05FF0072FF008B\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 17 minutes	\05FF007AFF0083\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 2 minutes	\05FF004AFF00B3\x0D

Global Scripter Module Communication Sheet

Revision: 11/12/2018

Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 20 seconds	\05FF0022FF00DB\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 3 minutes	\05FF0052FF00AB\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 30 seconds	\05FF002AFF00D3\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 4 seconds	\05FF000AFF00F3\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 40 seconds	\05FF0032FF00CB\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 5 minutes	\05FF005AFF00A3\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 7 minutes	\05FF0062FF009B\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate 8 seconds	\05FF0012FF00EB\x0D
Dim Level 0 Group Address 255 Application Address 255 Dimming Rate Instantaneous	\05FF0002FF00FB\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 1 minute	\0530003AFF0092\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 1.5 minutes	\05300042FF008A\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 10 minutes	\0530006AFF0062\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 12 seconds	\0530001AFF00B2\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 15 minutes	\05300072FF005A\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 17 minutes	\0530007AFF0052\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 2 minutes	\0530004AFF0082\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 20 seconds	\05300022FF00AA\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 3 minutes	\05300052FF007A\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 30 seconds	\0530002AFF00A2\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 4 seconds	\0530000AFF00C2\x0D

Global Scripter Module Communication Sheet

Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 40 seconds	\05300032FF009A\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 5 minutes	\0530005AFF0072\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 7 minutes	\05300062FF006A\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate 8 seconds	\05300012FF00BA\x0D
Dim Level 0 Group Address 255 Application Address 48 Dimming Rate Instantaneous	\05300002FF00CA\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 1 minute	\05FF003A00FFC3\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 1.5 minutes	\05FF004200FFB8\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 10 minutes	\05FF006A00FF93\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 12 seconds	\05FF001A00FFE3\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 15 minutes	\05FF007200FF8B\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 17 minutes	\05FF007A00FF83\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 2 minutes	\05FF004A00FFB3\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 20 seconds	\05FF002200FFDB\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 3 minutes	\05FF005200FFAB\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 30 seconds	\05FF002A00FFD3\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 4 seconds	\05FF000A00FFF3\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 40 seconds	\05FF003200FFCB\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 5 minutes	\05FF005A00FFA3\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 7 minutes	\05FF006200FF9B\x0D
Dim Level 255 Group Address 0 Application Address 255 Dimming Rate 8 seconds	\05FF001200FFEB\x0D

Global Scripter Module Communication Sheet

Revision: 11/12/2018

Dim Level 255 Group Address 0 Application Address 255 Dimming Rate Instantaneous	\05FF000200FFFB\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 1 minute	\0530003A00FF92\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 1.5 minutes	\0530004200FF8A\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 10 minutes	\0530006A00FF62\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 12 seconds	\0530001A00FFB2\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 15 minutes	\0530007200FF5A\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 17 minutes	\0530007A00FF52\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 2 minutes	\0530004A00FF82\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 20 seconds	\0530002200FFAA\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 3 minutes	\0530005200FF7A\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 30 seconds	\0530002A00FFA2\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 4 seconds	\0530000A00FFC2\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 40 seconds	\0530003200FF9A\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 5 minutes	\0530005A00FF72\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 7 minutes	\0530006200FF6A\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate 8 seconds	\0530001200FFBA\x0D
Dim Level 255 Group Address 0 Application Address 48 Dimming Rate Instantaneous	\0530000200FFCA\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 1 minute	\05FF003AFFFFC4\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 1.5 minutes	\05FF0042FFFFBC\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 10 minutes	\05FF006AFFFF94\x0D

Global Scripter Module Communication Sheet

Revision: 11/12/2018

Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 12 seconds	\05FF001AFFFFE4\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 15 minutes	\05FF0072FFFF8C\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 17 minutes	\05FF007AFFFF84\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 2 minutes	\05FF004AFFFFB4\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 20 seconds	\05FF0022FFFFDC\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 3 minutes	\05FF0052FFFFAC\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 30 seconds	\05FF002AFFFFD4\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 4 seconds	\05FF000AFFFFF4\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 40 seconds	\05FF0032FFFFCC\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 5 minutes	\05FF005AFFFFA4\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 7 minutes	\05FF0062FFFF9C\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate 8 seconds	\05FF0012FFFFEC\x0D
Dim Level 255 Group Address 255 Application Address 255 Dimming Rate Instantaneous	\05FF0002FFFFFC\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 1 minute	\0530003AFFFF93\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 1.5 minutes	\05300042FFFF8B\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 10 minutes	\0530006AFFFF63\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 12 seconds	\0530001AFFFFB3\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 15 minutes	\05300072FFFF5B\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 17 minutes	\0530007AFFFF53\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 2 minutes	\0530004AFFFF83\x0D

Global Scripter Module Communication Sheet

Revision: 11/12/2018

Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 20 seconds	\05300022FFFFAB\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 3 minutes	\05300052FFFF7B\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 30 seconds	\0530002AFFFA3\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 4 seconds	\0530000AFFFC3\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 40 seconds	\05300032FFFF9B\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 5 minutes	\0530005AFF73\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 7 minutes	\05300062FFFF6B\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate 8 seconds	\05300012FFFFBB\x0D
Dim Level 255 Group Address 255 Application Address 48 Dimming Rate Instantaneous	\05300002FFFFCB\x0D
Switch Light Off Group Address 0 Application Address 255	\05FF000100FB\x0D
Switch Light Off Group Address 0 Application Address 48	\0530000100CA\x0D
Switch Light Off Group Address 255 Application Address 255	\05FF0001FFFC\x0D
Switch Light Off Group Address 255 Application Address 48	\05300001FFCB\x0D
Switch Light On Group Address 0 Application Address 255	\05FF00790083\x0D
Switch Light On Group Address 0 Application Address 48	\053000790052\x0D
Switch Light On Group Address 255 Application Address 255	\05FF0079FF84\x0D
Switch Light On Group Address 255 Application Address 48	\05300079FF53\x0D