
This document provides additional assistance with wiring your Extron IP Link Pro Control Processor to your device. Different components may require a different wiring scheme than those listed below.

For complete operating instructions, refer to the user's manual for the specific IP Link Pro Control Processor or the documentation supplied by the manufacturer of the controlled device.

For more information on using Global Scriptor Modules, refer to the "[Guide to Using Scriptor Modules](#)" document.

Device Specifications

Device Type: Video Processor
Manufacturer: Colorlight
Firmware Version: N/A
Model(s): S6F

Tested on the Following Software and Firmware Versions

IP Link Pro Control Processor Firmware	Global Scriptor Version
3.04.0001-b002	2.3.1

Version History

Module Version	Date	Notes
1_0_0_0	10/14/2019	Initial Version

Module Notes

- Status is not supported

Supported Class and Example

EthernetClass
<code>InterfaceName = ModuleName.EthernetClass('192.168.254.254', 9099, Model='S6F')</code>

Control Commands

Format with Qualifier:

```
InterfaceName.Set(Command, Value, {'Qualifier Key': 'Qualifier Value'})
```

Format with Qualifier:

```
InterfaceName.Set(Command, Value)
```

Command	Value	Value	
Blank	'On'	'Off'	
# Blank example InterfaceName.Set('Blank', 'On')			
Command	Value		
Brightness	0 to 100 in steps of 1		
# Brightness example InterfaceName.Set('Brightness', 100)			
Command	Value		
ColorTemperature	2000 to 10000 in steps of 1		
# ColorTemperature example InterfaceName.Set('ColorTemperature', 10000)			
Command	Value	Value	
Freeze	'On'	'Off'	
# Freeze example InterfaceName.Set('Freeze', 'On')			
Command	Value	Value	
Input	'DVI'	'HDMI'	
# Input example InterfaceName.Set('Input', 'DVI')			
Command	Value	Value	
SwitchInputManually	'Enable'	'Disable'	
# SwitchInputManually example InterfaceName.Set('SwitchInputManually', 'Enable')			
Command	Value	Value	Value
TestPattern	'Normal'	'Red'	'Green'
	'Blue'	'White'	'Vertical Line'
	'Horizontal Line'	'Left Diagonal'	'Right Diagonal'
	'Gradient of Red'	'Gradient of Green'	'Gradient of Blue'
	'Gradient of White'	'Black'	
# TestPattern example InterfaceName.Set('TestPattern', 'Normal')			

Status Commands:

N/A

Network communication

When configuring the Ethernet module, be sure device settings match those of the Global Scripter ethernet interface.

Port Type:	Ethernet
Device Listen Port:	9099
Device Reply Port:	0
Logon Credentials Supported:	No
Multi-Connection Capabilities:	Undetermined
Listen Port Changeability:	Undetermined
Listen Port Changeability:	Undetermined

Ethernet Module Configuration Description

Please refer to user manual for settings and changes to the network communication

Notes for the Device

Appendix A. Set Commands

Blank Off	\x11\x00\x11\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x01
Blank On	\x11\x00\x11\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00
Brightness 0	!\x00\x14\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Brightness 100	!\x00\x14\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Color Temperature 10000	"\x00\x12\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Color Temperature 2000	"\x00\x12\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Freeze Off	\x12\x00\x11\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00
Freeze On	\x12\x00\x11\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00
Input DVI	3\x00\x12\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Input HDMI	3\x00\x12\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Switch Input Manually Disable	\x8B\x00\x11\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00
Switch Input Manually Enable	\x8B\x00\x11\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00
Test Pattern Black	2\x00\x17\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Test Pattern Blue	2\x00\x17\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Test Pattern Gradient of Blue	2\x00\x17\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Test Pattern Gradient of Green	2\x00\x17\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Test Pattern Gradient of Red	2\x00\x17\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Test Pattern Gradient of White	2\x00\x17\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Test Pattern Green	2\x00\x17\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Test Pattern Horizontal Line	2\x00\x17\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Test Pattern Left Diagonal	2\x00\x17\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Test Pattern Normal	2\x00\x17\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Test Pattern Red	2\x00\x17\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Test Pattern Right Diagonal	2\x00\x17\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Test Pattern Vertical Line	2\x00\x17\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00
Test Pattern White	2\x00\x17\x00\x00\x00\xFF\xFF\xFF\x00\x00\x00\x00\x00\x00\x00\x00\x00