

This document provides additional assistance with wiring your Extron IP Link Pro Control Processor to your device. Different components may require a different wiring scheme than those listed below.

For complete operating instructions, refer to the user's manual for the specific IP Link Pro Control Processor or the documentation supplied by the manufacturer of the controlled device.

For more information on using Global Scriptor Modules, refer to the "[Guide to Using Scriptor Modules](#)" document.

Device Specifications

Device Type: Controller
Manufacturer: Comm-Tec
Firmware Version: N/A
Model(s): CTG-DALI

Tested on the Following Software and Firmware Versions

IP Link Pro Control Processor Firmware	Global Scriptor Version
2.08.0002-b001	1.4.2

Version History

Module Version	Date	Notes
1_2_2_0	7/11/2018	Added Scaling command. Updated module timings and logic.
1_2_1_0	7/28/2016	Initial Version

Supported Classes and Examples

SerialClass
InterfaceName = ModuleName.SerialClass(ProcessorName, 'COM1', Model='CTG-DALI')
SerialOverEthernetClass
InterfaceName = ModuleName.SerialOverEthernetClass('192.168.254.254', 2001, Model='CTG-DALI')

Control Commands

Format with Qualifier:

```
InterfaceName.Set(Command, Value, {'Qualifier Key': 'Qualifier Value'})
```

Format without Qualifier:

```
InterfaceName.Set(Command, Value)
```

Command GroupControl	Value 'On' 'Maximum'	Value 'Off' 'Up'	Value 'Minimum' 'Down'
Qualifier Key 'Group'	Qualifier Value '1' – '16'	Qualifier Value 'All'	
# GroupControl example InterfaceName.Set('GroupControl', 'On', {'Group': '1'})			
Command Scaling	Value 1 to 254 in steps of 1		
Qualifier Key 'Group'	Qualifier Value '1' – '16'	Qualifier Value 'All'	
# Scaling example InterfaceName.Set('Scaling', 254, {'Group': '1'})			
Command SceneRecall	Value '1' – '16'		
Qualifier Key 'Group'	Qualifier Value '1' – '16'	Qualifier Value 'All'	
# SceneRecall example InterfaceName.Set('SceneRecall', '1', {'Group': '1'})			

Status Available

N/A

Cable and Adapter Requirements

Captive Screw to Male DB9 RS-232 Serial Cable

Notes for the Device

Serial communication

Port Type: RS-232

Baud Rate: 19200


Data Bits: 8

Parity: None


Stop Bits: One

Flow Control: None

Pin Assignments Diagram



Signal	Main Cable	Pin	Signal
TxD	→	2	RxD
RxD	←	3	TxD
GND	→	5	GND



Appendix A. Set Commands

Group Control Down Group 1	\x00\x81\x02\x0D
Group Control Maximum Group 1	\x00\x81\x05\x0D
Group Control Minimum Group 1	\x00\x81\x06\x0D
Group Control Off Group 1	\x00\x81\x00\x0D
Group Control On Group 1	\x00\x81\x08\x0D
Group Control Up Group 1	\x00\x81\x01\x0D
Group Control Down Group 16	\x00\x9F\x02\x0D
Group Control Maximum Group 16	\x00\x9F\x05\x0D
Group Control Minimum Group 16	\x00\x9F\x06\x0D
Group Control Off Group 16	\x00\x9F\x00\x0D
Group Control On Group 16	\x00\x9F\x08\x0D
Group Control Up Group 16	\x00\x9F\x01\x0D
Group Control Down Group All	\x00\xFF\x02\x0D
Group Control Maximum Group All	\x00\xFF\x05\x0D
Group Control Minimum Group All	\x00\xFF\x06\x0D
Group Control Off Group All	\x00\xFF\x00\x0D
Group Control On Group All	\x00\xFF\x08\x0D
Group Control Up Group All	\x00\xFF\x01\x0D
Scaling 1 Group 1	\x00\x80\x01\x0D
Scaling 254 Group 1	\x00\x80\xFE\x0D
Scaling 1 Group 16	\x00\x9E\x01\x0D
Scaling 254 Group 16	\x00\x9E\xFE\x0D
Scaling 1 Group All	\x00\xFE\x01\x0D
Scaling 254 Group All	\x00\xFE\xFE\x0D
Scene Recall 1 Group 1	\x00\x81\x10\x0D
Scene Recall 16 Group 1	\x00\x81\x1F\x0D
Scene Recall 1 Group 16	\x00\x9F\x10\x0D
Scene Recall 16 Group 16	\x00\x9F\x1F\x0D
Scene Recall 1 Group All	\x00\xFF\x10\x0D
Scene Recall 16 Group All	\x00\xFF\x1F\x0D