

GOLDEN POLYFIBER PUTTY



PRODUCT DESCRIPTION:

GP-240 is a two-component polyester glass-fiber putty for cover the cracks, and used to fill deep dents and irregular parts off the car body.



Materials for application:

GP240 GOLDEN POLYFIBER PUTTY.
HARDNER PEROXIDE.



SURFACE PREPRATION:

Degrease and sand the surface with p120 sand paper from old coatings and grease.



MIXING RATIO (by weight):

Golden polyfiber putty: 100
Hardener:2

POT LIFE:

5 MIN at 25c (when mixed with hardener).



APPLICATION PROCESS:

Mix 2% of hardener with the golden polyester putty, mixing verywell to achieve a homogenous mixture. Apply the mixed product with glazing knife. The putty can sand after 20 to 30 min, with p80-p180 dry sanding.

RECOARABILITY:

All golden preparatory products.





Drying times

Drying	25C	60C
Flash off	-	-
Dust free	5 min	-
Dry to handle	-	-
Dry to sand	30-45	-
Dry to polish	-	-



CLEANING OF EQUIPMEENT:

Tools should be cleaned immediately after use with thinner 903.



Physical properties:

Color	Grey
gloss	matt
Flash point	34 c
packaging	1 kg
Shelf life	12 months