# شـركـة الذهبيــة للصناعـات الكـيماويـة GOLDEN CHEMICHAL INDUSTRIES CO.



## **GOLDEN EGGSHELL**

## **Product Description:**

A high quality water-based paint based on acrylic polymers and high quality coloring materials. After application, it gives a smooth, regular, bright white surface that resembles an egg shell. It also gives long-term protection to the internal surfaces, it is characterized by high resistance to different atmospheres and with a high brushing rate and coverage.

### The use:

It is used for interior applications of concrete, cement and gypsum coatings.

## **Properties:**

Unique coverage
Super smoothness
Easy to apply without splashing
Excellent adhesion strength
Suitable for all building materials surfaces
Good alkali resistance
Very good wash ability

## **Certification:**

Conforming to Jordanian standard specification 31/2021



# شـركـة الذهبيــة للصناعـات الكـيماويـة GOLDEN CHEMICHAL INDUSTRIES CO.



## **Physical properties:**

general look	A shiny quarter	
Color	White according to the colors supported in the catalog	
Specific weight	0.05 ± 1.30	ASTM D1475
Solid size	40 ± 2 %	ASTM D2697
Dry layer thickening	40-50 Micron	
Theoretical spread rate	8-10 m²/liter	

## **Drying time:**

Surface dry 24 hours	30-60 minutes
Hard dry	2- 4 hours
Re-application	6 hours
Complete dry	24 hours

## **Surface Preparation:**

The surface must be clean, free of grease, oils, dust and suspended matter, and cement surfaces must be completely dry, and the surface must be cohesive, free from defects and bumps.

## Instructions for use:

The paint should be stirred well before use.

Sufficient amount of water may be added to obtain the appropriate viscosity for the application.

Do not paint over wet surfaces until after they are completely dry. Not to paint the next layer unless the previous layer is completely dry, taking into account the minimum time between the two coats. Adequate ventilation should be provided during application and dehydration

## شركة الذهبيـة للصناعات الكيماويـة GOLDEN CHEMICHAL INDUSTRIES CO.



Application tools: roller, brush and spray.

Diluent: water.

**Dilution percentage: 20-30%.** 

**Storage conditions:** 

As it is in the original Golden Bulletin Shelf life: one year from the date of production.



