

GP 900/901/902 2K ACRYLIC THINNER

Product Description:

GP 900 Special formulated Medium thinner for acrylic polyurethane coatings application contains organic volatile solvents, for treatment of large vehicles within the temperature range of 20°C.

GP 901 Special formulated slow thinner for acrylic polyurethane coatings application contains organic volatile solvents, for treatment of large vehicles within the temperature range of 20-30°C.

GP 902 Special formulated Extra Slow thinner for acrylic polyurethane coatings application contains organic volatile solvents, for spot & repairs or for complete re-sprays provided the temperature in the spray booth does not exceed 30-40°C.



Technical Information:

Color	Transparent
Product Weight	0.85 ± 0.02 kg/ltr
Distillation Range	100-180°C At 101.3kpa
Evaporation Rate	2.1 (nBuoAc = 1)
Surface Tension	29 Dyne/cm
Refractive Index	1.453 ± 0.002 at 25°C
V.O.C.	870 gm/liter
Flash Point	4-10°C

GP 900/901/902 2K ACRYLIC THINNER

Pack Size: 1 Liter, 4 Liter, 150 Kgs.

Shelf Life: 24 Months

Storage:

The product must be stored in accordance with national regulations.
The product must be kept in a cool and well-ventilated place, protected from heat and direct sunlight. Containers must be kept Tightly closed.

Health and Safety:

Wear appropriate protection such as gloves, goggles and facemask.
Provide adequate ventilation
Avoid eye or skin contact Close container after use
Store under normal dry conditions