

GOLDEN TEX

Product Description:

A high quality final rough spray paint, based on acrylic preparations, which is characterized by its resistance to weather conditions.

The use:

It is used for interior and exterior coatings for concrete, cement and gypsum surfaces.

Properties:

Resistant to weather conditions.
Excellent adhesion strength.
Good water resistance.
High durability.



Physical properties:

| | |
|-------------------------|--|
| general look | matte |
| Color | White according to the colors supported in the catalog |
| Specific weight | 1.70 ± 0.05 ASTM D1475 |
| Solid size | 62 ± 2% ASTM D2697 |
| Dry layer thickening | 300-600 microns |
| Theoretical spread rate | 1-2 m2 / L |



Drying time:

| | |
|----------------------|---------------|
| Surface dry 24 hours | 30-60 minutes |
| Hard dry | 2- 4 hours |
| Re-application | 6 hours |
| Complete dry | 24 hours |

Surface Preparation:

The surface must be clean, free of grease, oils, dust and suspended matter, and cement surfaces must be completely dry, and the surface must be cohesive, free from defects and protrusions.

Instructions for use:

The paint should be stirred well before use.

Sufficient amount of thinner may be added to obtain the appropriate viscosity for the application.

Do not paint over wet surfaces until after they are completely dry.

Not to paint the next layer unless the previous layer is completely dry, taking into account the minimum time between the two coats.

Adequate ventilation should be provided during application and dehydration.

Application tools: brush and spray.

Diluent:

Diluent: water.

Dilution percentage: 5%.

Storage conditions:

As it is

Shelf life: one year from the date of production.