

Class B Address – 192.168.x.x

No of Hosts	Subnet Bits	Host Bits	Subnet ID	1 st Host	Last Host	Broadcast	Mask
8000	000	00000.000000000	.0.0	.0.1	.31.254	.31.255	/19
2100	0010	0000.00000000	.32.0	.32.1	.47.254	.47.255	/20
612	001100	00.00000000	.48.0	.48.1	.52.254	.52.255	/22
420	0011010	0.00000000	.52.0	.52.1	.53.254	.53.255	/23
255	0011011	0.00000000	.54.0	.54.1	.55.254	.55.255	/23
100	00111000.0	0000000	.56.0	.56.1	.56.126	.56.127	/25
10	00111000.1000	0000	.56.128	.56.129	.56.142	.56.143	/28
2	00111000.100100	00	.56.144	.56.145	.56.146	.56.147	/30
2	00111000.100101	00	.56.148	.56.149	.56.150	.56.151	/30
2	00111000.100110	00	.56.152	.56.153	.56.154	.56.155	/30

1 2 4 8 16 32 64 128 256 512 1024 2048 4096 8192

8192	4096	2048	1024	512	256	128	64	32	16	8	4	2	1
						1	0	0	1	1	0	0	0

Once bits have decimal in calculate each 8-bit octet separately, ex 00100000 becomes 32, then 00000000 becomes 0