moda**LIGHT**®
SPECIFICATION

Project Name: _____   SKU: _____

MODA Contact: _____   E-Mail: _____

Type: _____   PO#: _____   Quantity: _____

Notes: _____

PHYSICAL

Dimensions	L: 12in (304mm)	W: 1 13/16in (46mm)
	L: 48in (1219mm)	H: 1 3/16in (30mm)

Weight	1ft: 0.38 lbs (0.17kg)
	4ft: 1.22 lbs (0.55 kg)
Applications	Cove, Accent, & Indirect General Illumination
Construction	6063 Aluminum Body, Polycarbonate Self-Locking Mounting Bracket and Polycarbonate Optical Lens
Ingress Protection	Dry/Damp Location IP52
Thermal Management	Moda Aluminum Heat Sink
Fixture Connections	Integral Male & Female Connectors
Operating Temperature	-4°F ~ 122°F (-20°C ~ 50°C)
Storage Temperature	-13°F ~ 158°F (-25°C ~ 70°C)
Humidity	20-70% Non Condensing

SPECIFICATIONS

	Lumens	Efficacy
1FT	284.74	48.26
4FT	1138.96	51.77

POWER CONSUMPTION

	120V AC	240V AC	277V AC
1FT	5.9W	6.3W	6.5W
4FT	22W	22.1W	22.2W

OUTPUT

Colors	RGBW
Beam Angle	200°
Color Bin Tolerance	Zero Bin
Lumen Maintenance	90,000 Hours L70 @ 25°C
	70,000 Hours L70 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

ELECTRICAL

Input Voltage	100-277V AC 50Hz/60Hz
Control	DMX512
Power Factor	≥ 0.98

MAX CONTINUOUS RUN

120V AC	240V AC	277V AC
120 ft	240 ft	240 ft

STANDARDS & CERTIFICATIONS

Certification	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, CCC, C-Tick, RoHS, & WEEE Compliant.
Class	1
Warranty	5 Year Limited Warranty

	FIXTURE	PART NUMBER	ORDERING SKU
1FT	Moda Mini Cove Interior Standard Output Silver DMX 512 RGBW 2700K HCRI 1FT	MMCI-S-S-DMX512-RGB27-1	105-1205
	Moda Mini Cove Interior Standard Output Silver DMX 512 RGBW 3000K HCRI 1FT	MMCI-S-S-DMX512-RGB30-1	105-1206
	Moda Mini Cove Interior Standard Output Silver DMX 512 RGBW 3500K HCRI 1FT	MMCI-S-S-DMX512-RGB35-1	105-1208
	Moda Mini Cove Interior Standard Output Silver DMX 512 RGBW 4000K HCRI 1FT	MMCI-S-S-DMX512-RGB40-1	105-1209
4FT	Moda Mini Cove Interior Standard Output Silver DMX 512 RGBW 2700K HCRI 4FT	MMCI-S-S-DMX512-RGB27-4	105-3205
	Moda Mini Cove Interior Standard Output Silver DMX 512 RGBW 3000K HCRI 4FT	MMCI-S-S-DMX512-RGB30-4	105-3206
	Moda Mini Cove Interior Standard Output Silver DMX 512 RGBW 3500K HCRI 4FT	MMCI-S-S-DMX512-RGB35-4	105-3208
	Moda Mini Cove Interior Standard Output Silver DMX 512 RGBW 4000K HCRI 4FT	MMCI-S-S-DMX512-RGB40-4	105-3209

ACCESSORIES	DESCRIPTION	PART NUMBER	ORDERING SKU
Leader Cable US 5 Pin 10FT	Power to first fixture of run	MLCI-US-5PIN-W-10FT	299-0100
Leader Cable US 5 Pin 25FT	Power to first fixture of run	MLCI-US-5PIN-W-25FT	299-0102
Jumper Cable US 5 Pin 1FT	Connection between fixtures	MJCI-US-5PIN-W-1FT	299-1100
Jumper Cable US 5 Pin 4FT	Connection between fixtures	MJCI-US-5PIN-W-4FT	299-1102
Leader Cable EU 5 Pin 3M	Power to first fixture of run	MLCI-EU-5PIN-W-3M	299-0101
Leader Cable EU 5 Pin 10M	Power to first fixture of run	MLCI-EU-5PIN-W-10M	299-0103
Jumper Cable EU 5 Pin 300MM	Connection between fixtures	MJCI-EU-5PIN-W-300MM	299-1101
Jumper Cable EU 5 Pin 1M	Connection between fixtures	MJCI-EU-5PIN-W-1M	299-1103
Terminator 5 Pin	Must be fixed to last fixture for safety	MTI-5PIN-W	299-2100
Mounting Track 20FT	Allows user to install fixtures in a continuous linear position. Packaged in 5 4ft sections in total of 20ft.	MMC-20-TRACK-1-S1-G	299-3200
Mounting Track Connector	Interior track connector	N/A	299-3202
Symmetric Louver 1FT	Symmetric louver for light control	N/A	299-4320
Asymmetric Louver 1FT	Asymmetric louver for light control	N/A	299-4231
Honeycomb Louver 1FT	Honeycomb louver for light control	N/A	299-4232
Blade Louver 1FT	Blade louver for light control	N/A	299-4233

CONTROLS	DESCRIPTION	PART NUMBER	ORDERING SKU
Kandi Touch	DMX512 Wall Mounted Touch Panel Controller with Color Display	KND-TCH-B (Black) KND-TCH-W (White)	250-0040 250-0041
MODA Touch*	DMX512 Wall Mounted Touch Panel Controller	MTCH-S1-B (Black) MTCH-S1-W (White)	MTCH-S1-B MTCH-S1-W

 * - MODA Touch default scene addressing can be found on MODA Touch Product Documentation and DMX Fixture Installation Guides.

CONTROL ACCESSORIES	DESCRIPTION	PART NUMBER	ORDERING SKU
Pathway DMX Splitter/Repeater	Wall-mount, 4 ports, E1.20 RDM Compliant, Small - 10in X 13in X 4 1/2in	PWREP WM P4 TERM RDM SML DMX-RDM	250-0153
Pathway DMX Splitter/Repeater	Wall-mount, 8 ports, E1.20 RDM Compliant, Medium - 10in X 23in X 4 1/2in	PWREP WM P8 TERM RDM MED DMX-RDM	250-0154
Pathway DMX Splitter/Repeater	Wall-mount, 12 ports, E1.20 RDM Compliant, Medium - 10in X 23in X 4 1/2in	PWREP WM P12 TERM RDM MED DMX-RDM	250-0155
Shielded Cable 500FT	RS-485 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	SW-L-19827-1-500FT	250-0251
Shielded Cable 1000FT	RS-485 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	SW-L-19827-1-1000FT	250-0252