



Project Name: _____ SKU: _____

MODA Contact: _____ E-Mail: _____

Type: _____ PO #: _____ Quantity: _____

Notes: _____



PHYSICAL

Dimensions	L: 12 3/8in (316mm)	W: 2 7/16in (61mm)
	L: 47 5/16in (1202mm)	H: 2 3/8in (60mm)
Weight	12in: 1lbs (0.45kg)	
	48in: 3.3lbs (1.5kg)	
Applications	Graze, Accent, & Indirect General Illumination	
Construction	Pure Aluminum Body, Polycarbonate Mounting Bracket and Polycarbonate Optical Lens	
Ingress Protection	Dry/Damp Location IP44	
Thermal Management	Moda Aluminum Heat Sink	
Fixture Connections	Integral Male & Female Connectors	
Operating Temperature	-40°F ~ 122°F (-40°C ~ 50°C)	
Storage Temperature	-40°F ~ 176°F (-40°C ~ 80°C)	
Humidity	0-95% Non Condensing	

SPECIFICATIONS

	Lumens		Efficacy	
	1FT	4FT	1FT	4FT
HO	1036 - 1353	3704 - 4356	103 - 135	92 - 109
HO+	1035 - 1197	4148 - 4795	103 - 119	103 - 119

POWER CONSUMPTION

	120V - 277V AC	
	1FT	4FT
HO	10W	40W
HO+	10W	40W

OUTPUT

CCT & SDCM	2200K - 6500K
	2 Step MacAdam Ellipse
Beam Angle	6°, 10°, 25°, 40°, 10°x40°, 30°x60°, Forward Throw Asymmetric, or 30°x100° optic options
Color Bin Tolerance	Single Bin
CRI	95-97
Lumen Maintenance	90,000 Hours L50 @ 25°C
	70,000 Hours L50 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

ELECTRICAL

Input Voltage	100-277V AC 50Hz/60Hz
Control	Electronic Low Voltage Reverse Phase Trailing Edge
Power Factor	≥ 0.98

MAX CONTINUOUS RUN

	120V - 277V AC	
	1FT	4FT
HO	80ft	80ft
HO+	80ft	80ft

STANDARDS & CERTIFICATIONS



Certification	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, CCC, C-Tick, RoHS, & WEEE Compliant.
Class	1
Warranty	3 Year Limited Warranty

1FT		6°		10°		25°		40°	
Output	CCT	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy
HO	2200K -	1208.00 -	120.80 -	1196.00 -	119.60 -	1182.00 -	118.20 -	1172.00 -	117.20 -
	6500K	1353.47	135.34	1341.47	134.14	1327.47	132.74	1317.47	131.74

1FT		10°x40°		30°x60°		30°x60°X5°	
Output	CCT	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy
HO	2200K -	1163.00 -	116.30 -	1038.39 -	103.83 -	1036.10 -	103.61 -
	6500K	1308.47	130.84	1184.54	118.45	1182.54	118.25

1FT		30°x100°	
Output	CCT	Lumens	Efficacy
HO+	2200K -	1035.93 -	103.59 -
	6500K	1197.61	119.76

4FT		6°		10°		25°		40°	
Output	CCT	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy
HO	3500K -	3704.69 -	92.61 -	3780.81 -	94.52 -	3768.70 -	94.21 -	3760.05 -	94.00 -
	6500K	4346.88	107.07	4370.88	109.27	4356.88	108.92	4346.88	108.67

4FT		10°x40°		30°x60°		30°x60°X5°	
Output	CCT	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy
HO	3500K -	3752.26 -	93.80 -	3749.67 -	93.74 -	3747.94 -	93.69 -
	6500K	4337.88	108.44	4334.88	108.37	4332.88	108.32

4FT		30°x100°	
Output	CCT	Lumens	Efficacy
HO+	3500K -	4148.26 -	103.70 -
	6500K	4795.68	119.89

BEAM ANGLE

	HO	HO+
6° / 10° / 25° / 40° / 10°x40° / 30°x60°	•	
Forward Throw Asymmetric		
30°x100°		•
	• Available	

MGI - - S1 - DW - -

 COMPLETE SKU SAMPLE: MGI-HO-S1-DW-4-25

A - FIXTURE & LOCATION

MGI — Moda Graze Interior

B - LIGHT OUTPUT

HO — High Output
 HO+ — High Output Plus
 —

C - SERIES NUMBER

S1 — Series 1

D - LED COLOR

DW — Dynamic White

E - LENGTH

1 — 1FT
 4 — 4FT

G - OPTIC

6* — 6° x 6°
 10* — 10° x 10°
 25* — 25° x 25°
 40* — 40° x 40°
 140* — 10° x 40°
 360* — 30° x 60°
 365* — Forward Throw Asymmetric
 310** — 30° x 100°

*Available only in HO

**Available only in HO+

ACCESSORIES	DESCRIPTION	ORDERING SKU
Leader Cable US 8 Pin 10FT	Power to first fixture of run	MLCI-US-8PIN-G-10FT
Leader Cable US 8 Pin 25FT	Power to first fixture of run	MLCI-US-8PIN-G-25FT
Jumper Cable US 8 Pin 1FT	Connection between fixtures	MJCI-US-8PIN-G-1FT
Jumper Cable US 8 Pin 4FT	Connection between fixtures	MJCI-US-8PIN-G-4FT
Leader Cable EU 8 Pin 3M	Power to first fixture of run	MLCI-EU-8PIN-G-3M
Leader Cable EU 8 Pin 10M	Power to first fixture of run	MLCI-EU-8PIN-G-10M
Jumper Cable EU 8 Pin 300MM	Connection between fixtures	MJCI-EU-8PIN-G-300MM
Jumper Cable EU 8 Pin 1M	Connection between fixtures	MJCI-EU-8PIN-G-1M
Terminator 8 Pin	Must be fixed to last fixture for safety	MTI-8PIN-G
Interior Bracket Lock	Holds fixture in place for vertical installation	MCGI-BL-G

CONTROLS	DESCRIPTION	PART NUMBER	ORDERING SKU
Kandi Touch	DMX512 Wall Mounted Touch Panel Controller with Color Display	KND-TCH-B (Black)	250-0040
		KND-TCH-W (White)	250-0041
MODA Touch	DMX512 Wall Mounted Touch Panel Controller	MTCH-S1-B (Black) MTCH-S1-W (White)	MTCH-S1-B MTCH-S1-W

CONTROL ACCESSORIES	DESCRIPTION	PART NUMBER	ORDERING SKU
Moda DMX Wiring Hub 2.0	Simplifies wiring and strengthens DMX signal.	N/A	250-0100
Shielded Cable 500FT	RS-485 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	SW-L-19827-1-500FT	250-0251
Shielded Cable 1000FT	RS-485 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	SW-L-19827-1-1000FT	250-0252