



Project Name: \_\_\_\_\_ SKU: \_\_\_\_\_

MODA Contact: \_\_\_\_\_ E-Mail: \_\_\_\_\_

Type: \_\_\_\_\_ PO #: \_\_\_\_\_ Quantity: \_\_\_\_\_

Notes: \_\_\_\_\_



## PHYSICAL

<b>Dimensions</b>	L: 12 3/8in (316mm) L: 47 5/16in (1202mm)	W: 2 7/16in (61mm) H: 2 3/8in (60mm)
<b>Weight</b>	12in: 1lbs (0.45kg) 48in: 3.3lbs (1.5kg)	
<b>Applications</b>	Graze, Accent, & Indirect General Illumination	
<b>Construction</b>	Pure Aluminum Body, Polycarbonate Mounting Bracket and Polycarbonate Optical Lens	
<b>Ingress Protection</b>	Dry/Damp Location IP44	
<b>Thermal Management</b>	Moda Aluminum Heat Sink	
<b>Fixture Connections</b>	Integral Male & Female Connectors	
<b>Operating Temperature</b>	-40°F ~ 122°F (-40°C ~ 50°C)	
<b>Storage Temperature</b>	-40°F ~ 176°F (-40°C ~ 80°C)	
<b>Humidity</b>	0-95% Non Condensing	

## SPECIFICATIONS

	Lumens		Efficacy	
	1FT	4FT	1FT	4FT
HO	952 - 1151	3551 - 4155	95 - 125	88 - 122
HO+	987 - 1141	3950 - 4566	98 - 114	98 - 114

## POWER CONSUMPTION

	120V - 277V AC	
	1FT	4FT
HO	10W	40W
HO+	10W	40W

## OUTPUT

<b>CCT &amp; SDCM</b>	1800K - 3000K - HO+ only 2200K - 3000K - HO only 2 Step MacAdam Ellipse
<b>Beam Angle</b>	6°, 10°, 25°, 40°, 10°x40°, 30°x60°, Forward Throw Asymmetric, or 30°x100° optic options
<b>Color Bin Tolerance</b>	Single Bin
<b>CRI</b>	90-95
<b>Lumen Maintenance</b>	90,000 Hours L50 @ 25°C 70,000 Hours L50 @ 50°C
<b>Testing Data</b>	Light Data LM-79-08 & LM-80-08

## ELECTRICAL

<b>Input Voltage</b>	100-277V AC 50Hz/60Hz
<b>Control</b>	Electronic Low Voltage Reverse Phase Trailing Edge
<b>Power Factor</b>	≥ 0.98

## MAX CONTINUOUS RUN

	120V - 277V AC	
	1FT	4FT
HO	80ft	80ft
HO+	80ft	80ft

## STANDARDS & CERTIFICATIONS



<b>Certification</b>	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, CCC, C-Tick, RoHS, & WEEE Compliant.
<b>Class</b>	1
<b>Warranty</b>	3 Year Limited Warranty

1FT		6°		10°		25°		40°	
Output	CCT	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy
HO	2200K -	995.96 -	99.59 -	985.58 -	98.55 -	973.47 -	97.34 -	964.82 -	96.48 -
	3000K	1151.40	125.15	1139.40	113.94	1125.40	112.54	1115.40	111.54

1FT		10°x40°		30°x60°		30°x60°X5°	
Output	CCT	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy
HO	2200K -	957.03 -	95.70 -	954.44 -	95.44 -	952.71 -	95.27 -
	3000K	1106.40	110.64	1103.40	110.64	1101.40	110.14

1FT		30°x100°	
Output	CCT	Lumens	Efficacy
HO+	1800K -	987.55 -	98.75 -
	3000K	1141.68	114.16

4FT		6°		10°		25°		40°	
Output	CCT	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy
HO	2200K -	3594.59 -	89.86 -	3584.21 -	89.60 -	3572.10 -	89.30 -	3563.45 -	89.08 -
	3000K	4155.60	103.89	4143.60	122.05	4129.60	103.24	4119.60	102.99

4FT		10°x40°		30°x60°		30°x60°X5°	
Output	CCT	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy
HO	2200K -	3555.66 -	88.89 -	3553.07 -	88.82 -	3551.34 -	88.78 -
	3000K	4110.60	118.75	4107.60	102.69	4105.60	102.64

4FT		30°x100°	
Output	CCT	Lumens	Efficacy
HO+	1800K -	3950.21 -	98.75 -
	3000K	4566.72	114.16

## BEAM ANGLE

	HO	HO+
6° / 10° / 25° / 40° / 10°x40° / 30°x60°	•	
Forward Throw Asymmetric		
30°x100°		•
	• Available	

MGI - - S1 - DWW - -



COMPLETE SKU SAMPLE: MGI-HO-S1-DWW-4-25

#### A - FIXTURE & LOCATION

MGI — Moda Graze Interior

#### B - LIGHT OUTPUT

HO — High Output  
HO+ — High Output Plus

#### C - SERIES NUMBER

S1 — Series 1

#### D - LED COLOR

DWW — Dynamic Warm

\* - Available only in HO

\*\* - Available only in HO+

#### E - LENGTH

1 — 1 FT  
4 — 4 FT

#### G - OPTIC

6\* — 6° x 6°  
10\* — 10° x 10°  
25\* — 25° x 25°  
40\* — 40° x 40°  
140\* — 10° x 40°  
360\* — 30° x 60°  
365\* — Forward Throw Asymmetric  
310\*\* — 30° x 100°

#### ACCESSORIES

#### DESCRIPTION

#### ORDERING SKU

Leader Cable US 8 Pin 10FT	Power to first fixture of run	MLCI-US-8PIN-G-10FT
Leader Cable US 8 Pin 25FT	Power to first fixture of run	MLCI-US-8PIN-G-25FT
Jumper Cable US 8 Pin 1FT	Connection between fixtures	MJCI-US-8PIN-G-1FT
Jumper Cable US 8 Pin 4FT	Connection between fixtures	MJCI-US-8PIN-G-4FT
Leader Cable EU 8 Pin 3M	Power to first fixture of run	MLCI-EU-8PIN-G-3M
Leader Cable EU 8 Pin 10M	Power to first fixture of run	MLCI-EU-8PIN-G-10M
Jumper Cable EU 8 Pin 300MM	Connection between fixtures	MJCI-EU-8PIN-G-300MM
Jumper Cable EU 8 Pin 1M	Connection between fixtures	MJCI-EU-8PIN-G-1M
Terminator 8 Pin	Must be fixed to last fixture for safety	MTI-8PIN-G
Interior Bracket Lock	Holds fixture in place for vertical installation	MCGI-BL-G

#### CONTROLS

#### DESCRIPTION

#### PART NUMBER

#### ORDERING SKU

Kandi Touch	DMX512 Wall Mounted Touch Panel Controller with Color Display	KND-TCH-B (Black)	250-0040
		KND-TCH-W (White)	250-0041
MODA Touch*	DMX512 Wall Mounted Touch Panel Controller	MTCH-S1-B (Black)	MTCH-S1-B
		MTCH-S1-W (White)	MTCH-S1-W

\* - MODA Touch default scene addressing can be found on MODA Touch Product Documentation and DMX Fixture Installation Guides.

#### CONTROL ACCESSORIES

#### DESCRIPTION

#### PART NUMBER

#### ORDERING SKU

Pathway DMX Splitter/Repeater	Wall-mount, 4 ports, E1.20 RDM Compliant, Small - 10in X 13in X 4 1/2in	PWREP WM P4 TERM RDM SML DMX-RDM	250-0153
Pathway DMX Splitter/Repeater	Wall-mount, 8 ports, E1.20 RDM Compliant, Medium - 10in X 23in X 4 1/2in	PWREP WM P8 TERM RDM MED DMX-RDM	250-0154
Pathway DMX Splitter/Repeater	Wall-mount, 12 ports, E1.20 RDM Compliant, Medium - 10in X 23in X 4 1/2in	PWREP WM P12 TERM RDM MED DMX-RDM	250-0155
Shielded Cable 500FT	RS-485 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	SW-L-19827-1-500FT	250-0251
Shielded Cable 1000FT	RS-485 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	SW-L-19827-1-1000FT	250-0252